

Advanced Programming 2017

Assignment 1

Tom Jager
dgr418@alumni.ku.dk

Tobias Ludwig
fqj315@alumni.ku.dk

September 26, 2017

1 New grammar

```
Expr ::= Term1 ExprOpt  
      | Term1
```

```
ExprOpt ::= ',' Expr
```

```
Term1 ::= Ident '=' Term1  
       | Term2
```

```
Term2 ::= Term3 '===' Term3  
       | Term3 '<' Term3  
       | Term3
```

```
Term3 ::= Term4 '+' Term4  
       | Term4 '-' Term4  
       | Term4
```

```
Term4 ::= Atom '*' Atom  
       | Atom '%' Atom  
       | Atom
```

```
Atom ::= Number  
      | String  
      | 'true'  
      | 'false'  
      | 'undefined'  
      | Ident  
      | '[' Exprs ']  
      | '[' ArrayFor ']  
      | '(' Expr ')'
```

```

Exprs ::= $\epsilon$
        | Expr1 CommaExprs

CommaExprs ::= $\epsilon$
              | ',' Expr1 CommaExprs

ArrayFor ::= 'for' '(' Ident 'of' Expr1 ')' ArrayCompr

ArrayIf ::= 'if' '(' Expr1 ')' ArrayCompr

ArrayCompr ::= Expr1
              | ArrayFor
              | ArrayIf

```

We transformed the given grammar by hand in order to make the code easier.

1. **Abolishing Left-recursion:** this is the case for the definition of **Expr** which consists of top-level instructions (again **Exprs**!) separated by comma. We can prevent the left-recursion by handling the case of a single vs. multiple inputs separately and by introducing a helper **ExprOpt** which calls **Expr** again circular.
2. **Precedence** is possible by defining the operators explicitly on different levels which we called **Term1** through **Term4** sticking to the numbering in the task description where level 1 corresponds to the lowest precedence. Because the parser will work through the grammar top-down, we will parse those first. This way we get a hierarchy of operators each of which can only be called with terms from lower levels.
3. **Associativity** comes into the game for the arithmetic operators is

Further aspects: Type checking: - Ident

Note if our hierarchy were that simple we could not use lower precedence level (e.g. Assignment, Term1) in computations of higher precedence, e.g. in **3 + (x=2)** could not be parsed. However, we have a remedy for that. We include the **'(' Expr ')'** as an option on the **Atom** level thereby closing the circle to the top of the hierarchy. Hence a proper nesting of expressions is possible maintaining a new frame of precedence in every parenthesized expression.

2 Parsers for Number, Ident and String

2.1 Number

Number is supposed to be a 9-digit signed integer. Parsec provides a function `count` which aids here.

3 The fuzzy gap between Parser and Interpreter

It is always a question of design how much interpreting is already done by the parser, with other words - where does Syntax end and Semantics start? For example we decided not to do any type-checking on the parser level.

