

TRUSTGUARD

User Story — How the Product Works

1. The Company

An online store uses several third-party integrations: Payment, Delivery, Analytics and Marketing. Each integration has access to the company's APIs and data based on what it is supposed to do.

2. The Integration Is Registered

The security team registers an integration in TrustGuard and creates its Integration Trust Profile.

Field	Example
Integration	Analytics Provider
Purpose	Collect anonymous website usage statistics
Allowed endpoints	/analytics/events
Allowed data	Anonymous usage events
Forbidden data	Customer profiles, payment details
Expected behaviour	Normal analytics traffic

3. Normal Request

The Analytics integration sends a normal request. The request passes through TrustGuard before reaching the application/API.

Application → TrustGuard → Third-Party API

TrustGuard checks the integration identity, endpoint, purpose, data being accessed, behaviour and current context. Everything matches the profile, so the risk score is low and the request is allowed.

4. The Integration Gets Compromised

Later, the integration credentials are compromised. An attacker now uses valid credentials to make requests. The API itself may accept the credentials, but the behaviour is no longer normal.

5. Suspicious Request #1

The Analytics integration suddenly requests a customer profile endpoint such as **/customers/profile**. The endpoint is outside its normal purpose.

TrustGuard detects: unfamiliar endpoint + purpose mismatch.

Risk increases. The request may still be allowed, but TrustGuard starts monitoring the integration closely.

6. Suspicious Request #2

The integration then requests sensitive payment information. This is completely outside the Analytics integration's declared purpose.

TrustGuard detects: sensitive data access + permission violation + purpose mismatch.

Risk rises sharply. TrustGuard applies a stronger response such as rate limiting or restricting the integration.

7. Abnormal Traffic Spike

The integration normally makes a small number of requests, but it suddenly starts requesting thousands of records. TrustGuard compares the activity with the integration's behavioural baseline and current context.

Example: 17.8× the normal request volume.

8. TrustGuard Calculates Risk

Risk	Meaning	Response
0–30	Trusted	ALLOW
31–60	Suspicious	ALLOW + MONITOR
61–80	High Risk	RATE LIMIT / RESTRICT
81–100	Critical	BLOCK / QUARANTINE + ALERT

9. The Security Team Sees Exactly Why

The TrustGuard dashboard shows the integration's current risk, recent requests, allowed resources, behaviour changes and security events.

Example explanation: **Payment data requested by Analytics integration; unfamiliar endpoint detected; traffic is 17.8× above baseline.**

10. Final Response

When the risk becomes critical, TrustGuard blocks and quarantines the integration, then alerts the security team. The company does not have to wait until the integration causes major damage before taking action.

11. The Complete User Journey

1. Register third-party integration
2. Define its purpose and allowed access
3. Route API requests through TrustGuard
4. Inspect every request
5. Compare activity with the integration's trust profile
6. Calculate a risk score
7. Apply a graded response
8. Explain the reason for the decision
9. Alert and quarantine critical behaviour

CORE PRODUCT IDEA

TrustGuard does not ask only: “Is this integration authorized?”

It asks: “Is this authorized integration still behaving like the integration we trusted?”