

# Lecture 11

# Dynamic Analysis

NMSU Reverse Engineering  
Joshua Reynolds  
Spring 2024

# Static vs. Dynamic Analysis

Everything we have done so far in the course has not actually required us to run malware – but sometimes this is helpful.

If you run malware inside a **sandbox** with instrumentation, you can see what it does to that environment

If you run malware with a **debugger**, you can pause at strategic locations, such as right after a cryptor or packer has unpacked the actual code to be run.

If you run malware with a **network simulator**, you can find indicators of compromise, what data is exported, and where the malware looks for **C<sup>2</sup>**

# FakeNet - Network Simulation tool in FlareVM

Intro: <https://www.mandiant.com/resources/blog/fakenet-ng-next-gen>

“By default, FakeNet-NG is configured to start several most commonly used services:

- DNS Listener on UDP port 53
- HTTP Listener on TCP port 80
- HTTPS Listener on TCP port 443
- SMTP Listener on TCP port 25
- Raw Binary Listener on both TCP and UDP ports 1337. This service is also used as a default listener to handle all communications. Default listeners are explained below.”

# RegShot - Registry Snapshot & Diff Tool in FlareVM

<https://bromiley.medium.com/malware-monday-regshot-6826ae22ba29>

## Steps:

1. Define the snapshot scope by registry hive and directories
2. Take a snapshot before running the malware
3. Run the malware
4. Take another snapshot, and compare to the first

# WinDBG – Windows GDB Equivalent

Debugger built by Microsoft (can also be used to debug kernel-mode drivers)

Activity 1 – Tutorial on how to use:

<https://learn.microsoft.com/en-us/windows-hardware/drivers/debugger/getting-started-with-windbg>

The textbook shows another debugger, x64dbg

(BTW, Ghidra and IDA both have built-in debuggers as well)

# Sandbox Services

Run instrumented virtual machines, allow you to upload malware to run.

Run for limited time, and provide a report of files changes, registry keys changed, screenshots of pop-ups, etc.

EX:

- [any.run](https://any.run)
- [hybrid-analysis.com](https://hybrid-analysis.com)
- [joesandbox.com](https://joesandbox.com)