

ADR 0045 — Push execution: a force that cannot be built, a lease checked by two parties, and a cancel that refuses to reassure

- **Status:** Accepted — implemented and tested.
- **Date:** 2026-08-02.
- **Milestone / issue:** M2.20e, issue #231 ("Push: force-with-lease, `--set-upstream`, progress/cancellation, and the never-force-pushes wording fix"), child of #73 (M2.20, "Remote operations"). Branch `feature/m2.20e-push-execution`, based on the unmerged `feature/m2.20d-pull-execution`.
- **Supersedes / superseded by:** Nothing. **Completes** the push half of the staging M2.20a (#227, ADR 0039) began — the widened `GitOperation::PushBranch` landed there with `planner::execute` refusing three of its four combinations with `501` — and closes the remote trio ADR 0043 (fetch) and ADR 0044 (pull) opened.
- **Related:** [0039](#) (the `ForcePublish` enum with no unguarded variant, the `Precondition::RefAt` lease, the `Destructive` risk class), [0043](#) (the streaming spawn, the progress parser and the cancellation latch this reuses whole), [0044](#) (the "one spawn, no second copy" posture applied to a different pair of halves), [0036](#) (forced `-c core.askpass=` and byte-level redaction, inherited unchanged because the spawn is not duplicated), [0037](#) (why the outcome is read from refs and only the failure *tag* is classified), [0018](#) (the staleness gate this executor's own lease check deliberately does not rely on), [0016](#) (the single funnel every write takes), `docs/SECURITY_MODEL.md`'s "Remote and Forge Credentials" and "Operation Risk Classes" sections (both annotated by this branch).

Context



Everything else this server does can be undone from this machine. A push cannot. It is the one operation whose effect lands somewhere nobody here controls, and — in its force-with-lease form — the one that can make **another person's commits unreachable**.

Three things were true on the base branch, and each of them mattered differently.

The type was already right. #227 gave `PushBranch` a `force: ForcePublish` field whose enum has exactly two variants, `None` and `WithLease { expected_remote_tip }`, and no third. A bare `git push --force` is not expressible in Rust and not deserializable off the wire. `planner::shape` turns a lease into a live `Precondition::RefAt` on `refs/remotes/<remote>/<branch>` and raises the plan's risk to `Destructive`.

The executor was not. `exec_push` ran `git push <remote> <branch>` — no `--progress`, no `--set-upstream`, no `--force-with-lease` — and **ignored the force value entirely**. That was deliberate and correct for #227: rather than silently downgrade a force the user had approved, `execute` matched only the one combination it could honour and refused the other three with `501`. But it left the capability as a type nobody could reach.

And the prose had gone stale. Three places in the codebase told the user "git-vista never force-pushes". The day `ForcePublish::WithLease` shipped, that sentence stopped being true as written — while the invariant it was actually describing (an *undo* never rewrites the remote) remained perfectly true and worth stating.




So this slice is not "add two flags". It is: carry a guarantee that currently stops at the type boundary all the way through to an argv, and be honest — in the response, the journal and the docs — about the one thing that changed.

Decisions

D1 — There is exactly one push argv builder, and no path through it reaches an unguarded force

`planner::push::push_argv` is the only function in this server that constructs a push command line. Its `match` over `ForcePublish` has **no wildcard arm**, and the one arm that emits a force flag emits `--force-with-lease=<branch>:<oid>`.




Why a function rather than three `if` s inline: the failure mode of the inline version is quiet. A future `ForcePublish` variant falling through to "no flag" silently *downgrades* a force the user approved; a fallback written the other way silently *upgrades* a fast-forward. Extracting the builder makes the property assertable over the entire input space without spawning anything, and the wildcard-free `match` turns a third variant into a build failure rather than a judgement call.

The assertion is deliberately precise, because the naive one is wrong: `--force` **does** appear in the argv, as the prefix of `--force-with-lease=`. So the property is *any element beginning `--force` must begin `--force-with-lease=`, and `-f` must never appear at all* (`push::tests::no_push_argv_can_carry_a_bare_force`). A source-level tripwire adds the half a function's own tests cannot see — that no *other* module builds a push argv: `planner.rs` must no longer contain the literal `"push"`, and `planner/push.rs`'s production half (the source above `#[cfg(test)]`) must contain the leased flag and none of the unguarded spellings (`contract_suite::only_planner_push_builds_a_push_argv_and_it_can_only_build_a_leased_force`).

D2 — The lease is checked twice, by two parties, against two different things

This is the decision the rest of the slice hangs off, and the temptation was to pick one.



Neither check subsumes the other, and the two failures they catch are genuinely different:

- **Check 1 catches a tip that never matched** — a stale client, a cached plan, a forged request body. It runs before any socket exists, so nothing is connected to, no credential is offered, and the refusal is a sentence naming both oids rather than git's `! [rejected] ... (stale info)`.
- **Check 2 catches the case that matters most** — someone else pushed between the plan being reviewed and it being submitted. This repository's remote-tracking ref is a *local cache*; it still holds the reviewed tip because nothing has fetched. Only the remote's own advertisement can see the other party's commit, so only git can refuse this one.

A version with only check 1 would hand an unverified oid to git anyway in the common case and would be worthless against the concurrent-push case. A version with only check 2 would open a socket for a request the server could already tell was wrong.

Why check 1 is not just `enforce_fresh`. ADR 0018's staleness gate already re-verifies the lease's `Precondition::RefAt` — **but only if it held at build time**, by design: a precondition that already failed when the plan was built is deliberately left to the executor's own guard so refusal wording stays per-operation. For every other operation that guard is git refusing. For a lease push it has to be this function, because "the precondition never held" is *exactly* the forged/stale case, and letting it fall through to `--force-with-lease` unchecked is the hole.

D3 — A lease that cannot be confirmed refuses; it never degrades to an unguarded force

Two ways the pre-flight can fail to confirm, and both refuse `409`:


Live refs/remotes/<remote>/<branch>	Decision
holds the reviewed oid	proceed
holds a different oid	refuse — name both oids, say a fetch is the remedy
does not exist	refuse — the tip cannot be confirmed
cannot be read (git did not run)	refuse 500 — D5's rule: an unread ref is evidence about nothing

The third row is the one that would be easiest to write wrong. Treating "no tracking ref" as "no lease to check" reads naturally and turns a lease into an unguarded force. It is pinned by its own test leg.

D4 — What a push did is observed from refs — and a cancelled push may not claim the remote is unchanged


`refs/remotes/<remote>/*` is listed before and after, and the difference is the answer, for success, failure and cancellation alike. That is ADR 0037 applied to a push, and it is cheap here because git updates the remote-tracking ref *only* when the remote reports the update accepted. It is also why the shared observation helpers moved into `planner::transfer` rather than being copied.

But the mirror image of ADR 0043's cancelled-fetch guarantee **does not hold**, and pretending otherwise would be the worst kind of comfortable lie:



A cancelled *fetch* can honestly say nothing arrived: the only machine involved is this one. A cancelled *push* cannot. So the terminal message states what was observed — the local remote-tracking ref did or did not move — and explicitly declines to conclude anything about the remote from it, ending with "Fetch to see where the remote actually is."

`honours_cancellation(PushBranch)` is therefore a promise that *the transfer stops*, never that nothing was published.



D5 — `--set-upstream` is reported only when it is observed



The flag says what was asked for. After a successful push that asked for one, the executor reads `<branch>@{upstream}` back out of the repository and the success sentence claims an upstream only if git actually recorded one; otherwise it says so.

This looks like belt-and-braces until you notice what the alternative fails at: a message built from the request would say "upstream set" for a git that quietly did not, and no test that only checks the sentence could tell the difference. The observation has its own paired positive/negative test against a real repository, and a mutation that replaced it with the plausible constant `origin/<branch>` is caught there and nowhere else.

(A footnote earned the hard way: `git rev-parse --abbrev-ref --quiet <b>@{upstream}` exits 128 for an unresolvable upstream but **echoes the spec back on stdout** while doing it. The flag is not used, so a failure leaves stdout empty.)

D6 — One progress parser for both directions, and Writing is a new tag rather than a reuse of Receiving

A fetch and a push print the same phase names for the work each side does; only which side does which work differs.




So `parse_progress` moved out of `planner::fetch` into `planner::transfer` and both executors call it. Two copies would drift, and nothing fails loudly when a progress bar is subtly wrong — which is precisely why it needs one owner.

`Writing` objects: is the one record shape a push prints and a fetch never does. Before this slice the parser did not know it, so a pushing user's progress stopped at `Compressing` and the whole transfer — the part that takes the time — reported nothing. It gets its **own** `TransferPhase::Writing` rather than being folded into `Receiving`, because a UI saying "receiving" while a user pushes is telling them the wrong story about which way their data is going.

D7 — `/api/push` keeps its `text/plain` contract; the failure taxonomy stays server-internal until the UI lands

Fetch and pull answer typed JSON (`FetchError` , `PullError`). Push does not, and that is a decision rather than an omission: `/api/push` has always answered `text/plain` , **the live frontend renders that body to the user verbatim**, and no client parses it. Promoting it to JSON in this slice would put raw JSON on an iPad screen for zero benefit, because the client that would parse it is M2.20g's (#232) — the same slice that designs the force-push confirmation ceremony.

The classification is still real and still load-bearing: an internal `PushFailure` enum picks the status code and the actionable sentence appended to git's own words.



Ordering is deliberate: `stale info` is checked **first**, because a rejected lease also prints `failed to push some refs` , and "your lease lost and the remote is untouched" is the actionable half. `409` for the two "the remote moved under you" cases matches every other staleness refusal in this server and matches the remedy (fetch, look, resubmit).


D8 — The request may default; the reviewed operation may not

`PushRequest` gives `set_upstream` and `force` serde defaults, so `{"branch": "main"}` — every client written before this slice, including the live frontend — keeps getting a plain fast-forward push, byte for byte. That defaulting lives in the request and **stops there**: `ForcePublish` still derives no `Default` and `GitOperation::PushBranch` 's fields still carry no `#[serde(default)]` , so the handler's `force.unwrap_or(ForcePublish::None)` is a construction site stating its posture out loud, exactly as #227 intended.

The rule that makes this safe to allow at all: **a default may only point at less capability**. Absent means "do less", never "force".

D9 — "Never force-pushes" becomes "no undo force-pushes"


Three sites said git-vista never force-pushes. The invariant they were describing is real, narrower, and now has to be said precisely, because the app *can* force-publish.



Fixed at `git-vista-core/src/activity.rs` (the `Undoable` doc and the `reset-undo` comment) and `git-vista/src/dialogs/confirm.rs` (the user-visible undo warning, which now reads "an undo never force-pushes ... Rewriting what origin has is a separate, explicit force-publish"). `docs/RELEASE_GATES.md` gained a clause distinguishing *this repository's* branch protection from anything the app does.

The issue also named `git-vista-protocol/src/plan.rs:242` as a fourth site. **That citation is wrong on this branch, not merely line-drifted:** the file contains no such text anywhere, and `RiskLevel::Remote`'s doc — the comment the issue meant — already says the correct thing ("A force push is *not* this tag: `git-vista` cannot express an unguarded force at all"). It was left alone.

Alternatives considered



Rely on git's `--force-with-lease` alone; add no server check. Rejected. Git's check is authoritative about the remote and cannot be replaced — but it only runs *after* a socket is open and a credential has been offered, and it says nothing about a tip this server could already see was wrong. A forged `expected_remote_tip` would reach a real remote before being refused, and the

refusal a user reads would be `! [rejected] main -> main (stale info)` rather than a sentence naming what did not match.

Rely on the server's check alone; drop `--force-with-lease` and use `--force`. Rejected, emphatically, and it is worth writing down *why* it is tempting: the server check looks like it does the same job, and the argv would be simpler. It is not the same job. The remote-tracking ref is a local cache of what this repository last saw; the whole scenario `force-with-lease` exists for — a colleague pushing between review and submit — is invisible to it. This alternative is exactly the "force push with a reassuring label" `ForcePublish` was designed to make unrepresentable. The mutation that implements it (`--force-with-lease=...` → `--force`) is caught by four separate tests, one of which is a behavioural test asserting the other party's commit is still on the remote.

Re-read the remote at execution time and lease against *that*. Rejected. It would assert "the remote has not moved since a millisecond ago", which is always true and protects nobody. The value that makes a lease mean anything is the one the *user reviewed*, which is why it lives in the operation and is bound by the plan's hash. (This is ADR 0039's reasoning, restated because it is exactly what an implementer of the execution layer is tempted to "fix".)

Let `enforce_fresh's Precondition::RefAt` be the only server-side lease check. Rejected — see D2. It is skipped precisely in the case that needs it.

Build the flags inline in `exec_push`. Rejected — see D1. The property becomes unassertable over the input space, and a future variant fails quietly.

Promote the failure taxonomy to a typed JSON body now. Deferred, not rejected — see D7. It ships with the client that parses it.

Give push its own progress parser. Rejected — ADR 0044's D1 reasoning, applied to a parser rather than a spawn. Two copies of a vocabulary that must match git's output byte for byte will drift, and a wrong progress bar fails silently.

Fold Writing into Receiving as a generic "transferring" phase. Rejected. The tag's whole job is to say what git is doing; a UI that says "receiving" during a push is wrong in the direction users notice.

Journal every successful push, as the old executor did. Rejected. The old `exec_push` journaled unconditionally on exit 0, so an "Everything up-to-date" push left an entry claiming a change. Journaling per *observed moved ref* matches `planner::fetch` and makes the feed auditable on the day someone is trying to understand a force-publish. A paired negative pins that an up-to-date push journals nothing.

Require `set_upstream` and `force` in `PushRequest` with no defaults, mirroring the operation vocabulary. Rejected. It would break every existing client for no safety gain: the guarantee #227 bought is about the *reviewed operation*, which still has no defaults, and a request default that points at less capability cannot smuggle a force past anybody.

Consequences

Good.

- The capability `ForcePublish` has described since #227 is reachable, and the guarantee it encodes now survives all the way to an argv rather than stopping at the type boundary.
- A push reports live transfer progress, including the phase where its objects actually leave the host, and can be cancelled — the last of the three remote operations to get both.
- The remote trio share one spawn, one progress parser, one ref-observation helper, and one set of #228 hardening. There is no second place for a credential to leak from.
- The activity feed distinguishes "pushed", "pushed with `--set-upstream`" and "force-published (lease) over `<tip>`", which is the difference a reader needs on the one day they care.

Costs and things a reader should know.

- `/api/push` answers prose, not a typed body. A client cannot branch on the failure kind yet. Deliberate (D7), and #232's to close.
- **A cancelled push cannot promise the remote is unchanged** (D4). The message says so; there is no way to make it stronger without a round trip this server has stopped making.

- **The kill reaches the direct child only.** ADR 0043's grandchild limitation is inherited unchanged: a transport helper git spawned may briefly outlive the SIGKILL.
- **Progress parsing is English-only.** git's phase names are gettext-translated and `SandboxedCommand` exposes no `env` setter by construction (#228's C10 hazard #1), so `LC_ALL=C` cannot be forced here. Under a non-English locale a push degrades to no progress bar, never a wrong one — ADR 0043's accepted gap, inherited.
- **Push tests need a real git:// remote.** A filesystem-path remote cannot receive a push under the sandbox at all (receive-pack's quarantine migration is a cross-directory rename and the shim withholds `LANDLOCK_ACCESS_FS_REFER`), so the behavioural suite spins a `git daemon` on the arbitrated port 9418 and serializes on `test_ports::PortClaim`. This is a real cost in test wall-clock, paid because the alternative is not testing a push.
- **The two ref listings run in the operation's tier, not the tightest one that would do.** `transfer::remote_tracking_refs` takes the caller's `NetworkNeed` and a push passes `Remote`, so the `git for-each-ref` before and after the transfer lands in `Tier::Network` — no bwrap namespaces, git's ports reachable — where `NetworkNeed::Local` would put it in `Tier::Strict`. This is inherited behaviour, not something #231 introduced: the helper came from `planner::fetch` (#229) already shaped this way, and a fetch and a pull do the same. It is reported rather than changed for two reasons. The exposure is not the one ADR 0044 §4 found on the pull path — that was about **hooks**, which `HookMode::Run` executes in every tier, and `for-each-ref` runs none and execs nothing. And tightening it would change fetch and pull as well, on a code path with no probe: the namespace test ADR 0044 uses works because a hook can `readlink /proc/self/ns/net`, and a command that runs no hooks offers no such observation, so the change could not be proved to have happened. Worth doing as its own slice, with `need` removed from the helper's signature the way #230 removed it from `unmerged_paths` — a structural proof rather than a test — not smuggled in here untested.

Testing, and how each claim was made to fail

Every mechanism below was broken on purpose and the run repeated; the named test is the one that went red. A test that stays green when its mechanism is deleted is worse than no test, and this repository has now found twelve of those — the last two in this slice's own cancellation wording, recorded under "The second review round" below.

Mutation	Caught by
the lease flag is never built	<code>push::only_a_lease_push_builds_a_force_flag_and_it_names_the_reviewed_tip ;</code> <code>push_suite::a_correct_lease_force_publishes_and_a_plain_push_of_the_same_branch_does_not</code>
--force-with-lease=... replaced by a bare -- force	<code>push::no_push_argv_can_carry_a_bare_force ;</code> <code>contract_suite::only_planner_push_builds_a_push_argv_and_it_can_only_build_a_leased_force ;</code> <code>push_suite::a_lease_lost_to_a_concurrent_push_is_refused_and_the_remote_keeps_the_other_commit</code> (the behavioural one — the other party's commit is destroyed)
the pre-flight lease check is removed	<code>push_suite::a_lease_tip_that_does_not_match_the_tracking_ref_never_reaches_the_remote ;</code> <code>contract_suite::every_push_combination_reaches_a_real_executor</code>
--set-upstream is never built	<code>push::set_upstream_is_present_exactly_when_requested ;</code> <code>push_suite::set_upstream_is_recorded_and_only_when_asked</code>
the Writing phase is dropped from the parser	<code>transfer::every_real_push_progress_record_shape_parses ;</code> <code>transfer::writing_and_receiving_are_not_the_same_phase ;</code> <code>push_suite::a_push_publishes_transfer_progress_including_the_writing_phase</code>
the journal write is removed	<code>push_suite::a_fast_forward_push_reaches_the_remote_and_journals_the_mode</code>
<code>child.start_kill()</code> is deleted	<code>push_suite::cancelling_a_running_push_kills_the_child_and_the_remote_does_not_move ;</code> <code>push_suite::a_cancelled_push_stream_leaves_a_signalled_child_not_an_exited_one</code>
the pre-spawn cancel latch is removed	<code>push_suite::a_cancel_that_lands_before_execution_stops_the_push_starting</code>
<code>upstream_of</code> returns the plausible constant <code>origin/<branch></code>	<code>push_suite::the_upstream_is_read_from_the_repository_not_assumed</code>
the cancelled-push message claims the remote is unchanged	<code>push_suite::cancelling_a_running_push_kills_the_child_and_the_remote_does_not_move</code>
the cancelled-push message's non-empty arm is garbled, or both arms collapse to one	<code>push::a_cancelled_push_says_which_of_the_two_things_it_observed ;</code> <code>push_suite::a_cancel_that_lands_after_the_ref_moved_reports_what_the_remote_accepted</code> — added by the second review round below; before them, every cancellation fixture blocked before any ref update, so <code>updated</code> was always empty and this arm never ran
<code>journal_updates</code> drops (or unconditionally appends) its " (the push was then cancelled)" tail	<code>push_suite::a_cancel_that_lands_after_the_ref_moved_reports_what_the_remote_accepted</code> (drops); <code>push_suite::a_fast_forward_push_reaches_the_remote_and_journals_the_mode</code> (unconditional) — added by the second review round below
<code>/api/push</code> ignores the request's force (a silent downgrade of every approved force-publish to a fast-forward)	<code>handlers::branch::tests::the_request_reaches_the_operation_whole ;</code> <code>...::every_force_mode_the_wire_can_carry_is_exercised_by_the_mapping_table</code> — added by the first review round below; before it, this mutation left all ~700 tests green
<code>/api/push</code> ignores the request's <code>set_upstream</code>	<code>handlers::branch::tests::the_request_reaches_the_operation_whole</code>
the <code>journal_unobserved</code> write is removed	<code>push_suite::a_push_whose_outcome_cannot_be_observed_is_journaled_as_unknown</code> — added by the first review round below; before it, this call had no coverage at all
<code>TransferPhase::Writing</code> 's wire spelling drifts	<code>operation::tests::transfer_phase_wire_names_are_stable_snake_case</code> — added by the first review round below; the variant shipped with no pinned wire name

The first review round, and the three holes it found

The first pass of this slice proved `planner::push` exhaustively and left three gaps that only mutation could surface. They are recorded here rather than quietly fixed, because the *shape* of each is the reusable lesson.


1. **A proven executor reached through an unproven mapping.** `handlers::branch::push_branch` destructured `PushRequest` and built `GitOperation::PushBranch` inline, and nothing tested that mapping. Replacing `force.unwrap_or(ForcePublish::None)` with a bare `ForcePublish::None` — an endpoint that silently downgrades every approved force-publish — left the entire crate green. Every property `push_argv` proves is a property of a function that was, on that mutation, never reached with a lease. The fix is structural as well as test-side: the mapping moved into `push_operation`, which **consumes the request by value and deconstructs it exhaustively**, so the handler has no field left to drop, and the mapping is asserted against *literal* operations over the whole request space (a table whose right-hand side re-derived values from the request would agree with any mapping, including one that swapped the two flags).
2. **A journal write with no coverage.** `push::journal_unobserved` — the one exit path where `git push` ran and `refs/remotes/<remote>/*` could not be re-read — had no test. Deleting the call was invisible. That is the worst place in this slice for the feed to go quiet: a fetch whose outcome is unobservable can be re-observed later from this machine, and a push's cannot, because what changed is on the remote. `push_suite::a_push_whose_outcome_cannot_be_observed_is_journaled_as_unknown` fills it, using `fetch_suite`'s lever — a `reference-transaction` hook that corrupts `packed-refs` once the tracking-ref update commits (verified: git 2.43.0 runs that hook for a *push*'s tracking-ref transaction, and `for-each-ref` then exits 128 while the loose ref stays on disk). The premise is asserted three ways so the entry cannot be passing over an early failure.
3. **A new wire variant with no pinned spelling.** `TransferPhase::Writing` was added to a `#[serde(rename_all)]` enum whose contract test is a *list*, and a list stops covering an enum the day it grows. The list is now backed by a census through an exhaustive `match`, so a seventh variant is a compile error there, and each spelling is asserted in both directions — a client reads these as well as writes them.

The second review round: half of cancellation was never exercised

A later anti-vacuity pass found that D4's careful two-branch cancellation wording had only **one** branch under test. Every cancellation fixture in `push_suite` hangs the remote's `pre-receive` hook, which by construction runs *before* any ref update, so `updated` was empty every time a test cancelled a push. The empty arm ("this repository never saw the remote accept it — fetch to see where the remote actually is") was well covered; the non-empty arm ("cancelled after N remote-tracking ref(s) had already been updated, so that much was accepted by the remote") and `journal_updates`' matching " (the push was then cancelled)" tail had **zero** coverage. Rewriting the non-empty sentence, or swapping the two arms outright, left all ~700 tests green.

That is the worst branch in this slice to lose, because it is the one sentence that tells a user their force-publish **partly landed** — the case where the remote has already moved and this process was killed before it could finish saying so.

Closing it needed a lever no remote-side hook can provide. `git push` does not call `transport_update_tracking_ref` until `push_refs` has returned, and `push_refs` does not return until `finish_connect` has reaped `receive-pack` — so a push hung by *either* `pre-receive` or `post-receive` has a tracking ref that has not moved. The hang therefore goes in the **pushing** repository: a `reference-transaction` hook that sleeps on `committed`, i.e. once `refs/remotes/origin/main` is durable and unlocked and the push is still alive to be killed. That is exactly D4's window, reproduced on demand:



Five legs keep the new test honest, and each was proven by mutation: the tracking ref must actually reach the pushed tip (or it is the empty case again), the child must still be alive and the driver unanswered at that instant (or the cancel never reaches the cancelled path — neutering the hook's condition makes the test fail *there*, not silently pass as a success), the driver must answer within the promptness budget with ~20 s of hook sleep still owed (deleting `child.start_kill()` fails here), the message must carry the non-empty phrase and **not** the empty one, and the remote's own `rev-parse` must agree that it accepted the update — so "accepted by the remote" is checked against the remote rather than against the same diff that produced the sentence.

The journal tail is paired in both directions: the cancelled push must carry it, and `a_fast_forward_push_reaches_the_remote_and_journals_the_mode` now asserts a completed push does **not**, so an unconditional tail fails too. Pluralisation and the count get a pure test (`push::a_cancelled_push_says_which_of_the_two_things_it_observed`), which also asserts each arm's discriminating phrase is absent from the other.

The reusable lesson: a fixture chosen for one property silently fixes the value of another. `pre-receive` was picked because it proves "the remote did not move", and that same choice pinned `updated` to empty in *every* cancellation test written afterwards. When a function branches on an observation, ask which branch the fixture makes unreachable — and build the second fixture for the other one.


Three structural notes about the suite itself:

- **The remote is the referee.** Every "was the remote protected?" assertion reads the bare repository's own `for-each-ref / rev-parse / merge-base --is-ancestor` with plain, unsandboxed git — never a status code, and never this repository's remote-tracking ref, which is a cache.

- **"Nothing was spawned" is an observed absence.** The pre-flight refusal tests use a path remote carrying a `pre-receive` hook that writes a sentinel file. The sentinel lives *inside* the served repository's tree, and that placement is load-bearing: the hook runs as a grandchild of the sandboxed push and inherits its Landlock ruleset, so a sentinel in the tempdir root cannot be written **even when the hook ran** — the first version of this suite had exactly that bug, and it made the assertions vacuous. The paired positive (`a_lease_that_matches_the_tracking_ref_is_let_through_the_pre_flight`) is what keeps it honest: it requires the sentinel to actually appear.
- **The force test has an anti-vacuity leg.** Before the lease push, the *same* diverged branch is pushed with `ForcePublish::None` and must be refused. Without it, the test would pass identically on a fixture where an ordinary fast-forward would have worked — proving nothing about forcing at all.

Reachability

Not a hypothetical concern here: #228 shipped a fully-tested harness with zero production callers, and this project has been paying attention since.



`/api/push` accepts `set_upstream` and `force` on the wire, so the lease path has a real caller and is not code awaiting a UI. The UI ceremony for choosing a force-publish is

232's; the capability is live and reachable today by any authenticated client.

Reachability is not only "is there a caller". The `push_operation` node above is drawn separately because that link is where this slice's first review round found the chain broken in a way a call-graph could not see: the caller existed, and dropped a field. A reachability argument has to cover *what arrives*, not just *that something arrives* — which is why the mapping is now a pure function with a literal-valued test rather than three lines inside a handler.

Annotations made by this branch

- `docs/SECURITY_MODEL.md` — "Remote and Forge Credentials" (push adds no new spawn; the same chokepoint, askpass hardening and redaction apply, proven by a real leaked-credential fixture on the push path) and "Operation Risk Classes" (the lease/CAS row moves from "typed, not yet executable" to executable, with both checks described).
- `docs/adr/README.md` — index row for this ADR; ADR 0039's row updated to say the force push is no longer unwired.

Signed: thomas2025 · 2026-08-02T16:03:35-04:00 **Amended (second review round — cancellation coverage):**
thomas2025 · 2026-08-02T20:57:42-04:00