

CLOUD-3 — #487: Push becomes a fold candidate, with the same care Pull got

Batch of 2026-08-26 · merge order 3 of 5 (after CLOUD-2 — same activity/journal subsystem; rebase on its landed format decision before you finalize).

```
task_id: gv-487-cloud-3
issue: 487
branch: cloud/487-push-fold
base: main          # rebase onto main AFTER CLOUD-2 lands, before opening your
PR
adr_number: 0086     # RESERVED — use only if your change turns contract-shaped; a
fold-candidate
                    # addition with tests is routine and needs NO ADR. If unused,
say so in the
                    # PR body; the number stays burned rather than reassigned.
sign_commits_as:
  name: Claude_Max
  email: 262510778+tom2025b@users.noreply.github.com
  # per-commit, ALWAYS: git -c user.name=Claude_Max -c
user.email=262510778+tom2025b@users.noreply.github.com commit ...
allowed_paths:
  - crates/git-vista-core/src/activity.rs
  - crates/git-vista-server/src/planner/push.rs
  - docs/adr/          # only if 0086 turns out needed
forbidden_paths:
  - crates/git-vista/src/**
  - ci/browser/**
deliverables:
  - branch pushed, PR opened with "Closes #487"
```

Environment truths — read before your first test run

- ~320 server tests fail in your container on unmodified main (no Landlock; sandbox tier refuses). Baseline first; only the diff is yours; both counts in the PR body.
- cargo build -p git-vista-server --bin gv-sandbox before any server test run.
- Browser leg unrun — say so in the PR body.

Truth-checked state (verified against main 682f3061, 2026-08-26)

- fold_ref_update_bursts at crates/git-vista-core/src/activity.rs:775, with the candidate gate at :780: matches!(e.kind, ActivityKind::Fetch | ActivityKind::Pull).
- push::journal_updates call sites at planner/push.rs:489/:505/:510 — the issue's : 684/:693 line numbers have drifted; the per-ref loop is in the function those calls reach. Open it and confirm the loop before building on it.

- The issue's survey stands: exactly two per-item journal loops exist (fetch — folded since #329 — and push), and the synthesized BranchDeleted loop is CORRECTLY per-item (N distinct user actions; its `old_oid` is what undo needs). Do not touch it.

The defect, plainly — and why it is latent

Push journals one entry per remote-tracking ref it moved, structurally identical to fetch — but `ActivityKind::Push` is not a fold candidate, so a push moving 4 refs renders 4 unfolded feed rows. Today the push endpoint pushes one named branch, so $N=1$ and nothing is wrong for the user. The fix is filed so the day a multi-ref push path arrives (`--all`, matching refspec, tags alongside), it does not become #329 with a different kind.

The job

1. Add `ActivityKind::Push` to the fold gate — **with the asymmetry Pull already carries**: `names_a_local_branch` exists because a pull's own branch movement is the row the user wants and must never be folded away. A push has the same asymmetry: remote-tracking bookkeeping is noise; anything naming a local branch is not. Read how Pull threads that exemption and give Push exactly the same treatment.
2. The issue's own caution: **"a pin would be asserting against a hypothetical" applied to the OLD state**. Once you make Push a candidate, the behavior is real and MUST be pinned: a multi-ref push burst folds; a push row naming a local branch survives folding. Build the multi-ref case in the test fixture even though production cannot emit it yet — the fold code cannot know that, and the test is about the fold.
3. The #485 per-ref `capture_refs` cost note: fetch's fix flows through the same `journal_app_event` → `journal::append` path. Confirm whether push already inherits the #485 batching on that path (read the landed #485 change); if it does, say so in the PR body; if it does not, that is a finding to REPORT in the PR body, not scope to absorb.
4. **Mutation-prove two different ways**: remove Push from the gate; then break the local-branch exemption. Red at different assertions, byte-identical restore verified.

Acceptance

1. Fold gate includes Push with the local-branch exemption, both pinned.
2. Mutation evidence in the PR body (two red assertion lines, verbatim).
3. `cargo fmt --all · clippy --all-targets -- -D warnings · core + server` suites zero new failures vs baseline (`cargo test -p git-vista-core` runs clean in a container — no sandbox dependency).
4. PR body: baseline counts, browser-leg-unrun line, the #485-inheritance answer, ADR 0086 used-or-not statement, your session tag.

Written by fable · 2026-08-26 · truth-checked against 682f3061 the same morning.