


ADR 0134 — Two censuses that must agree are checked against each other

- **Status:** Accepted — implemented, mutation-proved two ways per invariant, nine arms caught (five for the decision, four for the two inert guards grok found reviewing PR #724)
- **Date:** 2026-09-07
- **Issues:** #690 (two route censuses), #705 (the pre-session allowlist and its runtime)
- **Extends:** [ADR 0119](#) — "a list of known sites is not a fix, because that list was already incomplete twice — the safety has to live in the value," applied one level up: not to a list of call sites, but to two independently hand-maintained *descriptions of the same thing*, each individually complete and individually well-guarded, that must both change together
- **Builds on:** `route_authz.rs`'s existing route census and #703's `post_route_census`
- **Supersedes / superseded by:** —

The shape, in one sentence

When two artefacts describe the same underlying thing for different reasons, guarding each one against the *thing* is not enough — something must also check them against **each other**, or the first edit that satisfies one and forgets the other passes every test that exists.



Both censuses were always correct. Neither was ever wrong on its own. The defect lived in the *absence of an edge* between them.

Context


The two censuses

`crates/git-vista-server/src/route_authz.rs`'s `ROUTE_AUTHZ` classifies every route `main.rs`'s `api_router` registers by the authorization it must sit behind — `Unauthenticated`, `SessionRequired`, `SessionAndCsrf` — and pins a fixed `EXPECTED_ROUTE_COUNT`.

`crates/git-vista-server/src/planner/contract_suite.rs`'s `post_route_census` classifies every POST route as a git write that must reach the planner (`GitWrite(entry)`), a `NonGitWrite` (catalog, credential, auth, cancel), or a `ReadLike` POST — a read wearing a write's verb because the CSRF gate keys on the method.

Each has its own test proving it agrees with `main.rs` in both directions: nothing registered is unclassified, nothing classified has been quietly deleted. Each is strong. Nothing pointed from either to the other.

How the gap was found — #584 / PR #688



The hook knew about one table. It fired, ran the one test it knew, went green, and said nothing about the second table's existence. The local verification that ran alongside the edit could not have caught it either: `--bins` does not compile the integration-test target set, and the failure surfaced only in CI.

The author did nothing wrong. The process had no step at which the second table could have been discovered.

The same shape again, one layer down — #705

`route_authz.rs`'s `EXPECTED_UNAUTHENTICATED` pins the pre-session allowlist as three `(path, method)` pairs and presents itself as *exact*. `security.rs`'s `require_auth` is what actually enforces it. The two were written independently, and drifted in **shape**, not in content:

Before — the table and the runtime disagree in shape

EXPECTED_UNAUTHENTICATED

(path, method) pairs

GET /api/protocol

GET /api/session

POST /api/session

claims to
describe

session_exempt

path ==

NEGOTIATION_PATH

— every method —

|| (SESSION_PATH

&& GET|POST)

#705

After — both reason in pairs

EXPECTED_UNAUTHENTICATED

(path, method) pairs

unchanged

checked by
the_pre_session_exemption_is_method_qualified

session_exempt

(NEGOTIATION_PATH

&& GET)

|| (SESSION_PATH

&& GET|POST)

No bypass existed, and this ADR does not claim one.

`main.rs` registers only `get(protocol_info)` on that path, so `POST /api/protocol` ended at `405 Method Not Allowed` — the router refused it because no handler was there. That is a safe *accident*, not a guarantee: it holds only while nobody registers a write handler on the negotiation path. What was actually broken was the **audit**. A future `POST /api/protocol` could have been classified `SessionAndCsrft` in `ROUTE_AUTHZ`, satisfied every structural test in that file, and run with neither session nor CSRF checked.

The measured difference is exactly one status code, and it is the whole issue:


request, no session	before	after
<code>GET /api/protocol</code>	200 — exempt	200 — exempt (unchanged)
<code>POST /api/protocol</code>	405 — refused by the <i>router</i>	401 — refused by the <i>session gate</i>

A `405` there means the gate is open and only the missing handler is hiding it. The wire test asserts `401` specifically, rather than merely "not 2xx", because that is the only assertion able to tell the accident from the guarantee.

Decision

1. A third test reads both censuses directly and asserts their POST sets are identical

`route_authz_and_write_contract_agree_on_every_post_route`, in `planner/contract_suite.rs`, computes the POST-route set of `route_authz::ROUTE_AUTHZ` and the route set of `post_route_census()`, and panics naming the exact route *and which table is missing it*.



It reads the two tables **directly** rather than re-scanning `main.rs` a third way. A third scanner would be a third hand-maintained thing that could itself drift — the very failure this ADR exists to close, moved one step further out.

`ROUTE_AUTHZ`, its `Authz` enum (named because it appears in the table's element type, even though the test destructures it with `_`), and the `route_authz` module in `main.rs` became `pub(crate)` for exactly this. All remain `#[cfg(test)]`-gated at their module root.

One deliberate exception is mapped, not ignored:

`post_route_census`'s first row names the *handler* `create_session`, not a path, because session bootstrap is registered with a bare `.post(create_session)`. Its real route is `POST /api/session`, which is how `ROUTE_AUTHZ` names it, so the test maps across. A second such exception would mean the tables had stopped describing the same thing, and the comment says so.


2. The runtime pre-session exemption is method-qualified, and that shape is structural

`session_exempt` now names the same three pairs the table does. `the_pre_session_exemption_is_method_qualified` (in `route_authz.rs`, beside the table it defends) reads `security.rs`, splits the `session_exempt` expression on `||`, and requires **every disjunct to test a method as well as a path** — plus that each pinned path appears in the expression by its runtime constant, so renaming one and not the other cannot pass.

Checking the *shape* rather than the *count* is the point. Both sides counted three before the fix; a count check would have stayed green forever.

3. The `PostToolUse` hook is extended, not replaced

`route-census-check.sh` now fires on edits to `route_authz.rs`, `main.rs`, `contract_suite.rs` **and** `security.rs`, and runs four tests rather than one.



`contract_suite.rs` and `security.rs` are on the trigger list because the hook's whole purpose is to catch drift the moment *either side* is edited, not only when the router is. This is the fix for the failure #584 actually hit: the edit-time signal now covers the relationship, not just one endpoint of it.

4. A single source-of-truth table was considered and not built

The issue offered three directions. The single-source table — one row per route carrying both classifications — would work, but `ROUTE_AUTHZ` and `post_route_census` classify different things for different reasons (security posture vs. planner-funnel membership), are read by tests with different shapes, and carry failure messages tuned to what a maintainer must do next. Merging them is a larger, riskier refactor of two files to close a *discoverability* gap that the meta-census closes just as completely at a fraction of the risk. Nothing here forecloses it later: if a third census ever needs the same route set, that is the trigger to revisit, and this paragraph is the standing argument for doing so.

The doc-comment cross-reference (the issue's own weakest option) was rejected outright: a comment is exactly the fix that "looks read" without being enforced — the shape ADR 0119 already ruled out.

Consequences

- A route added to one census and not the other now fails **by name, in the same test binary as both tables**, rather than only in whichever CI job happens to exercise the table nobody thought to check.
- The hook catches the exact #584 failure at edit time, not merge time.

- `GET /api/protocol` is unchanged. `HEAD /api/protocol` is a **deliberate behaviour change**: Axum serves `HEAD` implicitly from a `get(...)` route, so it was previously pre-session and now requires a session like any other read. Nothing in this codebase issues one. Pinning a fourth pair instead would need a `HEAD` row in `ROUTE_AUTHZ` that `main.rs` never registers and the route census would then reject — stating the consequence is cheaper and more honest than bending the census around it.
- `ROUTE_AUTHZ`, `Authz` and the `route_authz` module are `pub(crate)` purely so the cross-check can read them. Nothing outside this crate's test code is expected to use the wider visibility.
- **The next hand-maintained pair with this shape should get the same treatment** rather than a bespoke fix. Two descriptions of one thing, each guarded only against the thing, is now a recognised defect shape in this project, and a cross-check between them is the default answer.

A note on how this landed

This branch originally hoisted `contract_suite.rs`'s table into its own `KNOWN_POST_ROUTES` const. While it sat unmerged, #703 landed a strictly better structure on `main` — `post_route_census()` returning typed `(path, handler, PostKind)` rows, with the git-write distinction in the *type* rather than in a comment, and carrying #87's three new bisect routes. The merge was resolved by taking `main`'s version of that file wholesale and rebuilding the meta-census on top of it, rather than stitching two tables together. The cross-check is the decision; which table it reads is not.

Mutation proof

Five arms through `failure-atlas`'s `mutation_check`, `run_key` `gv-lane-3-690-705`, every baseline green and the working tree clean (`source_working_tree_dirty: false`). Two arms per invariant, chosen to fail *differently* rather than to break the same thing twice.


#	invariant	mutation	verdict
410	#690 cross-check, A-not-B	remove <code>/api/rescan</code> from <code>post_route_census()</code> , leave it in <code>ROUTE_AUTHZ</code> — the exact #584 shape	caught — panics at <code>contract_suite.rs:3540</code> naming <code>/api/rescan</code> as present in <code>ROUTE_AUTHZ</code> , absent from <code>post_route_census()</code>
411	#690 cross-check, B-not-A	remove <code>/api/rescan</code> from <code>ROUTE_AUTHZ</code> , leave it in <code>post_route_census()</code>	caught — panics at <code>contract_suite.rs:3550</code> , the <i>opposite</i> <code>difference()</code> branch, a genuinely disjoint assertion

#	invariant	mutation	verdict
414	both censuses still bind to the router	add <code>POST /api/rescan-twice</code> to <code>main.rs</code> , update neither table	caught — <code>every_registered_route_is_classified</code> and <code>every_git_write_route_reaches_the_planner</code> both red (left: 49, right: 48)
412	#705 shape guard	revert <code>session_exempt</code> to the path-only clause	caught twice, differently — the structural test fails on clause shape; the wire test fails left: 405, right: 401
413	#705 value guard	keep it method-qualified but wrong: <code>Method::GET</code> → <code>Method::PATCH</code>	caught — the structural test correctly passes (still pair-shaped) while <code>the_negotiation_get_stays_pre_session</code> fails left: 401, right: 200

Arms 412 and 413 are the pair that matters most: they prove the structural test and the wire test cover genuinely different properties. 413 is green on the structural test and red on the wire

test, so neither is standing in for the other.

Arms 410, 411 and 414 together prove the property the issue actually asked for, which a one-sided check cannot give:



Satisfying one census leaves the build red until the other is updated too. That is the whole issue, and it is now a measured property rather than a claim.

The review found this same shape inside the fix — twice

PR #724's cross-family review (grok) found two guards **in this change** that could pass while checking nothing. Recording them here rather than quietly fixing them, because the recurrence is the lesson: the defect this ADR names is easy to reintroduce *while writing the fix for it*.

**The defect
shape**
a guard that
cannot fail

```
graph TD; A["The defect shape  
a guard that cannot fail"] --> B["Found in the code  
two censuses, no edge"]; A --> C["Found in the census hook  
libtest filter matching  
nothing exits 0"]; A --> D["Found in the shape guard  
naive scan to first ;  
truncates silently"]; A --> E["Found in the remap  
'only one exception'  
said in a comment"];
```

**Found in the
code**
two censuses, no
edge

**Found in the
census hook**
libtest filter
matching
nothing exits 0

**Found in the
shape guard**
naive scan to
first ;
truncates silently

**Found in the
remap**
'only one
exception'
said in a
comment

1. The shape guard read the expression with a naive scan to the first `;`. Its own comment asserted the expression "contains no string literals or nested statements" — a claim about code nobody has written yet, not a check on it. A `;` inside a string literal in a later clause truncates the slice, and the truncated head still contains both `||` arms, both `Method::` tests and both path constants, so **every assertion passes while a trailing `|| path == "/api/x"` goes entirely unread.** `session_exempt_expression()` now tracks string literals and bracket depth the way `strip_line_comments` already did — the sturdier tool was in the same file all along — and returns `None` rather than a truncated slice. It also *refuses loudly* on the two constructs it does not model (char literals, block comments) instead of assuming they will never appear, which is the assumption that made the first version inert.

2. The `create_session` remap's "keep this the only exception" was a comment. An *unmapped* extra handler-named row already failed the set difference; a second *mapped* exception would have stayed green. The exception set is now asserted — every row names a path except exactly one known handler-named row.

3. Still unproved, and named rather than hidden: the census hook's own hardening is verified by inspection, not by a test that can go red, because nothing in this repository tests `.claude/hooks/*.sh` at all. That is the one guard in this change whose correctness does not rest on a mutation proof.

The four review arms

#	invariant	mutation	verdict
424	the shape guard reads the <i>whole</i> expression	add a <code>;-</code> bearing string literal to a clause, then append <code>\\ \\ </code> path <code>==</code> <code>"/api/evil"</code> — the exact silent-truncation case	caught — and the panic prints the full expression <i>including</i> the trailing clause, proving the scan passed the string
425	it refuses what it cannot model	introduce a char literal <code>(path.starts_with('/'))</code>	caught — the refusal fires, at a different assertion and message than 424
426	a second handler-named row cannot slip in	rename <code>/api/rescan</code> to <code>rescan</code> in <code>post_route_census()</code>	caught — by the <i>new</i> assertion, which fires before the set difference, so it is live rather than shadowed
427	the exception filter is the right way round	invert <code>!route.starts_with('/')</code>	caught — a different failure mode again

`run_key` `gv-lane-3-724-review`, every baseline green, working tree clean.