

云计算实验一报告

作业 1:

```
Xshell 7 (Build 0137)
Copyright (c) 2020 NetSarang Computer, Inc. All rights reserved.

Type 'help' to learn how to use Xshell prompt.
[!C:\~!]$ ssh root@113.31.109.173

Connecting to 113.31.109.173:22...
Connection established.
To escape to local shell, press 'Ctrl+Alt+J'.

[WARNING!] The remote SSH server rejected X11 forwarding request.
Activate the web console with: systemctl enable --now cockpit.socket

[root@10-23-14-164 ~]# useradd tommy
[root@10-23-14-164 ~]# ls /home
tommy
[root@10-23-14-164 ~]# passwd tommy
Changing password for user tommy.
New password:
BAD PASSWORD: The password is shorter than 8 characters
Retype new password:
passwd: all authentication tokens updated successfully.
[root@10-23-14-164 ~]# usermod -aG wheel tommy
[root@10-23-14-164 ~]# exit
logout

Connection closed.

Disconnected from remote host(113.31.109.173:22) at 11:45:33.

Type 'help' to learn how to use Xshell prompt.
[!C:\~!]$ ssh tommy@113.31.109.173

Connecting to 113.31.109.173:22...
Connection established.
To escape to local shell, press 'Ctrl+Alt+J'.

[WARNING!] The remote SSH server rejected X11 forwarding request.
Activate the web console with: systemctl enable --now cockpit.socket

[tommy@10-23-14-164 ~]$
```

作业 2:

如果是直接查询文件中出现的“def”结果是不对的(最后一行那个 default 也被查到了)

```
[tommy@10-23-14-164 ~]$ grep def model.py
def __init__(self, path, batch_size, resume):
def create_tf_placeholders(self):
def create_tf_variables(self):
def init_hyper_param(self):
def get_filter(self, layer_num, layer_name):
def get_strides(self, layer_num):
def get_bias(self, layer_num, value=0.0):
def l2_loss(self):
def build_graph(self):
def add_summaries(self):
def save_model(self, sess, saver):
def restore_model(self, sess, saver):
def get_summary_writer(self, sess):
def train(self, epochs, thread='false'):
def test(self):
type=lambda x: x != 'False', default=True,
```

然后我采用了两种形式的正则表达式实现了需要的效果:

```
[tommy@10-23-14-164 ~]$ grep "def.*:" model.py
def __init__(self, path, batch_size, resume):
def create_tf_placeholders(self):
def create_tf_variables(self):
def init_hyper_param(self):
def get_filter(self, layer_num, layer_name):
def get_strides(self, layer_num):
def get_bias(self, layer_num, value=0.0):
def l2_loss(self):
def build_graph(self):
def add_summaries(self):
def save_model(self, sess, saver):
def restore_model(self, sess, saver):
def get_summary_writer(self, sess):
def train(self, epochs, thread='false'):
def test(self):
```

```
[tommy@10-23-14-164 ~]$ grep "def " model.py
def __init__(self, path, batch_size, resume):
def create_tf_placeholders(self):
def create_tf_variables(self):
def init_hyper_param(self):
def get_filter(self, layer_num, layer_name):
def get_strides(self, layer_num):
def get_bias(self, layer_num, value=0.0):
def l2_loss(self):
def build_graph(self):
def add_summaries(self):
def save_model(self, sess, saver):
def restore_model(self, sess, saver):
def get_summary_writer(self, sess):
def train(self, epochs, thread='false'):
def test(self):
```

作业 3:

重命名算是 mv 命令的另一个功能了:

```
[tommy@10-23-14-164 ~]$ ls
a-content.txt  model.py
[tommy@10-23-14-164 ~]$ mv a-content.txt a-content.csv
[tommy@10-23-14-164 ~]$ ls
a-content.csv  model.py
[tommy@10-23-14-164 ~]$ cat a-content.csv
line 1
line 2
line 3
line 4
line 5
line 6
line 7
line 8
line 10
[tommy@10-23-14-164 ~]$
```

作业 4:

这里我的思路是取 model.py 的前 400 行后再将其中靠后的那 101 行取出来 (这

样取出来的是 300-400 行, 如果是 tail -n 100 取出来的则是 301-400 行)

```
[tommy@10-23-14-164 ~]$ head -n 400 model.py | tail -n 101 | grep "def "
def restore_model(self, sess, saver):
def get_summary_writer(self, sess):
def train(self, epochs, thread='false'):
[tommy@10-23-14-164 ~]$
```