

云计算实验五报告

作业 1:

```
[root@10-23-157-103 ~]# rpm -ivh clickhouse-common-static-22.3.6.x86_64.rpm
Verifying... ##### [100%]
准备中... ##### [100%]
正在升级/安装...
 1:clickhouse-common-static-0:22.3.6##### [100%]
[root@10-23-157-103 ~]# rpm -ivh clickhouse-client-22.3.6.noarch.rpm
Verifying... ##### [100%]
准备中... ##### [100%]
正在升级/安装...
 1:clickhouse-client-0:22.3.6-1 ##### [100%]
[root@10-23-157-103 ~]# clickhouse-client --host=10.23.164.123 --port=9000 --user=admin --password=Test1234
ClickHouse client version 22.3.6.5 (official build).
Connecting to 10.23.164.123:9000 as user admin.
Connected to ClickHouse server version 22.3.6 revision 54455.

uck-p8lyi641pyt-ck-0-1 :)
```

作业 2:

```
uck-p8lyi641pyt-ck-0-1 :) SELECT * FROM ck_test.regression;

SELECT *
FROM ck_test.regression

Query id: 3028006f-3f2d-4474-ba5b-d60b2c9d0557



| id | y  | x1 | x2 |
|----|----|----|----|
| 1  | 5  | 2  | 3  |
| 2  | 10 | 7  | 2  |
| 3  | 6  | 4  | 1  |
| 4  | 8  | 3  | 4  |



4 rows in set. Elapsed: 0.005 sec.

uck-p8lyi641pyt-ck-0-1 :)
```

在快要交作业时我才发现这里还需要\q 之后的结果:

```
uck-p8lyi641pyt-ck-0-1 :) SELECT * FROM ck_test.regression;

SELECT *
FROM ck_test.regression

Query id: 31fcb17f-1079-417e-a28b-21b3965f9773



| id | y  | x1 | x2 |
|----|----|----|----|
| 1  | 5  | 2  | 3  |
| 2  | 10 | 7  | 2  |
| 3  | 6  | 4  | 1  |
| 4  | 8  | 3  | 4  |



4 rows in set. Elapsed: 0.005 sec.

uck-p8lyi641pyt-ck-0-1 :) \q
Bye.
[root@10-23-157-103 ~]#
```

作业 3:

```
[root@10-23-157-103 ~]# python3 insertTable.py
[root@10-23-157-103 ~]# touch selectTable.py
[root@10-23-157-103 ~]# nano selectTable.py
[root@10-23-157-103 ~]# python3 selectTable.py
File "selectTable.py", line 8
    print (row[0], "\t", row[1], "\t", row[2], "\t", row[3])
    ^
IndentationError: expected an indented block
[root@10-23-157-103 ~]# nano selectTable.py
[root@10-23-157-103 ~]# python3 selectTable.py
ID NAME ADDRESS SALARY
1 Paul California 20000.0
2 Allen Texas 15000.0
3 Eric Florida 25000.0
[root@10-23-157-103 ~]#
```

作业 4:

```
uck-p8lyi641pyt-ck-0-1 :) SELECT stochasticLinearRegression(0.01, 0.1, 2)(y, x1, x2) FROM ck_test.regression;
SELECT stochasticLinearRegression(0.01, 0.1, 2)(y, x1, x2)
FROM ck_test.regression
Query id: 3d777516-83fd-4b00-83df-3e18095a2c5d
[stochasticLinearRegression(0.01, 0.1, 2)(y, x1, x2)
[0.019561782943289238,0.020012289061927653,0.019971629018659252]]
1 rows in set. Elapsed: 0.007 sec.
uck-p8lyi641pyt-ck-0-1 :)
```

```
[stochasticLinearRegression(0.01, 0.1, 2)(y, x1, x2)
[0.019561782943289238,0.020012289061927653,0.019971629018659252]]

1 rows in set. Elapsed: 0.006 sec.

uck-p8lyi641pyt-ck-0-1 :) WITH (SELECT state FROM linear_model) AS model SELECT evalMLMethod(model, x1, x2) FROM ck_test.regression
WITH (
    SELECT state
    FROM linear_model
) AS model
SELECT evalMLMethod(model, x1, x2)
FROM ck_test.regression
Query id: 7760527e-1294-425d-a6ef-e4dd31a8897a
[evalMLMethod(model, x1, x2)
3.8402
8.365400000000001
4.7954
5.3864]

4 rows in set. Elapsed: 0.006 sec.
uck-p8lyi641pyt-ck-0-1 :)
```