

Unsupervised Learning for Time-series: Extracting Patterns in Brain Recordings

Thomas Moreau – Parietal – Inria



Who am I?

2014-2017: PhD – ENS Cachan (N. Vayatis & L. Oudre)

Applied Maths

Distributed optimization
Unsupervised learning
Representation learning

Healthcare Data

Gait analysis
Oculomotor recordings

2018-2019: Post-doc – Inria (Parietal)

Convolutional dictionary learning for MEG

⇒ **Local structure** analysis for signals

2019-∞: CR – Inria (Parietal)

Unsupervised learning for brain signals

⇒ Finding structure in brain recordings!

Unsupervised Learning for Electrophysiology


Convolutional Dictionary Model

References




K-Complex

Sleep Spindle





1 s

[S. Cole, B. Voytek (2017) Trends in Cognitive Sciences]




[Dupré la Tour, Tallot, Grabot, Doyère, van Wassenhove, Grenier, Gramfort
(2017) PLOS Computational biology]

Neural signals
exhibit diverse and
complex
morphologies



1 s

[S. Cole, B. Voytek (2017) Trends in Cognitive Sciences]



[Dupré la Tour, Tallot, Grabot, Doyère, van Wassenhove, Grenier, Gramfort
(2017) PLOS Computational biology]

K-Complex

Neural signals
exhibit diverse and
complex
morphologies

Sleep Spindle




25 μ V

Waveform shape is related to disease
e.g. Parkinson

[Jackson et al. (2019)]

1 s

[S. Cole, B. Voytek (2017) Trends in Cognitive Sciences]



[Dupré la Tour, Tallot, Grabot, Doyère, van Wassenhove, Grenier, Gramfort
(2017) PLOS Computational biology]



Gamma
(< 25 Hz)



Beta
(12 - 25 Hz)



Alpha
(8 - 12 Hz)




Theta
(8 - 12 Hz)



Delta
(1 - 4 Hz)

Linear filtering

After Linear filters, everything looks like a sinusoid.



⇒ Lose the asymmetry and the shape information.

Fourier Fallacy

” Even though it may be possible to analyze the complex forms of brain waves into a **number of different sine-wave** frequencies, this may lead only to what might be termed a “**Fourier fallacy**”, if one assumes **ad hoc** that all of the necessary frequencies actually occur as periodic phenomena in **cell groups** within the brain.”


[Jasper (1948)]

Fourier Fallacy


”Even though it may be possible to analyze the complex forms of brain waves into a **number of different sine-wave** frequencies, this may lead only to what might be termed a “**Fourier fallacy**”, if one assumes **ad hoc** that all of the necessary frequencies actually occur as periodic phenomena in **cell groups** within the brain.”

[Jasper (1948)]

Temporal pattern 11





Power spectral density 11



Fourier Fallacy


”Even though it may be possible to analyze the complex forms of brain waves into a **number of different sine-wave** frequencies, this may lead only to what might be termed a “**Fourier fallacy**”, if one assumes **ad hoc** that all of the necessary frequencies actually occur as periodic phenomena in **cell groups** within the brain.”

[Jasper (1948)]




Can't we learn the waveforms?


Local structure in signals




Local structure in signals



Local structure in signals



Local structure in signals



Local structure in signals



Local structure in signals





Local structure in signals





$$\boxed{x^n}[t] = \sum_{k=1}^K (\boxed{z_k^n} * \boxed{d_k})[t] + \varepsilon[t]$$

Data:




Data:



What to do
in the case of
multivariate
signals?


EM wave diffusion

- ▶ Recording here with 8 sensors




EM wave diffusion

- ▶ Recording here with 8 sensors
- ▶ EM activity in the brain




EM wave diffusion

- ▶ Recording here with 8 sensors
- ▶ EM activity in the brain
- ▶ The electric field is spread **linearly** and **instantaneously** over all sensors (Maxwell equations)




EM wave diffusion

- ▶ Recording here with 8 sensors
- ▶ EM activity in the brain
- ▶ The electric field is spread **linearly** and **instantaneously** over all sensors (Maxwell equations)




Learned atoms – Artifacts


Spatial pattern 2




Spatial pattern 0



Temporal pattern 2




Temporal pattern 0




Learned atoms – Evoked response


Spatial pattern 3




Spatial pattern 15




Temporal pattern 3





Temporal pattern 15




Learned atoms – Evoked response



Event 3 - 2-atoms



Event 4 - 2-atoms




Learned atoms – Evoked response




Learned atoms – Complex waveforms


A. Temporal waveform




B. Spatial pattern



C. PSD (dB)



D. Dipole fit



alphaCSC: Convolution sparse coding for time-series

build passing  codecov 82%

This is a library to perform shift-invariant **sparse dictionary learning**, also known as convolutional sparse coding (CSC), on time-series data. It includes a number of different models:

1. univariate CSC
2. multivariate CSC
3. multivariate CSC with a rank-1 constraint ^[1]
4. univariate CSC with an alpha-stable distribution ^[2]

A mathematical descriptions of these models is available [in the documentation](#).

Installation

To install this package, the easiest way is using `pip`. It will install this package and its dependencies. The `setup.py` depends on `numpy` and `cython` for the installation so it is advised to install them beforehand. To install this package, please run one of the two commands:

(Latest stable version)

```
pip install numpy cython
pip install alphacsc
```


alphaCSC: Convolution sparse coding for time-series

build passing  82%

This is a library to perform shift-invariant **sparse dictionary learning**, also known as time-series data. It includes a number of different models:

1. univariate CSC
2. multivariate CSC
3. multivariate CSC with a rank-1 constraint ^[1]
4. univariate CSC with an alpha-stable distribution ^[2]

A mathematical descriptions of these models is available **in the documentation**.

Installation

To install this package, the easiest way is using **pip**. It will install this package and its dependencies. The **setup.py** depends on **numpy** and **cython** for the installation so it is advised to install them beforehand. To install this package, please run one of the two commands:

(Latest stable version)

```
pip install numpy cython
pip install alphacsc
```

Python code online:
<https://alphacsc.github.io>

```
pip install alphacsc
```

alphaCSC: Convolution sparse coding for time-series

build passing  82%

This is a library to perform shift-invariant **sparse dictionary learning**, also known as time-series data. It includes a number of different models:

1. univariate CSC
2. multivariate CSC
3. multivariate CSC with a rank-1 constraint ^[1]
4. univariate CSC with an alpha-stable distribution ^[2]

A mathematical descriptions of these models is available **in the documentation**.

Installation

To install this package, the easiest way is using **pip**. It will install this package and depends on **numpy** and **cython** for the installation so it is advised to install them please run one of the two commands:

(Latest stable version)

```
pip install numpy cython
pip install alphacsc
```

Python code online:
<https://alphacsc.github.io>

```
pip install alphacsc
```

Examples reproduce figures
from this talk!

Convolutional Dictionary Learning

- ▶ Flexible pattern extraction technique,
- ▶ Computationally tractable for more and more problems,
- ▶ Some application are already beginning to emerge.

Challenges

- ▶ Theoretical challenges remains (convergence, recoverability),
- ▶ The evaluation (and thus the parameter choices) is still not clear,
- ▶ Can give some insight for deep learning models?

Going further: capturing temporal



How to highlight temporal dependency?

Model inter-atom interactions:

Pénalité ℓ_1

\Rightarrow independent activations

Independent activations



Going further: capturing temporal

How to highlight temporal dependency?

Model inter-atom interactions:



Pénalité ℓ_1

⇒ independent activations

Group penalty (e.g. $\ell_{1,2}$)

⇒ simultaneous activations

Simultaneous activations



Going further: capturing temporal

How to highlight temporal dependency?

Model inter-atom interactions:

Pénalité ℓ_1

⇒ independent activations



Group penalty (e.g. $\ell_{1,2}$)

⇒ simultaneous activations


Point process ponctuels (e.g. Hawkes)

⇒ temporal interactions

Temporal interactions



Deep Learning for Inverse problem



$$\text{Inverse Problem: } \operatorname{argmin}_{\mathbf{Z}} \|\mathbf{X} - \mathbf{F}\mathbf{Z}\|_2^2 + \mathcal{R}(\mathbf{Z})$$


- ▶ Fast iterative solvers to compute \mathbf{Z} [Massias et al. (2017)]
- ▶ Use of deep learning to inverse this system [Moreau et al. (2017); Ablin et al. (2019)]

Thanks!

Code available online:

 **alphacsc** : [alphacsc.github.io](https://github.com/alphacsc)

Slides are on my web page:

 [tommoral.github.io](https://github.com/tommoral)

 [@tomamoral](https://twitter.com/tomamoral)