

txporter (/dashboard)

Courseware (/courses/BerkeleyX/CS169.1x/2013_Spring/courseware)

Course Info (/courses/BerkeleyX/CS169.1x/2013_Spring/info)

Syllabus (/courses/BerkeleyX/CS169.1x/2013_Spring/syllabus/)

Textbook & VM (/courses/BerkeleyX/CS169.1x/2013_Spring/textbook_vm/)

Tutorials & Resources (/courses/BerkeleyX/CS169.1x/2013_Spring/tutorials_resources/)

Discussion (/courses/BerkeleyX/CS169.1x/2013_Spring/discussion/forum)

Wiki (/courses/BerkeleyX/CS169.1x/2013_Spring/course_wiki)

Progress (/courses/BerkeleyX/CS169.1x/2013 Spring/progress)

HW 1-3: ANAGRAMS

An anagram is a word obtained by rearranging the letters of another word. For example, "rats", "tars", and "star" are anagrams of one another, as are "dictionary" and "indicatory". We will call any array of single-word anagrams an anagram group. For instance, ["rats", "tars", "star"] is an anagram group, as is ["dictionary"].

Write a method <code>combine_anagrams(words)</code> that, given an array of strings <code>words</code>, groups the input words into anagram groups. Case doesn't matter in classifying strings as anagrams (but case should be preserved in the output), and the order of the anagrams in the groups doesn't matter. The output should be an array of anagram groups (i.e. an array of arrays).

Code skeleton:

```
def combine_anagrams(words)
    # your code here
end
```

Example test case:

Hint: You can quickly tell if two words are anagrams by sorting their letters, keeping in mind that upper vs. lowercase doesn't matter.

Choose Files No file chosen

Check

Show Discussion

New Post

Find Courses (/courses) About (/about) Blog (http://blog.edx.org/) Jobs (/jobs) Contact (/contact)



(http://www.facebook.com/EdxOnline) (https://twitter.com/edXOnline)

© 2013 edX, some rights reserved.

terms of service (/tos) privacy policy (/privacy) honor code (/honor) help (/help)