txporter (/dashboard) ▾

Courseware (/courses/BerkeleyX/CS169.1x/2013_Spring/courseware)   Course Info (/courses/BerkeleyX/CS169.1x/2013_Spring/info)

Syllabus (/courses/BerkeleyX/CS169.1x/2013_Spring/syllabus/)

Textbook & VM (/courses/BerkeleyX/CS169.1x/2013_Spring/textbook_vm/)

Tutorials & Resources (/courses/BerkeleyX/CS169.1x/2013_Spring/tutorials_resources/)

Discussion (/courses/BerkeleyX/CS169.1x/2013_Spring/discussion/forum)

Wiki (/courses/BerkeleyX/CS169.1x/2013_Spring/course_wiki)   Progress (/courses/BerkeleyX/CS169.1x/2013_Spring/progress)

L9P6: SAAS SCALABILITY

Other factors being equal, which statement is *not* true regarding SaaS scalability?

- ◯ Shared-nothing clusters scale better than systems built from mainframes
- ◯ Relational databases scale better than "NoSQL" databases ✔
- ◉ The programming language used (Ruby, Java, etc.) isn't a main factor in scalability
- ◯ Scalability can be impeded by any part of the app that becomes a bottleneck

| Check | Hide Answer |

Show Discussion   New Post