VERSION 13.11 R1 | Copyright© 2012 SANYO Energy (U.S.A.) Corporation. All Rights Reserved.

Panasonic

Lithium Ion NCR18650B


Features & Benefits

- · High energy density
- · Long stable power and long run time
- · Ideal for notebook PCs, boosters, portable devices,

Specifications


Rated capacity ⁽¹⁾	Min. 3200mAh
Capacity ⁽²⁾	Min. 3250mAh Typ. 3350mAh
Nominal voltage	3.6V
Charging	CC-CV, Std. 1625mA, 4.20V, 4.0 hrs
Weight (max.)	48.5 g
Temperature	Charge*: 0 to +45°C Discharge: -20 to +60°C Storage: -20 to +50°C
Energy density ⁽³⁾	Volumetric: 676 Wh/l Gravimetric: 243 Wh/kg

(1) At 20°C (2) At 25°C (3) Energy density based on bare cell dimensions




For Reference Only


Charge Characteristics




Cycle Life Characteristics



Discharge Characteristics (by temperature)



Discharge Characteristics (by rate of discharge)



The data in this document is for descriptive purposes only and is not intended to make or imply any guarantee or warranty.

For more information on how Panasonic can assist you with your battery power solution needs, visit us at www.panasonic.com/industrial/batteries-oem, e-mail secsales@us.panasonic.com, or call (469) 362-5600.

^{*} At temperatures below 10°C, charge at a 0.25C rate.