ISEP INSTITUTO SUPERIOR DE ENGENHARIA DO PORTO

# [Thesis Title]

**Tomás Domingues**

**A dissertation submitted in partial fulfillment of the requirements for the degree of Master of Science, Specialisation Area of Cybersecurity And Systems Administration**

**Advisor: Dr. Jane Smith**
**Supervisor: Dr. James Smith**

Porto, November 20, 2024

# Statement of Integrity

I hereby declare having conducted this academic work with integrity.

I have not plagiarised or applied any form of undue use of information or falsification of results along the process leading to its elaboration.

Therefore the work presented in this document is original and authored by me, having not previously been used for any other end.

I further declare that I have fully acknowledged the Code of Ethical Conduct of P.PORTO.

ISEP, Porto, November 20, 2024

# Dedicatory

The dedicatory is optional. Below is an example of a humorous dedication.

"To my wife Marganit and my children Ella Rose and Daniel Adam without whom this book would have been completed two years earlier." in "An Introduction To Algebraic Topology" by Joseph J. Rotman.

# Abstract

This document explains the main formatting rules to apply to a TMDEI Master Dissertation work for the MSc in Computer Engineering of the Computer Engineering Department (DEI) of the School of Engineering (ISEP) of the Polytechnic of Porto (IPP).

The rules here presented are a set of recommended good practices for formatting the disseration work. Please note that this document does not have definite hard rules, and the discussion of these and other aspects of the development of the work should be discussed with the respective supervisor(s).

This document is based on a previous document prepared by Dr. Fátima Rodrigues (DEI/ISEP).

The abstract should usually not exceed 200 words, or one page. When the work is written in Portuguese, it should have an abstract in English.

Please define up to 6 keywords that better describe your work, in the *THESIS INFORMATION* block of the `main.tex` file.

**Keywords:** Keyword1, ..., Keyword6

# Resumo

Trabalhos escritos em língua Inglesa devem incluir um resumo alargado com cerca de 1000 palavras, ou duas páginas.

Se o trabalho estiver escrito em Português, este resumo deveria ser em língua Inglesa, com cerca de 200 palavras, ou uma página.

Para alterar a língua basta ir às configurações do documento no ficheiro `main.tex` e alterar para a língua desejada ('english' ou 'portuguese')[1]. Isto fará com que os cabeçalhos incluídos no template sejam traduzidos para a respetiva língua.

[1] Alterar a língua requer apagar alguns ficheiros temporários; O target **clean** do **Makefile** incluído pode ser utilizado para este propósito.

# Acknowledgement

The optional Acknowledgment goes here... Below is an example of a humorous acknowledgment.

"I'd also like to thank the Van Allen belts for protecting us from the harmful solar wind, and the earth for being just the right distance from the sun for being conducive to life, and for the ability for water atoms to clump so efficiently, for pretty much the same reason. Finally, I'd like to thank every single one of my forebears for surviving long enough in this hostile world to procreate. Without any one of you, this book would not have been possible." in "The Woman Who Died a Lot" by Jasper Fforde.

# Contents

**List of Figures** **xv**

**List of Tables** **xvii**

**List of Algorithms** **xix**

**List of Source Code** **xxi**

**List of Acronyms** **xxiii**

**1 Introduction** **1**
1.1 Context . . . . . 1
1.2 Problem . . . . . 2
1.3 Objectives . . . . . 2
1.4 Research Contextualization . . . . . 3
1.5 Dissertation Structure . . . . . 3

**2 State of the Art** **5**
2.1 Theoretical Introduction . . . . . 5
2.1.1 Security Operations Center . . . . . 5
Definition and Characteristics of a SOC . . . . . 6
Key Responsibilities of a SOC . . . . . 6
Tiers of Operation . . . . . 6
Triage Specialist . . . . . 7
2.1.2 Security Information and Event Management . . . . . 8
Architectural Components . . . . . 9
2.1.3 Machine Learning . . . . . 10
2.1.4 Classification Models . . . . . 11
2.2 Automatic Classification of Security Alerts in SOC . . . . . 11
2.3 Technologies . . . . . 11
2.3.1 QRadar . . . . . 11
2.3.2 Jira . . . . . 11
2.3.3 Machine Learning Classification Models . . . . . 11

**3 Method and Implementation** **13**
3.1 Method . . . . . 13

**4 Chapter 4** **15**

**5 Chapter 5** **17**

**6 Results Discussions** **19**
6.1 Conclusions . . . . . 19

**Bibliography** **21**

# List of Figures

2.1 SOC Analyst Tier Responsibilities, from (Kokulu et al. 2019). . . . . 7
2.2 SIEM Architecture . . . . . 10

# List of Tables

# List of Algorithms

# List of Source Code

# List of Acronyms

| | |
|---|---|
| AI | Artificial Intelligence. |
| CND | Computer Network Defense. |
| CSIRT | Computer Security Incident Response Team. |
| ERD | Endpoint Detection and Response. |
| IDS | Intrusion and Detection System. |
| IPS | Intrusion and Prevension System. |
| ML | Machine Learning. |
| SIEM | Security Information and Event Management. |
| SOC | Security Operations Center. |

# Chapter 1

# Introduction

This chapter provides context for automating alert triage and its significance in enhancing security operations in a SOC, particularly for managing high volumes of security alerts. It begins with defining the problem and detailing the challenges associated with manual alert analysis and the critical requirements for automation. First, the objectives of this thesis are presented; second, this project's expected outcomes, including efficiency and accuracy improvements, are outlined, along with the selected approach for integrating an existing ML model to automate alert classification. Finally, an overview of the report's structure is provided.

## 1.1 Context

In today's world, cybersecurity has become essential for organizations of all sizes. (Vielberth et al. 2020) The rapid advancement of technology, particularly artificial intelligence, has fostered innovation and growth and equipped cybercriminals with increasingly sophisticated tools and techniques. Cyber threats have surged over recent years, and this trend is expected to continue, with global cybersecurity spending projected to rise from $6 trillion to $30 trillion by 2030. (Sovilj et al. 2020)

As these threats become more complex and frequent, Security Operations Center (SOC) have emerged as the primary line of defense. SOCs are crucial in monitoring, detecting, and responding to cyber threats, ensuring the protection of organizations' core digital assets—data, applications, and infrastructure. By combining human expertise with advanced technology, SOCs proactively defend systems, respond to incidents, and work to minimize the impact of potential breaches, safeguarding essential operations. (Jalalvand et al. 2024)

However, managing the overwhelming number of alerts generated daily within SOCs presents a significant challenge. Analysts must review and respond to thousands of tickets, a process that can quickly lead to burnout, as stated by Tines (2023), especially when the majority of alerts are false positives. A study found that many organizations receive over 10,000 alerts daily, with more than 50% being false positives. (CriticalStart 2019)

One of the stages in the SOC workflow with a higher alert volume is the initial triage process. At this stage, Tier 1 analysts are responsible for gathering raw data, assessing alarms, and determining the urgency and nature of each alert. For every ticket, they must evaluate whether the alert is valid or a false positive, assign priority based on the alert's severity, and identify any potential high-risk incidents. (Vielberth et al. 2020) This process demands significant time and effort, placing a heavy mental load on analysts as they deal with large volumes of information.

Integrating automation in the triage process, particularly for determining alert criticality and classification, could substantially reduce analyst fatigue. Machine Learning (ML) techniques are up-and-coming for processing large data volumes. They facilitate the classification and prioritization of alerts, enabling analysts to focus on high-priority threats. (Jalalvand et al. 2024)

This work explores how SOCs can use automation and ML to streamline alert triage, improve SOC efficiency, and more effectively protect organizations from an ever-evolving cyber threat landscape.

## 1.2 Problem

The main objective of this work is to develop an independent program that automates the triage of security alerts within a Security Operations Center (SOC) environment. This automation aims to enhance the overall efficiency and accuracy of the triage process, reduce the number of false positives, and alleviate the workload during the initial stages of the SOC workflow.

Improving the speed of analyzing initial alerts is crucial in a Security Operations Center (SOC) workflow. Faster analysis enables SOC analysts to respond to incidents quickly, which helps minimize the time that threats remain undetected. Without automation, this initial alert analysis depends heavily on manual inspection. Analysts face the challenge of sifting through a large volume of alerts to identify potential threats, which is time-consuming and susceptible to human error.

This reactive, manual method increases response times and raises the risk of missing critical threats. Analysts must manually classify alerts, assess their severity, and determine appropriate response actions while managing a continuous influx of new alerts. This approach can strain resources and often leads to alert fatigue, making it difficult for analysts to prioritize and respond effectively.

Key metrics such as Mean Time to Detect (MTTD) and Mean Time to Respond (MTTR) can significantly improve by reducing the time required for initial analysis. These metrics are essential for maintaining strong cybersecurity defenses. Automation in alert triage allows for faster and more accurate threat identification, enabling analysts to focus on high-priority threats. This not only increases overall productivity but also reduces fatigue among analysts, while boosting the effectiveness of cybersecurity.

This efficiency results in a more manageable workload, decreased burnout, and greater job satisfaction for employees. For the organization, streamlined response times enhance the security posture, lower the risk of breaches, and ultimately protect critical assets more effectively.

## 1.3 Objectives

The objectives for this project are as follows:

1. Literature search and review
    - A research into the latest advancements in security analysis and a thorough analysis of the tools, methodologies, and approaches researchers use in SOC automation and machine learning applications.

2. Study of existing Machine Learning (ML) models
   - An analysis of different models for alert triage in SOC environments and related fields, aiming to identify and improve the adopted approach.
3. Collection of security alert datasets
   - A compilation of accessible datasets on security alerts organized to supply training data for the selected ML model.
4. Integration with SIEM and other data sources
   - Connect the SIEM and relevant data sources for real-time data ingestion and analysis.
5. Developing a custom dashboard for analysts to submit feedback on the machine learning model.
   - While the ML model will be trained with existing datasets before deployment, it is still beneficial to provide a method for analysts to continue training the model over time.
6. Testing and evaluation of the selected ML model
   - The selected ML model will be tested with live data, followed by an analysis to assess its effectiveness in categorizing alerts and minimizing false positives.

## 1.4 Research Contextualization

## 1.5 Dissertation Structure

*[ Structure ]*

# Chapter 2

# State of the Art

This chapter is divided into three parts. Part I starts on the theoretical side by introducing Machine Learning, Security Operation Centers, Security Information and Event Managers and advanced threat detection and response mechanisms such as Intrusion and Prevension System (IPS), Intrusion and Detection System (IDS) and Endpoint Detection and Response (ERD). It also explains how popular ML classification models work and how to evaluate them. Understanding these topics is the groundwork for material considered later in the chapter.

The second part focuses on current works on the Automatic Classification of Security Alert Tickets. It starts with general information about these systems and then reviews several publicly available datasets. Finally, the chapter ends with a detailed assessment of existing systems similar to the one presented in this thesis. We have separated this analysis from the overview to explore their methods further.

The third and final part discusses existing technologies that SOC may utilize. These technologies are designed to support the workflow outlined in the first section about SOC. At least three different technologies will be presented and discussed for each aspect of the SOC workflow. The section will conclude with a summary of the key differences among the technologies and, if relevant, evaluate which one may be superior.

## 2.1 Theoretical Introduction

Before diving into the technologies, tools, and methodologies used for automating the classification of security alert tickets, it is essential to understand some fundamental concepts first. Concepts like, SOCs, Security Information and Event Management (SIEM) systems, Artificial Intelligence (AI)—particularly ML—and advanced threat detection and response mechanisms. Such a foundation is indispensable for comprehending these systems' functions, construction work, advantages and limitations, and the actual performance comparison among different methods. The chapter introduces SOC and how it functions diving into , then moves on to the foundations of ML and provides an overview of models frequently used for classification problems. It also provides an overview of the methods for assessing classification model performance to set this in context for how these are used within the project.

### 2.1.1 Security Operations Center

The complexity and frequency of cyber threats are increasing (Arianna 2024), which has led to the emergence of SOCs as a critical component of modern IT enterprises. SOCs are

the primary defenders in incident response planning, vulnerability management, and regulatory compliance. In today's interconnected world, integrating security operations to reduce defensive barriers allows organizations to optimize resources, enhance security posture, and safeguard critical assets.

A SOC is a unit (Rutledge 2024) that provides tailored and centralized Computer Network Defense (CND) (Zimmerman 2014). It defends computer networks against the growing world of cyber threats. The main objective of a SOC is to ensure continuous monitoring and incident response for enterprise systems (Zimmerman 2014). This primarily focuses on preventing unauthorized access, cyber-attacks, and data breaches.

This 24/7 facility leverages advanced technologies and skilled information security professionals to monitor the network continuously (Zimmerman 2014). With sophisticated tools to detect anomalies, a SOC can address threats before they escalate.

### Definition and Characteristics of a SOC

Zimmerman (2014) defined a SOC as:

> "A team primarily composed of security analysts organized to detect, analyze, respond to, report on, and prevent cybersecurity incidents."

This definition integrates elements from various sources, including the historical definition of Computer Security Incident Response Team (CSIRT) as detailed in references (Shirey 2007) and (Brownlee and Guttman 1998).

For an organization to qualify as a SOC, according to Zimmerman (2014), it must:

1. Establish a system for constituents to report cybersecurity incidents.
2. Provide comprehensive support for managing and resolving incidents effectively.
3. Convey incident-related information to internal and external stakeholders.

### Key Responsibilities of a SOC

A SOC has several critical missions, as outlined by various sources (Muniz, McIntyre, and AlFardan 2015; Zimmerman 2014):

- Preventing cybersecurity incidents by implementing proactive measures such as vulnerability scanning and threat analysis.
- Monitor, detect, and analyze potential security intrusions.
- Handle confirmed incidents and coordinate resources for effective countermeasures.
- Providing stakeholders with situational awareness regarding cybersecurity incidents, trends, and threats.

### Tiers of Operation

Analysts within a SOC operate in tiers (Vielberth et al. 2020). Tier 1 analysts monitor and conduct initial investigations, escalating complex cases to Tier 2 analysts, who perform in-depth analyses and take further actions like blocking activities or deactivating accounts. Generally, higher-tier analysts handle more complex incidents, which require more time to resolve.




Figure 2.1: SOC Analyst Tier Responsibilities, from (Kokulu et al. 2019).

Extra levels may exist that handle responsibilities like threat hunting, vulnerability assessments, and penetration testing. These levels are collectively termed Tier 3+. Figure 2.1 was taken from a paper on a qualitative study on a SOC (Kokulu et al. 2019) and illustrates a visual representation of these tiers and their associated tasks. Not all SOCs follow a hierarchical model. In some collaborative frameworks, team members may possess comparable skill sets, enabling them to manage incidents independently (Kokulu et al. 2019).

**Triage Specialist**

Since this project focuses on automating the triage process, it is crucial to gain a detailed understanding of the role of a triage specialist, their functions, and the advantages of automated triage in comparison.

Tier 1 analysts, also known as triage specialists, play a critical role in the initial stages of a SOC workflow (Vielberth et al. 2020).

As stated by Vielberth et al. (2020), a Tier 1 analyst's primary responsibilities include:

1. Collecting and analyzing raw data.
2. Reviewing alarms and alerts generated by monitoring systems.
3. Determining the validity and criticality of each alert.

They must improve alerts with additional contextual information and decide whether an alert represents a real threat or a false positive (Hámornik and Krasznay 2018; Sundaramurthy et al. 2014). This process demands meticulous attention to detail, as the triage specialist must assess individual alerts, notify potential high-risk events, and prioritize them according to their severity (Tao 2018).

The repetitive nature of triage work, coupled with the need to escalate unresolved issues to Tier 2 analysts, can result in mental fatigue and burnout (Iamnitchi et al. 2017; Tines 2023).

This exhaustion affects individual performance and can compromise the overall efficiency of the SOC, as delayed or missed alerts may result in critical threats going undetected (CriticalStart 2019).

In a 2018 study (Crowley and Pescatore 2018), 53% of respondents in a security survey identified inadequate automation as the most common shortcoming.

This study demonstrates that effectively structured and implemented automation can help mitigate some or many of a SOC's weaknesses, particularly in the repetitive aspects of the SOC's workflow, such as the triage process.

### 2.1.2 Security Information and Event Management

The increasing complexity of cybersecurity threats has compelled organizations to implement advanced technologies to protect their digital assets. SIEM systems have emerged as vital tools in this context (Shaw 2022).

SIEM systems gather and centralize security-related data to detect threats and respond to incidents effectively. These systems connect logs from various sources to support security analytics, enabling real-time monitoring and retrospective analysis of past events (Shaw 2022). SIEM systems normalize raw log data, correlate events, generate reports and issue alerts, and automate responses to security incidents using enriched contextual data (Vielberth 2021). They integrate with cyber threat intelligence platforms, providing human analysts with advanced visual tools for seamless information sharing between organizations. Additionally, they retain event data over extended periods, ensuring robust log management capabilities.

The key features of a SIEM system, as gathered from various published sources (Ali, Shah, and ElAffendi 2024; Harper et al. 2010; Sheeraz et al. 2023), are:

- **Log Collection:** SIEM gathers log data from various network devices such as servers, firewalls, and switches. Data can be collected using two methods:
  1. **Agent-based collection:** An intermediary agent collects and forwards logs.
  2. **Agent-less collection:** Servers retrieve logs directly from the source devices.
- **Log Aggregation:** Collected logs are analyzed and structured for meaningful insights. Aggregation methods include:
  1. **Push method:** Devices actively send logs to the SIEM.
  2. **Pull method:** SIEM retrieves logs as needed.
- **Parsing and Normalization:** Parsing converts raw logs into structured data, while normalization standardizes logs from diverse sources to eliminate redundancy.
- **Threat Analysis and Detection:** By correlating log data with known threat indicators, SIEM systems identify malicious activities. Statistical methods and predefined rules enhance their ability to detect sophisticated threats.
- **Response Automation:** SIEM systems issue real-time alerts and notifications, enabling rapid responses to potential incidents.
- **Reporting and Visualization:** Advanced reporting tools provide security analysts with actionable insights, enabling detailed investigations and trend analysis.

### Architectural Components

The architectural components of a security information and Event Management (SIEM) system consist of several essential elements that enable effective security monitoring, incident detection, and response (Sheeraz et al. 2023).

Data sources provide the raw material for analysis and threat detection (Ali, Shah, and ElAffendi 2024). These include a wide variety of log-generating devices and applications:

- **Network devices**: Firewalls, routers, and switches.
- **Endpoint devices**: Workstations, servers, and mobile devices.
- **Applications**: Web servers, databases, and cloud platforms.

A variety of data sources is crucial for effective monitoring and threat detection.

**Data collection** is a vital step with two main approaches to consider:

- **Agent-based collection**: Agent-based collection uses proxy agents on endpoint devices for better control and flexibility in log collection, but it is costly and complex to manage.
- **Agent-less collection**: Agent-less collection allows devices to send data directly to the SIEM, simplifying deployment but may reduce efficiency in high-volume data environments.

The **SIEM processing engine** is one of the critical components (Sheeraz et al. 2023) responsible for:

- **Parsing**: The conversion of raw log data into a structured format used for analysis.
- **Normalization**: Ensure the log formats are standardized to facilitate easier comparisons.
- **Correlation**: Finding relationships between events to strengthen security posture or incident response.

**Storage and rationalization** are vital for ensuring scalability and compliance. SIEM systems must store logs for future analysis. This means there has to be enough storage and a logical way of organizing this data for scalability or compliance requirements like GDPR and HIPAA (Sheeraz et al. 2023). Effective storage solutions should scale dynamically to handle large datasets without compromising performance or compliance standards.

**Visualization and reporting tools** play a key role in making data accessible and actionable. Critical functions that significantly benefit from good data visualization and reporting tools are incident investigation, trend analysis, and compliance audits (Sheeraz et al. 2023). These features not only improve user experience but also aid in making data actionable and accessible. Organizations can use these tools to conduct incident investigations, identify patterns occurring over time, and monitor compliance (Sheeraz et al. 2023). This comprehensive approach enables the development of scalable systems that can effectively handle increasing data demands.




Figure 2.2: SIEM Architecture

Figure 2.2 illustrates the architecture of a SIEM system, highlighting its critical components and their interactions. Data flows from network and endpoint devices, as well as applications, to the log collection module. The SIEM processing engine then parses, normalizes, and correlates this data for real-time security alert analysis, event monitoring, and threat detection.

The diagram also emphasizes the importance of visualization and reporting tools for turning data into actionable insights.

The graphic illustrates how these elements integrate into a SIEM.

### 2.1.3 Machine Learning

ML is a core part of AI but also overlaps with data mining, statistics, probability, and mathematics. Unlike traditional rule-based systems that rely on predefined logic, ML uses induction—it learns patterns from past data and forms assumptions that can be generalized to new cases. This method relies on datasets, which are groups of examples the ML algorithm analyzes to find patterns (Mohri, Rostamizadeh, and Talwalkar 2012). The goal is to use these learned patterns to predict or describe new data.

However, ML has its limitations. Since datasets are finite, no algorithm can predict every scenario, which highlights an essential aspect of inductive reasoning: it can suggest likely outcomes but cannot ensure certainty (Mohri, Rostamizadeh, and Talwalkar 2012).

In ML, achieving an optimal model involves balancing between two critical concepts: **bias** and **variance**. Bias refers to the error introduced when a model is excessively simplistic, which can lead to underfitting. Underfitting occurs when the model fails to capture the underlying patterns of the data, resulting in poor performance on both training and unseen datasets (ElSahly and Abdelfatah 2023). On the other hand, variance arises when a model becomes overly complex and sensitive to the fluctuations in the training data, culminating in overfitting. Overfitting means the model performs exceptionally well on the training dataset

but poorly on new, unseen data because it has memorized the noise instead of learning the actual signal (ElSahly and Abdelfatah 2023).

The primary objective in constructing a machine learning model is to identify the appropriate level of complexity that strikes the right balance, ensuring the model generalizes well and performs effectively on new data.

Despite these challenges, ML continues to evolve, with increasingly sophisticated algorithms enabling breakthroughs in many fields.

### 2.1.4 Classification Models

## 2.2 Automatic Classification of Security Alerts in SOC

## 2.3 Technologies

### 2.3.1 QRadar

### 2.3.2 Jira

### 2.3.3 Machine Learning Classification Models

# Chapter 3

# Method and Implementation

## 3.1 Method

# Chapter 4

Chapter 4

# Chapter 5

Chapter 5

# Chapter 6

# Results Discussions

## 6.1 Conclusions

# Bibliography


Ali, Gauhar, Sajid Shah, and Mohammed ElAffendi (Sept. 2024). *Enhancing Cybersecurity Incident Response: AI-Driven Optimization for Strengthened Advance Persistence Threat Detection*. doi: 10.20944/preprints202409.1725.v1. url: https://www.preprints.org/manuscript/202409.1725/v1.

Arianna, By (2024). *Cybersecurity Management Services: Why ITSM Services Essential?* url: https://forlicoupon.it/2024/07/17/cybersecurity-management-services-why-itsm-services-essential/.

Brownlee, N. and E. Guttman (June 1998). "Request for Comments 2350 Expectations for Computer Security Incident Response," in: url: http://www.ietf.org/rfc/rfc2350.txt.

CriticalStart (2019). *THE IMPACT OF SECURITY ALERT OVERLOAD*. url: https://www.criticalstart.com/wp-content/uploads/2021/02/CS_Report-The-Impact-of-Security-Alert-Overload.pdf.

Crowley, Christopher and John Pescatore (2018). *The Definition of SOC-cess? A SANS Survey*.

ElSahly, Osama and Akmal Abdelfatah (Aug. 2023). "An Incident Detection Model Using Random Forest Classifier". In: *Smart Cities* 6 (4), pp. 1786–1813. issn: 26246511. doi: 10.3390/SMARTCITIES6040083.

Hámornik, Balázs Péter and Csaba Krasznay (2018). "A team-level perspective of human factors in cyber security: Security operations centers". In: *Advances in Intelligent Systems and Computing* 593, pp. 224–236. issn: 21945357. doi: 10.1007/978-3-319-60585-2_21. url: https://www.researchgate.net/publication/318177610_A_Team-Level_Perspective_of_Human_Factors_in_Cyber_Security_Security_Operations_Centers.

Harper, Allen et al. (Dec. 2010). *Security Information And Event Management (SIEM) Implementation*. Ed. by MCGRAW-HILL EDUCATION - EUROPE, p. 464. isbn: 9780071701099.

Iamnitchi, Adriana et al. (2017). "An Anthropological Study of Security Operations Centers to Improve Operational Efficiency". In: url: https://digitalcommons.usf.edu/etd.

Jalalvand, Fatemeh et al. (Nov. 2024). "Alert Prioritisation in Security Operations Centres: A Systematic Survey on Criteria and Methods". In: *ACM Computing Surveys* 57 (2), pp. 1–36. issn: 0360-0300. doi: 10.1145/3695462. url: https://dl.acm.org/doi/10.1145/3695462.

Kokulu, Faris Bugra et al. (Nov. 2019). "Matched and mismatched SOCs: A qualitative study on security operations center issues". In: *Proceedings of the ACM Conference on Computer and Communications Security*. Association for Computing Machinery, pp. 1955–1970. isbn: 9781450367479. doi: 10.1145/3319535.3354239.

Mohri, Mehryar, Afshin Rostamizadeh, and Ameet Talwalkar (2012). *Foundations of Machine Learning*. isbn: 978-0-262-01825-8. url: https://www.hlevkin.com/hlevkin/45MachineDeepLearning/ML/Foundations_of_Machine_Learning.pdf.

Muniz, Joseph, Gary McIntyre, and Nadhem AlFardan (2015). *Security Operations Center: Building, Operating, and Maintaining your SOC*. url: https://books.google.pt/

books?hl=pt-PT&lr=&id=riraCgAAQBAJ&oi=fnd&pg=PT28&ots=SBNh-G3lCL&sig=6w_ipaEbsLDSFja80QABKEBW7GE&redir_esc=y#v=onepage&q&f=false.

Rutledge, Samantha (2024). *How SOC as a Service can help Sarah in Operations*. url: https://fractionalciso.com/how-soc-as-a-service-can-help-sarah-in-operations/.

Shaw, Megan (Aug. 2022). *Importance of SIEM in Supporting Digital Transformation Initiatives | DNIF*. url: https://www.dnif.it/en/blog/importance-of-siem-in-supporting-digital-transformation-initiatives.

Sheeraz, Muhammad et al. (Apr. 2023). *Effective Security Monitoring Using Efficient SIEM Architecture*. doi: 10.22967/HCIS.2023.13.023.

Shirey, R (2007). *Network Working Group*. url: http://tools.ietf.org/html/rfc4949.

Sovilj, Dušan et al. (2020). "A comparative evaluation of unsupervised deep architectures for intrusion detection in sequential data streams". In: *Expert Systems with Applications* 159, p. 113577. issn: 0957-4174. doi: https://doi.org/10.1016/j.eswa.2020.113577. url: https://www.sciencedirect.com/science/article/pii/S0957417420304012.

Sundaramurthy, Sathya Chandran et al. (Nov. 2014). "A tale of three security operation centers". In: *Proceedings of the ACM Conference on Computer and Communications Security* 2014-November (November), pp. 43–50. issn: 15437221. doi: 10.1145/2663887.2663904. url: https://www.researchgate.net/publication/265786529_A_Tale_of_Three_Security_Operation_Centers.

Tao, Lin (May 2018). "A DATA TRIAGE RETRIEVAL SYSTEM FOR CYBER SECURITY OPERATIONS CENTER". In.

Tines (2023). *Voice of the SOC 2023 Report*. url: https://www.tines.com/reports/voice-of-the-soc-2023/.

Vielberth, Manfred (2021). "Security Information and Event Management (SIEM)". In: Springer Berlin Heidelberg, pp. 1–3. doi: 10.1007/978-3-642-27739-9_1681-1.

Vielberth, Manfred et al. (2020). "Security Operations Center: A Systematic Study and Open Challenges". In: *IEEE Access* 8, pp. 227756–227779. issn: 21693536. doi: 10.1109/ACCESS.2020.3045514.

Zimmerman, Carson (2014). *Ten Strategies of a World-Class Cybersecurity Operations Center*. isbn: 9780692243107. url: www.mitre.org.