INT-A-PAK "Half Bridge" (Ultrafast Speed IGBT), 209 A

INT-A-PAK

FEATURES

- Generation 5 Non Punch Through (NPT) technology
- Ultrafast: optimized for hard switching speed
- Low $V_{CE(on)}$
- 10 µs short circuit capability
- Square RBSOA
- Positive $V_{CE(on)}$ temperature coefficient
- HEXFRED® antiparallel diode with ultrasoft reverse recovery characteristics
- Industry standard package
- Al_2O_3 DBC
- UL approved file E78996
- Designed for industrial level
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

Pb-free

RoHS COMPLIANT

BENEFITS

- Benchmark efficiency for UPS and welding application
- Rugged transient performance
- Direct mounting on heatsink
- Very low junction to case thermal resistance

PRIMARY CHARACTERISTICS	
V_{CES}	600 V
I_C DC	209 A
$V_{CE(on)}$ at 200 A, 25 °C	2.6 V
Speed	8 kHz to 30 kHz
Package	INT-A-PAK
Circuit configuration	Half bridge with SMD gate resistor

ABSOLUTE MAXIMUM RATINGS				
PARAMETER	SYMBOL	TEST CONDITIONS	MAX.	UNITS
Collector to emitter voltage	V_{CES}		600	V
Continuous collector current	I_C	T_C = 25 °C	209	A
		T_C = 80 °C	142	
Pulsed collector current	I_{CM}		400	
Clamped inductive load current	I_{LM}		400	
Diode continuous forward current	I_F	T_C = 25 °C	178	
		T_C = 80 °C	121	
Gate to emitter voltage	V_{GE}		± 20	V
Maximum power dissipation	P_D	T_C = 25 °C	781	W
		T_C = 80 °C	438	
Isolation voltage	V_{ISOL}	Any terminal to case, t = 1 min	2500	V
Operating junction temperature range	T_J		-40 to +150	°C

ELECTRICAL SPECIFICATIONS (T_J = 25 °C unless otherwise specified)						
PARAMETER	**SYMBOL**	**TEST CONDITIONS**	**MIN.**	**TYP.**	**MAX.**	**UNITS**
Collector to emitter breakdown voltage	$V_{BR(CES)}$	V_{GE} = 0 V, I_C = 500 µA	600	-	-	V
Collector to emitter voltage	$V_{CE(on)}$	V_{GE} = 15 V, I_C = 100 A	-	1.95	2.1	
		V_{GE} = 15 V, I_C = 200 A	-	2.6	2.84	
		V_{GE} = 15 V, I_C = 100 A, T_J = 125 °C	-	2.28	2.5	
		V_{GE} = 15 V, I_C = 200 A, T_J = 125 °C	-	3.14	3.48	
Gate threshold voltage	$V_{GE(th)}$	V_{CE} = V_{GE}, I_C = 500 µA	3	4.2	6	
Collector to emitter leakage current	I_{CES}	V_{GE} = 0 V, V_{CE} = 600 V	-	0.005	0.2	mA
		V_{GE} = 0 V, V_{CE} = 600 V, T_J = 150 °C	-	0.01	15	
Diode forward voltage drop	V_{FM}	I_C = 100 A	-	1.39	1.78	V
		I_C = 200 A	-	1.64	2.2	
		I_C = 100 A, T_J = 125 °C	-	1.32	1.69	
		I_C = 200 A, T_J = 125 °C	-	1.67	2.30	
Gate to emitter leakage current	I_{GES}	V_{GE} = ± 20 V	-	-	± 200	nA

SWITCHING CHARACTERISTICS (T_J = 25 °C unless otherwise specified)						
PARAMETER	**SYMBOL**	**TEST CONDITIONS**	**MIN.**	**TYP.**	**MAX.**	**UNITS**
Turn-on switching loss	E_{on}	I_C = 200 A, V_{CC} = 360 V, V_{GE} = 15 V, R_g = 10 Ω, L = 200 µH, T_J = 25 °C	-	3.65	-	mJ
Turn-off switching loss	E_{off}		-	6.9	-	
Total switching loss	E_{tot}		-	10.55	-	
Turn-on switching loss	E_{on}	I_C = 200 A, V_{CC} = 360 V, V_{GE} = 15 V, R_g = 10 Ω, L = 200 µH, T_J = 125 °C	-	3.8	-	
Turn-off switching loss	E_{off}		-	7.8	-	
Total switching loss	E_{tot}		-	11.6	-	
Turn-on delay time	$t_{d(on)}$		-	507	-	ns
Rise time	t_r		-	133	-	
Turn-off delay time	$t_{d(off)}$		-	538	-	
Fall time	t_f		-	92	-	
Reverse bias safe operating area	RBSOA	T_J = 150 °C, I_C = 400 A, R_g = 27 Ω, V_{GE} = 15 V to 0	Fullsquare			
Short circuit safe operating area	SCSOA	T_J = 150 °C, V_{CC} = 400 V, V_P = 600 V, R_g = 27 Ω, V_{GE} = 15 V to 0	10	-	-	
Diode reverse recovery time	t_{rr}	I_F = 50 A, dI_F/dt = 200 A/µs, V_{CC} = 400 V, T_J = 25 °C	-	226	260	ns
Diode peak reverse current	I_{rr}		-	17	20	A
Diode recovery charge	Q_{rr}		-	1900	2600	nC
Diode reverse recovery time	t_{rr}	I_F = 50 A, dI_F/dt = 200 A/µs, V_{CC} = 400 V, T_J = 125 °C	-	290	330	ns
Diode peak reverse current	I_{rr}		-	25	30	A
Diode recovery charge	Q_{rr}		-	3600	5000	nC

THERMAL AND MECHANICAL SPECIFICATIONS						
PARAMETER		SYMBOL	MIN.	TYP.	MAX.	UNITS
Operating junction and storage temperature range		T_J, T_{Stg}	-40	-	150	°C
Junction to case per leg	IGBT	R_{thJC}	-	0.13	0.16	°C/W
	Diode		-	0.19	0.32	
Case to sink per module		R_{thCS}	-	0.1	-	
Mounting torque	case to heatsink		-	-	4	Nm
	case to terminal 1, 2, 3		-	-	3	
Weight			-	185	-	g



Fig. 1 - Typical IGBT Output Characteristics
T_J = 25 °C, t_p = 500 µs



Fig. 3 - Typical Transfer Characteristics
V_{CE} = 20 V, t_p = 500 µs



Fig. 2 - Typical IGBT Output Characteristics
T_J = 125 °C, t_p = 500 µs



Fig. 4 - Typical Collector to Emitter Voltage vs. Junction Temperature



Fig. 5 - Diode Forward Characteristics,
t_p = 500 µs



Fig. 8 - Typical Switching Time vs. I_C
T_J = 125 °C, L = 200 µH, V_{CC} = 360 V,
R_g = 10 Ω, V_{GE} = 15 V



Fig. 6 - Maximum Collector Current vs.
Case Temperature



Fig. 9 - Typical Energy Loss vs. R_g
T_J = 125 °C, L = 200 µH, V_{CC} = 360 V,
I_{CE} = 200 A, V_{GE} = 15 V



Fig. 7 - Typical Energy Loss vs. I_C
T_J = 125 °C, L = 200 µH, V_{CC} = 360 V,
R_g = 10 Ω, V_{GE} = 15 V



Fig. 10 - Typical Switching Time vs. R_g
T_J = 125 °C, L = 200 µH, V_{CC} = 360 V,
I_{CE} = 200 A, V_{GE} = 15 V



Fig. 11 - Typical Diode I_{rr} vs. I_F
T_J = 125 °C



Fig. 14 - Typical Switching Losses vs. Gate Resistance
T_J = 125 °C, L = 200 µH, R_g = 10 Ω,
V_{CC} = 360 V, V_{GE} = 15 V



Fig. 12 - Typical Diode I_{rr} vs. R_g
T_J = 125 °C, I_F = 200 A



Fig. 15 - Typical Switching Losses vs.
Junction Temperature;
L = 200 µH, R_g = 10 Ω, V_{CC} = 360 V, V_{GE} = 15 V



Fig. 13 - Typical Diode I_{rr} vs. dI_F/dt
T_J = 125 °C, V_{CC} = 360 V, I_F = 200 A, V_{GE} = 15 V



Fig. 16 - Typical Switching Losses vs.
Collector to Emitter Current;
T_J = 125 °C,R_{g1} = 10 Ω, R_{g2} = 0 Ω, V_{CC} = 360 V, V_{GE} = 15 V



Fig. 17 - Maximum Transient Thermal Impedance, Junction to Case (IGBT)



Fig. 18 - Maximum Transient Thermal Impedance, Junction to Case (HEXFRED®)

ORDERING INFORMATION TABLE

Device code

VS-	G	B	200	T	S	60	N	PbF
1	2	3	4	5	6	7	8	9

1	-	Vishay Semiconductors product
2	-	Insulated gate bipolar transistor (IGBT)
3	-	B = IGBT Gen 5 NPT
4	-	Current rating (200 = 200 A)
5	-	Circuit configuration (T = half bridge)
6	-	Package indicator (S = INT-A-PAK)
7	-	Voltage rating (60 = 600 V)
8	-	Speed / type (N = ultrafast IGBT)
9	-	Lead (Pb)-free

CIRCUIT CONFIGURATION



LINKS TO RELATED DOCUMENTS	
Dimensions	www.vishay.com/doc?95543

INT-A-PAK IGBT

DIMENSIONS in millimeters (inches)



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, “Vishay”), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay’s knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer’s responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer’s technical experts. Product specifications do not expand or otherwise modify Vishay’s terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.