


**dotnamecpp::utils::
ICustomStringsLoader**

- + virtual ~ICustomStringsLoader
()=default
- + virtual Result< nlohmann
::json, JsonError > load
(const std::string &id) const =0
- + virtual std::optional
< std::string > getLocalized
String(const std::string
&id, const std::string &locale
="en") const =0
- + virtual std::optional
< std::string > getEmail
(const std::string &id)
const =0
- + virtual std::optional
< std::string > getUrl
(const std::string &id)
const =0
- + virtual std::optional
< std::string > getTel
(const std::string &id)
const =0
- + virtual std::optional
< std::string > getPath
(const std::string &id)
const =0
- + virtual std::string
getCustomStringSign
(const std::string &id) const =0



**dotnamecpp::utils::
CustomStringsLoader**

- + CustomStringsLoader
(std::shared_ptr< IAssetManager
> assetManager, std::shared
_ptr< IJsonSerializer > jsonSerializer,
std::string filename="customstrings.json")
- + CustomStringsLoader
(const CustomStringsLoader
&)=delete
- + CustomStringsLoader
& operator=(const CustomStrings
Loader &)=delete
- + CustomStringsLoader
(CustomStringsLoader
&&)=delete
- + CustomStringsLoader
& operator=(CustomStrings
Loader &&)=delete
- + ~CustomStringsLoader
() override=default
- + Result< nlohmann::json,
JsonError > load() const
override
- + std::optional< std
::string > getLocalizedString
(const std::string &id, const
std::string &locale="en") const override
- + std::optional< std
::string > getEmail
(const std::string &id) const
override
- + std::optional< std
::string > getUrl(const
std::string &id) const
override
- + std::optional< std
::string > getTel(const
std::string &id) const
override
- + std::optional< std
::string > getPath(const
std::string &id) const
override
- + std::string getCustomString
Sign() const override