

Sanity check outcome: your `alias-fn / simple-alias-fn` approach is doing the main job (function wrappers), and in the checked `*tomo*bash*` scripts I don't see a current **SKIP_TERM-style env-loss** case (env var bound to command 1 of a `;-chained alias`).

Main findings from `/tpo/misc/programs/bash/shell-scripts-devel`:

1. `alias-fn / simple-alias-fn` are defined in `tomohara-aliases.bash:198-217` and rely on raw `eval`.

2. In `tomohara-proper-aliases.bash`, env-prefixed wrappers that target another alias (`git-all-update-verbose`, `nvidia-batched-advanced`, `zip-from-parent-encrypted`) ultimately expand to a single command/function path, so no multi-command boundary issue like the old `init-desktop` case.

3. A few real gotchas:

- `simple-alias-fn` checks `"$3"` (`tomohara-aliases.bash:208`), which is brittle under `set -u`; better to use `(( $# == 2 ))`.
- `eval "function $alias { ... }"` (`202, 216`) has no name validation/collision checks and can be broken by malformed input.
- `simple-alias-fn` always appends `"$@"`; with multi-command bodies this feeds args to the last command, which can be surprising (`tomohara-proper-aliases.bash:1111`, `tomohara-aliases.bash:878`).
- Unquoted basename `$PWD` appears in `alias-fn` bodies (`tomohara-proper-aliases.bash:796, 819`) and will mis-handle spaces in path names.
- `$PAGER` is used as a command without fallback in some `alias-fn` bodies (`tomohara-proper-aliases.bash:550, 1032`).

Best-practice hardening tips (minimal changes):

- Validate function names and arity in both helpers (`[[ $name =~ ^[a-zA-Z_][a-zA-Z0-9_-]*$ ]], (( $# == 2 ))`).
- Add collision policy (`declare -F "$name" check: warn/fail/overwrite explicitly`).
- Split APIs: keep `simple-alias-fn` for single-command pass-through only, and use `alias-fn` for compound bodies.
- Add a pager-safe pattern in bodies: `"${PAGER:-cat}" file`.
- Quote path expansions inside embedded bodies: `$(basename "$PWD")`.