Data Sheet

HUBER+SUHNER

Flexible RF cable
RG_195_A/U Item: 22510048

Description

RG: RG type RF cables

RG195, 95 Ohm, 1 GHz, 205°C, ø3.7 mm, PFA jacket

Technical Data

Construction

	Material	Detail	Diameter
Centre conductor	Steel, Copper+Silver plated	Strand-07	0.3 mm
Dielectric	PTFE (Polytetrafluoroethylene)		2.52 mm
Outer conductor	Copper, Silver plated	Braid, 93%	3.1 mm
Jacket	PFA (Perfluoroalkoxy)	RAL 9010 - wh	3.7 mm +/- 0.15

Print: HUBER+SUHNER RG 195 A/U 95 Ohm (production order number)

Electrical Data

Impedance		95 Ω +/- 3
Operating Frequency		1 GHz
Capacitance		50 pF/m
Velocity of signal propagation		69 %
Signal delay		4.79 ns/m
Screening effectiveness		≥ 38 dB (up to 1 GHz)
Operating voltage		≤ 1 kV_{rms} (at sea level)
Test voltage		2 kV_{rms} (50 Hz/1 min)

Mechanical Data

Weight		2.8 kg/100 m
Min. bending radius	static	15 mm
		37 mm

Environmental Data

Temperature range	-65 °C ... +205 °C
Installation temperature	-20 °C... +60 °C
Halogen free	No
2011/65/EU (RoHS - including 2015/863 and 2017/2102)	compliant
1907/2006/EC (REACH)	compliant

Additional Information

Remarks

(For details refer to the HUBER+SUHNER RF CABLES GENERAL CATALOGUE or contact your nearest HUBER+SUHNER partner)

Suitable Connectors

Cable group	U99 Customer Specific

Data Sheet

HUBER+SUHNER

Flexible RF cable
RG_195_A/U Item: 22510048

Matrix typical Attenuation [formula: (a*f^0.5 + b*f)] and maximum Power CW [formula: (p/f^0.5)]
Coefficients:

a = 0.6128	b = 0.0264	f_{max} = 1	P at 1GHz = 35

Frequency (GHz)	Nom. attenuation (dB / m)	Nom. attenuation (dB / ft)	Max. CW power (W)
	sea level 25° C ambient temperature	sea level 25° C ambient temperature	sea level 40° C ambient temperature
0,05	0,14	0,042	157
0,1	0,2	0,060	111
0,15	0,24	0,074	90
0,2	0,28	0,085	78
0,25	0,31	0,095	70
0,3	0,34	0,105	64
0,35	0,37	0,113	59
0,4	0,4	0,121	55
0,45	0,42	0,129	52
0,5	0,45	0,136	49
0,55	0,47	0,143	47
0,6	0,49	0,150	45
0,65	0,51	0,156	43
0,7	0,53	0,162	42
0,75	0,55	0,168	40
0,8	0,57	0,173	39
0,85	0,59	0,179	38
0,9	0,61	0,184	37
0,95	0,62	0,190	36
1,0	0,64	0,195	35

Waiver: Fact and figures herein are for information only and do not represent any warranty of any kind.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HUBER+SUHNER:

RG_195_A/U