

Tomáš Meravý Murárik

ais:127232

Bonus:

Zabezpečte výmenu aspoň piatich rôznych signálov dvomi medzi procesmi. Pri každej výmene signálu vypíšte čo sa práve deje z pohľadu procesov. Za tým vypíšte jednu používateľom definovanú správu, ktorú vyberiete ako ďalší argument z pola argumentov obdržaných pri spustaní skriptu.

```
#!/bin/bash
USER_MESSAGE=$1
function handle_signal1() {
    echo "script1 received SIGUSR1"
    kill -USR2 $CHILD_PID
}
function handle_signal2() {
    echo "script1 received SIGUSR2"
    echo "script1 says: '$USER_MESSAGE'"
}
# traps
trap 'handle_signal1' USR1
trap 'handle_signal2' USR2
#start the child process
echo "script1: Starting child process..."
./second_script.sh "$USER_MESSAGE" &
CHILD_PID=$!
echo "script1: Child process started with PID $CHILD_PID."
# Loop to wait for signals
while ;; do
    wait
done
```

Skript 2

```
#!/bin/bash
USER_MESSAGE=$1
function handle_signal1() {
    echo "script2 received SIGUSR1."
    kill -USR2 $PARENT_PID
}
function handle_signal2() {
    echo "script2 received SIGUSR2"
    echo "script2 says '$USER_MESSAGE'"
}
# Setup traps
trap 'handle_signal1' USR1
trap 'handle_signal2' USR2
# id of parent / the script that called it
PARENT_PID=$PPID
echo "script2 running with PID $$, parent PID is $PARENT_PID."
#send and receive
for i in {1..5}; do
    echo "script2 sending SIGUSR1 to parent (attempt $i)..."
    kill -USR1 $PARENT_PID
    sleep 1
done
```

output >

script1: Starting child process...

script1: Child process started with PID 3405.
script2 running with PID 3405, parent PID is 3404.
script2 sending SIGUSR1 to parent (attempt 1)...
script1 received SIGUSR1
script2 received SIGUSR2
script2 says 'mycustomMessage'
script2 sending SIGUSR1 to parent (attempt 2)...
script1 received SIGUSR1
script2 received SIGUSR2
script2 says 'mycustomMessage'
script2 sending SIGUSR1 to parent (attempt 3)...
script1 received SIGUSR1
script2 received SIGUSR2
script2 says 'mycustomMessage'
script2 sending SIGUSR1 to parent (attempt 4)...
script1 received SIGUSR1
script2 received SIGUSR2
script2 says 'mycustomMessage'
script2 sending SIGUSR1 to parent (attempt 5)...
script1 received SIGUSR1
script2 received SIGUSR2
script2 says 'mycustomMessage'