

长江电气集团股份有限公司

CHANGJIANG GROUP STOCK CO.,LTD.

Add: Liushi Chanhe Industrial Zone, Yueqing City, Zhejiang Province, P.R.C.
Tel: 0086-577-61735322 0086-15967773077 **Fax:** 0086-577-61726102
Email:chkod@chko.cn **MSN:**lemon2007101@hotmail.com **Skype:**lemon2007101

ZLJM—200C

Magnetic latch DC Contactor

■ SPECIFICATION

Model No.	ZLJM-200C
Contact Arrangement	1H (SPST-NO)
Contact Material	AgSnO
Contact Rating(at Resistive load)	200A 48VDC 200A 250VAC
Max.Switching Voltage	60VDC, 250VAC
Max.Switching Power	50000VA
Endurance of Over Loading Current 7Ie/10S	1400A/10S
Coil Rated Voltage	12,24,48,60,120VDC,etc.
Pick-up Voltage	40-70% of coil rated voltage
Drop-out Voltage	5-30% of coil rated voltage
Contact Pressure Drop	At most 300mV when 100A
Insulation Resistance	Min.100MΩat 500VDC
Dielectric Strength (Between Insulated Electric Parts)	1000VAC 50/60Hz (1 minute)
Operate Time	Max.50mSec
Release Time	Max.50mSec
Ambient Temperature	-40~+85C
The shocking for fixed point	(10-200)HZ Acceleration <=3.5g
Shocking	(60-100) time/minute Acceleration<=4g
Mechanical life	100,000 Operation (no load)
Electrical life	50,000 Operation (at rated load)

■ Dimension

