

# Dijkstra's Shunting-Yard Algorithm

Converts ordinary (infix) notation to reverse Polish

Output (RPN)

Input (infix)

$3 + 5$

Stack for operators

# Dijkstra's Shunting-Yard Algorithm

Converts ordinary (infix) notation to reverse Polish

Output (RPN)

3

Input (infix)

+ 5

Stack for operators

# Dijkstra's Shunting-Yard Algorithm

Converts ordinary (infix) notation to reverse Polish

Output (RPN)

Input (infix)

3

5

Stack for operators

+

# Dijkstra's Shunting-Yard Algorithm

Converts ordinary (infix) notation to reverse Polish

Output (RPN)

Input (infix)

3 5

Stack for  
operators

+

# Dijkstra's Shunting-Yard Algorithm

Converts ordinary (infix) notation to reverse Polish

Output (RPN)

Input (infix)

3 5 +

Stack for  
operators


# Rules

- Input numbers (and variables) go straight to output
- Input ( goes to stack
- Input ) pops stack to output, as far as matching (
- Input function or infix operator goes to stack, but first pops stack to output, up to - but not including - something of lower precedence
- End of input pops stack to output

e.g.

$$(3 + 2)^* \sqrt{(x*x + y*y)} + 8$$

---



e.g.

$$3 + 2\sqrt{x^2 + y^2} + 8$$

---

(



e.g.

3

$$+ 2) \sqrt{x*x + y*y} + 8$$

(

e.g.

3

$$2) \sqrt{x^2 + y^2} + 8$$

+

(

e.g.

3 2

$$)^*\sqrt{(x*x + y*y)} + 8$$

+  
(

e.g.

3 2 +

\*  $\sqrt{(x*x + y*y)} + 8$

Brackets are  
never output

e.g.

3 2 +

$x*x + y*y) + 8$

(  
↓  
\*

Exercise: Finish it