MSc/ICY Software Workshop
Classes and Inheritance

Manfred Kerber   www.cs.bham.ac.uk/~mmk

2 November 2016

Object-Oriented Programming

Distinguish:

- **Classes**, e.g., BankAccount, Customer
- **Objects**, e.g., bankAccountJohn, customerMary
  created by a **Constructor**, e.g.
  `public BankAccount (Customer customer, String password)`
- **Methods**, e.g. getBalance()

Superclass vs subclass

- A subclass `SubclassA` inherits from its (unique) superclass `SuperclassB` (introduced by `public class SubclassA extends SuperclassB`)
- All methods not explicitly overridden in the subclass are inherited from the superclass.
- Overridden methods from the superclass are accessible via super in the body of the overriding method, e.g., in writing the code for a `toString()` method you can use `super.toString()`.
- Variables (and methods) private to the superclass are not accessible from the subclass.


Rationale for Inheritance

Inheritance is a very important feature of object oriented programming.

- Inherit methods, that is, methods that are common to the superclass can be used without duplication of code.
- Inheritance keeps code simpler.
- If code needs to be changed (and remember very often it needs to be changed) then it can be changed at a single point. This is important since it makes code maintainable (if code is duplicated any changes may be messy since parts may be overlooked and inconsistencies may be introduced).

Example: rudimentary library system

- The library offers books on loan, either on `shortLoan` (one day) or `longLoan` (at most 30 days).
- `User`s are either `StudentUser`, `StaffUser`, or `CommunityUser`.
- Assume that students can borrow at most 10 books, staff and members of the community as many as they like. Members of the community have to pay a fee of £ 1 per book (others not). `UGUser`s can borrow books for at most 10 days, `MScUser`s for at most 20 days, `PhDUser`s for at most 30 days.

Hierarchy of super- and subclasses

Abstract Class

E.g., `public abstract class User`.
Abstract classes do not have immediate objects, but only via subclasses.
With an abstract class `User`, with an abstract subclass `StudentUser` and (non-abstract) subclasses `StaffUser`, and `CommunityUser`
as well as the three subclasses of `StudentUser`:

- `UGUser`,
- `MScUser`, and
- `PhDUser`

each user object generated should be member of a class `UGStudent`, `MScStudent`, `PhDStudent`, `StaffUser`, or `CommunityUser`.

Classes

- have an abstract class `User`
- distinguish three subclasses of users: `StudentUser`, `StaffUser`, `CommunityUser`, using inheritance.
- distinguish three subclasses of `StudentUser`: `UGUser`, `MScUser`, `PhDUser`, using inheritance.
- For a `User` we know their `firstName`, `surname`, `phoneNumber`, `booksOnLoan`. Each `bookOnLoan` goes with the `Book`, the `DateTime` when it was borrowed, and the `DateTime` when it has to be given back.

Build suitable classes: `User`, `StudentUser`, `StaffUser`, `CommunityUser` making use of inheritance to model the situation.