A-SAFE

FlexiShield Column Guard

PRH-1034-A-SAFE-23112023-1

Production

Dimensions (mm/inches)

A	520 / 20½	H	100 / 4
B	300 / 11⅝	I	150 / 6
C	180 / 7	J	300 / 11⅝
D	250 / 9⅝		
E	200 / 7⅞		
F	100 / 4		
G	50 / 2		

The corner sizes and expansion panels combine in different configurations to fit any universal sized square or rectangle column.

Front



Corner Sizes



Expansion Panel Sizes



Colour Combination

Standard

Standard Yellow
RAL 1007*
PANTONE 7548*

*Please note that the RAL and PANTONE colours listed are the closest match to standard A-SAFE colours, but may not be exact matches of the actual product colour and should be used for guidance only.

Product Material

MEMAPLEX™

Ultimate strength polymer created from an exclusive composition of the most sophisticated polyolefins and rubber additives, expertly blended for unequalled strength and flexibility.

Weight of product

Per FlexiShield Unit	
100 x 100 / 4 x 4	12.71 Kg / 28.02 lbs
200 x 200 / 7⅞ x7⅞	15.51 Kg / 34.19 lbs
300 x 300 / 11⅝ x 11⅝	18.31 Kg / 40.37 lbs
400 x 400 / 15¾ x 15¾	21.11 Kg / 46.54 lbs
500 x 500 / 19⅔ x 19⅔	23.91 Kg / 52.71 lbs
600 x 600 / 23⅝ x 23⅝	26.71 Kg / 58.89 lbs
Per FlexiShield Spacer Unit	
100 / 4	3.76 Kg / 8.29 lbs
150 / 6	4.76 Kg / 10.49 lbs
300 / 11⅝	6.76 Kg / 14.90 lbs

Minimum order quantities

Not applicable on this product

Suitability

Environment

Internal and External use

ATEX Suitability

Not suitable in an explosive atmosphere

Vehicle Suitability

Pedestrians	Manual Pallet Truck	Electric Pedestrian Stacker	Frame Rail Container

Fit for purpose application

Building and equipment protection	Column protection

Impact Zone
0 - 1000mm
(0 - 39⅜ inches)

Material Properties	MEMAPLEX™
Temperature Range	-10°C to 50°C
Ignition Temperature	370°C to 390°C
Flash Point	350°C to 370°C
Toxicity	Not Hazardous
Chemical Resistance	Excellent - ISO/TR 10358
Weathering Stability (Grey Scale)	5/5*
Light Stability (Blue Wool Scale)	7/8**
Static Rating (Surface Resistivity)	10^{15} - 10^{16} Ω
Hygiene Seals	No

* Weathering scale 1 is very poor and 5 is excellent ** Light stability scale 1 is very poor and 8 is excellent

Fire information

Manufactured from polypropylene. Polypropylene has an ignition temperature of 370º Celsius which is significantly higher than materials such as wooden pallets or polymers such as flexible PVC. This means that for combustion of an A-SAFE barrier to occur, a facility fire would need to be both large and well advanced, by which time any personnel would have already been evacuated to safety.

Polymer has been engineered to remain stable up to a temperature of 350º Celsius. In contrast, PVC starts breaking down at between 249º Celsius and 273º Celsius, and materials such as wood will burn instantly.

Our material has been specially developed to minimise the release of smoke during combustion. Furthermore, unlike environmentally hazardous polymers like PVC, it does not release harmful dioxins, hydrogen cyanide or hydrogen chloride when burnt.

Environmental information

Research conducted by a leading plastic solutions company* showed that producing one metric tonne of polymer generates less carbon emissions than producing a tonne of steel**. Therefore, from the very outset of raw material production, polymer provides a significant CO_2 saving over steel.

For more information visit A-SAFE.com

* http://www.borealisgroup.com ** www.liloontheweb.org.uk/handbook/carbonfootprint

Recycling Information	
Packaging	Column Guard
Mixed Recycled	5

Part Codes

1. A-01-14-0040 – A-01-14-0050 =
FlexiShield Column Guard
100mm x 100mm >
600mm x 600mm,
Yellow

Based on
100mm x 100mm
FlexiShield Column
Protection

P-01-03-0088 =
36 OD 2.5mm wall x 497mm
Black x 4 No

E-01-01-0011 =
30 OD 8.75mm wall tube,
Black - 497mm (G)

R-01-01-0005 =
Column Protector 50mm Corner,
Yellow x 4 No

2. A-01-14-0051 – A-01-14-0056 =
FlexiShield Column Guard Spacer Set
100mm > 300mm,
Black or Yellow

Data Sheets

Testing Videos

CAD

Install Documents

Certificates

If you have any questions please contact
the product management team at A-SAFE HQ
Product.Management@asafe.com

A-SAFE
PIONEERING WORKPLACE SAFETY

PRODUCTHUB

Document Reference	PRH-1034-A-SAFE-23112023-1
Document Description	FlexiShield Column Guard
Date Created	November 2023
Author/s	Matthew Briggs
Checked by	Alex Dougherty / Nathaniel Hyde
Approved by	Ben Allen
Revision	Version 1 - November 2023