



# The Federated GraphQL Subscriptions Zoo



Tom Houlé

# Subscriptions are special... in GraphQL

“a long-lived request that fetches data in response to a sequence of events over time”

— GraphQL spec (draft)

# Subscriptions are special... in GraphQL

"a long-lived request that fetches data in response to a sequence of events over time"

— GraphQL spec (draft)

"GraphQL supports type name introspection within any selection set in an operation, with the single exception of selections at the root of a subscription operation."

— GraphQL spec (draft)

# Subscriptions are special... in GraphQL

# Subscriptions are special... in GraphQL

"Subscription operations must have exactly one root field.

To enable us to determine this without access to runtime variables, we must forbid the @skip and @include directives in the root selection set."

— GraphQL spec (draft)

# Subscriptions are special... in GraphQL

"Subscription operations must have exactly one root field.

To enable us to determine this without access to runtime variables, we must forbid the @skip and @include directives in the root selection set."

— GraphQL spec (draft)

"While each subscription must have exactly one root field, a document may contain any number of operations, each of which may contain different root fields. When executed, a document containing multiple subscription operations must provide the operation name as described in `GetOperation()`."

— GraphQL spec (draft)

# **Subscriptions are special... in GraphQL-over-HTTP**

# Subscriptions are special... in GraphQL-over-HTTP

"GraphQL Subscriptions are beyond the scope of this specification at this time."

— GraphQL over HTTP spec (draft)



**Subscriptions are actually not that special in Federated GraphQL**

# Subscriptions are actually not that special in Federated GraphQL

Schema of the sales subgraph:

```
1 type Product @key(fields: "id") {  
2   id: ID!  
3 }  
4  
5 type Subscription {  
6   productSales: Product  
7 }
```



Schema of the products subgraph:

```
1 type Product @key(fields: "id") {  
2   id: ID!  
3   name: String!  
4 }  
5  
6 type Query {  
7   productById(  
8     id: ID!  
9   ): Product @lookup  
10 }
```



# Subscriptions are actually not that special in Federated GraphQL

Client → Gateway

```
1 subscription ProductSalesWithName {  
2   productSales {  
3     name  
4   }  
5 }
```



Gateway → sales subgraph

```
1 subscription {  
2   productSales {  
3     id  
4   }  
5 }
```



Gateway → products subgraph

```
1 query {  
2   productById(id: $id) {  
3     name  
4   }  
5 }
```



# Subscriptions are actually not that special in Federated GraphQL

Data returned to the client:

```
1  {"name": "Labubu"}
2  {"name": "Labubu"}
3  {"name": "Crocs"}
4  {"name": "Zune"}
5  {"name": "Furbies (12 pack)"}
6  {"name": "Labubu"}
7  {"name": "Google Glass"}
```







# The problems with Federated Subscriptions

- Lack of transport standardisation has led to fragmentation:
  - WebSockets (HTTP/1.1)
  - SSE (HTTP/2 and 3)
- Stateful connections impose extra burden on the subgraphs and the gateway
- Connection loss is both more likely and harder to handle
- One connection between the Gateway and the relevant subgraph per subscribed client, even when they all subscribe to the same events
- Multi-protocol subscriptions





# Multi-protocol subscriptions

-  Client —  → Gateway —  →  Subgraph

# Multi-protocol subscriptions

-  Client —  → Gateway —  →  Subgraph
- At each step, one of
  - SSE,
  - WebSockets
    - `subscriptions-transport-ws`
    - `graphql-ws` / `graphql-transport-ws`
- And different handshake shapes between each!
  - Headers vs init payload formats

# Multi-protocol subscriptions

-  Client —  → Gateway —  →  Subgraph
- At each step, one of
  - SSE,
  - WebSockets
    - subscriptions
    - graphql-ws / g
- And different hand
  - Headers vs init





# Event queue to gateway

- Two implementations
  - EDFS
  - Grafbase extensions

# Takeaways

- Pros of traditional federated subscriptions
  - Federate existing GraphQL subgraphs, no need to modify them
  - Subscription fields are managed directly in your subgraphs, next to your other logic

# Takeaways

- Pros of traditional federated subscriptions
  - Federate existing GraphQL subgraphs, no need to modify them
  - Subscription fields are managed directly in your subgraphs, next to your other logic
- Pros of subscriptions offloaded to a message queue
  - Stream deduplication
  - Non-GraphQL services can publish to subjects directly

# Takeaways

- Pros of traditional federated subscriptions
  - Federate existing GraphQL subgraphs, no need to modify them
  - Subscription fields are managed directly in your subgraphs, next to your other logic
- Pros of subscriptions offloaded to a message queue
  - Stream deduplication
  - Non-GraphQL services can publish to subjects directly

**You can mix and match both approaches**

# Conclusion

Take care.

**Also**

**Also**

Workshop!

**Also**

Workshop! Tomorrow!



**Also**

Workshop! Tomorrow!

Grote Zaal - 2nd Floor.

**Also**

Workshop! Tomorrow!

Grote Zaal - 2nd Floor. 10:45am

**Also**

Workshop! Tomorrow!

Grote Zaal - 2nd Floor. 10:45am .

# **Appendices**

## Links

- WebSockets
  - Issues and security implications with subscriptions-transport-ws
- SSE
  - GraphQL-SSE spec
- Pen Pineapple Apple Pen