Chapter 6
Trees

This chapter offers a thorough exploration of tree data structures, covering basic concepts and different types such as binary trees, binary search trees (BST), AVL trees, B-trees, heaps, and trie trees. It explains tree traversal methods, as well as insertion and deletion operations in BSTs. Additionally, the chapter discusses practical applications and performance considerations, providing a comprehensive understanding of trees.

6.1 Introduction to Trees

A tree is a hierarchical data structure that simulates a hierarchical tree structure with a root value and subtrees of children, represented as a set of linked nodes. Trees are widely used in computer science due to their efficiency in various operations and their ability to model relationships between data elements naturally. Each tree structure is composed of nodes, where each node holds a value or condition, and references to other nodes. The fundamental concepts essential to understanding trees include nodes, edges, root, leaves, and height.

Nodes: A node is an individual element of a tree holding data. Each node can have zero or more child nodes. The nodes that have the same parent are called siblings.

Edges: An edge is the connection between two nodes. It signifies the relationship between the parent and the child nodes.

Root: The node at the top of the tree is called the root. It is the only node with no parent. Every tree must have a root node.

Leaves: Nodes that do not have any children are called leaves or leaf nodes. They are also known as external nodes.

Height of a Tree: The height of a tree is the length of the longest path from the root to a leaf. It signifies the maximum number of edges from the root to the leaf.

Depth of a Node: The depth of a node is the number of edges from the root to the node.

Subtree: A subtree represents any node of the tree and all of its descendants.

The hierarchical nature of trees makes them suitable for representing hierarchical data structures such as organizational structures, file systems, and abstract syntax trees. Trees provide several beneficial properties:

- Efficient traversal and search operations.
- Hierarchical representation of data.
- Recursive nature enabling simpler implementation of algorithms.

Types of Trees:

- **Binary Trees**: Each node has at most two children, often termed the left and right child.
- **Binary Search Trees (BST)**: A binary tree with the property that the left child of a node contains a value less than the node's value, and the right child contains a value greater than the node's value.
- **AVL Trees**: A self-balancing binary search tree where the difference between the heights of the left and right subtrees of any node is no more than one.
- **B-Trees**: A generalization of binary search trees where nodes can have more than two children. They are optimized for systems that read and write large blocks of data.
- **Heaps**: A special tree-based data structure that satisfies the heap property. In a max-heap, each parent node is greater than or equal to its children; in a min-heap, each parent node is less than or equal to its children.
- **Trie Trees**: A tree used to store a dynamic set or associative array where the keys are usually strings.

Tree Representation: There are multiple ways to represent trees in a program. The most common representations include:

1. Linked Representation: Each node is an object. Nodes have references to their children.

```
class TreeNode:
   def __init__(self, key):
      self.key = key
      self.left = None
      self.right = None
```

2. List Representation: Parent nodes and child nodes are indexed in a list.

```
tree = [
   [1, 2], # Node 0 has children 1 and 2
   [None, None], # Node 1 is a leaf node
   [None, None] # Node 2 is a leaf node
]
```

Traversal Methods: Trees can be traversed in multiple ways. The fundamental tree traversal methods include:

- **Pre-order traversal**: Process the root node first, then recursively process the left subtree, followed by the right subtree.
- **In-order traversal**: Recursively process the left subtree first, then the root node, followed by the right subtree.
- **Post-order traversal**: Recursively process the left subtree, the right subtree, and finally the root node.
- **Level-order traversal**: Traverse nodes level by level, starting from the root.

In many applications, trees help improve the efficiency and performance for operations such as search, insertion, and deletion, particularly when compared to linear data structures like arrays or linked lists.

Understanding the fundamental concepts of trees and their various types and representations is crucial for mastering more advanced topics in data structures and algorithms. Subsequent sections will delve into specific tree types and explore their properties, operations, and applications in greater depth.

6.2 Binary Trees

A binary tree is a hierarchical data structure in which each node has at most two children, referred to as the left child and the right child. A binary tree is defined recursively as either being empty or consisting of a root node with two subtrees, each of which is also a binary tree. This structure forms the basis of many algorithms and data structures, making it essential to understand its properties, implementation, and real-world applications.

Properties of Binary Trees:

- *Maximum Nodes:* A binary tree of depth d (where the root node is at depth 0) can have at most 2^d nodes at depth d, and $2^{d+1} - 1$ nodes in total.
- *Minimum Nodes:* The minimum number of nodes in a binary tree of depth d is $d + 1$ (a tree where each node has only one child).
- *Height of Binary Tree:* The height of a binary tree is defined as the length of the longest path from the root to a leaf. For a tree with a single node, the height is 0.
- *Balanced Binary Tree:* A binary tree is balanced if, for every node in the tree, the height difference of the left and right subtrees is at most one.

Binary Tree Representation: Binary trees can be implemented using various representations, two of which are array representation and linked representation.

Array Representation: In an array representation of a binary tree, the nodes are stored in a sequential manner. The root is placed at the first position of the array (index 0 or 1 depending on 1-based or 0-based indexing). For a node at index i,

- The left child is at index $2i + 1$ (0-based indexing) or $2i$ (1-based indexing).
- The right child is at index $2i + 2$ (0-based indexing) or $2i + 1$ (1-based indexing).

This method is efficient in terms of space but becomes inefficient when the tree is sparse because it leads to wasted space.

Linked Representation: In the linked representation, each node is an object containing three fields:

- A data element.
- A reference to the left child.
- A reference to the right child.

This approach is often used as it allows the tree to grow dynamically. Below is an example of a simple binary tree node class in Python using the linked representation.

```
class TreeNode:
   def __init__(self, key):
      self.left = None
      self.right = None
      self.val = key

# Example of creating a binary tree with this class
root = TreeNode(1)
root.left = TreeNode(2)
root.right = TreeNode(3)
root.left.left = TreeNode(4)
root.left.right = TreeNode(5)
```

Traversing a Binary Tree: Traversal of a binary tree refers to the process of visiting each node in the tree exactly once in a systematic way. There are several common methods of binary tree traversal, each serving different purposes.

- *Inorder Traversal (Left, Root, Right):*

```
def inorder_traversal(root):
   if root:
      inorder_traversal(root.left)
      print(root.val, end=' ')
      inorder_traversal(root.right)
```

- *Preorder Traversal (Root, Left, Right):*

```
def preorder_traversal(root):
   if root:
      print(root.val, end=' ')
      preorder_traversal(root.left)
      preorder_traversal(root.right)
```

- *Postorder Traversal (Left, Right, Root):*

```
def postorder_traversal(root):
   if root:
      postorder_traversal(root.left)
      postorder_traversal(root.right)
      print(root.val, end=' ')
```

Applications of Binary Trees: Binary trees are fundamental structures in computer science, often utilized in the following scenarios:

- *Expression Trees:* Used in compilers to represent expressions. Each leaf is an operand, and each internal node is an operator.
- *Binary Search Trees (BSTs):* Facilitates efficient searching, insertion, and deletion operations.
- *Heaps:* Implement priority queues.

- *Decision Trees:* Used in machine learning for decision-making processes.
- *Syntax Trees:* Used in natural language processing to parse sentences.

The straightforward nature of binary trees and their extensive applicability in various domains highlight their importance in both theoretical and practical aspects. Whether through array or linked representations, the ability to traverse and manipulate binary trees efficiently is a foundational skill for proficient programming and algorithm design. Detailed understanding of binary tree traversal methodologies lays the groundwork for mastering more complex tree structures and algorithms discussed in subsequent sections.

6.3 Tree Traversal Methods

In computer science, tree traversal refers to the process of visiting each node in a tree data structure exactly once in a systematic manner. Efficient traversal methods are critical for performing operations such as searching, inserting, and deleting nodes in trees. This section discusses commonly used tree traversal methods: Pre-order, In-order, Post-order, and Level-order traversal.

Pre-order Traversal: In a pre-order traversal, the nodes are recursively visited in this order: the root node, the left subtree, and then the right subtree. For a tree with root R, left child L, and right child R, the traversal follows R → L → R. The pseudo-code for pre-order traversal is:

```
def preOrderTraversal(node):
   if node is not None:
      print(node.data)
      preOrderTraversal(node.left)
      preOrderTraversal(node.right)
```

For example, given the following tree structure:

```
     A
    / \
  B    C
 / \
D   E
```

The pre-order traversal would visit the nodes in the following order: A → B → D → E → C. The output is:

```
A B D E C
```

In-order Traversal: In-order traversal visits the nodes in the following order: the left subtree, the root node, and then the right subtree. This method is often utilized for binary search trees (BSTs) because it results in nodes being visited in non-decreasing order. The pseudo-code for in-order traversal is:

```
def inOrderTraversal(node):
   if node is not None:
      inOrderTraversal(node.left)
```

```
        print(node.data)
        inOrderTraversal(node.right)
```

Using the same example tree, the in-order traversal would visit the nodes in the following order: D → B → E → A → C. The output is:
D B E A C

Post-order Traversal: Post-order traversal recursively visits nodes in the following order: the left subtree, the right subtree, and then the root node. It is often used for deleting or freeing nodes and various tree-related algorithms that require processing child nodes before their parent nodes. The pseudo-code for post-order traversal is:

```
def postOrderTraversal(node):
    if node is not None:
        postOrderTraversal(node.left)
        postOrderTraversal(node.right)
        print(node.data)
```

For the example tree, the post-order traversal would visit the nodes in the following order: D → E → B → C → A. The output is:
D E B C A

Level-order Traversal: Level-order traversal, also known as breadth-first traversal, visits nodes level by level from top to bottom and left to right within each level. This is typically implemented using a queue data structure to keep track of the nodes. The pseudo-code for level-order traversal is:

```
from collections import deque

def levelOrderTraversal(root):
    if root is None:
        return

    queue = deque([root])

    while queue:
        node = queue.popleft()
        print(node.data)

        if node.left is not None:
            queue.append(node.left)
        if node.right is not None:
            queue.append(node.right)
```

In the example tree, the level-order traversal would visit the nodes in the following order: A → B → C → D → E. The output is:
A B C D E

These traversal methods provide comprehensive ways to visit every node in a tree, each serving different practical scenarios depending on the requirements of the tree-based operation. The choice of traversal method is determined by the desired order in which the nodes should be processed.

6.4 Binary Search Trees (BST)

A Binary Search Tree (BST) is a particular type of binary tree that maintains a specific order among its elements, facilitating efficient search, insertion, and deletion operations. In a BST, each node contains a key, and possibly associated data, with the key values organized such that:

- The key in the left child of a node is less than the key in the parent node.
- The key in the right child of a node is greater than the key in the parent node.
- Both the left and right sub-trees of each node are also binary search trees.

This ordering allows for binary search properties to be applied, ensuring operations are logarithmic in complexity in the average case.

Definition and Properties

Formally, a BST is defined as a binary tree where for every node *n*:

$$key(left(n)) < key(n) < key(right(n))$$

where *left*(*n*) and *right*(*n*) denote the left and right children of *n*, respectively.

The primary properties of BSTs include:

- **Searching:** Given a key, the structure of the BST allows for efficient querying by recursively traversing left or right sub-trees, depending on whether the key is lesser or greater than the current node's key.
- **Insertion:** New keys are inserted by recursively finding the correct position that maintains the binary search property.
- **Deletion:** Removing a node from a BST is more complex and involves three primary cases: deleting a leaf node, deleting a node with one child, and deleting a node with two children.

Operations in BSTs

Search Operation

Given a BST, the search operation is performed by comparing the target key with the root node's key. Based on the comparison, the algorithm decides to proceed to either the left or the right sub-tree, continually narrowing down the search space.

```
class Node:
   def __init__(self, key):
      self.left = None
      self.right = None
```

```
        self.val = key

def search(root, key):
    if root is None or root.val == key:
        return root

    if root.val < key:
        return search(root.right, key)

    return search(root.left, key)
```

Insertion Operation

Insertions in a BST maintain its ordered structure. Starting from the root, we recursively find the position to insert the new key such that the binary search property is preserved.

```
def insert(root, key):
    if root is None:
        return Node(key)

    if key < root.val:
        root.left = insert(root.left, key)
    else:
        root.right = insert(root.right, key)

    return root
```

Deletion Operation

Deletion in a BST handles three distinct cases:

1. **Node to be deleted is a leaf node:** Simply remove the node. 2. **Node to be deleted has one child:** Remove the node and replace it with its child. 3. **Node to be deleted has two children:** - Find the in-order successor (the smallest key in the right sub-tree). - Replace the node’s key with the in-order successor’s key. - Delete the in-order successor.

```
def minValueNode(node):
    current = node
    while(current.left is not None):
        current = current.left
    return current

def deleteNode(root, key):
    if root is None:
        return root

    if key < root.val:
        root.left = deleteNode(root.left, key)
```

```
    elif key > root.val:
        root.right = deleteNode(root.right, key)
    else:
        if root.left is None:
            temp = root.right
            root = None
            return temp
        elif root.right is None:
            temp = root.left
            root = None
            return temp

        temp = minValueNode(root.right)
        root.val = temp.val
        root.right = deleteNode(root.right, temp.val)

    return root
```

Traversal Methods

Traversal methods for BSTs include in-order, pre-order, and post-order traversals, which are defined the same way as for binary trees. In-order traversal is particularly useful for BSTs as it visits nodes in ascending order of their keys.

```
def inorderTraversal(root):
    if root:
        inorderTraversal(root.left)
        print(root.val, end=" ")
        inorderTraversal(root.right)
```

Performance Considerations

BSTs offer logarithmic time complexity operations for balanced trees, but the worst-case complexity can degrade to linear time when the tree becomes skewed (i.e., resembles a linked list). The shape of the tree depends on the order of insertions and deletions.

Balanced variants such as AVL trees or Red-Black trees are often employed to ensure logarithmic time complexities for all operations. These balanced trees automatically adjust to maintain their structure, generally ensuring O(log n) performance.

Understanding and implementing BSTs form a critical foundation for advanced data structures and algorithms. The operations and properties outlined serve as the cornerstone for understanding more complex balanced trees explored in subsequent sections.

6.5 Insertion in BST

The insertion operation in a Binary Search Tree (BST) is a fundamental procedure that maintains the tree's distinctive property: for any given node, all elements in the left subtree are less than the node's key, and all elements in the right subtree are greater than the node's key. This section delves into the mechanisms of the insertion process, detailing the algorithm, its implementation in Python, and the implications on the BST's structure and balance.

To insert a new key into a BST, we initially start at the root and traverse the tree following the BST property until we find the correct location for the new node. The following steps outline this process:

1. **Start at the Root**: Begin the operation at the root node. 2. **Traverse the Tree**: Compare the key of the new node, *k*, with the key of the current node:

- If *k* is less than the current node's key, move to the left child.
- If *k* is greater than the current node's key, move to the right child.

3. **Find the Position**: Continue this procedure recursively until the appropriate NULL position is found (where either the left or right pointer of a node is NULL). 4. **Insert the Node**: Insert the new node at the identified position.

The time complexity of the insertion operation in a BST is $O(h)$, where h is the height of the tree. In the worst-case scenario, for an unbalanced BST, h can be as large as n, the number of nodes, resulting in $O(n)$ complexity. In a balanced tree, $h = \log n$, yielding $O(\log n)$ complexity.

Python Implementation

The following Python code demonstrates the insertion process in a BST.

```
class Node:
   def __init__(self, key):
      self.left = None
      self.right = None
      self.val = key

def insert(root, key):
   # If the tree is empty, return a new node
   if root is None:
      return Node(key)

   # Otherwise, recur down the tree
   if key < root.val:
      root.left = insert(root.left, key)
   else:
      root.right = insert(root.right, key)

   # return the (unchanged) node pointer
   return root
```

```
# Function to do inorder tree traversal
def inorder(root):
   if root:
      inorder(root.left)
      print(root.val, end=' ')
      inorder(root.right)

# Driver program to test the above functions
root = None
keys = [20, 8, 22, 4, 12, 10, 14]

for key in keys:
   root = insert(root, key)

print("Inorder traversal of the BST:")
inorder(root)
```

In the provided implementation, the ‘insert()‘ function initiates by checking if the current root is NULL. If so, it creates a new node with the specified key. Otherwise, it compares the key with the value of the root node and recursively calls itself to either the left or right subtree accordingly. The ‘inorder()‘ function is used for verification of the insertion process by performing an inorder traversal of the tree, which should produce a sorted sequence of inserted keys.

Example Execution

```
Inorder traversal of the BST:
4 8 10 12 14 20 22
```

This output verifies that keys are correctly inserted and placed to conform to the BST properties.

Effect on Tree Structure

The insertion of nodes affects the overall structure and balance of the tree. Repeated insertions of sequential or random keys can result in highly unbalanced trees with unfavorable height. For example, inserting keys in ascending or descending order will yield a degenerate tree (similar to a linked list), where each node has only one child. This scenario is detrimental as it degrades the performance of search, insertion, and deletion operations to $O(n)$.

Effective strategies to maintain tree balance, such as self-balancing mechanisms (e.g., AVL trees, Red-Black trees), will be discussed in subsequent sections. Ensuring balance is crucial for achieving the ideal performance of $O(\log n)$ for the aforementioned operations.

Understanding the insertion process in BSTs forms the bedrock for mastering tree data structures. The presented approach and implementation are fundamental, serving as a precursor to more sophisticated tree algorithms and structures.

6.6 Deletion in BST


Deletion in a Binary Search Tree (BST) is a fundamental operation that ensures the integrity and utility of the data structure as elements are dynamically removed. When an element is deleted from a BST, three primary cases must be handled: deleting a leaf node, deleting a node with one child, and deleting a node with two children. Each case maintains the BST property, i.e., for any given node, all elements in the left subtree are less than the node, and all elements in the right subtree are greater.

Let’s delve into each case with meticulous detail.

Case 1: Deleting a Leaf Node


A leaf node is a node that has no children. Deleting a leaf node is the simplest case. We only need to remove the node from the tree and update the parent node to adjust its reference accordingly.

For example, consider the following BST:



To delete the node 20: 1. Find the node to be deleted (20). 2. Since 20 is a leaf node, simply remove it.

The resulting BST is:




Case 2: Deleting a Node with One Child

This case involves a node that has exactly one child, either left or right. The process requires the child to take the place of the node to be deleted.

Consider the same BST example, and let’s delete the node 30, which has one child (node 40):

1. Find the node to be deleted (30). 2. Since 30 has one child (40), remove 30 and replace it with 40.

The resulting BST is:



Case 3: Deleting a Node with Two Children

This is the most complex case. A node with two children requires finding the node's in-order predecessor or successor to maintain the BST properties.


The process to delete a node with two children is as follows:

1. Find the node to be deleted. 2. Find its in-order successor (smallest node in the right subtree) or in-order predecessor (largest node in the left subtree). 3. Replace the node's value with the in-order successor's (or predecessor's) value. 4. Delete the in-order successor (or predecessor), which will now have at most one child.

Consider again the BST example. To delete the node 50, which has two children:

1. Find the node to be deleted (50). 2. Find the in-order successor of 50, which is 60 (smallest node in the right subtree of 50). 3. Replace the value of 50 with 60. 4. Delete the node 60, which has no children.

The resulting BST is:



Python Implementation

The following Python code demonstrates the deletion process in a BST:

```
class TreeNode:
   def __init__(self, key):
      self.left = None
      self.right = None
      self.val = key

def deleteNode(root, key):
   if root is None:
      return root

   if key < root.val:
      root.left = deleteNode(root.left, key)
   elif key > root.val:
      root.right = deleteNode(root.right, key)
   else:
      if root.left is None:
         return root.right
      elif root.right is None:
         return root.left
```

```
        temp = minValueNode(root.right)
        root.val = temp.val
        root.right = deleteNode(root.right, temp.val)

    return root

def minValueNode(node):
    current = node
    while current.left is not None:
        current = current.left
    return current
```

The `deleteNode` function follows the aforementioned steps for deletion: 1. It searches for the node with the specified key. 2. Once found, if the node has no children or only one child, the node is simply replaced by its child. 3. If the node has two children, it replaces the node's value with its in-order successor's value and recursively deletes the successor node.

The helper function `minValueNode` finds the in-order successor, ensuring the proper maintenance of BST properties during deletion.

Ensuring correctness in these operations is critical for maintaining the efficiency and structural integrity of the BST, keeping operations like search, insertion, and deletion at optimal time complexities.

6.7 AVL Trees

AVL trees, named after their inventors Adelson-Velsky and Landis, are a type of self-balancing binary search tree (BST). In an AVL tree, the heights of the two child subtrees of any node differ by at most one, ensuring that the tree remains approximately balanced. This balancing is crucial as it guarantees $O(\log n)$ time complexity for insertion, deletion, and lookup operations, where n is the number of nodes in the tree.

An AVL tree maintains its balance through a series of rotations that adjust the structure after insertions or deletions. This section delves into the fundamental properties of AVL trees, their balancing mechanisms, and the operations for insertion and deletion with corresponding rotations.

Balance Factor:

The balance factor of a node in an AVL tree is the difference between the heights of the left and right subtrees. Formally, for a node N:


$$\text{BalanceFactor(N)} = \text{Height(LeftSubtree)} - \text{Height(RightSubtree)}$$

A node is considered balanced if its balance factor is -1, 0, or 1. If the balance factor of any node becomes less than -1 or greater than 1, the tree requires rebalancing.


Rotations:

Rotations are operations that change the structure of the tree without altering the in-order sequence of elements, thereby preserving the BST property. There are four types of rotations used to restore balance in an AVL tree:


1. **Left Rotation (LL Rotation)**: A left rotation is performed when a right-heavy subtree becomes unbalanced.




Transforms to:



2. **Right Rotation (RR Rotation)**: A right rotation is performed when a left-heavy subtree becomes unbalanced.



Transforms to:



3. **Left-Right Rotation (LR Rotation)**: When a left subtree is right-heavy, a double rotation (left-right) is needed. This involves a left rotation on the left child followed by a right rotation on the unbalanced node.

4. **Right-Left Rotation (RL Rotation)**: When a right subtree is left-heavy, a double rotation (right-left) is needed. This involves a right rotation on the right child followed by a left rotation on the unbalanced node.

Insertion in AVL Tree:

The insertion process in an AVL tree involves performing a standard BST insertion followed by verifying and restoring balance through rotations if necessary.

Consider the following function for inserting a node in an AVL tree:

```
class TreeNode:
   def __init__(self, key):
      self.key = key
      self.left = None
      self.right = None
      self.height = 1

def insert(node, key):
   # Step 1: Perform the normal BST insertion
   if not node:
      return TreeNode(key)
   elif key < node.key:
      node.left = insert(node.left, key)
   else:
      node.right = insert(node.right, key)

   # Step 2: Update the height of the ancestor node
   node.height = 1 + max(get_height(node.left), get_height(node.right))

   # Step 3: Get the balance factor
   balance = get_balance(node)

   # Step 4: If the node becomes unbalanced, then balance it
   # Case 1: Left Left
   if balance > 1 and key < node.left.key:
      return right_rotate(node)

   # Case 2: Right Right
   if balance < -1 and key > node.right.key:
      return left_rotate(node)

   # Case 3: Left Right
   if balance > 1 and key > node.left.key:
      node.left = left_rotate(node.left)
      return right_rotate(node)

   # Case 4: Right Left
   if balance < -1 and key < node.right.key:
      node.right = right_rotate(node.right)
      return left_rotate(node)
```

```
    return node

def left_rotate(z):
    y = z.right
    T2 = y.left

    y.left = z
    z.right = T2

    z.height = 1 + max(get_height(z.left), get_height(z.right))
    y.height = 1 + max(get_height(y.left), get_height(y.right))

    return y

def right_rotate(z):
    y = z.left
    T3 = y.right

    y.right = z
    z.left = T3

    z.height = 1 + max(get_height(z.left), get_height(z.right))
    y.height = 1 + max(get_height(y.left), get_height(y.right))

    return y

def get_height(node):
    if not node:
        return 0
    return node.height

def get_balance(node):
    if not node:
        return 0
    return get_height(node.left) - get_height(node.right)
```

Executing the insertion and rotations ensures the AVL tree remains balanced after each insertion.

Deletion in AVL Tree:

Deletion in an AVL tree involves similar steps: performing a standard BST deletion followed by verifying and restoring the balance through rotations.

Consider the deletion procedure outlined below:

```
def delete(node, key):
    if not node:
```

```
        return node

    # Step 1: Perform standard BST deletion
    if key < node.key:
        node.left = delete(node.left, key)
    elif key > node.key:
        node.right = delete(node.right, key)
    else:
        if node.left is None:
            return node.right
        elif node.right is None:
            return node.left

        temp = get_min_value_node(node.right)
        node.key = temp.key
        node.right = delete(node.right, temp.key)

    # Step 2: Update the height of the current node
    node.height = 1 + max(get_height(node.left), get_height(node.right))

    # Step 3: Get the balance factor
    balance = get_balance(node)

    # Step 4: Restore balance if necessary
    # Case 1: Left Left
    if balance > 1 and get_balance(node.left) >= 0:
        return right_rotate(node)

    # Case 2: Left Right
    if balance > 1 and get_balance(node.left) < 0:
        node.left = left_rotate(node.left)
        return right_rotate(node)

    # Case 3: Right Right
    if balance < -1 and get_balance(node.right) <= 0:
        return left_rotate(node)

    # Case 4: Right Left
    if balance < -1 and get_balance(node.right) > 0:
        node.right = right_rotate(node.right)
        return left_rotate(node)

    return node

def get_min_value_node(node):
    if node is None or node.left is None:
```

```
        return node
    return get_min_value_node(node.left)
```

This deletion operation ensures that the AVL tree remains balanced by performing necessary rotations after each deletion.

The balancing operations through rotations maintain the tree's height at $O(\log n)$, which is critical for ensuring efficient performance in dynamic set operations. These detailed procedures facilitate a deeper understanding of how AVL trees manage structural modifications to preserve their balanced nature.

6.8 B-Trees

B-Trees are balanced tree data structures that maintain sorted data and allow searches, sequential access, insertions, and deletions in logarithmic time. The B-Tree, a generalization of the binary search tree (BST), is optimized for systems that read and write large blocks of data, such as databases and file systems.

Unlike a binary tree, where each node has at most two children, a B-Tree of order m (also denoted as a *B-m* Tree) allows a node to have up to m children and $m - 1$ keys. This feature contributes to the B-Tree's high degree of balancement, ensuring that the tree remains shallow, facilitating efficient disk reads and writes.

Key properties of B-Trees are:

- Each node has at most m children.
- Each internal node contains between $\lceil m/2 \rceil$ and m children (except for the root, which may have as few as two children).
- All leaves appear on the same level.

Structure of B-Tree Node:

A B-Tree node comprises the following components:

- An array of k keys ($k \leq m - 1$), each key separating the values in its subtrees.
- An array of child pointers, where each pointer references a subtree, thus maintaining the property of sorted order.

Thus, if x is a B-Tree node with $n[x]$ keys, and k_i denoting the i-th key, then:

$$k_1 < k_2 < \ldots < k_{n[x]}$$

The pointers $c_1, c_2, \ldots, c_{n[x]+1}$ point to the subtrees where any key k in the subtree c_i satisfies:

$$k_{i-1} < k < k_i$$

for $i = 1, 2, \ldots, n[x] + 1$, assuming that $k_0 = -\infty$ and $k_{n[x]+1} = +\infty$.

Searching in B-Trees:

Searching in a B-Tree starts at the root and proceeds until a leaf node is reached. Consider a B-Tree where each node contains keys $k_1,k_2,\ldots,k_n$ and child pointers $c_1,c_2,\ldots,c_{n+1}$.

To search for a key k:

1. Start at the root node.
2. Check the current node for the key k.
3. If the key is found, return the node along with the position of k in that node.
4. If the key is not found, identify the interval $[k_{i-1},k_i)$ where k should belong, and proceed to the child node at position c_i.
5. Repeat the process until reaching a leaf node.

Below is the code for searching in a B-Tree:

```
class BTreeNode:
   def __init__(self, t, leaf=False):
      self.t = t
      self.keys = []
      self.children = []
      self.leaf = leaf

def search(x, k):
   i = 0
   while i < len(x.keys) and k > x.keys[i]:
      i += 1

   if i < len(x.keys) and k == x.keys[i]:
      return (x, i)
   elif x.leaf:
      return None
   else:
      return search(x.children[i], k)
```

Insertion in B-Trees:

Insertion in a B-Tree requires maintaining the tree properties, particularly ensuring that nodes do not overflow. When a node exceeds the maximum permissible number of keys, it is split into two nodes, and the middle key is promoted to the parent node. This process may propagate up to the root, possibly increasing the height of the tree.

Steps for inserting a key k into a B-Tree of order t:

1. If the root node is full (contains $2t - 1$ keys), split the root and create a new root.
2. Traverse from the root to the appropriate leaf node as in a search operation.
3. Insert the key k into the leaf node in sorted order.

4. If the leaf node exceeds the permissible keys, split the node, and promote the median key to the parent node.

Below is the code for insertion in a B-Tree:

```
def split_child(parent, i, child):
   t = child.t
   new_child = BTreeNode(t, child.leaf)

   parent.keys.insert(i, child.keys[t-1])
   parent.children.insert(i+1, new_child)

   new_child.keys = child.keys[t:]
   child.keys = child.keys[:t-1]

   if not child.leaf:
      new_child.children = child.children[t:]
      child.children = child.children[:t]

def insert_non_full(x, k):
   i = len(x.keys) - 1
   if x.leaf:
      x.keys.append(0)
      while i >= 0 and x.keys[i] > k:
         x.keys[i+1] = x.keys[i]
         i -= 1
      x.keys[i+1] = k
   else:
      while i >= 0 and x.keys[i] > k:
         i -= 1
      i += 1
      if len(x.children[i].keys) == 2*x.t - 1:
         split_child(x, i, x.children[i])
         if k > x.keys[i]:
            i += 1
      insert_non_full(x.children[i], k)

def insert(tree, k):
   r = tree.root
   if len(r.keys) == 2 * tree.t - 1:
      s = BTreeNode(tree.t, False)
      tree.root = s
      s.children.insert(0, r)
      split_child(s, 0, r)
      insert_non_full(s, k)
```

```
    else:
        insert_non_full(r, k)
```

Deletion in B-Trees:

Deletion in B-Trees is more complex than insertion. The goal is to remove a key while maintaining B-Tree properties. Key scenarios include deleting from a leaf node, deleting from an internal node, and ensuring internal nodes retain the minimum number of keys.

Three major cases guide the deletion process:

1. If the key is in a leaf node, remove it directly.
2. If the key is in an internal node:
   - If the predecessor or successor has at least *t* keys, replace the key with it and recursively delete the predecessor or successor.
   - If both the preceding and subsequent children have the minimum number of keys, merge these children.
3. If the key is not present in the node, proceed to the appropriate child node:
   - If the child has the minimum number of keys, ensure it has at least *t* keys by borrowing or merging nodes.

Below is the code for deletion in a B-Tree:

```
def merge(parent, i):
    child = parent.children[i]
    sibling = parent.children[i+1]

    child.keys.append(parent.keys[i])

    child.keys.extend(sibling.keys)
    if not child.leaf:
        child.children.extend(sibling.children)

    parent.keys.pop(i)
    parent.children.pop(i+1)

def borrow_from_next(parent, i):
    child = parent.children[i]
    sibling = parent.children[i+1]

    child.keys.append(parent.keys[i])
    parent.keys[i] = sibling.keys[0]
    sibling.keys.pop(0)

    if not sibling.leaf:
        child.children.append(sibling.children[0])
        sibling.children.pop(0)
```

```
def borrow_from_prev(parent, i):
   child = parent.children[i]
   sibling = parent.children[i-1]

   child.keys.insert(0, parent.keys[i-1])
   parent.keys[i-1] = sibling.keys.pop()

   if not child.leaf:
      child.children.insert(0, sibling.children.pop())

def fill(parent, i):
   if i != 0 and len(parent.children[i-1].keys) >= parent.t:
      borrow_from_prev(parent, i)
   elif i != len(parent.children) - 1 and len(parent.children[i+1].keys) >= parent.t:
      borrow_from_next(parent, i)
   else:
      if i != len(parent.children) - 1:
         merge(parent, i)
      else:
         merge(parent, i-1)

def delete_from_non_leaf(node, idx):
   k = node.keys[idx]
   if len(node.children[idx].keys) >= node.t:
      pred = get_pred(node, idx)
      node.keys[idx] = pred
      delete(node.children[idx], pred)
   elif len(node.children[idx+1].keys) >= node.t:
      succ = get_succ(node, idx)
      node.keys[idx] = succ
      delete(node.children[idx+1], succ)
   else:
      merge(node, idx)
      delete(node.children[idx], k)

def delete(node, k):
   idx = 0
   while idx < len(node.keys) and node.keys[idx] < k:
      idx += 1
   if idx < len(node.keys) and node.keys[idx] == k:
      if node.leaf:
         node.keys.pop(idx)
      else:
         delete_from_non_leaf(node, idx)
   else:
```

```
    if node.leaf:
        return
    flag = (idx == len(node.keys))
    if len(node.children[idx].keys) < node.t:
        fill(node, idx)

    if flag and idx > len(node.keys):
        delete(node.children[idx-1], k)
    else:
        delete(node.children[idx], k)
```

B-Trees effectively balance nodes to maintain search, insertion, and deletion operations' efficiency, making them a suitable choice for filesystem and database management systems. Their structured nature ensures consistent performance even with substantial data growth, adhering to logarithmic time complexity guarantees.

6.9 Heaps

Heaps are a specialized tree-based data structure that satisfies the heap property. This property is what distinguishes heaps from other types of trees. A heap can be of two types: a **min-heap** or a **max-heap**. In a min-heap, for any given node *i*, the value of *i* is less than or equal to the values of its children. Conversely, in a max-heap, the value of *i* is greater than or equal to the values of its children. This characteristic makes heaps particularly useful for implementing priority queues.

Properties of Heaps:

- A heap is a complete binary tree. This means all levels of the tree are fully filled except possibly for the last level, which must be filled from left to right.
- The heap property must be maintained after any insertion or deletion operation, ensuring the min-heap or max-heap property is preserved.

Heap Representation:

Heaps are typically represented using arrays, which allows for efficient storage and manipulation. Given a node at index *i* in an array:

- The left child can be found at index $2i + 1$
- The right child can be found at index $2i + 2$
- The parent can be found at index $\lfloor \frac{i-1}{2} \rfloor$

The array representation allows efficient access and manipulation of the heap's elements.

Basic Operations on Heaps:

1. **Insertion:** Inserting a new element into a heap involves adding the element at the end of the heap (maintaining the complete binary tree property) and then performing a **heapify-up** (also known as bubble-up, percolate-up, sift-up, or trickle-up) operation to restore the heap property.

```
def heapify_up(heap, index):
   parent_index = (index - 1) // 2
   if parent_index >= 0 and heap[index] < heap[parent_index]:
      heap[index], heap[parent_index] = heap[parent_index], heap[index]
      heapify_up(heap, parent_index)

def insert(heap, element):
   heap.append(element)
   heapify_up(heap, len(heap) - 1)
```

2. **Deletion:** The removal of the root element (the minimum in the case of a min-heap or the maximum in the case of a max-heap) requires replacing the root with the last element of the heap and then performing a **heapify-down** (also known as bubble-down, percolate-down, sift-down, or trickle-down) operation to restore the heap property.

```
def heapify_down(heap, index):
   left_child_index = 2 * index + 1
   right_child_index = 2 * index + 2
   smallest = index

   if left_child_index < len(heap) and heap[left_child_index] < heap[smallest]:
      smallest = left_child_index
   if right_child_index < len(heap) and heap[right_child_index] < heap[smallest]:
      smallest = right_child_index

   if smallest != index:
      heap[index], heap[smallest] = heap[smallest], heap[index]
      heapify_down(heap, smallest)

def delete_min(heap):
   if len(heap) == 1:
      return heap.pop()
   root = heap[0]
   heap[0] = heap.pop()
   heapify_down(heap, 0)
   return root
```

3. **Heap Construction:** Building a heap from an arbitrary list of elements can be done efficiently in $O(n)$ time using the **heapify** process. Starting from the lowest non-leaf nodes and moving upwards, we perform heapify-down on each node.

```
def build_heap(elements):
   heap = elements.copy()
   start_index = len(heap) // 2 - 1
   for index in range(start_index, -1, -1):
      heapify_down(heap, index)
   return heap
```

Applications of Heaps:

Heaps have diverse applications in various domains:

- **Priority Queues:** Heaps are the ideal choice for priority queues where elements with higher (or lower) priority need to be served first.
- **Heap Sort:** An efficient comparison-based sorting algorithm that uses a heap data structure. The time complexity of heap sort is $O(n \log n)$.
- **Graph Algorithms:** Dijkstra's Shortest Path and Prim's Minimum Spanning Tree algorithms leverage heaps for efficient edge selection.

Through the formal definition, properties, and operations discussed, we gain comprehensive insight into heaps' functioning and implementation. The following is an example that demonstrates the insertion, deletion, and heap construction in a priority queue context implemented using a min-heap.

```
class MinHeap:
   def __init__(self):
      self.heap = []

   def insert(self, element):
      self.heap.append(element)
      heapify_up(self.heap, len(self.heap) - 1)

   def extract_min(self):
      if len(self.heap) == 0:
         return None
      if len(self.heap) == 1:
         return self.heap.pop()
      root = self.heap[0]
      self.heap[0] = self.heap.pop()
      heapify_down(self.heap, 0)
      return root

   def build_heap(self, elements):
      self.heap = build_heap(elements)

mh = MinHeap()
mh.build_heap([10, 20, 15, 30, 40])
print(mh.extract_min())
```

```
10
```

In this implementation, the class `MinHeap` encapsulates heap operations, providing an efficient and reusable data structure for managing priorities.

6.10 Trie Trees

Trie trees, commonly referred to simply as tries (pronounced “trees” or “try”), are specialized tree-based data structures that efficiently store a dynamic set of strings where the keys are usually strings. Tries are particularly useful for tasks involving collections of strings, such as autocomplete features, spell checkers, and IP routing.

A trie is defined by its nodes and edges. Each node represents a prefix of the strings inserted into the trie, and each edge represents a single character extending from one prefix to its next. The root node corresponds to the empty prefix, and each subsequent node corresponds to the prefixes formed by the characters traversed from the root to that node.

A fundamental characteristic of a trie is that all descendants of a node share a common prefix. The root is associated with the empty string, and each descending node adds one more character to the accumulated value of the parent node.

To construct a trie, we consider each character of a string as a step deeper into the tree. Here’s how insertion of a string into a trie can be implemented in Python:

```
class TrieNode:
   def __init__(self):
      self.children = {}
      self.is_end_of_word = False

class Trie:
   def __init__(self):
      self.root = TrieNode()

   def insert(self, word):
      node = self.root
      for char in word:
         if char not in node.children:
            node.children[char] = TrieNode()
         node = node.children[char]
      node.is_end_of_word = True
```

In this implementation, the `TrieNode` class represents individual nodes of the trie. Each node has a dictionary variable `children` that stores its child nodes and a boolean `is_end_of_word` to mark the end of a word. The `Trie` class maintains the root node of the trie and provides an `insert` function to add words.

To search for a string in a trie, you traverse the trie according to the characters in the string. If you reach the end of the string and the node `is_end_of_word` is True, the string exists in the trie:

```
def search(self, word):
   node = self.root
   for char in word:
      if char not in node.children:
         return False
```

```
            node = node.children[char]
        return node.is_end_of_word
```

The time complexity for both insertion and search operations in a trie is $O(m)$, where m is the length of the string. This efficiency owes to the fact that each character in the string corresponds to one depth level of the trie.

Another common operation in a trie is searching for all words with a given prefix. This is particularly useful for implementing autocompletion. Starting from the node representing the prefix, a Depth-First Search (DFS) can be used to collect all words that have the prefix:

```
def _collect_all_words(self, node, prefix, words):
    if node.is_end_of_word:
        words.append(prefix)
    for char, child_node in node.children.items():
        self._collect_all_words(child_node, prefix + char, words)

def autocomplete(self, prefix):
    node = self.root
    for char in prefix:
        if char not in node.children:
            return []
        node = node.children[char]

    words = []
    self._collect_all_words(node, prefix, words)
    return words
```

In the `autocomplete` function, the `_collect_all_words` helper function performs the DFS from the node that corresponds to the end of the prefix, collecting all words that stem from that node.

Trie trees also have numerous variations to optimize specific use-cases. One such variation is the compressed trie (or Radix tree), which collapses chains of single nodes. Another variation is the ternary search tree, which stores characters at nodes in a binary search tree fashion, conserving space.

Tries are space-intensive since each node may have up to 26 children (for the English alphabet) or more for larger character sets. This increased space requirement can be mitigated by using more space-efficient structures such as hash maps for child nodes or implementing the aforementioned compressed tries.

Tries are essential for various algorithmic problems, making them a vital tool for real-time systems needing fast and efficient string manipulations. They feature heavily in applications requiring prompt lookups and pattern matching tasks.

6.11 Applications of Trees

Trees are a fundamental data structure in computer science and find extensive applications in various domains. Their hierarchical nature and efficient search, insert, and delete capabilities make them suitable for a wide range of tasks. This section delves into the practical implementations and advantages of using tree structures in real-world scenarios, focusing on areas such as databases, file systems, network routing, and more.

- **Database Indexing:** One of the prime applications of trees, particularly B-trees and their variants like B+ trees, is in database indexing. Databases need to perform rapid search and retrieval, insertion, and deletion operations. B-trees are balanced, maintaining sorted data and allowing for logarithmic time complexity for these operations. This balance ensures that the path from the root to any leaf node is about the same length, providing efficiency in high-volume database transactions. B+ trees enhance B-trees by storing all values at the leaf nodes and maintaining pointers to these leaf nodes, further optimizing range queries.
- **File Systems:** Modern file systems often leverage tree structures for efficient file storage and retrieval. Examples include the ext4 file system in Linux, which uses a complex tree structure known as an extent tree to manage file allocations. Hierarchical structures such as directories can also be represented using trees, simplifying navigation and management.
- **Network Routing:** Trees are essential in network routing algorithms. Spanning trees, for example, are utilized in network topology management to prevent loops. The Spanning Tree Protocol (STP) allows switches to communicate, ensuring a loop-free network topology by creating a spanning tree that includes all the network's bridges or switches. Additionally, IP routing uses tries (prefix trees) to store routing tables efficiently, enabling quick lookups for routing decisions.
- **Syntax Tree in Compilers:** Abstract syntax trees (ASTs) are used in compilers to represent the structure of program code. During the parsing phase, source code is analyzed and converted into a tree structure that reflects the hierarchical nature of the syntax. This tree is then used in the subsequent steps of compilation, such as semantic analysis and code generation. ASTs are crucial for optimizing code and error checking.
- **Artificial Intelligence:** In AI, particularly in decision-making algorithms and game theory, trees play a crucial role. Decision trees are used for classification and regression tasks. They split the data into branches based on feature values, helping in predictive modeling. Moreover, game trees are a cornerstone in designing algorithms for playing strategic games like chess, where each node represents a possible game state.
- **Data Compression:** Trees, specifically Huffman trees, are instrumental in data compression algorithms. Huffman encoding uses a binary tree to assign variable-length codes to input characters, based on their frequencies. Characters that occur more frequently are given shorter codes, which helps in reducing the overall size of the data. This method is foundational in technologies like ZIP compression and multimedia codecs.
- **Geographical Information Systems (GIS):** In GIS applications, spatial data often requires efficient access and manipulation. Quadtrees and K-D trees are used to index multi-dimensional information such as geographical coordinates. These trees decompose space into manageable sections, making operations like range queries and nearest neighbor searches more efficient.
- **Expression Parsing in Calculators:** Evaluations of mathematical expressions in calculators and other arithmetic processing tools often make use of expression trees. Each node in the tree represents an operator, and the children nodes represent the operands. This structure

allows for the implementation of various order traversals like infix, prefix, and postfix, which are essential in evaluating the expressions properly.
- **Concurrent Programming:** In concurrent or multi-threaded programming, trees like concurrent hash tries are used to manage shared data structures efficiently. These trees allow multiple threads to perform operations without significant locking, thereby improving performance and scalability.
- **Genealogy and Historical Research:** Tree structures are naturally suited to represent genealogical data, such as family trees or lineage charts. They can depict ancestral connections and descendants in a clear, hierarchical manner, making it easier to track lineage and heritage.

Through these applications, it is evident that tree structures are not only versatile but also indispensable across various technological and research domains. Their ability to provide structured, efficient, and scalable solutions makes them a cornerstone of modern computing and data management.

6.12 Performance Considerations in Trees

Analyzing the performance of tree data structures requires examining various factors such as time complexity, space complexity, and balancing criteria. Tree-based algorithms' performance is contingent on the type of tree and the specific operations being performed.

Time complexity for common operations such as insertion, deletion, and search is typically discussed. For a binary search tree (BST), performance is inherently linked to the tree's height. The time complexity for basic operations in a BST is $O(h)$ where h is the height of the tree. In the worst-case scenario, the height of a BST can become $O(n)$, where n is the number of nodes, leading to linear time complexity. This occurs when nodes are inserted in a sorted order, degenerating the BST into a linked list.

Balanced trees such as AVL trees and Red-Black trees aim to keep the height of the tree approximately logarithmic with respect to the number of nodes, $h = O(\log n)$. This logarithmic height ensures logarithmic time complexity, $O(\log n)$, for insertion, deletion, and search operations, thus significantly enhancing performance for large datasets.

```
class Node:
   def __init__(self, key):
      self.key = key
      self.left = None
      self.right = None
      self.height = 1

class AVLTree:
   def insert(self, root, key):
      # Perform the normal BST rotation
      if not root:
         return Node(key)
      elif key < root.key:
```

```
            root.left = self.insert(root.left, key)
        else:
            root.right = self.insert(root.right, key)

        # Update the height of the ancestor node
        root.height = 1 + max(self.getHeight(root.left), self.getHeight(root.right))

        # Get the balance factor
        balance = self.getBalance(root)

        # If the node is unbalanced, then try the 4 cases

        # Left Left Case
        if balance > 1 and key < root.left.key:
            return self.rightRotate(root)

        # Right Right Case
        if balance < -1 and key > root.right.key:
            return self.leftRotate(root)

        # Left Right Case
        if balance > 1 and key > root.left.key:
            root.left = self.leftRotate(root.left)
            return self.rightRotate(root)

        # Right Left Case
        if balance < -1 and key < root.right.key:
            root.right = self.rightRotate(root.right)
            return self.leftRotate(root)

        return root

    def leftRotate(self, z):
        y = z.right
        T2 = y.left
        y.left = z
        z.right = T2
        z.height = 1 + max(self.getHeight(z.left), self.getHeight(z.right))
        y.height = 1 + max(self.getHeight(y.left), self.getHeight(y.right))
        return y

    def rightRotate(self, z):
        y = z.left
        T3 = y.right
        y.right = z
        z.left = T3
```

```
        z.height = 1 + max(self.getHeight(z.left), self.getHeight(z.right))
        y.height = 1 + max(self.getHeight(y.left), self.getHeight(y.right))
        return y

    def getHeight(self, root):
        if not root:
            return 0
        return root.height

    def getBalance(self, root):
        if not root:
            return 0
        return self.getHeight(root.left) - self.getHeight(root.right)
```

The balance of AVL trees ensures that the performance remains efficient, even in the worst-case scenarios. Similarly, B-trees and heaps are designed to maintain balanced structures to optimize performance. B-trees are especially beneficial in scenarios involving databases and file systems, as they minimize disk reads, which are significantly slower compared to in-memory operations. B-trees maintain balance by ensuring that all leaf nodes are at the same level and by distributing keys across multiple child nodes to maintain the height as $O(\log n)$.

The heap data structure, particularly binary heaps, provides efficient support for priority queue operations. In binary heaps, insertion, and deletion operations maintain the structure's properties, resulting in $O(\log n)$ time complexity. Min-heaps and max-heaps are fundamental in applications requiring efficient retrieval of the minimum and maximum elements, respectively.

```
class MinHeap:
    def __init__(self):
        self.heap = []

    def insert(self, key):
        self.heap.append(key)
        i = len(self.heap) - 1
        while i > 0 and self.heap[i] < self.heap[(i - 1) // 2]:
            self.heap[i], self.heap[(i - 1) // 2] = self.heap[(i - 1) // 2], self.heap[i]
            i = (i - 1) // 2

    def heapify(self, i):
        smallest = i
        left = 2 * i + 1
        right = 2 * i + 2
        if left < len(self.heap) and self.heap[left] < self.heap[smallest]:
            smallest = left
        if right < len(self.heap) and self.heap[right] < self.heap[smallest]:
            smallest = right
        if smallest != i:
```

```
            self.heap[i], self.heap[smallest] = self.heap[smallest], self.heap[i]
            self.heapify(smallest)
```

While analyzing space complexity, we consider both the auxiliary space required by the algorithms and the extra space consumed by maintaining tree properties. Trees naturally use $O(n)$ space to store n nodes. Self-balancing trees, like AVL trees, require additional space to store height or balance information at each node, though this is a linear addition in terms of complexity. B-trees, particularly in database applications, are designed to reduce expensive disk I/O by ensuring that nodes are densely packed and thus minimizing the height of the tree.

Performance considerations extend to traversal methods as well. In-order, pre-order, and post-order tree traversals have time complexity $O(n)$ as each node is visited exactly once. Though these traversal methods are efficient, choosing the appropriate one can impact the overall performance depending on the specific algorithm requirements. Breadth-first traversal, typically implemented using a queue, may have higher space complexity compared to depth-first traversals due to additional storage requirements.

The performance of trees is greatly impacted by the requirement for maintenance operations to ensure the trees remain balanced. While these balancing operations might introduce overhead, the performance improvements for large datasets can be significant. Consequently, understanding the performance characteristics and trade-offs of various tree structures is critical for effective data structure selection in software development.