

## **Top View of Assembly**




# SECTION A-A End View of Assembly







# SECTION B-B Side View of Assembly




### **Top View Looking Inside Box**



#### SECTION C-C Boss Heights





	Maximum P.C. Boa	rd Size
	3.25 <b>&gt;</b> [.128]	<b>-</b>
29.00   [1.142] <sub>23.50</sub>   [.925]	Ø2.50 [.098] R3.00 [.118]	3.25 [.128]
	20.00 — [.787] 44.00 — [1.732]	R1.0

# NOTE Purchased assembly includes lid and box made from GP ABS material and cover screws.

1551G			
1551G Enclosure			
Black Enclosure - RAL 9011 - UL94 - HB	1551GBK		
Gray Enclosure - RAL 7035 - UL94 - HB	1551GGY		
Translucent Blue - UL94 - HB	1551GTBU		
ACCESSORIES			
Recommended Screw Torque: 15-20 ozf.in (10-15 cN.m)			
Black Enclosure Cover Screws (Pkg 100) [#4 X1/2" Self Tapping]	1591TS100BK		
Grey Enclosure Cover Screws (Pkg 100) [#4 X1/2" Self Tapping]	1591TS100		
P.C. Board Screws (Pkg 100) [#2 x 3/16" Self Tapping]	1551ATS100		

HAMMOND
MANUFACTURING
M

1551G

www.hammondmfg.com

2

# **PRODUCT DATASHEET**

is brought to you by



# SOS electronic distribution of electronic components

Click to view availability, pricing and lifecycle information.

Visit <a href="https://www.soselectronic.com/">https://www.soselectronic.com/</a>