

Introduction to AI

KNOWLEDGE REPRESENTATION

Pedro Meseguer

Institut d'Investigació en Intel·ligència Artificial (IIIA)
Consejo Superior de Investigaciones Científicas (CSIC)



1

Contents

1. Motivation: Knowledge vs Search
2. Knowledge Representation and Logic
3. Production rules
4. Semantic networks and frames
5. Ontologies
6. Default reasoning
7. Metaknowledge
8. Uncertainty
9. Knowledge Engineering
10. Some names
11. Wrap-up

ideal world

real world

2

1. Knowledge: AI takes another route



3

1. How far can you go with plain search?

- ▶ **Medical diagnosis** (AI task, MYCIN)
 - ▶ Hundred of symptoms
 - ▶ If considered as a whole → huge state-space
 - ▶ Data:
 - ▶ All information from the patient before any deduction
 - ▶ Silly or illogical questions (imagine asking a man for pregnancy)
- ▶ **Change of paradigm:** use knowledge to guide and limit search
 - ▶ In the same way humans do to narrow possibilities
 - ▶ Focus on what is relevant
 - ▶ Perform search in a different way

4

1. Information and knowledge

- **Information:** set of basic data without interpretation (of a problem)
- **Knowledge:**
 - high level description of that model that structure the experience from a domain and allows the interpretation of the basic data.
 - symbolic
- Example: the blood test
 - Information: the numerical data from the test
 - Knowledge: the concepts and the reasoning that allows to interpret these values as normal or problematic for a particular person (anaemia, leukopenia...)



5

1. Knowledge: Representation and Types

- Representation:** knowledge represented in data structures to be automatically operated by a computer program.
- **Declarative:** expressed in a way that is directly accessible by humans
 - Inheritable : concepts with a hierarchical structure that base their inference on inheritance (ontologies)
 - Logical: expressed by logical formulas and derived by logical inference (rules)
 - **Procedural:** hidden in particular procedures (algorithms) executed on knowledge data structures (simple relations in semantic nets) (complex procedures among facts)

6

1. What is symbolic KR about?

Symbols

Propositions

A — yesterday rained

B — I will learn a lot at the UAB

C — that person loves me

Given a problem, concepts could be expressed as propositions

Propositions have two possible truth values: *true* and *false*

Producing new knowledge


Modus ponens (expressed as logical implications)

A is true

$A \rightarrow B$ is true

it is legal to conclude that B is true

Inheritance



7

2. Knowledge Representation and Logic

- **Logic:**
 - branch of mathematics about legal deductions and propagation of truth
 - Georg Boole, Bertrand Russell...
- **Knowledge Representation:**
 - static declarative knowledge + current problem instance = produce new knowledge that allows to solve the problem
- You want to operate knowledge to derive new knowledge
- Logic appears as a natural language for declarative KR
 - Because of that, logic is in all AI textbooks

8

2. Propositional logic

► Propositions: A, B, C...

A: *today is sunny*

B: *we enjoy a walk in nature*

C: *my tailor is rich*

► Truth values: true (1), false (0)

► Logical operators: negation ($\neg A$), conjunction ($A \wedge B$), disjunction ($A \vee B$), implication ($A \rightarrow B$), equivalence ($A \leftrightarrow B$)

9

2.KR: Propositional logic – Truth tables

negation

A	$\neg A$
1	0
0	1

disjunction (or, \vee)

A	B	$A \vee B$
1	1	1
1	0	1
0	1	1
0	0	0

conjunction (and, \wedge)

A	B	$A \wedge B$
1	1	1
1	0	0
0	1	0
0	0	0

implication
(imp, \rightarrow)

A	B	$A \rightarrow B$
1	1	1
1	0	0
0	1	1
0	0	1

A	B	$A \leftrightarrow B$
1	1	1
1	0	0
0	1	0
0	0	1

equivalence
(equiv, \leftrightarrow)

10

10

2.KR: Propositional logic – Truth tables (II)

► Perfect way to check the legal inferences:

► $(A \rightarrow B) \leftrightarrow (\neg A \vee B)$ (??)

A	B	$A \rightarrow B$	$\neg A \vee B$	$(A \rightarrow B) \leftrightarrow (\neg A \vee B)$
1	1	1	1	1
1	0	0	0	1
0	1	1	1	1
0	0	1	1	1

both have the same
truth tables

Tautology: a sentence
that is always true

► Theorems are tautologies.

11

3. *Modus ponens* – Production rules

► Modus ponens (since Aristotle):

► If A is *true*, and

► $A \rightarrow B$ is *true*, then it is legal to deduce that

► B is *true*

► A single line of the truth table

A	B	$A \rightarrow B$
1	1	1
1	0	0
0	1	1
0	0	1

► Production rules: to be used for modus ponens inference only ($A \Rightarrow B$) [in logical terms, they are Horn clauses]

12

12

3. Production rules

- ▶ Rules:
 - ▶ Two parts: left hand side (conjunction of conditions on facts), right hand side (a conclusion on a fact); condition – action pairs
 - ▶ Interpreted by an inference engine (that performs chaining)
 - ▶ With a solid theoretical (logical) base
- ▶ Firing: when condition is true, action is added to the fact base
- ▶ A rule:
 - ▶ codifies a simple (elemental) inference step
 - ▶ solution: involves a sequence of firing rules
- ▶ Declarative knowledge: although attractive, it is difficult to maintain
- ▶ Monotonicity: always adds new facts

13

3. Production rules in expert systems

Internal deductive space divided in two:

- ▶ Facts base:
 - ▶ facts that are data of the current case
 - ▶ they can be: initial, derived
 - age=48 pain=yes blurry vision=yes meningitis=may_be*
- ▶ Rule base: static knowledge on a particular domain, codified in rules
 - ▶ *If gramnegative and rod and anaerobic => bacteroides [0.6]*

14

3. Production rules: example

PREMISE (SAND(SAME CNTXT INFECT PRIMARY-BACTEREMIA)
(MEMBF CNTXT SITE STERILESITES)
(SAME CNTXT PORTAL GI))

ACTION (CONCLUDE CNTXT IDENT BACTEROIDES TALLY .7)

If (1) the infection is primary-bacteremia, and
(2) the site of the culture is one of the sterilesites, and
(3) the suspected portal of entry of the organism is the gastro-intestinal tract,
then there is suggestive evidence (.7) that the identity of the organism is bacteroides.

A rule from the MYCIN knowledge base. SAND and \$OR are the multivalued analogues of the standard Boolean AND and OR.

15

3. Production rules: chaining

Rules are always fired from condition (IF) to action (THEN); however, the strategy of the inference engine could be:

- ▶ Forward chaining: from the facts, any rule is fired as soon as satisfied
- ▶ Backward chaining: from the goals, as follows
 - ▶ A goal is established
 - ▶ Firing is limited to: (i) the rules that conclude that goal, (ii) the rules that conclude the conditions of (i), etc.
 - ▶ Inference is more focused on the system objectives
 - ▶ If external conditions are asked, ES behaviour is more meaningful for the human operator

16

3. Production rules: chaining

- ▶ Forward chaining
 - ▶ Repeat until all applicable rules have been processed
 - ▶ Match the facts in the set of facts against the conditions of the rules
 - ▶ Those rules whose conditions are fulfilled are potentially applicable
 - ▶ Select one of these rules
 - ▶ Apply the rule by adding the conclusion to the set of facts
- ▶ Backward chaining:
 - ▶ Select a goal
 - ▶ Repeat until the goal is achieved
 - ▶ Look for rules whose conclusion match the goal
 - ▶ All matched rules become potentially applicable
 - ▶ One of these rules is selected
 - ▶ Its conditions are new subgoals to be achieved

17


4. Semantic networks

Directed graph:

- ▶ nodes are concepts
- ▶ arcs are labelled with relations
- ▶ Codify some static knowledge of the problem domain
- ▶ Simple concepts
- ▶ Simple inferences are made traversing the graph

18

4. Semantic networks: example



19

4. Frames

- ▶ Structured objects (slot-and-filler architectures)
- ▶ Very close to records in Computer Science
- ▶ Stereotypical situations
- ▶ Same motivation as semantic nets, but for complex objects
- ▶ Relations of semantic nets → appear as attributes in frames

20

4. Frames: example

SLOTS	VALUES
Title	Artificial Intelligence
Genre	Computer Science
Author	Peter Norvig
Edition	Third Edition
Year	1996
Page	1152

21

5. Ontologies

- Definition: An explicit, machine-readable specification of a shared conceptualization
- Motivation:
 - Desire to share structure of domains across applications
 - To separate operational knowledge (rules) from static domain conceptualization
- Developed for:
 - domain specific
 - ambition: a general ontology
 - with the help of Wikipedia
 - inference: inheritance


22

5. Ontologies (cont.)

- Operationally, an ontology is a hierarchy of categories
- Relations:
 - Class—subclass—member → inheritance
 - Part_of, composed_objects
- Some ontologies:
 - Dbpedia
 - TextRunner
 - OpenMind

23

5. Ontologies: example



24

6. Default reasoning

Does Tweety fly?

- ▶ Tweety is a bird (belongs to the BIRD category)
- ▶ and birds fly, so Tweety flies (simple inheritance)



This is Tweety,
it has a broken wing → Tweety does not fly

- ▶ Default reasoning:
 - ▶ Inherit values
 - ▶ Unless other some more specific information is available

25

25

6. Default reasoning (cont.)

- ▶ What happens if, after performing reasoning, one knows that Tweety has a broken wing?
- ▶ Non-monotonic reasoning:
 - ▶ Capacity to remove previous deductions when new facts are known that contradict old ones:
 - ▶ Humans are very good at that; not the case for machines
 - ▶ Inferred facts do not grow monotonically
 - ▶ Assumption-based Truth Maintenance Systems (ATMS)
 - ▶ Circumscription (logical approach)

26

26

7. Metaknowledge

Knowledge about knowledge:

- ▶ Control knowledge:
 - ▶ How deduction is made
 - ▶ Usually local to KB (knowledge base) parts
- ▶ Special rules (metarules)
 - ▶ Establishing goals and strategies
 - ▶ Focusing deduction on a group of rules
 - ▶ Have preference on normal rules
- ▶ Execution:
 - ▶ Rules: at the domain level
 - ▶ Metarules: at metalevel

27

27

7. Metaknowledge (cont.)

- ▶ Example:
 - ▶ KB = group of KB modules
 - ▶ KB module = goals, rules, metarules
 - ▶ KB module goal: pursued by the rules of module
 - ▶ KB modules are activated according to metarules
 - ▶ There is an INIT module, that activates first

28

28

8. Uncertainty

- ▶ Our knowledge of the world is always incomplete:
 - ▶ Causal inferences are not 100% valid
 - ▶ Odd cases, exceptions
 - ▶ Especially in the medical realm
 - ▶ Facts are partially known, often qualitative:
 - ▶ Weather report: partially cloudy, little rain,
- ▶ (Real) Knowledge representation has to be extended to handle uncertainty for all its types: facts / rules / metarules
- ▶ Two basic forms to handle uncertainty:
 - ▶ Probabilities
 - ▶ Fuzzy logic

29

8. Uncertainty: probability (frequentist)

- ▶ Probability is applied to well-defined propositions: only makes sense *true* or *false*. Ex. Are you pregnant?
- ▶ Frequentist approach:
 - ▶ $\Pr(\text{event } i) = \frac{\text{\#favourable cases}}{\text{\#possible cases}}$ ^{*ideal world*}
 - ▶ Applied to cards games, balls, etc.
 - ▶ Not of much use in AI

30

8. Uncertainty: conditioned probability

- ▶ Prior probability:
 - ▶ Before an event happens
 - ▶ Usually based on reasons of regularity, symmetry...
- ▶ Conditioned probability:
 - ▶ After an event E that changes probabilities
 - ▶ $\Pr(X|E)$ = probability of X given that we observed E
 - ▶ Posteriori or conditioned probability
 - ▶ Bayes' formula connects prior and conditioned probabilities

31

8. Uncertainty: conditioned probability example

- ▶ Example: breaking the code of Enigma (SWW):
 - ▶ Enigma machine: encryption/decryption of messages
 - ▶ British (Turing) broke the encryption
 - ▶ Prior probability of each letter: uniform
 - ▶ Events: common subsentences in messages
 - ▶ Weather report
 - ▶ Heil Hitler!
 - ▶ Modify the probability of each letter: no longer uniform (a posteriori, conditioned probability)

32

8. Uncertainty: fuzzy logic

- ▶ Intuitive approach to handle uncertainty; adequated for graded propositions
- ▶ Imagine: *Fred is Young* (he could be very young, half young, not young)
 - ▶ True if *Fred* is 19 (*Fred* belongs completely to the fuzzy set YOUNG)
 - ▶ False if *Fred* is 50 (*Fred* does not belong to the fuzzy set YOUNG)
 - ▶ In between if *Fred* is 30 (*Fred* belongs partially to the fuzzy set YOUNG)
- ▶ How *Fred* belongs to the fuzzy set YOUNG
 - ▶ Membership function: Instead of 0 or 1 (as for classical sets), it is a number in the interval $[0, 1]$
- ▶ Fuzzy logic also allows graded qualifiers of natural language: *Fred is very young*
- ▶ In fuzzy logic, intermediate degrees of truth between [*false*, *true*]

33

8. Uncertainty: certainty factors

- ▶ In expert systems, the degree of confidence represented by certainty factors in:
 - ▶ Facts
 - ▶ Rules
- ▶ Combination:
 - degree of confidence of condition
 - degree of confidence of rule
 - to produce
 - degree of confidence in conclusion

34

9. Knowledge Engineering

- ▶ Develop the procedures to interpret the declarative knowledge
 - ▶ Rule inference
 - ▶ Inheritance
- ▶ Organize the declarative/procedural knowledge for:
 - ▶ Performance
 - ▶ Validation
 - ▶ Maintenance (hard task!)
- ▶ Generate the adequate data structures for handling knowledge at run time
 - ▶ Facts base
 - ▶ Goals in backward chaining

35

10. KR names: John McCarthy



- ▶ (1927 – 2011)
- ▶ MIT, full profesor Stanford
- ▶ One of the big old names
- ▶ Father of AI (conference of Darmouth)
- ▶ Proposed circumscription (nonmonotonic reasoning)

36

10.KR names: Marvin Minsky



- ▶ (1927 – 2016)
- ▶ Full professor MIT
- ▶ One of the founders (conference of Darmouth)
- ▶ Worked on perceptrons
- ▶ Proposed frames (complex objects in semantic networks)

37

10.KR names: Bruce Buchanan



- ▶ (?)
- ▶ Full profesor Carnegie-Mellon (Pittsburg)
- ▶ Many contributions to expert systems
- ▶ MYCIN (Univ. Stanford)

38


10.KR names: Ronald Branchman



- ▶ (?)
- ▶ University / Company ??
- ▶ Many contributions to knowledge representation
- ▶ KL-ONE

39

10.KR names: Hector Levesque



- ▶ (?) Canadian
- ▶ Full profesor Toronto univ.
- ▶ Many contributions to knowledge representation
- ▶ Theoretical work

40

10.KR names: MYCIN

- ▶ Diagnoses blood infections (in the 70s)
- ▶ Early ES in medicine
 - ▶ Rules
 - ▶ Certainty factors
 - ▶ Forward and backward chaining
 - ▶ Usability by doctors
 - ▶ Ethical issues unsolved
- ▶ Caused an early ES shell: EMYCIN

41

10.KR names: KL-ONE

KL-ONE (80s)

- ▶ Knowledge representation Language:
 - ▶ Semantic networks
 - ▶ Frames
 - ▶ Inheritance
- ▶ Developed by Ronald Branchman and others

42

10.KR names: CYC



- ▶ 80's
- ▶ An attempt to make a massive symbolic artificial intelligence
- ▶ Capture common sense knowledge
- ▶ It was unfinished
- ▶ May of KR issues were reworked

43

11.Wrap-up

- ▶ Symbolic Knowledge Representation
- ▶ Main research topic in 80s, 90s
- ▶ Somehow, now is not in the AI main stream
- ▶ Nevertheless, it is useful to know the achievements and contributions on this topic
 - ▶ To understand current symbolic AI systems
 - ▶ To get familiar with existing AI tools

44

11.Wrap-up (cont.)

- ▶ Symbolic Knowledge Representation
- ▶ Logic
- ▶ Rules
- ▶ Semantic networks
- ▶ Frames
- ▶ Ontologies
- ▶ Default reasoning
- ▶ Metaknowledge
- ▶ Uncertainty
- ▶ Knowledge engineering

45

Further reading

- ▶ Russel & Norvig 3rd ed:
7.1, 7.3, 7.4, 7.5, 12.1, 12.2, 12.5, 12.6
Bibliographical Notes chapters 7 and 12
- ▶ Ginsberg, *Essentials of Artificial Intelligence*
2.3, 9.3, 11.1, 12.1
Further Reading chapters 2, 9, 10, 12

46