Question 1							
1. What function would you use to join an element on the front of a list? (1 mark)							
2. Assuming $\iota$ is long enough, what expression involving hd and $t\iota$ would give the 2nd element of the list $\iota$ ? (1 mark)							
3. What expression involving the functions $nil$ and $cons$ could be used to construct the list [1,2,3]? (1 mark)							
Please write your answers here:							
Question 2							
Question 2  If 11 has length 3, how long is the list returned by calling append1(11,11)? (Note that this is append1 not append.)							
If 11 has length 3, how long is the list returned by calling append1(11,11)? (Note that this is append1							
If 11 has length 3, how long is the list returned by calling append1(11,11)? (Note that this is append1 not append.)							
If 11 has length 3, how long is the list returned by calling append1(11,11)? (Note that this is append1 not append.)							
If 11 has length 3, how long is the list returned by calling append1(11,11)? (Note that this is append1 not append.)  3  0							
If 11 has length 3, how long is the list returned by calling append1(11,11)? (Note that this is append1 not append.)  3  0  4							

```
Question 3
Look at the following code:
  String f(String s) {
    String to_return = "";
    while(true) {
      if(s.equals("")) return to_return;
// at this point s is not ""
      char c2 = s.charAt(0);
if(c2< 'l') { to_return += c2; }
s=s.substring(1);</pre>
  }
What is the result of calling f("hello")?
true
false
☐ he
helo
hello
Question 4
Look at the following code:
  List g(int i, List l) {
    List to_return = nil();
    while(true) {
      if((l.isEmpty()) return to_return;
int j = (Integer)(hd(l));
if(i < j) {</pre>
         to_return=append1(to_return,i);
         to_return=append1(to_return,j);
      i=j;
      l=tl(l);
    }
What is the result of calling g(3,[1,2,4,5])?
 [1,2,4,5] 
 [1,2,3] 
[1,2,2,4,4,5]
[1,2,4,5,3]
something else
```

Question 5
Look at the following code:
<pre>List r(int i0) {    List to_return = nil();    int i = i0;    while(true) {     if (i&lt;=0) return to_return;      to_return = cons(0,to_return);     i = i - 1;    } }</pre>
What is the result of calling $r(3)$ ?
□ [0,1,2]
□ [0,1,2,3]
[2,1,0]
[3,2,1,0]
[0,0,0]
Question 6
Look at the following code:
<pre>public String mn(String s) {    String to_return="";    String str = "";    while(true) {      if(s.equals("")) return to_return;      char c = s.charAt(0);      str=str+c;      to_return=to_return+str;      s=s.substring(1);    } }</pre>
What is the result of calling mn("abc d")?
□ "abc d"
☐ "aababcabcabcd"
☐ "ababcabc abc d"
☐ "aababcabc abc d"
something else

## Question 7 Look at the following code: boolean pn(String s1, String s2) { while(true) { if(s1.equals("")) return false; if(s2.equals("")) return true; if(s1.charAt(0)>s2.charAt(0)) return false; s1=s1.substring(1); s2=s2.substring(1); } What is the result of calling pn("tomab", "tomc")? An exception is thrown ☐ The program fails to compile true false something else Question 8 Look at the following code: String rs(String s, String to\_return) { if(s.equals("")) return to\_return; char c = s.charAt(0); to\_return = (c + to\_return); s=s.substring(1); return rs(s,to\_return); What is the result of calling rs(rs("def", "abc"), "")? ☐ "abc" ☐ "defabc" "fedabc" ucbafed" something else

## Question 9 Look at the

Look at the following code:

```
public List uv(List l, int n) {
  List to_return = nil();
  while(true) {
    if(l.isEmpty()) return to_return;
    int i = (Integer)(hd(l));
    if(i*i<n) { to_return = append1(to_return,i); }
    l=tl(l);
  }
}</pre>
```

What is the result of calling uv([1,9,2,8,4,3],16)?

	Г	1	,2,	.3	.4
		_	, –	, •	, .

[1,2,3,4,8]

[1,2,3,4,8,9]

[1,2,3]

something else

## Question 10

Look at the following code:

```
List wx(List l1, List l2) {
  List to_return = nil();
  while(true) {
    if(l1.isEmpty()) return append(to_return,l2);
    to_return = append1(to_return,hd(l1));
    to_return = append1(to_return,hd(l2));
    l1 = tl(l1);
    l2 = tl(l2);
  }
}
```

What is the result of calling wx([1,3,5,0,-2],[6,4,2])?

```
\square [1, 6, 3, 4, 5, 2, 0, -2]
```

[1, 6, 3, 4, 5, 2]

 $\square$  [1, 3, 5, 6, 4, 2, 0, -2]

 $\square$  [-2, 0, 1, 2, 3, 4, 5, 6]

something else