

Using A.I. to generate peptide therapeutics against the VWF-GP1b α interaction

Thomas David Daniel Kazmirchuk¹, Maha Othman^{2,3,4}, and Ashkan Golshani¹

¹Department of Biology and the Ottawa Institute of Systems Biology, Faculty of Science, Carleton University. Ottawa, Ontario, Canada.

²Department of Biomedical and Molecular Sciences, Faculty of Medicine, Queen's University. Kingston, Ontario, Canada.

³School of Baccalaureate Nursing, St Lawrence College, Kingston, Ontario, Canada.

⁴Clinical Pathology Department, Faculty of Medicine, Mansoura University, Mansoura, Egypt.

Introduction: Platelet glycoprotein-1b alpha (GP1b α) is a surface glycoprotein that is functionally defective in platelet-type von Willebrand disease (PT-VWD), which is characterized by gain-of-function mutations within the β -sheet thereby converting GP1b α to an open conformation. This results in the excessive association of GP1b α with its receptor von Willebrand clotting factor (VWF), counterintuitively leading to a bleeding phenotype in PT-VWD patients. The β -sheet mutations (clustered within the Trp230 - Met239 window) therefore represent an attractive site to develop peptide therapeutics. Recently, we developed the *In-Silico Protein Synthesizer* (InSiPS), which is a computational tool that intelligently designs small peptides to interfere with important protein-protein interactions (PPIs). Thus, we used InSiPS to generate small peptides against the GP1b α -VWF interaction.

Methods: We first used InSiPS to generate a peptide candidate list specific to GP1b α . InSiPS is a genetic algorithm developed around co-occurring protein motifs that mediate PPIs. It is a closed system that generates small peptides with a given interaction profile. The resulting peptides can bind to specific regions of a target protein while also avoiding interactions with a set of predefined, non-target proteins. These peptides are constantly improved through a cycle of evaluating and mutating an initial pool of sequences. After generating a ranked-list of peptide candidates that specifically target GP1b α , we took the top five-scoring peptides and performed a combination of in-silico docking experiments and in-vitro binding assays.

Results: We have generated five peptides that are specific to GP1b α . The interaction between some of these peptides and GP1b α were further confirmed in-silico using AlphaFold2. Our preliminary in-vitro data confirms the interaction between some of these peptides and GP1b α . We will further evaluate the ability of these peptides to interfere with the interaction between GP1b α and VWF.

Conclusions: We conclude that InSiPS is a suitable tool to develop small peptides against pharmaceutically important targets, such as GP1b α . Future work will focus on testing the efficacy of these peptides against GP1b α in a mammalian system.