1 Introduction

Machine learning research has long been captivated by the potential of autonomous agents and their capabilities. In recent times, incorporating large language models into these agents (Wang et al. 2023b; Xi et al. 2023) has unveiled a broad spectrum of applications, even extending beyond academia (Yang et al. 2023a; Nakajima 2023; Significant-Gravitas 2023). One of the significant advantages of LLMs lies in their world knowledge, allowing them to be inherently versatile across various scenarios (Zhao et al. 2023b).

On the one hand, previous works investigated finetuning LLMs with a large number of environment interactions (Yao et al. 2023c) or with a large amount of human-labeled datasets (Nakano et al. 2021; Shaw et al. 2023). This class of methods incurs high computational costs and needs access to the LLM's parametric weights. Furthermore, finetuning an LLM restricts its functionalities and can hurt its generalization abilities (Du et al. 2022). On the other hand, prompting methods can augment an LLM with better sequential decision-making planning abilities with only a few in-context examples (Hao et al. 2023; Lin et al. 2023b; Sun et al. 2023). However, since current LLMs are bounded by context window size (Tworkowski et al. 2023), these agents have no recollections of what they have seen, and therefore no learning can be done outside of a few demonstrations. *So, how can we strike a balance between these paradigms?*

We present the Experiential Learning (ExpeL) agent as a solution. Our agent autonomously gathers experiences from a collection of training tasks through trial and error. From these experiences, it derives natural language insights and employs its own successful experiences as in-context examples during test time. Our agent's learning process is analogous to a student studying for an exam and then taking it on a single attempt, reflecting many real-world situations. Unlike self-improvement methods like Reflexion (Shinn et al. 2023), our approach emphasizes the importance of retaining experiences across multiple tasks to enhance agent performance. Moreover, ExpeL learns without parameter updates, making it compatible with powerful closed-source models like GPT-4 or Claude. Lastly, the experience-gathering step does not require a large amount of data or human labels.

We evaluated ExpeL on three vastly different domains and consistently outperformed strong baselines. Additionally, we showcased a transfer learning scenario where our agent that accumulated knowledge from source tasks showed positive forward transfer to target tasks. Finally, we highlighted some unexpected emerged abilities the ExpeL agent gained.

In summary, our key contributions are as follows: (1) we introduced ExpeL, a novel LLM agent that autonomously learns from experience *without gradient updates*; (2) We evaluated ExpeL on a diverse set of tasks to showcase its learning abilities and improvement on top of existing planning methods; (3) we showed a novel setting of transfer learning for our LLM agent and demonstrated forward transferability from source tasks to target tasks. Lastly, we believe that as planning algorithms and foundational models continue to improve, ExpeL's paradigm stands to gain significant benefits from their enhanced performances.

2 Related Work

We discuss the most relevant related works in this section. See Appendix A for detailed discussions on related works.

Prompt-based Learning: Prompt-based learning refines label prediction tasks by modifying the input context, facilitating swift adaptation to new tasks with minimal data (Liu et al. 2023a). This approach capitalizes on LLMs for answers without parameter tuning as they can be augmented using in-context learning (Brown et al. 2020). LAMA (Petroni et al. 2019) and GPT-3 (Brown et al. 2020) are early works that promoted this formulation. Efforts to reduce the intricacies of prompt design include automatic reasoning chains for NLP (Kojima et al. 2022; Zhang et al. 2023). Similarly, the ExpeL agent also autonomously learns from experiences using extracted insights and self-generated in-context trajectories by altering the execution prompt.

Retrieval Augmented Generation (RAG): Retrieval allows LLMs to access databases, mitigating hallucinations (Li et al. 2022; Wang, Yang, and Wei 2023; Rubin, Herzig, and Berant 2022; Liu et al. 2022). Retrieval has also been used to enhance the capabilities of decision-making agents (Humphreys et al. 2022; Zhao et al. 2023a). In contrast to these works, we focus on retrieving the ExpeL agent's self-generated experiences, thus reducing the dependency on gold examples and leveraging domain-specific corpus.

Planning for LLM Agents: Application of LLM agents in fields like robotics, natural sciences, game-playing, and workflows has surged, with emphasis on their world knowledge in fewshot settings (Ha, Florence, and Song 2023; Mu et al. 2023; Bran et al. 2023; Boiko, MacKnight, and Gomes 2023; Yang et al. 2023b; Lin et al. 2023a; Nakano et al. 2021; Wang et al. 2023c; Liu et al. 2023b). Moreover, LLMs have demonstrated promising zero/few-shot planning and reasoning capabilities in various configurations (Sumers et al. 2023), including embodied environments and reasoning tasks (Huang et al. 2022; Yao et al. 2023a; Wei et al. 2022b; Yao et al. 2023b; Gong et al. 2023).

Self-improvement and Memory for LLM Agents: Agents like Reflexion showcase feedback-based improvement, yet often lack cross-task memory (Shinn et al. 2023). Other agents exhibit potential in persistent memory within multi-agent contexts (Park et al. 2023; Maas et al. 2023). Our ExpeL agent combines these approaches, focusing on task-solving while benefiting from self-generated in-context examples and abstracted insights from memory.

3 Preliminaries

Complex Interactive Tasks We work with complex interactive tasks where at each time step $i \in \{0, \dots, H\}$, the agent receives an observation $o \in \mathcal{O}$, and from its observation history H_t decides to perform action $a \in \mathcal{A}$. The objective of the agent is to achieve some goal $g \in \mathcal{G}$. We only deal with deterministic environments in this work.

Large Language Models A large language model is a statistical model of the natural language, typically a neural network. In our setting, we use an autoregressive language model (OpenAI 2023; Brown et al. 2020; Touvron