FULL-BRIDGE THIN-BEAM LOAD CELLS FOR LOADS 0-113 g TO 0-18 kg

LCL Series





- ✓ Measures Force or Displacement
- Thermally Matched, Fully Active, Full-Bridge Gage for Optimal **Temperature Tracking**

When frequent small-load measurements are required, OMEGA® LCL Series thin-beam load cells are the answer. The LCL Series is designed to measure many different parameters found in medical instrumentation, home appliances, process control, robotics, automotive, and other high-volume applications. A specially developed integrated strain gage includes all balancing, compensating, and conductive elements and is laminated to the beam to provide excellent stability and reliability.

SPECIFICATIONS

Excitation: 5 Vdc, 12 V max Rated Output: 2 mV/V ±20%

(to minimize ±20% tolerance, end user must calibrate with a known weight)

Zero Balance: 0.3 mV/V Combined Error: 0.25% FS

Operating Temperature: -54 to 93°C

(-65 to 200°F)

Compensated Temperature: -7 to 49°C (20 to 120°F)

Temperature Effects: Zero balance 0.02% FS/°F; output 0.02%/°F

Resistance (Input and Output):

1200 ±300 Ω

Insulation Resistance: 1000 @ 50 Vdc

Seal: Urethane coated Safe Overload: 150% FS


Full Scale Deflection: 0.25 to 1.27 mm

(0.010 to 0.050")

Lead Wire: 9" shielded PVC 4-conductor 30 AWG

Material: 301 SS (beryllium copper

1/4 and 1/2 lb units)



MOST POPULAR MODELS HIGHLIGHTED!

To Order <i>(Specify Model Number)</i>							
CAPACITY		MODEL NO.	PRICE	COMPATIBLE METERS*			
113 g	0.25 lb	LCL-113G	\$69	DP2000S5, DP25B-S, DPiS			
227 g	0.5 lb	LCL-227G	69	DP2000S5, DP25B-S, DPiS			
454 g	1 lb	LCL-454G	69	DP2000S5, DP25B-S, DPiS			
816 g	2 lb	LCL-816G	69	DP2000S5, DP25B-S, DPiS			
2.27 kg	5 lb	LCL-005	69	DP2000S5, DP25B-S, DPiS			
4.54 kg	10 lb	LCL-010	69	DP2000S5, DP25B-S, DPiS			
9.07 kg	20 lb	LCL-020	69	DP2000S5, DP25B-S, DPiS			
18.14 kg	40 lb	LCL-040	69	DP2000S5, DP25B-S, DPiS			

^{*} See section D for compatible meters.

Ordering Examples: LCL-113G, beam, LCL-CL1, mounting bracket, \$69 + 15 = \$84. LCL-020, beam, LCM-CL1, mounting bracket, \$69 + 30 = \$99.

MOUNTING HARDWARE


MODEL NO.	PRICE	MOUNTING
LCL-CL1	¢15	For LCL-113G through LCL-816G
LCL-CL1	\$15	through LCL-816G
LCM-CL1	30	For LCL-005
LCIVI-CL I		For LCL-005 through LCL-040

ACCESSORY


MODEL NO.	PRICE	DESCRIPTION
OP-17	\$15	Reference Book: Measure for Measure
		M 1


INSTALLATION CONSIDERATIONS FOR THIN-BEAM LOAD CELLS


Careful design considerations must be taken into account when mounting OMEGA's LCL Series thin-beam load cells. The sensor's performance depends on the mechanical interface. All thin-beam load cells require mounting clamps to create a "double bend" during loading, as shown in Figure A. This illustration is exaggerated to show the clamp's effectiveness in producing opposing moments that create the double bend. An electrical output is generated as the double bend causes tension and compression on the sensor strain gage.



Two typical mounting arrangements are shown below. For high-accuracy applications, reinforcement plates should be slightly harder than the beam material, and the interfacing corners should be sharp. Because of low loads and sensor construction associated with the LCL113G through LCL-816G, in-line loading (Type 2) is not recommended.







Your One-Stop Source for Process Measurement and Control!

One Omega Drive | Stamford, CT 06907 | 1-888-TC-OMEGA (1-888-826-6342) | info@omega.com

www.omega.com



UNITED STATES

www.omega.com 1-800-TC-OMEGA Stamford, CT.

CANADA

www.omega.ca Laval(Quebec) 1-800-TC-OMEGA

GERMANY

www.omega.de Deckenpfronn, Germany 0800-8266342

UNITED KINGDOM

www. omega.co.uk Manchester, England 0800-488-488

FRANCE

www.omega.fr Guyancourt, France 088-466-342

CZECH REPUBLIC

www.omegaeng.cz Karviná, Czech Republic 596-311-899

BENELUX

www.omega.nl Amstelveen, NL 0800-099-33-44



More than 100,000 Products Available!

Temperature

Calibrators, Connectors, General Test and Measurement Instruments, Glass Bulb Thermometers, Handheld Instruments for Temperature Measurement, Ice Point References, Indicating Labels, Crayons, Cements and Lacquers, Infrared Temperature Measurement Instruments, Recorders Relative Humidity Measurement Instruments, RTD Probes, Elements and Assemblies, Temperature & Process Meters, Timers and Counters, Temperature and Process Controllers and Power Switching Devices, Thermistor Elements, Probes and Assemblies, Thermocouples Thermowells and Head and Well Assemblies, Transmitters, Wire

Flow and Level

Air Velocity Indicators, Doppler Flowmeters, Level Measurement, Magnetic Flowmeters, Mass Flowmeters, Pitot Tubes, Pumps, Rotameters, Turbine and Paddle Wheel Flowmeters, Ultrasonic Flowmeters, Valves, Variable Area Flowmeters, Vortex Shedding Flowmeters

pH and Conductivity

Conductivity Instrumentation, Dissolved Oxygen Instrumentation, Environmental Instrumentation, pH Electrodes and Instruments, Water and Soil Analysis Instrumentation

Data Acquisition

Auto-Dialers and Alarm Monitoring Systems, Communication Products and Converters, Data Acquisition and Analysis Software, Data Loggers Plug-in Cards, Signal Conditioners, USB, RS232, RS485 and Parallel Port Data Acquisition Systems, Wireless Transmitters and Receivers

• Pressure, Strain and Force

Displacement Transducers, Dynamic Measurement Force Sensors, Instrumentation for Pressure and Strain Measurements, Load Cells, Pressure Gauges, Pressure Reference Section, Pressure Switches, Pressure Transducers, Proximity Transducers, Regulators, Strain Gages, Torque Transducers, Valves

Heaters

Band Heaters, Cartridge Heaters, Circulation Heaters, Comfort Heaters, Controllers, Meters and Switching Devices, Flexible Heaters, General Test and Measurement Instruments, Heater Hook-up Wire, Heating Cable Systems, Immersion Heaters, Process Air and Duct, Heaters, Radiant Heaters, Strip Heaters, Tubular Heaters