

FMUSER FUQ-4353 Dual-Channel Encoder **HDMI-SDI-YPbPr-CVBS Inputs ASI-IP Outputs MPEG-2 H.264** **Encoding Web NMS Broadcast IPTV Solution**

Product Overview



The FMUSER FUQ-4353 is a dual-channel encoder supporting HD/SD MPEG-2 & H.264 video and MP2/AAC/AC3 audio. It accepts pluggable HDMI/3G-SDI/YPbPr+CVBS inputs and delivers ASI re-muxed outputs (MPTS/SPTS) or IP streams (UDP/RTP). The 1RU rack-mount unit features PSI/SI editing and web-based NMS for broadcast and IPTV workflows.

Key feature

Centralized Control: Web GUI and SNMP v2 for remote management via network

Technical Specifications

HDMI Input	Video	Input	HDMI*1 (with one for backup)
HDMI Input	Video	Encoding	MPEG2; MPEG4 AVC/H.264
HDMI Input	Video	Bitrate	1-19.5Mbps
HDMI Input	Video	Resolution	1920*1080_60P, 1920*1080_50P, (-for MPEG4 AVC/H.264 only) 1920*1080_60i, 1920*1080_50i, 1280*720_60p, 1280*720_50P 720*480_60i, 720*576_50i
HDMI Input	Video	Low Delay	Normal, Mode 1, Mode 2

HDMI Input	Video	Chroma	4:2:0
HDMI Input	Video	Aspect Ratio	16:9,4:3
HDMI Input	Audio	Encoding	MPEG1 Layer II; MPEG 2-AAC; MPEG 4-AAC and Dolby Digital AC3 2.0
HDMI Input	Audio	Sample rate	48KHz
HDMI Input	Audio	Bitrate	64/96/128/192/256/320kbps
HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Video (HDMI)	Encoding	MPEG2; MPEG4 AVC/H.264
HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Video (HDMI)	Input	HDMI*1
HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Video (HDMI)	Bitrate	1-19.5Mbps
HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Video (HDMI)	Resolution	1920*1080_60P, 1920*1080_50P, -for MPEG4 AVC/H.264 only) 1920*1080_60i, 1920*1080_50i, 1280*720_60p, 1280*720_50P 720*480_60i, 720*576_50i
HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Video (HDMI)	Low Delay	Normal, Mode 1, Mode 2
HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Video (HDMI)	Chroma	4:2:0
HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Video (HDMI)	Aspect Ratio	16:9,4:3
HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Audio (HDMI)	Encoding	MPEG1 Layer II ,MPEG2-AAC, MPEG4-AAC and Dolby Digital AC3 2.0

HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Audio (HDMI)	Input	HDMI*1
HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Audio (HDMI)	Sample rate	48KHz
HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Audio (HDMI)	Bitrate	64/96/128/ 192/256/320kbps
HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Video (YpbPr/ CVBS)	Encoding	MPEG2; MPEG4 AVC/H.264
HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Video (YpbPr/ CVBS)	Input	YpbPr*1 / CVBS *1
HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Video (YpbPr/ CVBS)	Bitrate	1-19.5Mbps
HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Video (YpbPr/ CVBS)	Resolution	CVBS: 720x576_50i (PAL); 720x480_60i (NTSC) YpbPr: 1920*1080_60i, 1920*1080_50i; 1280*720_60p, 1280*720_50P
HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Video (YpbPr/ CVBS)	Low Delay	Normal, Mode 1, Mode 2
HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Video (YpbPr/ CVBS)	Chroma	4:2:0
HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Video (YpbPr/ CVBS)	Aspect Ratio	16:9, 4:3
HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Audio (YpbPr/ CVBS)	Encoding	MPEG1 Layer II; MPEG2-AAC; MPEG4-AAC and Dolby Digital AC3 2.0
HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Audio (YpbPr/ CVBS)	Interface	1*Stereo/2*mono

HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Audio (YpbPr/ CVBS)	Sample rate	48KHz
HDMI/YPbPr/CVBS 3-in-1 Input (under developing)	Audio (YpbPr/ CVBS)	Bit rate	64/96/128/ 192/256/320kbps

General	System	Local interface	LCD + control buttons
General	System	Remote management	Web NMS
General	System	Stream In	1 ASI in for re-multiplexing
General	System	Stream Out	2 ASI out (BNC type, same one TS, mirror as MPTS or SPTS)
General	System	Stream Out	IP (1 MPTS & 2 SPTS) over UDP, RTP/RTSP (RJ45, 1000M)
General	System	DATA Port	1000M
General	System	NMS interface	RJ45, 100M
General	System	Language	English
General	Physical Specification	Power supply	100~240VAC, 50/60Hz
General	Physical Specification	Dimensions	482*300*44mm
General	Physical Specification	Operation temp	0~45℃

About Us

FMUSER is a company specializing in broadcasting and television transmission systems and integrating hotel IPTV systems. The company was established in 2009 and has served over 180 countries worldwide. More than 20,000 television stations, radio stations, and hotel clients from different.

Contact: Tomleequan Email sales@fmuser.com whatsapp: [+8613922702227](https://wa.me/8613922702227)