



Analyzing Twitter Data


Alex Hanna
Computational Social Scientist



Why Analyze Twitter Data?

Twitter sentiment versus Gallup Poll of Consumer Confidence

Brendan O'Connor, Ramnath Balasubramanyan, Bryan R. Routledge, and Noah A. Smith. 2010. From Tweets to Polls: Linking Text Sentiment to Public Opinion Time Series. In ICWSM-2010



Why Analyze Twitter Data?




Fig. 2. The political retweet network, laid out using a force-directed algorithm. Node colors reflect cluster assignments (see text).

Source: Conover et al. (2011)




What you can't analyze

- Can't collect data on observers
- Free-level of access is restrictive
 - Can't collect historical data
 - Only a 1% (unverified) sample



What you can analyze



- 1% sample is still a few million tweets
- Within a tweet
 - Text
 - User profile information
 - Geolocation
 - Retweets and quoted tweets





Let's review!





Collecting data through the Twitter API

Alex Hanna
Computational Social Scientist



Twitter API

- API: Application Programming Interace
 - Method of accessing data
- Twitter APIs
 - Search API
 - Ads API
 - Streaming API



Streaming API

- Streaming API
 - Real-time tweets
- Filter endpoint
 - Keywords
 - User IDs
 - Locations
- Sample endpoint
 - Random sample



Using tweepy to collect data

- tweepy
 - Python package for accessing Streaming API



SListener



tweepy authentication

```
from tweepy import OAuthHandler
from tweepy import API

auth = OAuthHandler(consumer_key, consumer_secret)

auth.set_access_token(access_token, access_token_secret)

api = API(auth)
```



Collecting data with tweepy

```
from tweepy import Stream

listen = SListener(api)

stream = Stream(auth, listen)

stream.sample()
```





Let's practice!





Understanding Twitter JSON

Alex Hanna
Computational Social Scientist



Contents of Twitter JSON

```
"created_at": "Thu Apr 19 14:25:04 +0000 2018",
    "id": 986973961295720449,
    "id_str": "986973961295720449",
    "text": "Writing out the script of my @DataCamp class
        and I can't help but mentally read it back to myself in
        @hugobowne's voice.",
    "retweet_count": 0,
    "favorite_count": 1,
    ...
}
```

- How many retweets, favorites
- Language
- Reply to which tweet
- Reply to which user



Child JSON objects

```
"user": {
    "id": 661613,
    "name": "Alex Hanna, Data Witch",
    "screen_name": "alexhanna",
    "location": "Toronto, ON",
    ...
}
```



Places, retweets/quoted tweets, and 140+ tweets

- place and coordinate
 - contain geolocation
- extended tweet
 - tweets over 140 characters
- retweeted_status and quoted_status
 - contain all tweet information of retweets and quoted tweets



Accessing JSON

```
import json

tweet_json = open('tweet-example.json', 'r').read()

tweet = json.loads(tweet_json)

tweet['text']
```



Child tweet JSON

```
tweet['user']['screen_name']

tweet['user']['name']

tweet['user']['created_at']
```





Let's practice!