KOHLER. Generators

Full Line Preview



THE ANSWER TO MOTHER NATURE'S MOOD SWINGS.

Keep the lights on, the movie playing and the coffee brewing. Whatever the weather's doing doesn't matter. Because unlike portable generators, KOHLER_® generators restore your power automatically and keep you connected to what you love to do.

You can trust a KOHLER generator – for good reasons.

It just works.

Every KOHLER generator is extensively quality-tested – before model release *and* before leaving the factory. The result is proven reliability.

It can power everything.

In as little as 10 seconds, it automatically powers your AC, heat, sump pump and major appliances like your fridge and oven. All at the same time.*

It comes with the best warranty.

You get our exclusive 5-year, 2,000-hour protection, plus a corrosion-proof enclosure that's built to last.**

It protects your electronics.

A KOHLER generator creates steady, high-quality power, which means your electronics are protected from erratic power surges.

It's trusted everywhere.

Hospitals, nuclear power plants and even the National Weather Service trust in hard-working, long-lasting KOHLER generators.

Digital Voltage Regulation Response Time

Warranty

Find the perfect size for your needs.





+/- 1.0%

10 Seconds

5-Year Limited'





+/- 1.5%

| 8.5RES | 14RESA | 20RESA | 30RESA | | |
|--|---|---|---|--|--|
| 8.5/7.0 | 14/12 | 20/18 | 30/27 | | |
| 120/240 | 120/240 | 120/240 | 120/240 | | |
| 35/29 | 58/50 | 83/75 | 125/112 | | |
| 3600 | 3600 | 3600 | 3600 | | |
| 624 cc | 725 cc | 999 cc | 1.6 L | | |
| 15.4 hp | 23.6 hp | 30.9 hp | 52 hp | | |
| KOHLER Command PRO OHV CH640 | KOHLER Command PRO OHV CH740 | KOHLER Command PRO OHV CH1000 | General Motors OHC | | |
| V-Twin | V-Twin | V-Twin | Inline 4-Cylinder | | |
| Hydraulic Valve Lifters | | | | | |
| LPG/NG | | | | | |
| Air Liquid | | | | | |
| Galvanized Steel 100% Corrosion-Proof Composite Galvan | | | Galvanized Steel | | |
| 65 | 63 | 64 | 68 | | |
| 65 | 67 | 69 | 68 | | |
| 44 x 29 x 32 | 48 x 26 x 29 | 48 x 26 x 29 | 73 x 36 x 37 | | |
| | 8.5/7.0 120/240 35/29 3600 624 cc 15.4 hp KOHLER Command PRO OHV CH640 V-Twin Galvanized Steel 65 65 | 8.5/7.0 14/12 120/240 120/240 35/29 58/50 3600 3600 624 cc 725 cc 15.4 hp 23.6 hp KOHLER KOHLER Command PRO OHV CH740 V-Twin V-Twin Hydraulic V Air Galvanized Steel 100% Corrosion-65 63 63 65 67 | 8.5/7.0 14/12 20/18 120/240 120/240 120/240 35/29 58/50 83/75 3600 3600 3600 624 cc 725 cc 999 cc 15.4 hp 23.6 hp 30.9 hp KOHLER KOHLER KOHLER Command PRO Command PRO Command PRO OHV CH640 OHV CH740 OHV CH1000 V-Twin V-Twin V-Twin Hydraulic Valve Lifters LPG/NG Air Galvanized Steel 100% Corrosion-Proof Composite 65 63 64 65 67 69 | | |

+/- 1.5%

RATINGS: Standby ratings apply to installations served by a reliable utility source. All single-phase units are rated at 1.0 power factor. The standby rating is applicable to variable loads with an average load factor of 80% for the duration of the power outage. No overload capacity is specified at this rating. Ratings are in accordance with ISO--3046/1, BS5514, AS2789 and DIN 6271.

^{*}Based on generator and load size.

^{**14} and 20 kW models feature corrosion-proof enclosures; all other models feature corrosion-resistant enclosures

^{*}Non-standby warranty of 18 months or 1000 hours available on 6VSG, 8.5/14RES models.

^{**5-}year extended warranty is an included option for quick ship 60 – 150 kW models.

New Products



38RCL and 48RCL Generators

Provide more protection for homes and businesses with up to 200-amp electrical service in a small footprint. Ultra quiet, aluminum enclosure standard.



6VSG Generator

5-Year Limited*

Efficiently charges battery banks for renewable energy, telecom and other remote applications. 24, 36 & 48 V direct current (DC) output available.

Accessories



OnCue_® Generator Management System

Provides true, remote monitoring and management of your system with online viewing and email notifications.



Load Control Module

Helps your generator balance high electrical loads by cycling them on and off.



RXT and RDT Transfer Switches

Automatically transfer power to and from utility and generator during an outage.



Programmable Interface Module

Activates critical items like storm shutters or a security system when you're away from home. Requires OnCue System.











5-Year Limited**





| 38RCL | 48RCL | 60ERESB | 80ERESD | 100ERESE | 125ERESC | 150ERESC | | |
|------------------------------|--------------------------|--------------------------|--|--------------------------|--------------------------|--------------------------|--|--|
| 38/38 | 48/48 | 60/60 | NA/80 | 95/100 | 113/125 | 134/144 | | |
| 120/240 | 120/240 | 120/240 | 120/240 | 120/240 | 120/240 | 120/240 | | |
| 158/158 | 200/200 | 250/250 | NA/333 | 396/417 | 469/521 | 557/600 | | |
| 1800 | 1800 | 1800 | 1800 | 1800 | 1800 | 1800 | | |
| 4.3 L | 5.0 L | 5.7 L | 5.7 L Turbo | 5.7 L Turbo | 8.8 L Turbo | 8.8 L Turbo | | |
| 75 hp | 89 hp | 105 hp | 133 hp | 162 hp | 218 hp | 259 HP | | |
| General Motors Vortec | General Motors Vortec | General Motors Vortec | General Motors Vortec | General Motors Vortec | General Motors Vortec | General Motors Vortec | | |
| V-6 | V-8 | V-8 | V-8 | V-8 | V-8 | V-8 | | |
| Hydraulic Valve Lifters | | | | | | | | |
| LPG/NG | | | NG | LPG/NG | | | | |
| Liquid | | | | | | | | |
| Corrosion-Resistant Aluminum | | | Galvanized Steel (Aluminum Also Available) | | | | | |
| 58 | 58 | 64 | 72 | 71 | 73 | 73 | | |
| 61 | 61 | 64 | 72 | 71 | 73 | 73 | | |
| 90 x 34 x 45 | 90 x 34 x 45 | 102 x 42 x 60 | 139 x 45 x 65 | 139 x 45 x 65 | 138 x 46 x 67 | 138 x 46 x 67 | | |
| +/- 1.0% | | | | +/- 0.5% | | | | |
| 10 Seconds | | | | | | | | |

Trusted by the National Weather Service

To keep their remote stations operating during power outages, the National Weather Service and National Oceanic and Atmospheric Administration depend on KOHLER® home generators.



Get more great information.

Then find your local dealer at Kohler Generators com

KOHLER Generators

KOHLER GENERATORS ■ KOHLER, WISCONSIN 53044

Printed in U.S.A 01/13 G12-392 © 2013 Kohler Co. KOHLER, OnCue, and Command PRO, are trademarks of Kohler Co. Use of this material for reproduction on the Internet and World Wide Web is strictly prohibited without written permission from Kohler Co.