KOHLER. Generators

Small Business Backup Power



THE POWER'S OUT EVERYWHERE ELSE. BUT YOU'RE STILL RINGING UP SALES.

Whether you run a restaurant, bank or convenience store, KOHLER, generators keep your customers coming and your business in business.

Why Kohler?

You can trust a KOHLER generator – for good reasons.

It just works.

Every KOHLER generator is extensively quality-tested - before model release and before leaving the factory. The result is proven reliability.

It protects your electronics.

A KOHLER generator creates steady, high-quality power, which means your computers and electronics are protected from erratic power surges.

It can power everything.

In as little as 10 seconds, it automatically powers your HVAC, lights, coolers, cash registers and computers. All at the same time.*

It's trusted everywhere.

Hospitals, nuclear power plants and even the National Weather Service trust in hard-working, long-lasting KOHLER generators.

You get our exclusive 5-year, 2,000hour protection, plus a corrosion-proof enclosure that's built to last.**

Response Time

Warranty

Find the perfect size for your needs.







10 Seconds 5-Year Limited*



Model number	8.5RES	14RESA	20RESA	30RESA		
Rated Power LPG (Liquid Propane)/ NG (Natural Gas) (kW)	8.5/7.0	14/12	20/18	30/27		
Voltage @ 60 Hz	120/240	120/240	120/240	120/240		
Amps LPG/NG @ 240 V	35/29	58/50	83/75	125/112		
Engine/Alternator RPM	3600	3600	3600	3600		
	624 cc	725 cc	999 cc	1.6 L		
Engine	15.4 hp	23.6 hp	30.9 hp	52 hp		
	KOHLER Command PRO OHV CH640	KOHLER Command PRO OHV CH740	KOHLER Command PRO OHV CH1000	General Motors OHC		
	V-Twin	V-Twin	V-Twin	Inline 4-Cylinder		
	Hydraulic Valve Lifters					
Fuel	LPG/NG					
Engine Cooling		Liquid				
Enclosure	Galvanized Steel 100% Corrosion-Proof Composite			Galvanized Steel		
Sound Output at Variable Speed Weekly Exercise (dBA at 23 Ft)	65	63	64	68		
Sound Output During Normal Operation (dBA at 23 Ft)	65	67	69	68		
Dimensions (L x W x H) In	44 x 29 x 32	48 x 26 x 29	48 x 26 x 29	73 x 36 x 37		
Digital Voltage Regulation	+/- 1.5% +/- 1.0% +/- 1.5%			+/- 1.5%		

RATINGS: Standby ratings apply to installations served by a reliable utility source. All single-phase units are rated at 1.0 power factor. The standby rating is applicable to variable loads with an average load factor of 80% for the duration of the power outage. No overload capacity is specified at this rating. Ratings are in accordance with ISO--3046/1, BS5514, AS2789 and DIN 6271.

It comes with the best warranty.

^{*}Based on generator and load size.

^{**14} and 20 kW models feature corrosion-proof enclosures; all other models feature corrosion-resistant enclosures.

^{*}Non-standby warranty of 18 months or 1000 hours available on 6VSG, 8.5/14RES models.

^{**5-}year extended warranty is an included option for quick ship 60 – 150 kW models.

New Products



38RCL and 48RCL Generators

Provide more protection for your business with up to 200-amp electrical service in a small footprint. Ultra quiet, aluminum enclosure standard.



6VSG Generator

5-Year Limited*

Efficiently charges battery banks for renewable energy, telecom and other remote applications. 24, 36 and 48 V direct current (DC) output available.

Accessories



OnCue_® Generator Management System

Provides true, remote monitoring and management of your system with online viewing and email notifications.



Load Control Module

Helps your generator balance high electrical loads by cycling them on and off.



RXT and RDT Transfer Switches

Automatically transfer power to and from utility and generator during an outage.



Programmable Interface Module

Remotely activates critical items like a security system or lights when you're away from your business. Requires OnCue System.











5-Year Limited**





38RCL	48RCL	60ERESB	80ERESD	100ERESE	125ERESC	150ERESC		
38/38	48/48	60/60	NA/80	95/100	113/125	134/144		
120/240	120/240	120/240	120/240	120/240	120/240	120/240		
158/158	200/200	250/250	NA/333	396/417	469/521	557/600		
1800	1800	1800	1800	1800	1800	1800		
4.3 L	5.0 L	5.7 L	5.7 L Turbo	5.7 L Turbo	8.8 L Turbo	8.8 L Turbo		
75 hp	89 hp	105 hp	133 hp	162 hp	218 hp	259 HP		
General Motors Vortec	General Motors Vortec	General Motors Vortec	General Motors Vortec	General Motors Vortec	General Motors Vortec	General Motors Vortec		
V-6	V-8	V-8	V-8	V-8	V-8	V-8		
Hydraulic Valve Lifters								
LPG/NG			NG	LPG/NG				
Liquid								
Corrosion-Resistant Aluminum			Galvanized Steel (Aluminum Also Available)					
58	58	64	72	71	73	73		
61	61	64	72	71	73	73		
90 x 34 x 45	90 x 34 x 45	102 x 42 x 60	139 x 45 x 65	139 x 45 x 65	138 x 46 x 67	138 x 46 x 67		
+/- 1.0%			+/- 0.5%					
10 Seconds								

Trusted by the National Weather Service

To keep their remote stations operating during power outages, the National Weather Service and National Oceanic and Atmospheric Administration depend on KOHLER® home generators.



Get more great information.

Then find your local dealer at KohlerGenerators com

KOHLER Generators

KOHLER GENERATORS ■ KOHLER, WISCONSIN 53044

Printed in U.S.A 01/13 G12-393 © 2013 Kohler Co.
KOHLER, OnCue, and Command PRO, are trademarks of Kohler Co.
Use of this material for reproduction on the Internet and World Wide Web is strictly prohibited without written permission from Kohler Co.

