

Pocket SDR C Library API Reference

ver.0.15b 2026-05-01

Table of Contents

- [Overview](#)
- [Constants and Macros](#)
- [Key Structures](#)
- [sdr_cmn.c - Common Utility Functions](#)
- [sdr_usb.c - USB Device Functions](#)
- [sdr_dev.c - Pocket SDR FE Device Functions](#)
- [sdr_sdev.c - SoapySDR Device Functions](#)
- [sdr_conf.c - SDR Device Configuration Functions](#)
- [sdr_func.c - Common SDR Functions](#)
- [sdr_code.c - GNSS Code Functions](#)
- [sdr_ch.c - Receiver Channel Functions](#)
- [sdr_nav.c - Navigation Data Decoder Functions](#)
- [sdr_fec.c - Forward Error Correction Functions](#)
- [sdr_ldpc.c - LDPC Decoder Functions](#)
- [sdr_nb_ldpc.c - Non-Binary LDPC Decoder Functions](#)
- [sdr_pvt.c - Position/Velocity/Time Functions](#)
- [sdr_array.c - Antenna Array Functions](#)
- [sdr_rcv.c - SDR Receiver Functions](#)

Overview

This API reference describes the **Pocket SDR** C library (`libsdr`). The library provides the building blocks for a software-defined GNSS receiver: USB / SoapySDR / file front-ends, IF buffer management, GNSS code generation and acquisition / tracking, navigation message decoding (FEC, LDPC, NB-LDPC), PVT (single-point positioning, observation/RTCM3 output), and antenna-array calibration and beam-forming. All entry points are declared in the single public header `pocket_sdr.h`.

- Scope and capabilities
 - Front-end I/O: Pocket SDR FE 2/4/8CH (Cypress EZ-USB), generic SoapySDR devices, IF data files, and TCP streams.
 - IF data processing: real (I) and complex (IQ) sampling, bit-packed RAW8 / RAW16 / RAW16I / RAW32 formats, fs/4 real-to-complex mixing, optional FIR LPF.
 - Acquisition and tracking: FFT-based code search, Doppler bin generation, fine Doppler estimation, multi-correlator (E/P/L plus 81 extra) DLL/PLL, Costas option.
 - Navigation decoding: per-system frame sync, convolutional / Reed-Solomon / LDPC / NB-LDPC decoders.
 - PVT: RTKLIB-based single-point positioning with antenna offsets and DCB; outputs include NMEA, RTCM3 obs/nav, and IF data log streams.
 - Antenna array: per-epoch EKF calibration of attitude (roll/pitch/yaw) and per-RF-CH hardware delays; beam-forming with quantized weights and up to 8 array channels.
- Conventions
 - Units: SI (m, s, Hz, sps). Angles are radians unless explicitly noted as degrees. Carrier phase observations are in cycles; pseudoranges in meters.
 - Time scales: GPST (`gtime_t` from RTKLIB) for navigation; UTC for receiver wall clock.
 - Frames: ENU for sky-plot directions; antenna positions are in body frame (X right, Y forward, Z up). Yaw is mathematical CCW from +X seen from +Z.
 - Memory: All `sdr_malloc()` allocations abort on failure (no NULL is returned). Buffers passed to APIs must remain valid for the call lifetime.
 - Threading: A receiver runs an IF data thread plus per-channel tracking threads. Public state queries (`sdr_rcv*_stat`) take an internal mutex; concurrent `sdr_rcv*` calls from the GUI thread are safe.
- Using the library
 - Include `pocket_sdr.h` and link `libsdr.a` (or `libsdr.so`). Initialize the library once with `sdr_func_init()`. Open a receiver via `sdr_rcv_open_dev` / `sdr_rcv_open_sdev` / `sdr_rcv_open_file`, then close with `sdr_rcv_close`.
 - For low-level use (custom front-ends), build the IF buffer / channel state directly with `sdr_buff_new`, `sdr_ch_new`, etc.

Constants and Macros

- **Library identity**

- `SDR_LIB_NAME` = "Pocket SDR"
- `SDR_LIB_VER` = library version string (e.g., "0.15b")

- **Channel and buffer limits**

- `SDR_MAX_RFCH` (8): maximum number of RF channels.
- `SDR_MAX_ARCH` (8): maximum number of antenna-array channels.
- `SDR_MAX_BUFF` (`SDR_MAX_RFCH+SDR_MAX_ARCH`): maximum number of IF data buffers.
- `SDR_MAX_NPRN` (256): maximum PRNs per signal.
- `SDR_MAX_NCH` (1500): maximum number of receiver channels.
- `SDR_MAX_NSYM` (2000): maximum nav symbol buffer length.
- `SDR_MAX_DATA` (4096): maximum nav data buffer length.
- `SDR_N_CORRX` (81): number of additional (extra) correlators.
- `SDR_W_CORRX` (4.0e-6 s): width of additional correlators.
- `SDR_MAX_CORR` (`6+SDR_N_CORRX`): total correlators per channel.
- `SDR_N_HIST` (5000): P-correlator history length.
- `SDR_N_CODES` (10): resampled code bank size.

- **Numeric scales**

- `SDR_CSCALE` ($\approx 1/11.2$): carrier scale; keeps $\max(IQ) \cdot \sqrt{2} / \text{scale} \leq 127$.
- `SDR_CYC` (1e-3 s): IF data processing cycle.
- `PI` (3.14159265358979).

- **Device types (`sdr_rcv_t.dev`)**

- `SDR_DEV_FILE` (1), `SDR_DEV_USB` (2), `SDR_DEV_STR` (3), `SDR_DEV_SOAPY` (4).

- **USB identifiers**

- `SDR_DEV_NAME` = "Pocket SDR".
- `SDR_DEV_VID` = 0x04B4 (Cypress).
- `SDR_DEV_PID1` = 0x1004 (EZ-USB FX2LP), `SDR_DEV_PID2` = 0x00F1 (EZ-USB FX3).
- `SDR_DEV_IF` = 0, `SDR_DEV_EP` = 0x86.

- **USB vendor requests**

- `SDR_VR_STAT` (0x40): get status.
- `SDR_VR_REG_READ` (0x41) / `SDR_VR_REG_WRITE` (0x42): MAX2771 register access.
- `SDR_VR_START` (0x44) / `SDR_VR_STOP` (0x45): bulk transfer control.
- `SDR_VR_RESET` (0x46): device reset.

- `SDR_VR_SAVE` (0x47): persist settings.
- **IF data formats (`sdr_rcv_t.fmt`)**
 - `SDR_FMT_INT8` (1): int8 real (I).
 - `SDR_FMT_INT8X2` (2): int8×2 complex with Q-polarity flipped.
 - `SDR_FMT_RAW8` (3): packed 8-bit raw, 2 RF CH.
 - `SDR_FMT_RAW16` (4): packed 16-bit raw, 4 RF CH.
 - `SDR_FMT_RAW16I` (5): packed 16-bit raw, 8 RF CH (Spider SDR FE).
 - `SDR_FMT_RAW32` (6): packed 32-bit raw, 8 RF CH (Pocket SDR FE 8CH).
 - `SDR_FMT_CS8` (7): int8×2 complex.
 - `SDR_FMT_CS16` (8): int16×2 complex.
- **Channel states (`sdr_ch_t.state`)**
 - `SDR_STATE_IDLE` (1), `SDR_STATE_SRCH` (2), `SDR_STATE_LOCK` (3).
- **FFT direction**
 - `SDR_FFT_FORWARD` (0), `SDR_FFT_BACKWARD` (1).
- **Packed complex helpers (4-bit I + 4-bit Q in a single byte)**
 - `SDR_CPX8(re, im)` : pack signed 4-bit I/Q into `sdr_cpx8_t`.
 - `SDR_CPX8_I(x)` : extract signed 4-bit I (sign-extended to int8).
 - `SDR_CPX8_Q(x)` : extract signed 4-bit Q (sign-extended to int8).

Key Structures

- `sdr_cpx8_t` (`uint8_t` alias)
 - Packed 4-bit I + 4-bit Q complex sample. Use `SDR_CPX8` / `SDR_CPX8_I` / `SDR_CPX8_Q` to access.
- `sdr_cpx16_t`
 - Fields: `int8_t I, Q`. 16-bit (8+8) signed complex sample.
- `sdr_cpx_t` (`float[2]`)
 - Single-precision complex `{Re, Im}` for FFT and correlator outputs.
- `sdr_lpf_t` (opaque)
 - 9-tap symmetric FIR (Hamming-windowed sinc) low-pass filter state. Construct with `sdr_lpf_new`, apply with `sdr_lpf_apply`, free with `sdr_lpf_free`.
- `sdr_thread_t` / `sdr_mutex_t`
 - Thin platform abstractions over Win32 SRWLOCK / pthread. `SDR_MUTEX_INIT` provides a static initializer.
- `sdr_usb_t`
 - USB device handle (Cypress CyAPI on Windows; libusb-1.0 on Linux/macOS) with up to `SDR_MAX_UBUFF` outstanding transfers.
- `sdr_dev_t` (Pocket SDR FE)
 - USB device wrapper plus a ring buffer (`buff`, `rp`, `wp`) and a USB-event-handler thread/mutex.
- `sdr_sdev_t` (SoapySDR)
 - SoapySDR device/stream wrappers with a ring buffer, sample size, sample rate, reading thread/mutex.
- `sdr_acq_t`
 - Acquisition state: code FFT, Doppler bin array, current Doppler external assist, accumulated correlation power and accumulation count.
- `sdr_trk_t`

- Tracking state: correlator positions and complex outputs; P history (`SDR_N_HIST`); secondary code sync/polarity; phase / code error; accumulators for DLL/PLL; resampled code and code FFT.
- `sdr_nav_t`
 - Navigation decoder state: symbol/frame sync flags, polarity, error count, sequence/type/status, code offset (CSK), symbol/data buffers, subframe lock times, OK/error counters.
- `sdr_ch_t`
 - Receiver baseband channel: identifier, code references, carrier/code/Doppler frequencies, lock counts, week/TOW, observation index, plus owned `acq` / `trk` / `nav` substructures.
- `sdr_buff_t`
 - IF data buffer: `data` array of `sdr_cpx8_t`, sampling type `IQ` (1=I, 2=IQ), and length `N`.
- `sdr_stats_t`
 - IF data statistics: std-dev, data rate (MB/s), cumulative size (MB), buffer usage (%), running accumulators, sample count.
- `sdr_ch_th_t`
 - Channel thread state: run flag, owning `sdr_ch_t`, IF buffer read pointer, back-pointer to receiver, OS thread handle.
- `sdr_pvt_t`
 - PVT state: epoch and cycle index, satellite count, RTKLIB `obs_t` / `nav_t` / `sol_t` / `ssat_t` / `rtcm_t`, latency, sol/obs/nav counters, back-pointer to receiver.
- `sdr_rfch_t`
 - Per-RF-CH configuration: LO frequency `fo`, sampling type `IQ`, sample bit width, optional `sdr_lpf_t`, and a raw→IF lookup table `LUT`.
- `sdr_arch_t`
 - Per-array-CH beam state: azimuth/elevation, scale (`<= 0` disables this beam), and quantized weight buffer `w[SDR_MAX_RFCH*2]` of int16 Q8 values `[Re_0, Im_0, Re_1, Im_1, ...]`.
- `sdr_array_t`

- Antenna array state: back-pointer to receiver, frequency index, RF-CH count (`nrpch` , snapshotted from `rcv->nrpch` at construction so calibration entry points do not need to re-thread it), per-element enable flags and body-frame positions, calibration run flag and epoch count, EKF state `x[3+SDR_MAX_RFCH]` = {roll, pitch, yaw, bias_1..bias_n} and covariance `P` , RMS. The number of array channels (`narch`) and per-array-CH beam states (`arch[]`) live in `sdr_rcv_t` .
- `sdr_rcv_t`
 - SDR receiver state: run flag, device type/pointer, IF data format / sampling rate / buffer length / channel counts (`nch` , `nrpch` , `narch`), current search channel, IF cycle count, per-RF-CH config (`rfch[]`), per-array-CH beam state (`arch[]`), per-CH IF buffers (RF + array), channel threads, optional `sdr_array_t` , `sdr_pvt_t` , IF data statistics, output streams (NMEA, RTCM3 obs, RTCM3 nav, IF data log), receiver start time (UTC), file replay scale, options string, IF data thread, and mutex.

sdr_cmnm.c - Common Utility Functions

Overview

Process-wide utilities: zeroed-and-checked memory allocation, monotonic time, thread/mutex wrappers, and the library identity strings.

API Functions

void *sdr_malloc(size_t size)

- **Description:** Allocate **size** bytes initialized to zero.
- **Arguments:**
 - size: number of bytes
- **Return:** pointer to allocated buffer
- **Notes:**
 - Aborts the process on allocation failure (never returns NULL); callers must not add NULL checks.

void sdr_free(void *p)

- **Description:** Free a buffer obtained via **sdr_malloc()**.
- **Arguments:**
 - p: pointer (NULL is safe; treated as no-op)
- **Return:** none

void sdr_get_time(double *t)

- **Description:** Get current wall-clock time as **t[0..5]** = year/month/day/hour/minute/second (UTC).
- **Arguments:**
 - t: 6-element output array
- **Return:** none

uint32_t sdr_get_tick(void)

- **Description:** Monotonic millisecond tick (wraps every ~49.7 days).
- **Return:** tick value

void sdr_sleep_msec(int msec)

- **Description:** Sleep for `msec` milliseconds.
- **Arguments:**
 - msec: milliseconds (≤ 0 : returns immediately)

```
const char *sdr_get_name(void)
```

- **Description:** Library name (`SDR_LIB_NAME`).
- **Return:** pointer to a static string

```
const char *sdr_get_ver(void)
```

- **Description:** Library version (`SDR_LIB_VER`).
- **Return:** pointer to a static string

```
int sdr_thread_create(sdr_thread_t *thread, void *(func)(void *), void *arg)
```

- **Description:** Start a new OS thread running `func(arg)`.
- **Arguments:**
 - thread: output thread handle
 - func: thread entry point
 - arg: opaque argument passed to `func`
- **Return:** 1 on success, 0 on error

```
void sdr_thread_join(sdr_thread_t thread)
```

- **Description:** Wait for `thread` to finish.
- **Arguments:**
 - thread: thread handle returned by `sdr_thread_create()`

```
void sdr_mutex_init(sdr_mutex_t *mtx)
```

- **Description:** Initialize a mutex (only required when `SDR_MUTEX_INIT` cannot be used).
- **Arguments:**
 - mtx: mutex pointer

```
void sdr_mutex_lock(sdr_mutex_t *mtx)
```

- **Description:** Acquire the mutex (blocking).

```
void sdr_mutex_unlock(sdr_mutex_t *mtx)
```

- **Description:** Release the mutex.

sdr_usb.c - USB Device Functions

Overview

Low-level USB transport for Pocket SDR FE devices. Wraps Cypress CyAPI (Windows) and libusb-1.0 (POSIX). Vendor requests are documented in the *Constants* section (`SDR_VR_*`).

API Functions

```
sdr_usb_t *sdr_usb_open(int bus, int port, const uint16_t *vid, const uint16_t *pid,
int n)
```

- **Description:** Open the first USB device matching one of the listed VID/PID pairs.
- **Arguments:**
 - bus: USB bus number (-1 for any)
 - port: USB port number (-1 for any)
 - vid: array of `n` USB vendor IDs
 - pid: array of `n` USB product IDs
 - n: length of `vid` / `pid` arrays
- **Return:** USB device handle (NULL: not found / error)

```
void sdr_usb_close(sdr_usb_t *usb)
```

- **Description:** Close USB device.

```
int sdr_usb_req(sdr_usb_t *usb, int mode, uint8_t req, uint16_t val, uint8_t *data,
int size)
```

- **Description:** Issue a vendor-specific control transfer.
- **Arguments:**
 - usb: USB handle
 - mode: 0 for IN (device→host), 1 for OUT (host→device)
 - req: request code (one of `SDR_VR_*`)
 - val: wValue field
 - data: I/O buffer
 - size: buffer size in bytes
- **Return:** 1 on success, 0 on error

sdr_dev.c - Pocket SDR FE Device Functions

Overview

Higher-level USB front-end abstraction with bulk IF data transfer and optional MAX2771 control. Spawns a USB-event-handler thread that fills an internal ring buffer; consumers poll via `sdr_dev_read()`.

API Functions

```
sdr_dev_t *sdr_dev_open(int bus, int port)
```

- **Description:** Open and initialize a Pocket SDR FE device.
- **Arguments:**
 - bus: USB bus (-1 for any)
 - port: USB port (-1 for any)
- **Return:** device handle (NULL: error)

```
void sdr_dev_close(sdr_dev_t *dev)
```

- **Description:** Stop transfers, close USB, free buffers.

```
int sdr_dev_start(sdr_dev_t *dev)
```

- **Description:** Start IF data bulk transfers and the USB event thread.
- **Return:** 1 on success, 0 on error

```
int sdr_dev_stop(sdr_dev_t *dev)
```

- **Description:** Stop bulk transfers and join the event thread.
- **Return:** 1 on success, 0 on error

```
int sdr_dev_read(sdr_dev_t *dev, uint8_t *buff, int size)
```

- **Description:** Copy up to `size` bytes of IF data from the internal ring buffer.
- **Arguments:**
 - dev: device handle
 - buff: caller-supplied output buffer
 - size: byte count requested
- **Return:** number of bytes actually copied (0 if empty)

```
int sdr_dev_get_info(sdr_dev_t *dev, int *fmt, double *fs, double *fo, int *IQ, int *bits)
```

- **Description:** Read MAX2771 / FX2LP-FX3 configuration into out parameters.
- **Arguments:**

- dev: device
- fmt: IF data format (`SDR_FMT_*`)
- fs: sampling rate (sps)
- fo: per-RF-CH LO frequency array (length $\geq$ `SDR_MAX_RFCH`)
- IQ: per-RF-CH sampling type (1=I, 2=IQ)
- bits: per-RF-CH bit width
- **Return:** 1 on success, 0 on error

```
int sdr_dev_get_gain(sdr_dev_t *dev, int ch)
```

- **Description:** Read PGA gain of RF channel `ch` (1-indexed).
- **Return:** gain (dB) or negative on error

```
int sdr_dev_set_gain(sdr_dev_t *dev, int ch, int gain)
```

- **Description:** Set PGA gain of RF channel `ch` (1-indexed) to `gain` dB.
- **Return:** 1 on success, 0 on error

```
int sdr_dev_get_filt(sdr_dev_t *dev, int ch, double *bw, double *freq, int *order)
```

- **Description:** Read MAX2771 IF filter parameters of RF channel `ch`.
- **Arguments:**
 - bw: filter bandwidth (Hz, output)
 - freq: filter center frequency (Hz, output)
 - order: filter order (output)
- **Return:** 1 on success, 0 on error

```
int sdr_dev_set_filt(sdr_dev_t *dev, int ch, double bw, double freq, int order)
```

- **Description:** Set MAX2771 IF filter parameters of RF channel `ch`.
- **Return:** 1 on success, 0 on error

sdr_sdev.c - SoapySDR Device Functions

Overview

Generic SDR front-end via SoapySDR. Compiled in when `-DSOAPYSDR` is set. Supports any device whose driver advertises a contiguous CS8 / CS16 stream.

API Functions

```
int sdr_sdev_list(void)
```

- **Description:** Print available SoapySDR devices to stderr.
- **Return:** number of devices found

```
sdr_sdev_t *sdr_sdev_open(const char *driver, int fmt, double rate, double freq,  
double bw, double gain)
```

- **Description:** Open a SoapySDR device.
- **Arguments:**
 - driver: SoapySDR driver string (e.g., "lime", "rtlsdr")
 - fmt: IF data format (**SDR_FMT_***)
 - rate: sampling rate (sps)
 - freq: center frequency (Hz)
 - bw: analog filter bandwidth (Hz, ≤ 0 : default)
 - gain: front-end gain (dB, ≤ 0 : AGC)
- **Return:** device handle (NULL: error)

```
void sdr_sdev_close(sdr_sdev_t *sdev)
```

- **Description:** Close SoapySDR device.

```
int sdr_sdev_start(sdr_sdev_t *sdev)
```

- **Description:** Activate the stream and start the reading thread.
- **Return:** 1 on success, 0 on error

```
int sdr_sdev_stop(sdr_sdev_t *sdev)
```

- **Description:** Deactivate the stream and join the reading thread.
- **Return:** 1 on success, 0 on error

```
int sdr_sdev_read(sdr_sdev_t *sdev, uint8_t *buff, int size)
```

- **Description:** Copy up to **size** bytes of IF data from the internal ring buffer.
- **Return:** number of bytes copied

sdr_conf.c - SDR Device Configuration Functions

Overview

Read and write Pocket SDR FE register configuration files (MAX2771 / FX2LP / FX3 register dumps).

API Functions

```
int sdr_conf_read(sdr_dev_t *dev, const char *file, int opt)
```

- **Description:** Apply registers from `file` to the device.
- **Arguments:**
 - `dev`: device handle
 - `file`: configuration file path
 - `opt`: option flags (reserved; pass 0)
- **Return:** 1 on success, 0 on error

```
int sdr_conf_write(sdr_dev_t *dev, const char *file, int opt)
```

- **Description:** Read the device's current registers and write them to `file`.
- **Return:** 1 on success, 0 on error

sdr_func.c - Common SDR Functions

Overview

General DSP and bookkeeping helpers: complex/FFT primitives, IF buffer / file I/O, code search and tracking correlators (scalar + AVX2 paths), Doppler bin generation, PSD utilities, log streams, packed-bit accumulators, and the digital LPF.

API Functions

```
void sdr_func_init(const char *file)
```

- **Description:** Library-wide initialization (FFTW wisdom, tables, RNG seed). Must be called once before any other SDR functions.
- **Arguments:**
 - file: FFTW wisdom file path (NULL or empty: skip)

```
sdr_cpx_t *sdr_cpx_malloc(int N)
```

- **Description:** Allocate **N**-element single-precision complex array (FFTW-aligned).
- **Return:** pointer

```
void sdr_cpx_free(sdr_cpx_t *cpx)
```

- **Description:** Free a buffer from `sdr_cpx_malloc()`.

```
float sdr_cpx_abs(sdr_cpx_t cpx)
```

- **Description:** Absolute value of a single complex sample.
- **Return:** $|cpx|$

```
void sdr_cpx_mul(const sdr_cpx_t *a, const sdr_cpx_t *b, int N, float s, sdr_cpx_t *c)
```

- **Description:** Element-wise complex multiply with scale: $c[i] = s * a[i] * b[i]$.

```
int sdr_cpx_fft(sdr_cpx_t *cpx1, int N, int dir, sdr_cpx_t *cpx2)
```

- **Description:** N-point FFT via FFTW3 or PocketFFT.
- **Arguments:**
 - cpx1: input array (length N)
 - N: FFT length

- dir: `SDR_FFT_FORWARD` or `SDR_FFT_BACKWARD`
- cpx2: output array (length N)
- **Return:** 1 on success, 0 on error

```
sdr_buff_t *sdr_buff_new(int N, int IQ)
```

- **Description:** Allocate an IF data buffer of length `N` samples with sampling type `IQ` (1=I, 2=IQ).
- **Return:** buffer pointer (with `data` set to `sdr_malloc`'d storage)

```
void sdr_buff_free(sdr_buff_t *buff)
```

- **Description:** Free an IF data buffer.

```
sdr_buff_t *sdr_read_data(const char *file, double fs, int IQ, double T, double toff)
```

- **Description:** Read up to `T` seconds of IF data from a file starting at offset `toff` seconds.
- **Arguments:**
 - file: IF data file path
 - fs: sampling rate (sps)
 - IQ: sampling type (1=I, 2=IQ)
 - T: duration to read (s)
 - toff: file offset (s)
- **Return:** filled `sdr_buff_t` (NULL: error)

```
int sdr_tag_write(const char *file, const char *prog, gtime_t time, int fmt, double fs, const double *fo, const int *IQ, const int *bits)
```

- **Description:** Write a `<file>.tag` companion file describing IF data parameters.
- **Return:** 1 on success, 0 on error

```
int sdr_tag_read(const char *file, char *prog, gtime_t *time, int *fmt, double *fs, double *fo, int *IQ, int *bits)
```

- **Description:** Read a `<file>.tag` companion file. Output pointers may be NULL to skip.
- **Return:** 1 on success, 0 on error / no tag

```
void sdr_search_code(const sdr_cpx_t *code_fft, double T, const sdr_buff_t *buff, int ix, int N, double fs, double fi, const float *fds, int len_fds, float *P)
```

- **Description:** Run FFT-based code/Doppler search over the precomputed conjugate-spectrum `code_fft` and the IF buffer slice `[ix, ix+N)`. Accumulates $|R(f_d, \tau)|^2$ into `P` (`len_fds ×`

N row-major).

```
float sdr_corr_max(const float *P, int N, int Nmax, int M, double T, int *ix)
```

- **Description:** Find the peak of the 2D power matrix **P** and return its peak-to-mean ratio (PMR).
- **Arguments:**
 - P: power matrix
 - N: code dimension length
 - Nmax: number of code samples to consider
 - M: Doppler dimension length
 - T: code period (s)
 - ix: 2-element array; **ix[0]** = Doppler index, **ix[1]** = code-offset sample
- **Return:** PMR

```
double sdr_fine_dop(const float *P, int N, const float *fds, int len_fds, const int *ix)
```

- **Description:** Estimate Doppler with sub-bin resolution by parabolic fit around **ix[0]**.
- **Return:** Doppler frequency (Hz)

```
double sdr_shift_freq(const char *sig, int fcn, double fi)
```

- **Description:** Apply a signal-specific carrier shift (e.g., GLONASS FDMA channel offset) to the nominal IF.
- **Arguments:**
 - sig: signal name (e.g., "L1CA", "G1CA")
 - fcn: GLONASS frequency channel number
 - fi: nominal IF (Hz)
- **Return:** shifted IF (Hz)

```
float *sdr_dop_bins(double T, float dop, float max_dop, int *len_fds)
```

- **Description:** Generate Doppler bins centered at **dop** spaced by $\approx 1/(2T)$ up to $\pm$ **max_dop**.
- **Arguments:**
 - T: code period (s)
 - dop: center Doppler (Hz)
 - max_dop: half-range (Hz)
 - len_fds: output length
- **Return:** heap-allocated float array (free with **sdr_free()**)

```
void sdr_corr_std(const sdr_cpx16_t *IQ, const sdr_cpx16_t *code, int N, double coff, const double *pos, int n, sdr_cpx_t *corr, sdr_cpx_t *C)
```

- **Description:** Standard time-domain correlator (real-code) for `n` correlator positions; writes outputs to `C[0..n-1]`. `corr` is the per-sample running buffer.

```
void sdr_corr_std_cpx_code(const sdr_cpx16_t *IQ, const sdr_cpx16_t *code, int N,
double coff, const double *pos, int n, sdr_cpx_t *corr, sdr_cpx_t *C)
```

- **Description:** Time-domain correlator with complex code (e.g., L6/E6 BCH).

```
void sdr_corr_std_cpx(const sdr_cpx_t *buff, int len_buff, int ix, int N, double fs,
double fc, double phi, const float *code, const double *pos, int n, sdr_cpx_t *corr)
```

- **Description:** Time-domain correlator that mixes carrier (`fc`, `phi`) on the fly while accumulating into `corr`.

```
void sdr_corr_fft(const sdr_cpx16_t *IQ, const sdr_cpx_t *code_fft, int N, sdr_cpx_t
*corr)
```

- **Description:** Frequency-domain correlation: forward FFT of IQ, multiply by `code_fft`, inverse FFT into `corr`.

```
void sdr_corr_fft_cpx(const sdr_cpx_t *buff, int len_buff, int ix, int N, double fs,
double fc, double phi, const sdr_cpx_t *code_fft, sdr_cpx_t *corr)
```

- **Description:** Same as above but mixes carrier from a complex IF buffer.

```
void sdr_mix_carr(const sdr_buff_t *buff, int ix, int N, double fs, double fc, double
phi, sdr_cpx16_t *IQ)
```

- **Description:** Wipe-off carrier from `buff[ix..ix+N)` using $\cos/\sin(2\pi \cdot fc \cdot t + \phi)$ and write 8-bit complex baseband to `IQ`.

```
void sdr_psd_cpx(const sdr_cpx_t *buff, int len_buff, int N, double fs, int IQ, float
*psd)
```

- **Description:** Compute a Welch-style PSD over `len_buff` samples with FFT length `N`.
- **Arguments:**
 - `psd`: output array of length `N` (IQ=2) or `N/2` (IQ=1) in dB/Hz

```
stream_t *sdr_str_open(const char *path)
```

- **Description:** Open an RTKLIB output stream (file/serial/TCP/...).

```
void sdr_str_close(stream_t *str)
```

- **Description:** Close an RTKLIB output stream.

```
int sdr_str_write(stream_t *str, uint8_t *data, int size)
```

- **Description:** Write `size` bytes to `str`.
- **Return:** number of bytes written

```
int sdr_log_open(const char *path)
```

- **Description:** Open the library log file.
- **Return:** 1 on success, 0 on error

```
void sdr_log_close(void)
```

- **Description:** Close the library log file.

```
void sdr_log_level(int level)
```

- **Description:** Set the log verbosity level (higher = more verbose).

```
void sdr_log_mask(const int *mask, int n)
```

- **Description:** Set per-tag log filtering mask of length `n`.

```
void sdr_log(int level, const char *msg, ...)
```

- **Description:** Emit a printf-formatted message at `level`.

```
int sdr_log_stat(void)
```

- **Description:** Get the current log status (1: open, 0: closed).

```
int sdr_get_log(char *buff, int size)
```

- **Description:** Read accumulated log lines into `buff` (NUL-terminated).
- **Return:** number of bytes written

```
int sdr_parse_nums(const char *str, int *prns)
```

- **Description:** Parse an integer list like `"1,3-5,7"` into `prns[]`.

- **Return:** number of values parsed

```
void sdr_add_buff(void *buff, int len_buff, void *item, size_t size_item)
```

- **Description:** Shift `buff` left by `size_item` bytes and append `item` at the tail (FIFO insert at end).

```
void sdr_pack_bits(const uint8_t *data, int nbit, int nz, uint8_t *buff)
```

- **Description:** Pack `nbit` data bits (one bit per byte) into `buff`, prepending `nz` zero pad bits.

```
void sdr_unpack_bits(const uint8_t *data, int nbit, uint8_t *buff)
```

- **Description:** Unpack `nbit` bits from packed `data` into `buff` (one bit per byte).

```
void sdr_unpack_data(uint32_t data, int nbit, uint8_t *buff)
```

- **Description:** Unpack the lower `nbit` bits of `data` (MSB-first) into `buff`.

```
uint8_t sdr_xor_bits(uint32_t X)
```

- **Description:** Population-count parity of `X` (XOR of all bits).
- **Return:** 0 or 1

```
int sdr_gen_fftw_wisdom(const char *file, int N)
```

- **Description:** Generate FFTW wisdom for FFT length `N` and save to `file`.
- **Return:** 1 on success, 0 on error

```
sdr_lpf_t *sdr_lpf_new(double fc, double fs)
```

- **Description:** Allocate a 9-tap Hamming-windowed FIR low-pass filter with one-sided cutoff `fc`.
- **Arguments:**
 - `fc`: cutoff frequency (Hz; must satisfy $0 < fc < fs/2$)
 - `fs`: sampling rate (Hz)
- **Return:** LPF instance (NULL on invalid arguments)

```
void sdr_lpf_free(sdr_lpf_t *lpf)
```

- **Description:** Free an LPF instance (NULL safe).

```
void sdr_lpf_apply(sdr_lpf_t *lpf, sdr_cpx8_t *data, int N)
```

- **Description:** Apply the LPF in place to **N** packed complex samples. Filter state is updated for streaming use.

sdr_code.c - GNSS Code Functions

Overview

GNSS spreading-code generators and resampling: GPS L1/L2/L5, Galileo E1/E5a/E5b/E6, BeiDou B1I/B1C/B2a/B2b/B3I, QZSS L1/L2/L5/L6, GLONASS L1/L2 (FDMA), NavIC L5/S, SBAS L1/L5. Includes secondary code lookup, resampling, and pre-FFT code spectra for fast acquisition.

API Functions

```
int8_t *sdr_gen_code(const char *sig, int prn, int *N)
```

- **Description:** Return a pointer to the primary spreading code for `(sig, prn)`. Length is written to `*N`.
- **Arguments:**
 - sig: signal name (e.g., "L1CA")
 - prn: PRN number
 - N: code length (chips, output)
- **Return:** pointer to internal code (read-only); NULL on invalid input

```
int sdr_gen_code_cpx(const char *sig, int prn, int8_t **code_I, int8_t **code_Q, int *N)
```

- **Description:** Return I/Q components for complex pilot+data signals (e.g., L5, E5).
- **Return:** 1 on success, 0 on error

```
int sdr_gen_code_cpx_sec(const char *sig, int prn, int sec, int8_t **code_I, int8_t **code_Q, int *N)
```

- **Description:** Same as above but applies the secondary code at index `sec` (e.g., 0/1).

```
int8_t *sdr_sec_code(const char *sig, int prn, int *N)
```

- **Description:** Return the secondary code for `(sig, prn)` and its length in `*N`.
- **Return:** pointer to internal code (read-only); NULL if none

```
double sdr_code_cyc(const char *sig)
```

- **Description:** Primary-code period in seconds.

```
int sdr_code_len(const char *sig)
```

- **Description:** Primary-code length in chips.

```
double sdr_sig_freq(const char *sig)
```

- **Description:** Nominal RF carrier frequency for `sig` (Hz).

```
void sdr_sat_id(const char *sig, int prn, char *sat)
```

- **Description:** Compose RTKLIB satellite ID from signal/PRN (e.g., "G01", "E05").

```
int sdr_sig_boc(const char *sig)
```

- **Description:** Return BOC modulation order (e.g., 1 for BOC(1,1)) or 0 for BPSK.

```
int sdr_sig_cpx(const char *sig)
```

- **Description:** 1 if the signal has complex spreading (pilot+data), 0 otherwise.

```
int sdr_sig_e5abq(const char *sig)
```

- **Description:** 1 if the signal is Galileo E5 AltBOC (E5abQ); 0 otherwise.

```
void sdr_res_code(const int8_t *code, int len_code, double T, double coff, double fs,
int N, int Nz, sdr_cpx16_t *code_res)
```

- **Description:** Resample a real spreading code at sample rate `fs` with code offset `coff`, length-`N` output and `Nz` zero-padding.

```
void sdr_res_code_cpx(const int8_t *code_I, const int8_t *code_Q, int len_code,
double T, double coff, double fs, int N, int Nz, sdr_cpx16_t *code_res)
```

- **Description:** Same as above for a complex (I+Q) code.

```
void sdr_gen_code_fft(const int8_t *code, int len_code, double T, double coff, double
fs, int N, int Nz, sdr_cpx_t *code_fft)
```

- **Description:** Resample a real code and produce its conjugate FFT (matched filter spectrum) of length `N` for use with `sdr_search_code()`.

```
void sdr_gen_code_fft_cpx(const int8_t *code_I, const int8_t *code_Q, int len_code,
double T, double coff, double fs, int N, int Nz, sdr_cpx_t *code_fft)
```


- **Description:** Same as above for a complex code.

sdr_ch.c - Receiver Channel Functions

Overview

Per-signal baseband channel: signal acquisition (FFT search → fine Doppler), tracking (3rd-order PLL with Costas, 2nd-order DLL), secondary code sync, and lock counters. The IF data is consumed via

`sdr_ch_update()`; correlator state is exposed via `sdr_ch_corr_stat()` / `sdr_ch_corr_hist()`.

API Functions

`sdr_ch_t *sdr_ch_new(const char *sig, int prn, double fs, double fi)`

- **Description:** Allocate and initialize a receiver channel for `(sig, prn)` at sampling rate `fs` and IF `fi`.
- **Return:** channel pointer (NULL on invalid signal)

`void sdr_ch_free(sdr_ch_t *ch)`

- **Description:** Free a receiver channel (along with its `acq` / `trk` / `nav` state).

`void sdr_ch_update(sdr_ch_t *ch, double time, const sdr_buff_t *buff, int ix)`

- **Description:** Run one update cycle: acquisition or tracking step on the IF buffer slice starting at `ix`.
- **Arguments:**
 - `ch`: channel
 - `time`: receiver time (s) for log/state stamping
 - `buff`: IF data buffer
 - `ix`: read pointer (samples)

`void sdr_ch_set_corr(sdr_ch_t *ch, int nposx)`

- **Description:** Configure the number of extra correlator positions (0.. `SDR_N_CORRX`) used for diagnostics.

`int sdr_ch_corr_stat(sdr_ch_t *ch, double *stat, double *pos, sdr_cpx_t *C, double *P)`

- **Description:** Snapshot the current correlator state.

- **Arguments:**
 - stat: scalar stats {fd, coff, adr, cn0, lock, lost, ...}
 - pos: correlator positions (chips)
 - C: complex correlator outputs
 - P: P-correlator history (length `SDR_N_HIST`)
- **Return:** 1 on success, 0 if channel is idle

```
int sdr_ch_corr_hist(sdr_ch_t *ch, double tspan, double *stat, sdr_cpx_t *P)
```

- **Description:** Return P-correlator history covering the past `tspan` seconds.
- **Return:** number of samples returned

sdr_nav.c - Navigation Data Decoder Functions

Overview

Top-level navigation message decoders. Each call to `sdr_nav_decode()` consumes new symbols from the channel's tracking output, performs frame sync, runs the appropriate FEC, and emits decoded ephemerides / almanacs to the receiver's `nav_t`.

API Functions

```
sdr_nav_t *sdr_nav_new(void)
```

- **Description:** Allocate a navigation decoder state (zero-initialized).

```
void sdr_nav_free(sdr_nav_t *nav)
```

- **Description:** Free the decoder state.

```
void sdr_nav_init(sdr_nav_t *nav)
```

- **Description:** Reset all sync flags and counters in `nav`.

```
void sdr_nav_decode(sdr_ch_t *ch)
```

- **Description:** Decode navigation symbols for the channel's signal type. Updates `ch->nav` and emits to the parent receiver's `nav_t` when a frame is complete.

sdr_fec.c - Forward Error Correction Functions

Overview

Convolutional decoder (rate-1/2, k=7, generator [171, 133]) and Reed-Solomon decoder used by GPS L5 / L2C / L6 and similar.

API Functions

```
void sdr_decode_conv(const uint8_t *data, int N, uint8_t *dec_data)
```

- **Description:** Viterbi decode **N** rate-1/2 soft symbols (uint8 in [0,255]) into **N/2** hard bits.

```
int sdr_decode_rs(uint8_t *syms)
```

- **Description:** Decode an RS(255,223) codeword in place; returns the number of corrected errors or -1 on failure.

sdr_ldpc.c - LDPC Decoder Functions

Overview

Belief-propagation LDPC decoder for BeiDou B1C, B2a, B2b, GPS L1C, etc.

API Functions

```
int sdr_decode_LDPC(const char *type, const uint8_t *syms, int N, uint8_t *syms_dec)
```

- **Description:** Decode **N** LDPC soft symbols using the parity-check matrix selected by **type** (e.g., "B1C", "B2a", "L1C").
- **Return:** number of corrected errors or -1 on decode failure

sdr_nb_ldpc.c - Non-Binary LDPC Decoder Functions

Overview

Non-binary LDPC decoder (used by some new GNSS signals). The parity-check matrix is supplied by the caller.

API Functions

```
int sdr_decode_NB_LDPC(const uint8_t H_idx[][4], const uint8_t H_ele[][4], int m, int n, const uint8_t *syms, uint8_t *syms_dec)
```

- **Description:** Decode a non-binary LDPC codeword with parity-check matrix described by `H_idx/H_ele` ($m \times n$).
- **Return:** 1 on success, 0 on failure

sdr_pvt.c - Position/Velocity/Time Functions

Overview

Single-point positioning and observation aggregation built on RTKLIB. The receiver thread feeds observations and decoded nav data into the PVT state, then `sdr_pvt_udsol()` runs `pntpos()` and dispatches output streams (NMEA, RTCM3, \$POS log).

API Functions

```
sdr_pvt_t *sdr_pvt_new(sdr_rcv_t *rcv)
```

- **Description:** Allocate a PVT state owned by `rcv`. `rcv->pvt` is set automatically inside `sdr_rcv_*` openers.

```
void sdr_pvt_free(sdr_pvt_t *pvt)
```

- **Description:** Free the PVT state.

```
void sdr_pvt_udobs(sdr_pvt_t *pvt, int64_t ix, sdr_ch_t *ch)
```

- **Description:** Update observation data for IF cycle `ix` from a tracking channel.

```
void sdr_pvt_udnav(sdr_pvt_t *pvt, sdr_ch_t *ch)
```

- **Description:** Update navigation data from a tracking channel that completed a frame.

```
void sdr_pvt_udsol(sdr_pvt_t *pvt, int64_t ix)
```

- **Description:** Run the per-epoch PVT solution: ambiguity check, sort obs, write logs/streams, call `pntpos()`, update `sol/ssat`, trigger array calibration step (`sdr_rcv_array_step()`), and advance the next epoch time.

```
void sdr_pvt_solstr(sdr_pvt_t *pvt, char *buff, int size)
```

- **Description:** Format the latest PVT solution into a single-line text string.
- **Return:** none (writes up to `size` bytes including NUL)

sdr_array.c - Antenna Array Functions

Overview

Antenna-array calibration and beam-forming. Calibration uses a per-epoch EKF over single-difference carrier-phase residuals between RF channel 1 (reference) and the others. The EKF state is `{roll, pitch, yaw, bias_1..bias_n}` (bias_1 is held near zero by a rank-deficiency tie-down so the remaining biases are interpreted relative to CH1). Beam-forming weights are quantized int16 (Q8) per RF CH so they can be applied with integer math in the IF data path. Per-CH beam state lives in `sdr_rcv_t.arch[]`; the calibration EKF state lives in `sdr_array_t`.

Models and Algorithms

- Body-to-ENU rotation: $R = R_z(\text{yaw}) \cdot R_y(\text{pitch}) \cdot R_x(\text{roll})$ (X-Y-Z = right / forward / up).
- Calibration SD model: $\lambda \cdot \text{SD}_L \approx \text{proj_calib} - \text{bias_calib}$, where $\text{proj_calib} = \text{sd_proj}() = -e \cdot R \cdot b$ (e = LOS unit vector in ENU, $b = b_k - b_0$ body-frame baseline).
- Bias sign convention (important): $\text{bias_calib} = -\text{bias_phys}$. The EKF stores the **negation** of the physical per-channel cable delay (in meters); a positive physical delay on CH k produces a negative entry in the state vector.
- Beam-forming weight: $w_a = (\text{scale} \cdot \text{bit_gain}) \cdot \exp(j \cdot \text{phi}_a)$ with $\text{phi}_a = -2\pi/\lambda \cdot (\text{proj_beam} + \text{bias_calib})$ and $\text{proj_beam} = e_{\text{body}} \cdot b = (R^T \cdot e) \cdot b = +e \cdot R \cdot b$. The two **proj** definitions deliberately differ in sign so the bias term is **added**, not subtracted, in the beam formula. Weights are quantized to int16 Q8 (`ARRAY_W_SCALE = 256`).
- Initialization: yaw grid search (15° step) plus iterative LSQ per epoch; subsequent calls run a standard EKF predict (random-walk) + update.

API Functions

`sdr_array_t *sdr_array_new(sdr_rcv_t *rcv, int freq)`

- **Description:** Allocate and initialize an antenna array. When `rcv != NULL` and `rcv->narch > 0`, all per-CH beams in `rcv->arch[]` are initialized to a default zenith equal-weight sum (scale `1/rcv->nrfch`). Initial `ant_pos` is all-zero and `ant_ena[0..nrfch-1]` is 1.
- **Arguments:**
 - `rcv`: back-pointer to receiver (NULL allowed for standalone calibration only)
 - `freq`: frequency index (0=L1, 1=L2, ...)
- **Return:** array pointer (never NULL — `sdr_malloc` aborts on failure)
- **Notes:**
 - Antenna geometry, attitude/bias, and beam directions are configured by the wrapper functions in `sdr_rcv.c` after construction.

`void sdr_array_free(sdr_array_t *array)`

- **Description:** Free the array state (NULL-safe).

```
int sdr_array_ant_pos(sdr_array_t *array, const double *ant_pos, const int *ant_ena)
```

- **Description:** Update body-frame antenna positions and per-element enable flags.
- **Arguments:**
 - array: array state (uses `array->nrfch` for buffer sizes)
 - ant_pos: `array->nrfch * 3` doubles in row-major order
 - ant_ena: `array->nrfch` enable flags (`ant_ena[0]` must be 1, the call is rejected otherwise)
- **Return:** 1 on success, 0 when `ant_ena[0] == 0`

```
int sdr_array_calib(sdr_array_t *array, const obsd_t *obs, int nob, const nav_t *nav, const double *rr)
```

- **Description:** Apply one epoch of single-difference carrier-phase observations to the EKF (or initialize the state if this is the first epoch).
- **Arguments:**
 - array: array state (updated in place)
 - obs: observation array; `obs[i].rcv` is the 1-indexed RF CH number
 - nob: number of observations
 - nav: navigation data
 - rr: receiver ECEF position (m)
- **Return:** 1 on success, 0 if convergence/initialization failed
- **Notes:**
 - Requires `ant_pos` already populated via `sdr_array_ant_pos()` (or the receiver wrapper).
 - The first call (when `P[0] == 0`) does a yaw grid search and LSQ; later calls run the EKF.

```
int sdr_array_run(sdr_array_t *array, int run)
```

- **Description:** Drive the EKF run flag.
- **Arguments:**
 - array: array state (must satisfy `array->nrfch >= 2`)
 - run: 0 stop, 1 start fresh (resets EKF state), 2 clear (resets state and stops)
- **Return:** 1 on success, 0 on error

```
int sdr_array_inject(sdr_array_t *array, const double *rpy, const double *bias)
```

- **Description:** Inject saved calibration values into the EKF state and re-seed the covariance.
- **Arguments:**
 - array: array state (must satisfy `array->nrfch >= 2`)

- rpy: attitude {roll, pitch, yaw} (3 doubles)
- bias: per-RF-CH calibration biases (`array->nrfch` doubles)
- **Return:** 1 on success, 0 on error

```
int sdr_array_stat(sdr_array_t *array, double *rpy, double *bias, double *rms, int *nep)
```

- **Description:** Read the current calibration state. `bias[0]` is always returned as 0 (reference CH); `bias[1..nrfch-1]` come from the EKF state.
- **Return:** current calibration run flag (1 = running, 0 = stopped); 0 also on error.

```
void sdr_array_step(sdr_array_t *array, const obsd_t *obs, int nobs, const nav_t *nav, const double *rr)
```

- **Description:** Per-epoch driver. When the run flag is set and `obs` / `rr` are valid, calls `sdr_array_calib()` and increments the epoch counter on success.

```
void sdr_arch_free(sdr_arch_t *arch)
```

- **Description:** Reset a per-array-CH beam state in place (zero az/el/scale and clear weights). NULL-safe.

```
int sdr_arch_set_beam(sdr_arch_t *arch, const sdr_array_t *array, double az, double el, double scale)
```

- **Description:** Compute beam-forming weights for one array CH pointing in ENU direction (`az` , `el`) and install them into `arch` .
- **Arguments:**
 - arch: per-array-CH beam state to update
 - array: array state (must have `array->rcv != NULL`)
 - az: beam azimuth (rad, from N CW)
 - el: beam elevation (rad, above horizon)
 - scale: per-CH weight magnitude (`<= 0` disables this beam — installs zero weights)
- **Return:** 1 on success, 0 on error
- **Notes:**
 - Reads the current rpy/bias and ant_pos from `array` . Caller is responsible for holding `rcv->mtx` when calling concurrently with `sdr_arch_combine()` .
 - Bit-range expansion gain is applied automatically based on the smallest `bits` among participating L1 RF CHs.

```
int sdr_arch_get_beam(const sdr_arch_t *arch, double *az, double *el)
```


- **Description:** Read the most recently set beam direction.
- **Return:** 1 on success, 0 on NULL `arch`

```
void sdr_arch_combine(const sdr_arch_t *arch, const sdr_array_t *array, int base)
```

- **Description:** Combine RF CH IF data into one array CH IF data buffer using the current weights. Reads `rcv->buff[0..nrfch-1]` and writes `rcv->buff[nrfch + m]` (where `m = arch - rcv->arch`), each starting at sample offset `base`. No-op when `arch->scale <= 0`.
- **Arguments:**
 - `arch`: per-array-CH beam state (selects the destination buffer by its offset within `rcv->arch[]`)
 - `array`: array state (must have `array->rcv != NULL`)
 - `base`: starting sample offset in each buffer
- **Return:** none
- **Notes:**
 - Caller-locked: the receiver loop calls this under `rcv->mtx` so beam updates are atomic relative to the integer combine.

sdr_rcv.c - SDR Receiver Functions

Overview

Top-level receiver lifecycle and state queries. A receiver wraps a front-end (USB / SoapySDR / file / stream), an IF data thread that demuxes raw samples into per-RF-CH `sdr_buff_t`s, multiple `sdr_ch_t` channel threads driving acquisition / tracking / nav decoding, an `sdr_pvt_t` for solutions, an optional `sdr_array_t`, and four output streams (NMEA, RTCM3 obs, RTCM3 nav, IF data log).

Receiver Options String

`sdr_rcv_open_*` and `sdr_rcv_new` take an `opt` string with space-separated tokens:

- `-RFCH <sig>:<ch>[{,|-}<ch>...]` — assign a signal to specific RF CH(s).
- `-LPF=<rfch>:<MHz>[,<rfch>:<MHz>...]` — enable digital LPF on RF CH(s) (two-sided BW in MHz). Real-sampling RF CHs (`IQ=1`) are auto-LPFed at $0.9 \cdot f_s / 2$ even without this option.
- `-ARCH=<nch>` — number of antenna-array channels.
- `-ARRAY` — output one RTCM3 obs stream per array element (station ID = CH).
- `-SCALE=<scale>` — raw-to-IF LUT scale for INT8 / CS8 / CS16 formats (0 enables AGC; default 1.0).
- `-TRACE[=<level>]` — enable debug trace logging at `<level>`.

API Functions

```
sdr_rcv_t *sdr_rcv_new(const char **sigs, const int *prns, int n, int fmt, double fs,
const double *fo, const int *IQ, const int *bits, const char *opt)
```

- **Description:** Allocate and initialize a receiver with `n` (signal, PRN) pairs, IF data format, and per-RF-CH parameters.
- **Arguments:**
 - `sigs`: array of signal name strings (length `n`)
 - `prns`: array of PRN numbers (length `n`)
 - `n`: number of (sig, prn) pairs
 - `fmt`: IF data format (`SDR_FMT_*`)
 - `fs`: sampling rate (sps)
 - `fo`: per-RF-CH LO frequencies (length $\geq$ number of RF CHs in `fmt`)
 - `IQ`: per-RF-CH sampling type (1=I, 2=IQ)
 - `bits`: per-RF-CH sample bit width
 - `opt`: receiver options string
- **Return:** receiver pointer (NULL: error)
- **Notes:**
 - Sets up `sdr_rfch_t[]`, IF buffers, channel threads, PVT, and (if `-ARCH  $\geq$  1`) `sdr_array_t`. Use `sdr_rcv_open_*` for the common combined-allocate-and-start path.

```
void sdr_rcv_free(sdr_rcv_t *rcv)
```

- **Description:** Free a receiver including all owned channels, buffers, PVT, and array state.

```
int sdr_rcv_start(sdr_rcv_t *rcv, int dev, void *dp, const char **paths)
```

- **Description:** Attach a device source (`SDR_DEV_*`) and start the IF data and channel threads.
- **Arguments:**
 - rcv: receiver
 - dev: device type
 - dp: device pointer (matching `dev`: `sdr_dev_t*`, `sdr_sdev_t*`, `FILE*`, or `stream_t*`)
 - paths: 4-element array of output stream paths (NULL/"" disables a slot): NMEA, RTCM3 obs, RTCM3 nav, IF data log
- **Return:** 1 on success, 0 on error

```
void sdr_rcv_stop(sdr_rcv_t *rcv)
```

- **Description:** Stop all threads (does not free `rcv`).

```
sdr_rcv_t *sdr_rcv_open_dev(const char **sigs, int *prns, int n, int bus, int port,  
const char *conf_file, const char **paths, const char *opt)
```

- **Description:** Open a Pocket SDR FE USB device and start a receiver.
- **Arguments:**
 - bus / port: USB bus / port (-1 for any)
 - conf_file: optional MAX2771 / FX register file ("" : skip)
 - other arguments as in `sdr_rcv_new()`
- **Return:** receiver pointer (NULL: error)

```
sdr_rcv_t *sdr_rcv_open_sdev(const char **sigs, int *prns, int n, const char *driver,  
int fmt, double rate, double freq, const char **paths, const char *opt)
```

- **Description:** Open a SoapySDR device and start a receiver.

```
sdr_rcv_t *sdr_rcv_open_file(const char **sigs, int *prns, int n, int fmt, double fs,  
const double *fo, const int *IQ, const int *bits, double toff, double tscale, const  
char *file, const char **paths, const char *opt)
```

- **Description:** Open an IF data file and start a receiver replaying it.
- **Arguments:**
 - toff: file offset to start from (s)

- `tscale`: replay time scale (1.0 = real-time; 0 = fastest)
- `file`: IF data file path. If a `<file>.tag` exists, `fmt` / `fs` / `fo` / `IQ` / `bits` are overridden by tag values.
- **Return**: receiver pointer (NULL: error)

```
void sdr_rcv_close(sdr_rcv_t *rcv)
```

- **Description**: Stop the receiver, close the underlying device, and free all resources.

```
void sdr_rcv_setopt(const char *opt, double value)
```

- **Description**: Set a global library option. Recognized keys: "epoch", "lag_epoch", "log_lvl", "fftw_wisdom", ... (see `sdr_rcv.c`).

```
int sdr_rcv_rcv_stat(sdr_rcv_t *rcv, char *buff, int size)
```

- **Description**: Format receiver-level statistics (time, fmt/CH counts, LO/fs, sampling, IF rate, buffer usage, ...) into `buff`.
- **Return**: number of bytes written

```
void sdr_rcv_str_stat(sdr_rcv_t *rcv, int *stat)
```

- **Description**: Get per-output-stream connection state into `stat[0..3]` (NMEA, RTCM3 obs, RTCM3 nav, IF data log).

```
int sdr_rcv_sat_stat(sdr_rcv_t *rcv, const char *sat, char *buff, int size)
```

- **Description**: Format per-satellite status text for `sat` (e.g., "G05") into `buff`.
- **Return**: number of bytes written

```
int sdr_rcv_ch_stat(sdr_rcv_t *rcv, const char *sys, int all, double min_lock, int rfch, int opt, char *buff, int size)
```

- **Description**: Dump receiver-channel status table.
- **Arguments**:
 - `sys`: filter by system ("ALL", "GPS", "GLONASS", ...)
 - `all`: include idle channels
 - `min_lock`: minimum lock time (s) to include
 - `rfch`: filter by RF CH (0 = all)
 - `opt`: option flags (reserved)
 - `buff/size`: output buffer
- **Return**: number of bytes written

```
void sdr_rcv_sel_ch(sdr_rcv_t *rcv, int ch)
```

- **Description:** Select the channel currently shown in correlator views (0 = none).

```
int sdr_rcv_corr_stat(sdr_rcv_t *rcv, int ch, double *stat, double *pos, sdr_cpx_t *C, double *P)
```

- **Description:** Snapshot correlator state for channel `ch` (1-indexed). Returns 1 on success.

```
int sdr_rcv_corr_hist(sdr_rcv_t *rcv, int ch, double tspan, double *stat, sdr_cpx_t *P)
```

- **Description:** P-correlator history for channel `ch` over the past `tspan` s.
- **Return:** number of samples returned

```
int sdr_rcv_rfch_stat(sdr_rcv_t *rcv, int ch, double *stat)
```

- **Description:** Snapshot per-RF-CH (or per-array-CH) status into `stat[0..7]` = {dev, fmt, fs, fo, IQ, bits, std-dev, rtoc-flag}. `ch` is 1-indexed (1..nrfch+narch).
- **Return:** 1 on success, 0 on error

```
int sdr_rcv_rfch_psd(sdr_rcv_t *rcv, int ch, double tave, int N, float *psd)
```

- **Description:** Compute PSD over the latest `tave` seconds with FFT length `N`.
- **Return:** number of PSD bins written

```
int sdr_rcv_rfch_hist(sdr_rcv_t *rcv, int ch, double tave, int *val, double *hist1, double *hist2)
```

- **Description:** I/Q sample histograms over the latest `tave` seconds. Outputs share a common bin-value array `val[]` and per-component frequencies `hist1[]` (I), `hist2[]` (Q).
- **Return:** number of histogram bins

```
int sdr_rcv_pvt_sol(sdr_rcv_t *rcv, char *buff, int size)
```

- **Description:** Format the latest PVT solution as a single-line text string.
- **Return:** number of bytes written

```
int sdr_rcv_get_gain(sdr_rcv_t *rcv, int ch)
```

- **Description:** USB device only — get RF CH `ch` PGA gain (dB). 0 / negative on error.

```
int sdr_rcv_set_gain(sdr_rcv_t *rcv, int ch, int gain)
```

- **Description:** USB device only — set RF CH `ch` PGA gain (dB).
- **Return:** 1 on success, 0 on error

```
int sdr_rcv_get_filt(sdr_rcv_t *rcv, int ch, double *bw, double *freq, int *order)
```

- **Description:** USB device only — read MAX2771 IF filter parameters of RF CH `ch`.
- **Return:** 1 on success, 0 on error

```
int sdr_rcv_set_filt(sdr_rcv_t *rcv, int ch, double bw, double freq, int order)
```

- **Description:** USB device only — set MAX2771 IF filter parameters of RF CH `ch`.
- **Return:** 1 on success, 0 on error

```
int sdr_rcv_array_ant_pos(sdr_rcv_t *rcv, const double *ant_pos, const int *ant_ena)
```

- **Description:** Set per-RF-CH antenna body-frame positions and enable flags. After the state update, all active array CH beams are atomically refreshed with the latest geometry (current `az/el` preserved).
- **Arguments:**
 - `rcv`: receiver (must have `array != NULL`)
 - `ant_pos`: `nr_fch*3` doubles (row-major), or NULL to leave positions unchanged
 - `ant_ena`: `nr_fch` enable flags (`ant_ena[0]` must be 1), or NULL to leave flags unchanged
- **Return:** 1 on success, 0 on error or when `ant_ena[0] == 0`

```
int sdr_rcv_array_calib(sdr_rcv_t *rcv, int run)
```

- **Description:** Drive the calibration EKF run flag. After the update, all active array CH beams are atomically refreshed with the latest state.
- **Arguments:**
 - `rcv`: receiver (must have `array != NULL`)
 - `run`: 0 stop, 1 start fresh (resets EKF state), 2 clear
- **Return:** 1 on success, 0 on error
- **Notes:**
 - To inject saved calibration values, use `sdr_rcv_array_load_calib()`.

```
int sdr_rcv_array_save_calib(sdr_rcv_t *rcv, const char *file)
```

- **Description:** Snapshot the current calibration state and write it to `file`. Returns 0 (no write) when the EKF has not produced any data yet.
- **Return:** 1 on success, 0 on error / nothing to save

```
int sdr_rcv_array_load_calib(sdr_rcv_t *rcv, const char *file)
```

- **Description:** Load attitude and per-CH biases from `file` (format produced by `sdr_rcv_array_save_calib()`) and inject them into the EKF state. Refreshes all active beams afterwards.
- **Return:** 1 on success, 0 on error

```
int sdr_rcv_array_stat(sdr_rcv_t *rcv, double *rpy, double *bias, double *rms, int *nep)
```

- **Description:** Read current array calibration state. Outputs are filled when the array exists; `bias[0]` is always 0.
- **Return:** current calibration run flag (1 = running, 0 = stopped); 0 also when `array == NULL`.

```
int sdr_rcv_array_set_beam(sdr_rcv_t *rcv, int ach, double az, double el)
```

- **Description:** Set beam direction for array CH `ach` (absolute index `nr_fch ≤ ach < nr_fch+narch`). Recomputes weights from the current calibration state and antenna geometry.
- **Return:** 1 on success, 0 on error

```
int sdr_rcv_array_get_beam(sdr_rcv_t *rcv, int ach, double *az, double *el)
```

- **Description:** Get the most recently set beam direction for array CH `ach`.
- **Return:** 1 on success, 0 on error

```
void sdr_rcv_array_step(sdr_rcv_t *rcv, const obsd_t *obs, int nob, const nav_t *nav, const double *rr)
```

- **Description:** Per-epoch driver invoked by `sdr_pvt_udsol()` after each PVT update. Holds `rcv->mtx` while calling `sdr_array_step()`.