Release Notes: ProcessMaker 3.5.5

Release Date: November 16th, 2020

This document contains Release Notes for ProcessMaker 3.5.5. Release Notes are cumulative, and document improvements and bug fixes associated with this release unless otherwise noted. A list of older ProcessMaker Release Notes is included at the end of this document.

Links to System Requirements and Special Instructions for This Release

1. Supported Stacks
2. Supported Web Browsers
3. Review the ProcessMaker versions to upgrade to ProcessMaker 3.5.x
4. Due to the first improvement, this release requires to run the `translation-repair` command.

Improvements

This section documents improvements for ProcessMaker 3.5.5:

1. **Set Task Scheduler to run up to twice a day:** Task Scheduler may now be set to run once or twice each day at a specific time and time zone. Ensure to run the `translation-repair` command for this improvement.

2. **ProcessMaker performance improved:** ProcessMaker performs queries to the `APP_ASSIGN_SELF_SERVICE_VALUE` and `APP_ASSIGN_SELF_SERVICE_VALUE_GROUP` tables faster to more quickly display the **Unassigned** tray when the ProcessMaker server has millions of cases.

Bug Fixes

This section documents bug fixes for ProcessMaker 3.5.5:

1. **SQL injection vulnerability cannot be exploited:** A SQL injection vulnerability via the `Category` parameter in the `proxyNewCasesList` endpoint cannot be exploited, thereby ensuring data confidentiality and security.

2. **Stored cross-site scripting vulnerability cannot be exploited:** A stored cross-site scripting vulnerability by running a case with an email address field in a Dynaform cannot be exploited, thereby ensuring data security.

ProcessMaker

3. **Reflected cross-site scripting vulnerability cannot be exploited:** A reflected cross-site scripting vulnerability by running the `APPUID` parameter in the `appProxy/requestOpenSummary` endpoint cannot be exploited, thereby ensuring data security.

Previous Release Notes

Refer to the previous Release Notes from ProcessMaker versions 3.2 through 3.5.4:

- [3.5.4](#)
- [3.5.3](#)
- [3.5.2](#)
- [3.5.1](#)
- [3.5.0](#)
- [3.4.11](#)
- [3.4.10](#)
- [3.4.9](#)
- [3.4.8](#)
- [3.4.7](#)
- [3.4.6](#)
- [3.4.5](#)
- [3.4.4](#)
- [3.4.3](#)
- [3.4.2](#)
- [3.4.0](#)
- [3.3.17](#)
- [3.3.16](#)
- [3.3.15](#)
- [3.3.14](#)
- [3.3.13](#)
- [3.3.12](#)
- [3.3.11](#)
- [3.3.10](#)
- [3.3.9](#)
- [3.3.8](#)
- [3.3.7](#)
- [3.3.6](#)
- [3.3.5](#)
- [3.3.4](#)
- [3.3.3](#)
- [3.3.2](#)

ProcessMaker