set_cmd :

```
set_cmd :

                                    ┌─────────────────────┐
                                 ┌─▶│    SET EXPLAIN ON    │──┐
                                 │  └─────────────────────┘  │
                                 │  ┌─────────────────────┐  │
                                 ├─▶│   SET EXPLAIN OFF    │──┤
                                 │  └─────────────────────┘  │
                                 │  ┌───────────────────┐    ┌─────────────────┐
                                 ├─▶│ SET LOCK MODE TO WAIT │─▶│ <integer value> │─┤
                                 │  └───────────────────┘    └─────────────────┘
                                 │  ┌──────────────────────────┐
                                 ├─▶│  SET LOCK MODE TO NOT WAIT │──┤
                                 │  └──────────────────────────┘
  <use session>                  │
                                 │  ┌────────────────────────────┐
                                 ├─▶│ SET ISOLATION TO DIRTY READ │──┤
                                 │  └────────────────────────────┘
                                 │  ┌────────────────────────────┐
                                 ├─▶│  SET ISOLATION DIRTY READ   │──┤
                                 │  └────────────────────────────┘
                                 │  ┌─────────────────────────────────┐
                                 ├─▶│ SET ISOLATION TO REPEATABLE READ │──┤
                                 │  └─────────────────────────────────┘
                                 │  ┌─────────────────────────────────┐
                                 ├─▶│  SET ISOLATION REPEATABLE READ   │──┤
                                 │  └─────────────────────────────────┘
                                 │  ┌──────────────────────────────────┐
                                 ├─▶│ SET ISOLATION TO CURSOR STABILITY │──┤
                                 │  └──────────────────────────────────┘
                                 │  ┌──────────────────────────────────┐
                                 ├─▶│  SET ISOLATION CURSOR STABILITY   │──┤
                                 │  └──────────────────────────────────┘
                                 │  ┌──────────────────────────────────┐
                                 ├─▶│  SET ISOLATION TO COMMITTED READ  │──┤
                                 │  └──────────────────────────────────┘
                                 │  ┌──────────────────────────────────┐
                                 └─▶│   SET ISOLATION COMMITTED READ    │──┘
                                    └──────────────────────────────────┘
```

SET EXPLAIN ON

SET EXPLAIN OFF

SET LOCK MODE TO WAIT   <integer value>

SET LOCK MODE TO NOT WAIT

SET ISOLATION TO DIRTY READ

SET ISOLATION DIRTY READ

SET ISOLATION TO REPEATABLE READ

SET ISOLATION REPEATABLE READ

SET ISOLATION TO CURSOR STABILITY

SET ISOLATION CURSOR STABILITY

SET ISOLATION TO COMMITTED READ

SET ISOLATION COMMITTED READ