

# L<sup>A</sup>T<sub>E</sub>X FOR UNDERGRADUATES

## FORMATTING

### Lecture Notes

Tom Schenk Jr.

*Version of January 9, 2006*

## 1 Motivation

You may have noticed a handful of operators are used to begin and end commands, for instance, `\` and `{ }` are often used in the syntax. So what happens if we want to actually make those characters appear in the text and not function as operators (such as above)?

More importantly, how do we italicize, bold, or use different fonts in a document? As explained earlier, L<sup>A</sup>T<sub>E</sub>X will take care of most of our formatting needs (e.g. section headers), nevertheless, it is still necessary to use traditional formatting throughout a document.

Lastly, this lecture will explore how to create bulleted or enumerate lists in our document. The material on lists is directly related to the next lecture on environments.

## 2 Formatting

### 2.1 Special Characters

A number of characters are “special” characters. That is, they are used in regular English syntax, but serve an important function in L<sup>A</sup>T<sub>E</sub>X. I have already pointed out that `\` is one of these characters. Simply including it in our code will cause L<sup>A</sup>T<sub>E</sub>X to misinterpret its meaning. Instead, we must use commands to make certain characters. Below is a list of characters and their corresponding

codes: `\$` `\%` `\&` `\#` `\{` `\}` `\-` `\^{}{}` `\~{}{}` You may have noticed

some of the special commands are followed with `{}`. Let us take a look at the carrot (^) character as an example. The following is what “apple” should look like if properly preceded by a carrot: `^apple` (`\^{}apple`). Say, for instance, I omitted the `{}`, then it would appear as `apple` (`\apple`). As you can see, the carrot then acts as an accent character. Implicitly, `{}` acts as an artificial space between `^` and “apple.” The same is true for the tildē character.

Table 1: Built-in Logo Commands

Command	Logo
<code>\LaTeX\</code>	L <sup>A</sup> T <sub>E</sub> X
<code>\LaTeXe\</code>	L <sup>A</sup> T <sub>E</sub> X 2 <sub>ε</sub>
<code>\TeX\</code>	T <sub>E</sub> X

Along with special formatting commands, there are special logo's that L<sup>A</sup>T<sub>E</sub>X can recognize. Below is a list of commands and their respective outputs: This is a nifty tool, but seldom used when not creating a L<sup>A</sup>T<sub>E</sub>X tutorial. You may have noticed the use of an extra `\` at the end of the commands. Again, this is to solve a spacing problem. If you were not to include the extra backslash, then it would appear like this: L<sup>A</sup>T<sub>E</sub>XTutorial (`\LaTeX Tutorial`).

## 2.2 Formatting

Formatting text is rather simple. `\textbf{argument}`, for instance, will produce **bold** text. `\texttt{argument}` will produce typewriter font; `\textsc{argument}` will use SMALL CAPS; `\textbf{argument}` will make the text appear *slanted*. `\textit{argument}` will produce *italicized* font, but so will `\emph{argument}`—depending on the circumstances. Normally, italicizing a word is meant to emphasize its importance; meanwhile, italicizing is usually meant for design purposes.

Consider the following two paragraphs. Both use `\emph` to emphasize a word. Although the second paragraph's default is italics, emphasized words are still contrasted.

A student may be absent up to *six* times before being dismissed from class. Likewise, he or she may only be tardy *twelve* times before also being dismissed. An absent or tardiness can be excused if he or she brings a valid note.

*A student may be absent up to six times before being dismissed from class. Likewise, he or she may only be tardy twelve times before also being dismissed. An absent or tardiness can be excused if he or she brings a valid note.*

Figure 2 outlines some basic formatting commands and their results.

## 2.3 Font Sizes

Recall from Lecture 2.1.1, an author may change the font size as an option in the *document class* command (e.g. `\documentclass[12pt]{article}`). Sometimes, one may want to temporarily change a font size. This may be done with a variety of commands. For instance, `\tiny` will change all proceeding text to

Table 2: Widely Used Formatting Commands

Command	Output
<code>\textbf{<i>text</i>}</code>	<b>bold</b>
<code>\textit{<i>text</i>}</code>	<i>italic</i>
<code>\texttt{<i>text</i>}</code>	<b>typewriter</b>
<code>\textsl{<i>text</i>}</code>	<i>slanted</i>
<code>\emph{<i>text</i>}</code>	<i>emphasized</i>
<code>\textsf{<i>text</i>}</code>	<b>sans serif</b>
<code>\textsc{<i>text</i>}</code>	SMALL CAPS

size 5 font (note: there are no brackets with this command). On the other hand, `\large` will create size 12 font. To return to your default font size, you must turn off the command with `\normalsize`. Consider the following example:

Here is an example of `\footnotesize` footnotesize font.  
`\normalsize` After returning to normal size, you may want to use a  
`\LARGE` large font.

And its output:

Here is an example of footnotesize font. After returning to normal size,  
you may want to use a large font.

It should be noted that these commands are case sensitive. That is, `\LARGE` is different from `\Large`. Table 3 shows font commands and their respective output. In general, each increase (decrease) in font size is +2 (-2) in point size.

## 2.4 Justifications

### 2.4.1 Flushleft, Center, and Flushright

Justifications are another aesthetic tool for a word processor. In general,  $\text{\LaTeX}$  indents the first paragraph<sup>1</sup> on the left margin, but aligned on the right margin. The author may control the alignment, however, with *environments*—this concept will be developed in a later lecture.

For instance, one would follow the following syntax:

`\begin{argument}` Desired text...`\end{argument}` Where *argument* is either **center**, **flushleft**, or **flushright**. The text between begin and end will function accordingly. Below is an example code and output of centered text.

<sup>1</sup>You may prevent and indentation by using `\noindent`.

Table 3: Font Commands and Their Respective Output (default is 10pt)

Command	Output
<code>\tiny</code>	tiny font
<code>\scriptsize</code>	script size font
<code>\footnotesize</code>	footnote size font
<code>\small</code>	small font
<code>\normalsize</code>	normal font
<code>\large</code>	large font
<code>\Large</code>	larger font
<code>\LARGE</code>	even larger font
<code>\huge</code>	huge font
<code>\huge</code>	largest font

```
\begin{center}
```

Text between the beginning and end portion of the command will be centered. Try it with `flushleft` and `flushright`.

```
\end{center}
```

Text between the beginning and end portion of the command will be centered.  
Try it with `flushleft` and `flushright`.

#### 2.4.2 Quote

L<sup>A</sup>T<sub>E</sub>X has a few predefined justification commands, such as `quote`.<sup>2</sup> This will add a block indentation on the left, but remain the font size the same. Below is an example.

```
\begin{quote}
```

The quote environment is best utilized when quoting text that is three lines or more. I have used it to make examples stand out.

```
\end{quote}
```

The quote environment is best utilized when quoting text that is three lines or more. I have used it to make examples stand out.

### 2.5 Bullets and Enumerations

Setting up bulleted or numbered lists are similar to justifications insofar as they are placed between `\begin{argument}` and `\end{argument}`. However, when creating a bulleted list, the *argument* is `itemize`. Each item in the list begins

<sup>2</sup>Similar justifications are covered more extensively in Lecture 3.1.1.

with `\item`. You may customize how a bullet looks by placing a character between square brackets after `item`, such as `item[-]`.

```
\begin{itemize}
\item First item.
\item[-] Second item.
\item[+] Then some more\ldots
\end{itemize}
```

- First item.
- Second item.
- + Then some more...

A similar syntax is used for numbered lists. However, a numerated list is **enumerated**. You can create sub-numbering (or sub-bullets) by creating another list under an item. The following is a large example.

```
\begin{enumerate}
\item First item.
\item Second item.
\begin{enumerate}
\item Sub-item.
\item Another sub-item.
\end{enumerate}
\item Then some more\ldots
\begin{itemize}
\item Bulleted item.
\end{itemize}
\end{enumerate}
\begin{verbatim}
\item First item.
\item Second item.
\begin{enumerate}
\item Sub-item.
\item Another sub-item.
\end{enumerate}
\item Then some more\ldots
\begin{itemize}
\item Bulleted item.
\end{itemize}
\end{verbatim}
```

### 3 Conclusion

A lot of material was covered in this section. Table 1 lists some basic logos that  $\text{\LaTeX}$  has built-in. Likewise, a number of characters that are used by  $\text{\LaTeX}$

can usually be shown in a document by preceding it with a backslash (\)—one notable exception is the backslash which is shown with `\backslash`. Table 2 list some basic formatting commands (e.g. italics, bolding). Table 3 shows the font commands to change the font from the default.

Bulleted and enumerated lists were also introduced. One notable concept was placing text between `\begin` and `\end`. This form of a command will be brought up again in Lecture 3.1 and is very powerful.