Planes and Birds: Minimizing energy

Tao Su

HornorsCalc1 Fall 2024 Project Final



© Targn Pleiades / Shutterstock.com

Figure 1: A flying Bird

November 13, 2024

The Introduction

MALL birds, such as finches, alternate between flapping their wings and gliding, a behavior essential to managing energy during flight. This project focuses on the relationship between a bird's flight speed, the power required, and the average energy consumed, exploring how different speeds impact energy efficiency.

The analysis uses calculus, particularly derivatives, to examine how variations in speed affect both power and energy expenditure. By calculating the rate of change in power requirements with respect to speed, we aim to determine optimal flight conditions that minimize energy use.

This approach draws on principles similar to those for fixed-wing aircraft, where energy and power requirements are essential to understanding flight dynamics. This project applies mathematical analysis to a biological context, using derivatives to derive meaningful insights about energy efficiency in bird flight.

Through this study, we aim to gain a deeper understanding of the mathematical relationships governing flight, which aligns with the course objectives of applying calculus to real-world phenomena and deepening our understanding of energy optimization in dynamic systems.

Part 1:



Figure 2: The trajectory of a flying bird.

The power needed to propel an airplane forward at velocity v is:

$$P = Av^3 + \frac{BL^2}{v}.$$

where A and B are positive constants specific to the particular aircraft, and L is the lift—the upward force supporting the weight of the plane (or bird).

To determine the relationship between the power P and the speed v, we can start with finding the derivative of P' with respect to v.

The derivative of P with respect to v is:

$$P'(v) = 3Av^2 - \frac{BL^2}{v^2}.$$

To find the critical point of P(v), we set P'(v) = 0:

$$P'(v) = 3Av^2 - \frac{BL^2}{v^2} = 0.$$

Solving for v, we get:

$$v^4 = \frac{BL^2}{3A}.$$

Therefore, we can find the speed V as:

$$V = \sqrt[4]{\frac{BL^2}{3A}}.$$

To determine whether this speed represents a minimum or maximum, we test the second derivative:

$$P''(v) = 6Av + \frac{2BL^2}{v^3}.$$

Since A and B are positive constants, and L^2 and v are always positive, we find that:

$$P''(v) = 6Av + \frac{2BL^2}{v^3} > 0.$$

Thus, when P'(v)=0 and P''(v)>0, P concaved up, indicating an absolute minimum. Therefore, when

the speed
$$V$$
 when power p is minimized $V_p = \sqrt[4]{\frac{BL^2}{3A}}$

the required power P is minimized.

Part 2:

The speed found in Part 1 minimizes power, but a faster speed might use less fuel. The energy needed to propel the airplane/bird a unit distance is $E = \frac{P}{v}$. At what speed is energy minimized?

To find out the answer, we first need to know the relationship between E and v.

Fortunately, we know:

$$P = Av^3 + \frac{BL^2}{v}$$
 from the beginning, and $E = \frac{P}{v}$

So, we can easily derive the equation for E(v):

$$E(v) = Av^2 + \frac{BL^2}{v^2}$$

Next, let's take the derivative of E respect to v:

$$E'(v) = 2Av - \frac{2BL^2}{v^3}$$

Same as part 1, we also need to find the critical point of E'(v):

We set
$$E'(v) = 2Av - \frac{2BL^2}{v^3} = 0$$
, solve for $v, v^4 = \frac{2BL^2}{2A}, v = \sqrt[4]{\frac{BL^2}{A}}$.

Then we take the second derivative of E' respect to v:

$$E''(v) = 2A + \frac{6BL^2}{v^4}$$
, because $2A > 0$, and $\frac{6BL^2}{v^4} > 0$, $E''(v) > 0$.

Therefore,

when the speed $V_e = \sqrt[4]{\frac{BL^2}{A}}, E$ has the absolute minimum,

the energy is minimized.

Part 3:

How much faster is the speed for minimum energy than the speed for minimum power?

By observation, we found that both V_p (the speed V when power p is minimized) and V_e (the speed V when energy e is minimized) are 4th root, therefore, we can compare these two value by dividing V_e by V_p :

$$\frac{V_e}{V_p} = \frac{\sqrt[4]{\frac{BL^2}{A}}}{\sqrt[4]{\frac{BL^2}{3A}}} = \sqrt[4]{3}$$

Therefore, we can conclude that, the speed V_e for minimum energy is $\sqrt[4]{3}$ times faster than the speed for minimum power V_p .

Part 4:

In applying the equation of Part 1 to bird flight we split the term Av^3 into two parts: A_bv^3 for the bird's body and A_wv^3 for its wings. Let x be the fraction of flying time spent in flapping mode. If m is the bird's mass and all the lift occurs during flapping, then the lift is $\frac{mg}{x}$ and so the power needed during flapping is:

$$P_{\text{flap}} = (A_b + A_w)v^3 + \frac{B(\frac{mg}{x})^2}{v}$$

The power while wings are folded is $P_{\text{fold}} = A_b v^3$. Show that the average power over an entire flight cycle is:

$$\overline{P} = P_{\text{flap}} + (1 - x)P_{\text{fold}} = A_b v^3 + xA_w v^3 + \frac{Bm^2 g^2}{xv}$$