

# Capstone Data Logistic Regression - Predict Lodgepole Pine

*Tom Thorpe*

*July 25, 2018*

## Objective

Use Logistic regression to predict tree coverage.

```
# Include required libraries.
```

```
library(gsubfn)
```

```
## Loading required package: proto
```

```
library(dplyr)
```

```
##
```

```
## Attaching package: 'dplyr'
```

```
## The following objects are masked from 'package:stats':
```

```
##
```

```
##      filter, lag
```

```
## The following objects are masked from 'package:base':
```

```
##
```

```
##      intersect, setdiff, setequal, union
```

```
library(ggplot2)
```

```
library(ggribes) # for easier viewing of sub-group distributions
```

```
library(ROCR)
```

```
## Loading required package: gplots
```

```
##
```

```
## Attaching package: 'gplots'
```

```
## The following object is masked from 'package:stats':
```

```
##
```

```
##      lowess
```

```
suppressMessages(library(latticeExtra, warn.conflicts = FALSE, quietly=TRUE))
```

```
#library(latticeExtra)
```

```
curTime=Sys.time()
```

```
print(paste("Forest Cover Logistic script started at",curTime))
```

```
## [1] "Forest Cover Logistic script started at 2018-08-12 19:01:57"
```

```
#Point to data. The forestcover_clean_full.csv is the cleaned data to be graphed.
```

```
calcROC <- 1
```

```
saveFileName="ForestCoverLogisticStats.csv"
```

```
infile="C:/Users/Tom/git/datasciencefoundation/ForestCoverage/forestcover_clean_full.csv"
```

```

#infile="C:/Users/Tom/git/datasciencefoundation/ForestCoverage/forestcover_clean.csv"
#infile="C:/Users/Tom/git/datasciencefoundation/ForestCoverage/forestcoversmall_clean_full.csv"
#infile="C:/Users/Tom/git/datasciencefoundation/ForestCoverage/forestcoversmall_clean.csv"
out2file="C:/Users/Tom/git/datasciencefoundation/ForestCoverage/forestcover_graph.csv"
#out1file="C:/Users/Tom/git/datasciencefoundation/ForestCoverage/forestcoversmall_clean_full.csv"
#out2file="C:/Users/Tom/git/datasciencefoundation/ForestCoverage/forestcoversmall_clean.csv"

alphaVal<-0.05 # large data
#alphaVal<-0.1 # small data

forestcover <- read.csv(infile,header=TRUE,sep=",") %>% tbl_df()
curTime=Sys.time()
print(paste("Forest Cover data load completed at",curTime))

## [1] "Forest Cover data load completed at 2018-08-12 19:02:39"

forestcover$SoilType<-as.factor(forestcover$SoilType)
forestcover$ClimateZone<-as.factor(forestcover$ClimateZone)
forestcover$GeoZone<-as.factor(forestcover$GeoZone)

# glimpse(forestcover)

# table(forestcover$Sed_mix)
#knitr::knit_exit()

# Coverage binary outcome Vars:
# Aspen
# Cottonwood_Willow
# DouglasFir
# Krummholz
# LodgepolePine
# PonderosaPine
# Spruce_Fir

```

A table showing the number of occurrences for each tree type is shown below.

```

covCount<-data.frame(table(forestcover$CovName))
totCount<-nrow(forestcover)
covCount <- mutate(covCount,Percent = as.integer(covCount$Freq*1000/totCount)/10)
LodgePct<-covCount$Percent[covCount$Var1=="Lodgepole"]
SpruceAndFirPct<-covCount$Percent[covCount$Var1=="Spruce&Fir"]
LodgeAndSpruceAndFir<-LodgePct+SpruceAndFirPct
#```
#```{r echo=TRUE}
covCount

```

```

##           Var1    Freq Percent
## 1         Aspen   9493      1.6
## 2 Cotton&Willow   2747      0.4
## 3   DouglasFir  17367      2.9
## 4    Krummholz  20510      3.5
## 5   Lodgepole 283301     48.7
## 6   Ponderosa  35754      6.1
## 7   Spruce&Fir 211840     36.4

```

Lodge pole Pine represents 48.7 percent of the sample. So always guessing “Lodge pole” would provide success

rate of 48.7 percent and can be used as a baseline for comparing our predictions. Spruce & Fir represent the next largest number of trees. The two together represent 85.1 percent.

## Logistic Model Accuracy Function

A function to help determine threshold for best accuracy and testing is shown below.

```
source("logisticAccuracy.R") # for calcLogisticModelAccuracy function
bestThreshIndex=11
#save("calcLogisticModelAccuracy", file="logisticAccuracy.Rdata")
```

## Create Training and Testing Sets

Split data into training and testing data for logistic regression. The split is based on cover type so that the different coverage types will be split proportionately for all cover types in the training and test sets.

```
library(caTools)
set.seed(127)
split = sample.split(forestcover$CovType, 0.70) # we want 65% in the training set
forestTrain = subset(forestcover, split == TRUE)
forestTest  = subset(forestcover, split == FALSE)
```

Check training set coverage percentages and compare with test set to ensure there is a representative amount of data in each set for each coverage type.

### View Training Set Coverage Percentages

Check training set coverage percentages.

```
covCount<-data.frame(table(forestTrain$CovName))
totCount<-nrow(forestTrain)
covCount <- mutate(covCount,Percent = as.integer(covCount$Freq*1000/totCount)/10)
covCount
```

##	Var1	Freq	Percent
## 1	Aspen	6645	1.6
## 2	Cotton&Willow	1923	0.4
## 3	DouglasFir	12157	2.9
## 4	Krummholz	14357	3.5
## 5	Lodgepole	198311	48.7
## 6	Ponderosa	25028	6.1
## 7	Spruce&Fir	148288	36.4

### View Test Set Coverage Percentages

Check test set coverage percentages.

```
covCount<-data.frame(table(forestTest$CovName))
totCount<-nrow(forestTest)
covCount <- mutate(covCount,Percent = as.integer(covCount$Freq*1000/totCount)/10)
covCount
```

##	Var1	Freq	Percent
## 1	Aspen	2848	1.6
## 2	Cotton&Willow	824	0.4
## 3	DouglasFir	5210	2.9
## 4	Krummholz	6153	3.5
## 5	Lodgepole	84990	48.7
## 6	Ponderosa	10726	6.1
## 7	Spruce&Fir	63552	36.4

```
# knitr::knit_exit() # exit early

#glimpse(forestTrain)
#glimpse(forestTest)
#summary(forestTrain)
#summary(forestTest)
#table(forestTrain$Sed_mix)
#table(forestTrain$GeoName)
#table(forestTrain$LodgepolePine)
#table(forestTest$LodgepolePine)

# the above all work without error.

#table(forestTest$Rock_Land)
# Get the following error with above code:
# Error in table(SpfFir_test$Rock_Land) : object 'SpfFir_test' not found
# Calls: <Anonymous> ... withCallingHandlers -> withVisible -> eval -> eval -> table

#table(forestTrain$Rock_Land)
#table(forestTest$Rock_Land)
#table(forestTrain$Rubbly)
#table(forestTest$Rubbly)

#table(forestTrain$Sed_mix)
#table(forestTrain$Gateview)
#table(forestTrain$Rubbly)
#table(forestTest$Sed_mix)
#table(forestTest$Gateview)
#table(forestTest$Rubbly)

##### Start Start Start Start Start Start Start Start #####
```

## Lodgepole Pine Logistic Regression

Logistic regression models are created and compared for the Lodgepole Pine coverage type. The outcome is based on the binary 'LodgepolePine' variable.

### Lodgepole Pine Logistic Regression - All Variables

#### Create Lodgepole Pine Logistic Model - All Vars

Create the Lodgepole Pine logistic model for the Aggregated Soil data using all independent variables.

## Lodgepole Pine All Aggregated Soil Types

The original project used aggregated Soil Types. Compute a logistic regression model using the aggregated soil types to see how the dis-aggregated / individuated variables compare.

```
# You can remove the levels of the factor variables using the option exclude:
# lm(dependent ~ factor(independent1, exclude=c('b','d')) + independent2)
# This way the factors b, d will not be included in the regression.

curTime=Sys.time()
print(paste("LodgepolePine aggregated Logistic Model Calculation started at",curTime))

## [1] "LodgepolePine aggregated Logistic Model Calculation started at 2018-08-12 19:02:45"
```

```
Lodge_Agg_LogMod =
  glm(LodgepolePine ~
    Elev +      # Elevation in meters of data cell
    Aspect +    # Direction in degrees slope faces
    Slope +     # Slope / steepness of hill in degrees (0 to 90)
    H2OHD +     # Horizontal distance in meters to nearest water
    H2OVD +     # Vertical distance in meters to nearest water
    RoadHD +    # Horizontal distance in meters to nearest road
    FirePtHD +  # Horizontal distance in meters to nearest fire point
    Shade9AM + Shade12PM + Shade3PM + # Amount of shade at 9am, 12pm and 3pm
    # Wilderness areas:
    RWwild + NEwild + CMwild + CPwild +
    # Aggregated Soil type:
    ST01 + ST02 + ST03 + ST04 + ST05 + ST06 + ST07 + ST08 + ST09 + ST10 +
    ST11 + ST12 + ST13 + ST14 + ST15 + ST16 + ST17 + ST18 + ST19 + ST20 +
    ST21 + ST22 + ST23 + ST24 + ST25 + ST26 + ST27 + ST28 + ST29 + ST30 +
    ST31 + ST32 + ST33 + ST34 + ST35 + ST36 + ST37 + ST38 + ST39 + ST40 ,
    data=forestTrain, family=binomial)

# save model for later use
Lodge_Agg_All_LogMod = Lodge_Agg_LogMod
save("Lodge_Agg_All_LogMod", file="Lodge_Agg_All_LogMod.Rdata")

Lodge_Agg_All_aic<-as.integer(Lodge_Agg_LogMod$aic)
Lodge_Agg_All_aic

## [1] 418219
```

```
curTime=Sys.time()
print(paste("LodgepolePine aggregated Logistic Model Calculation completed at",curTime))
```

```
## [1] "LodgepolePine aggregated Logistic Model Calculation completed at 2018-08-12 19:04:35"
```

Check the coefficients for the Lodgepole Pine model using all aggregated data.

```
summary(Lodge_Agg_LogMod)

##
## Call:
## glm(formula = LodgepolePine ~ Elev + Aspect + Slope + H2OHD +
##     H2OVD + RoadHD + FirePtHD + Shade9AM + Shade12PM + Shade3PM +
##     RWwild + NEwild + CMwild + CPwild + ST01 + ST02 + ST03 +
##     ST04 + ST05 + ST06 + ST07 + ST08 + ST09 + ST10 + ST11 + ST12 +
##     ST13 + ST14 + ST15 + ST16 + ST17 + ST18 + ST19 + ST20 + ST21 +
```

```

##      ST22 + ST23 + ST24 + ST25 + ST26 + ST27 + ST28 + ST29 + ST30 +
##      ST31 + ST32 + ST33 + ST34 + ST35 + ST36 + ST37 + ST38 + ST39 +
##      ST40, family = binomial, data = forestTrain)
##
## Deviance Residuals:
##      Min        1Q      Median        3Q        Max
## -2.9282  -0.8783  -0.0957   0.8612   3.6264
##
## Coefficients: (2 not defined because of singularities)
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)  4.216e+00  2.777e-01  15.182 < 2e-16 ***
## Elev        -5.501e-03  3.050e-05 -180.359 < 2e-16 ***
## Aspect      -3.117e-04  4.641e-05  -6.715 1.88e-11 ***
## Slope        1.541e-02  1.424e-03  10.824 < 2e-16 ***
## H20HD        1.536e-03  2.459e-05  62.482 < 2e-16 ***
## H20VD        4.869e-04  8.996e-05   5.412 6.22e-08 ***
## RoadHD       8.098e-05  3.110e-06  26.037 < 2e-16 ***
## FirePtHD     1.346e-05  3.427e-06   3.929 8.54e-05 ***
## Shade9AM     2.064e-04  1.553e-03   0.133  0.8943
## Shade12PM    2.523e-02  1.280e-03  19.710 < 2e-16 ***
## Shade3PM    -2.880e-03  1.274e-03  -2.260  0.0238 *
## RWwild       4.706e+00  4.000e-02 117.647 < 2e-16 ***
## NEwild       5.203e+00  4.222e-02 123.241 < 2e-16 ***
## CMwild       4.556e+00  3.575e-02 127.427 < 2e-16 ***
## CPwild       NA         NA         NA         NA
## ST01        -1.369e+01  2.891e+01  -0.474  0.6358
## ST02        -2.626e+00  8.598e-02 -30.543 < 2e-16 ***
## ST03        -1.133e+00  8.752e-02 -12.949 < 2e-16 ***
## ST04        -1.535e+00  7.719e-02 -19.888 < 2e-16 ***
## ST05        -1.355e+01  4.002e+01  -0.339  0.7349
## ST06         1.071e+00  9.032e-02  11.853 < 2e-16 ***
## ST07         1.621e+01  1.710e+02   0.095  0.9245
## ST08         1.644e+00  2.078e-01   7.913 2.52e-15 ***
## ST09         1.271e+00  1.240e-01  10.245 < 2e-16 ***
## ST10         7.310e-01  7.428e-02   9.841 < 2e-16 ***
## ST11         1.461e+00  7.579e-02  19.271 < 2e-16 ***
## ST12         2.752e+00  7.469e-02  36.841 < 2e-16 ***
## ST13         2.099e+00  7.390e-02  28.402 < 2e-16 ***
## ST14        -1.566e+01  5.665e+01  -0.276  0.7822
## ST15        -1.338e+01  8.341e+02  -0.016  0.9872
## ST16         1.204e+00  8.780e-02  13.713 < 2e-16 ***
## ST17        -6.423e-01  8.717e-02  -7.368 1.73e-13 ***
## ST18         1.224e+00  1.156e-01  10.585 < 2e-16 ***
## ST19         1.282e+00  8.027e-02  15.976 < 2e-16 ***
## ST20         1.210e+00  7.507e-02  16.123 < 2e-16 ***
## ST21        -1.574e+00  2.807e-01  -5.607 2.06e-08 ***
## ST22         9.140e-01  7.087e-02  12.897 < 2e-16 ***
## ST23         1.243e+00  7.015e-02  17.716 < 2e-16 ***
## ST24         1.854e+00  7.159e-02  25.895 < 2e-16 ***
## ST25         3.098e+00  1.485e-01  20.861 < 2e-16 ***
## ST26         2.525e+00  9.701e-02  26.025 < 2e-16 ***
## ST27         1.505e+00  1.026e-01  14.660 < 2e-16 ***
## ST28         3.350e+00  1.926e-01  17.389 < 2e-16 ***
## ST29         2.000e+00  7.011e-02  28.525 < 2e-16 ***

```

```
## ST30      1.931e+00  7.173e-02  26.921 < 2e-16 ***
## ST31      1.939e+00  7.148e-02  27.121 < 2e-16 ***
## ST32      2.265e+00  7.039e-02  32.177 < 2e-16 ***
## ST33      2.000e+00  7.068e-02  28.297 < 2e-16 ***
## ST34      3.360e+00  1.214e-01  27.677 < 2e-16 ***
## ST35     -1.878e+00  3.853e-01  -4.874 1.09e-06 ***
## ST36      1.729e+00  2.335e-01   7.406 1.30e-13 ***
## ST37     -1.158e+01  9.901e+01  -0.117  0.9069
## ST38     -3.934e-02  8.212e-02  -0.479  0.6319
## ST39     -5.306e-01  9.331e-02  -5.687 1.29e-08 ***
## ST40              NA          NA          NA          NA
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## (Dispersion parameter for binomial family taken to be 1)
##
##      Null deviance: 563568  on 406708  degrees of freedom
## Residual deviance: 418114  on 406656  degrees of freedom
## AIC: 418220
##
## Number of Fisher Scoring iterations: 14
```

WOW! The intercept is huge and listed as not significant. Wilderness area and several soil types are not significant and can be removed in the next iteration.

## Lodgepole Pine All Individuated Soil Types

Create a logistic model using the Individuated variables that were derived from the Soil Types. The Soil Type was the intersection of climate zone, geology zone, soil families, and rock content. These variables are used instead of the Soil types.

```
curTime=Sys.time()
print(paste("LodgepolePine Individual Logistic Model Calculation started at",curTime))

## [1] "LodgepolePine Individual Logistic Model Calculation started at 2018-08-12 19:04:35"
Lodge_Ind_LogMod =
  glm(LodgepolePine ~
    Elev +      # Elevation in meters of cell
    Aspect +    # Direction in degrees slope faces
    Slope +     # Slope / steepness of hill in degrees (0 to 90)
    H2OHD +     # Horizontal distance in meters to nearest water
    H2OVD +     # Vertical distance in meters to nearest water
    RoadHD +    # Horizontal distance in meters to nearest road
    FirePtHD +  # Horizontal distance in meters to nearest fire point
    Shade9AM + Shade12PM + Shade3PM + # Amount of shade at 9am, 12pm and 3pm
    # Wilderness areas:
    RWwild + NEwild + CMwild + CPwild +
    # Climate Zone:
    # ClimateName +
    Montane_low + Montane + SubAlpine + Alpine + Dry + Non_Dry +
    # Geology Zone:
    # GeoName +
    Alluvium + Glacial + Sed_mix + Ign_Meta +
    # Soil Family:
```

```

    Aquolis_cmplx + Argiborolis_Pachic + Borohemists_cmplx + Bross +
    Bullwark + Bullwark_Cmplx + Catamount + Catamount_cmplx +
    Cathedral + Como + Cryaquepts_cmplx + Cryaquepts_Typic + Cryaquolls +
    Cryaquolls_cmplx + Cryaquolls_Typic + Cryaquolls_Typic_cmplx +
    Cryoborolis_cmplx + Cryorthents + Cryorthents_cmplx + Cryumbrepts +
    Cryumbrepts_cmplx + Gateview + Gothic + Granile + Haploborolis +
    Legault + Legault_cmplx + Leighcan + Leighcan_cmplx + Leighcan_warm +
    Moran + Ratake + Ratake_cmplx + Rogert + Supervisor_Limber_cmplx +
    Troutville + Unspecified + Vanet + Wetmore +
    # Soil Rock composition:
    Bouldery_ext + Rock_Land + Rock_Land_cmplx + Rock_Outcrop +
    Rock_Outcrop_cmplx + Rubbly + Stony + Stony_extreme + Stony_very +
    Till_Substratum ,
    data=forestTrain, family=binomial)

## Warning: glm.fit: algorithm did not converge

## Warning: glm.fit: fitted probabilities numerically 0 or 1 occurred

# save model for later use
Lodge_Ind_All_LogMod = Lodge_Ind_LogMod
save("Lodge_Ind_All_LogMod", file="Lodge_Ind_All_LogMod.Rdata")

#table(forestTrain$GeoName)
#table(forestTrain$Sed_mix)
#table(forestTrain$Gateview)
# above: Error in table(SpfFir_test$Gateview) : object 'SpfFir_train' not found <-----

Lodge_Ind_All_aic<-as.integer(Lodge_Ind_LogMod$aic)
Lodge_Ind_All_aic

## [1] 418474

summary(Lodge_Ind_LogMod)

##
## Call:
## glm(formula = LodgepolePine ~ Elev + Aspect + Slope + H2OHD +
##      H2OVD + RoadHD + FirePthd + Shade9AM + Shade12PM + Shade3PM +
##      RWwild + NEwild + CMwild + CPwild + Montane_low + Montane +
##      SubAlpine + Alpine + Dry + Non_Dry + Alluvium + Glacial +
##      Sed_mix + Ign_Meta + Aquolis_cmplx + Argiborolis_Pachic +
##      Borohemists_cmplx + Bross + Bullwark + Bullwark_Cmplx + Catamount +
##      Catamount_cmplx + Cathedral + Como + Cryaquepts_cmplx + Cryaquepts_Typic +
##      Cryaquolls + Cryaquolls_cmplx + Cryaquolls_Typic + Cryaquolls_Typic_cmplx +
##      Cryoborolis_cmplx + Cryorthents + Cryorthents_cmplx + Cryumbrepts +
##      Cryumbrepts_cmplx + Gateview + Gothic + Granile + Haploborolis +
##      Legault + Legault_cmplx + Leighcan + Leighcan_cmplx + Leighcan_warm +
##      Moran + Ratake + Ratake_cmplx + Rogert + Supervisor_Limber_cmplx +
##      Troutville + Unspecified + Vanet + Wetmore + Bouldery_ext +
##      Rock_Land + Rock_Land_cmplx + Rock_Outcrop + Rock_Outcrop_cmplx +
##      Rubbly + Stony + Stony_extreme + Stony_very + Till_Substratum,
##      family = binomial, data = forestTrain)
##
## Deviance Residuals:
##      Min       1Q   Median       3Q      Max

```



```

## -2.9325 -0.8765 -0.0946 0.8602 3.6419
##
## Coefficients: (21 not defined because of singularities)
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)    7.252e+00  3.174e-01  22.846 < 2e-16 ***
## Elev          -5.530e-03  3.062e-05 -180.588 < 2e-16 ***
## Aspect         -3.153e-04  4.644e-05  -6.789 1.13e-11 ***
## Slope          1.553e-02  1.425e-03  10.902 < 2e-16 ***
## H20HD          1.544e-03  2.460e-05  62.767 < 2e-16 ***
## H20VD          4.626e-04  8.975e-05   5.154 2.55e-07 ***
## RoadHD         7.959e-05  3.116e-06  25.546 < 2e-16 ***
## FirePtHD       1.418e-05  3.431e-06   4.131 3.61e-05 ***
## Shade9AM       -4.269e-04  1.551e-03  -0.275 0.783104
## Shade12PM      2.609e-02  1.280e-03  20.385 < 2e-16 ***
## Shade3PM       -3.477e-03  1.273e-03  -2.731 0.006307 **
## RWwild         4.725e+00  3.984e-02 118.596 < 2e-16 ***
## NEwild         5.240e+00  4.199e-02 124.776 < 2e-16 ***
## CMwild         4.567e+00  3.555e-02 128.462 < 2e-16 ***
## CPwild         NA         NA         NA         NA
## Montane_low    2.463e+12  4.698e+11   5.242 1.59e-07 ***
## Montane        2.463e+12  4.698e+11   5.242 1.59e-07 ***
## SubAlpine     -1.001e+00  1.386e-01  -7.218 5.27e-13 ***
## Alpine         -4.366e+00  1.850e-01 -23.605 < 2e-16 ***
## Dry           -2.463e+12  4.698e+11  -5.242 1.59e-07 ***
## Non_Dry       -2.463e+12  4.698e+11  -5.242 1.59e-07 ***
## Alluvium      -3.324e+00  1.669e-01 -19.915 < 2e-16 ***
## Glacial       -9.682e-01  2.577e-02 -37.568 < 2e-16 ***
## Sed_mix        NA         NA         NA         NA
## Ign_Meta       NA         NA         NA         NA
## Aquolis_cmplx  2.463e+12  4.698e+11   5.242 1.59e-07 ***
## Argiborolis_Pachic NA         NA         NA         NA
## Borohemists_cmplx 2.787e+00  2.934e-01   9.500 < 2e-16 ***
## Bross          3.231e+00  2.922e-01  11.055 < 2e-16 ***
## Bullwark       -1.622e+00  1.058e-01 -15.334 < 2e-16 ***
## Bullwark_Cmplx -1.535e-01  1.379e-01  -1.113 0.265524
## Catamount      9.256e-02  8.583e-02   1.078 0.280830
## Catamount_cmplx 6.311e-02  2.433e-02   2.593 0.009503 **
## Cathedral      -1.636e-01  1.139e+04   0.000 0.999989
## Como           5.584e-02  1.039e-01   0.537 0.590994
## Cryaquepts_cmplx -4.540e-01  4.258e-01  -1.066 0.286311
## Cryaquepts_Typic 2.259e+00  2.241e-01  10.081 < 2e-16 ***
## Cryaquolls     3.293e+00  1.493e-01  22.056 < 2e-16 ***
## Cryaquolls_cmplx 1.449e+00  1.309e-01  11.071 < 2e-16 ***
## Cryaquolls_Typic -1.255e-01  3.209e-01  -0.391 0.695669
## Cryaquolls_Typic_cmplx 3.292e-01  2.000e-02  16.463 < 2e-16 ***
## Cryoborolis_cmplx NA         NA         NA         NA
## Cryorthents     6.627e-01  1.617e-01   4.100 4.14e-05 ***
## Cryorthents_cmplx -2.128e+01  2.585e+04  -0.001 0.999343
## Cryumbrepts     NA         NA         NA         NA
## Cryumbrepts_cmplx NA         NA         NA         NA
## Gateview        NA         NA         NA         NA
## Gothic          2.569e+01  4.448e+04   0.001 0.999539
## Granile         5.190e-01  1.225e-01   4.237 2.27e-05 ***
## Haploborolis    2.329e+01  9.203e+03   0.003 0.997981

```

```
## Legault -2.430e-01 1.407e-01 -1.728 0.084043 .
## Legault_cmplx NA NA NA NA
## Leighcan -6.315e-02 1.010e-01 -0.625 0.531940
## Leighcan_cmplx 2.328e-01 1.314e-01 1.771 0.076487 .
## Leighcan_warm -1.219e-02 1.332e-01 -0.092 0.927070
## Moran NA NA NA NA
## Ratake 2.289e+01 9.203e+03 0.002 0.998015
## Ratake_cmplx 2.183e+01 9.203e+03 0.002 0.998107
## Rogert NA NA NA NA
## Supervisor_Limber_cmplx NA NA NA NA
## Troutville NA NA NA NA
## Unspecified 2.463e+12 4.698e+11 5.242 1.59e-07 ***
## Vanet NA NA NA NA
## Wetmore 2.551e+01 9.203e+03 0.003 0.997789
## Bouldery_ext NA NA NA NA
## Rock_Land -7.086e-02 1.827e-02 -3.879 0.000105 ***
## Rock_Land_cmplx 7.600e-01 9.157e-02 8.299 < 2e-16 ***
## Rock_Outcrop NA NA NA NA
## Rock_Outcrop_cmplx 2.921e-02 8.560e-02 0.341 0.732946
## Rubbly NA NA NA NA
## Stony NA NA NA NA
## Stony_extreme NA NA NA NA
## Stony_very NA NA NA NA
## Till_Substratum NA NA NA NA
```

```
## ---
```

```
## Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
```

```
##
```

```
## (Dispersion parameter for binomial family taken to be 1)
```

```
##
```

```
## Null deviance: 563568 on 406708 degrees of freedom
```

```
## Residual deviance: 418369 on 406656 degrees of freedom
```

```
## AIC: 418475
```

```
##
```

```
## Number of Fisher Scoring iterations: 25
```

```
curTime=Sys.time()
```

```
print(paste("LodgepolePine Individual Logistic Model Calculation completed at",curTime))
```

```
## [1] "LodgepolePine Individual Logistic Model Calculation completed at 2018-08-12 19:09:48"
```

```
#table(forestTest$Rock_Land)
```

```
# Get the following error with above code:
```

```
# Error in table(SpfFir_test$Rock_Land) : object 'SpfFir_test' not found
```

```
# Calls: <Anonymous> ... withCallingHandlers -> withVisible -> eval -> eval -> table
```

## Predict Lodgepole Pine Logistic Model Probabilities - All Aggregated Vars

### Lodgepole Pine Probabilities - All Aggregated Data

Predict the probability of Lodgepole Pine for aggregated Data - all variables.

```
# Predict Lodgepole Pine Agg Data - all variables
```

```
Lodge_Agg_Train_predict= predict(Lodge_Agg_LogMod, type="response")
```

```
Lodge_Agg_Train_Logit= predict(Lodge_Agg_LogMod)
```

```
summary(Lodge_Agg_Train_predict)

##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
## 0.0000 0.2595 0.5047 0.4876 0.7231 1.0000

str(Lodge_Agg_Train_predict)

## Named num [1:406709] 0.935 0.935 0.942 0.926 0.95 ...
## - attr(*, "names")= chr [1:406709] "1" "2" "3" "4" ...

#plot(table(Lodge_Agg_Train_predict))
#plot(table(Lodge_Agg_Train_Logit))
dens<-data.frame(table(Lodge_Agg_Train_predict))
# str(dens)

Lodge_Agg_Test_predict= predict(Lodge_Agg_LogMod, type="response",newdata=forestTest)

## Warning in predict.lm(object, newdata, se.fit, scale = 1, type =
## ifelse(type == : prediction from a rank-deficient fit may be misleading

summary(Lodge_Agg_Test_predict)

##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
## 0.0000 0.2602 0.5038 0.4874 0.7231 1.0000

str(Lodge_Agg_Test_predict)

## Named num [1:174303] 0.903 0.919 0.883 0.908 0.883 ...
## - attr(*, "names")= chr [1:174303] "1" "2" "3" "4" ...
```

## Lodgepole Pine Probabilities - All Individuated Data

Predict the probability of Lodgepole Pine for Individual Data - all variables.

```
Lodge_Ind_Train_predict= predict(Lodge_Ind_LogMod, type="response")
summary(Lodge_Ind_Train_predict)

##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
## 0.0000 0.2581 0.5045 0.4876 0.7239 1.0000

Lodge_Ind_Test_predict= predict(Lodge_Ind_LogMod, type="response",newdata=forestTest)

## Warning in predict.lm(object, newdata, se.fit, scale = 1, type =
## ifelse(type == : prediction from a rank-deficient fit may be misleading

summary(Lodge_Ind_Test_predict)

##      Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
## 0.0000 0.2585 0.5034 0.4874 0.7236 1.0000
```

## Lodgepole Pine Receiver Operating Characteristic (ROC) - All Vars

### Lodgepole Pine Receiver ROC - All Aggregated Data

Next, look at the True Positive and False Positive rates based on threshold value for the aggregated data.

```
if (calcROC) {
  curTime=Sys.time()
  print(paste("ROC graph 1 started at",curTime))
}
```

```

ROCpred_Lodge_Agg = prediction(Lodge_Agg_Train_predict, forestTrain$LodgepolePine)
summary(ROCpred_Lodge_Agg)
ROCperf_Lodge_Agg = performance(ROCpred_Lodge_Agg, "tpr", "fpr")
summary(ROCperf_Lodge_Agg)

Lodge_Agg_All_ROC_AUC = as.numeric(performance(ROCpred_Lodge_Agg, "auc")@y.values)
Lodge_Agg_All_ROC_AUC=as.integer(as.numeric(Lodge_Agg_All_ROC_AUC)*1000)/10
print(paste("Lodge_Agg_All_ROC_AUC=",Lodge_Agg_All_ROC_AUC))

jpeg(filename="Fig-ROCR_perf_Lodge_Agg.jpg")
plot(ROCperf_Lodge_Agg, colorize=TRUE, print.cutoffs.at=seq(0,1,0.1), text.adj=c(-0.2,1.7))
dev.off()
} else {
  Lodge_Agg_All_ROC_AUC = 84.2
}

## [1] "ROC graph 1 started at 2018-08-12 19:09:53"
## [1] "Lodge_Agg_All_ROC_AUC= 82.6"

## pdf
## 2

```

### Lodgepole Pine Receiver ROC - All Individuated Data

The Response Operating Curve for the individuated data is shown below.

```

if (calcROC) {
  curTime=Sys.time()
  print(paste("ROCR graph 2 started at",curTime))

  ROCpred_Lodge_Ind = prediction(Lodge_Ind_Train_predict, forestTrain$LodgepolePine)
  summary(ROCpred_Lodge_Ind)
  ROCperf_Lodge_Ind = performance(ROCpred_Lodge_Ind, "tpr", "fpr")
  summary(ROCperf_Lodge_Ind)

  Lodge_Ind_All_ROC_AUC = as.numeric(performance(ROCpred_Lodge_Ind, "auc")@y.values)
  Lodge_Ind_All_ROC_AUC=as.integer(as.numeric(Lodge_Ind_All_ROC_AUC)*1000)/10
  print(paste("Lodge_Ind_All_ROC_AUC=",Lodge_Ind_All_ROC_AUC))

  jpeg(filename="Fig-ROCR_perf_Lodge_Ind.jpg")
  plot(ROCperf_Lodge_Ind, colorize=TRUE, print.cutoffs.at=seq(0,1,0.1), text.adj=c(-0.2,1.7))
  dev.off()
} else {
  Lodge_Ind_All_ROC_AUC = 84.2
}

## [1] "ROCR graph 2 started at 2018-08-12 19:12:54"
## [1] "Lodge_Ind_All_ROC_AUC= 82.6"

## pdf
## 2

```

The threshold graphs are essentially identical. This is making me think that there is not much difference between the two models. The AIC score for the Soil Type model is AIC: 351676 and for the individuated variables is: AIC: 351839. The Soil type model AIC score is 0.046% better than the individuated model.




Figure 1: Lodgepole Pine ROC for All Aggregated Data




Figure 2: Lodgepole Pine ROC for All Individuated Data

```
curTime=Sys.time()
print(paste("ROCR graph 2 completed at",curTime))
```

```
## [1] "ROCR graph 2 completed at 2018-08-12 19:15:35"
```

## Calculate Accuracy of Lodgepole Pine Logistic Models - All Vars

### Calculate Lodgepole Pine Aggregated Data Logistic Model Accuracy - All Vars

Find best threshold for Lodgepole Pine using all aggregated data.

```
result = calcLogisticModelAccuracy (forestTrain$LodgepolePine, Lodge_Agg_Train_predict,
                                   0.0, 1, 10, "Lodgepole", "Other", 1,1)
```

```
## [1] "Searching for threshold producing best Sensitivity_Specificity"
## [1] "start= 0 end= 1 inc= 0.1"
## [1] "Thresh=0, Accuracy=48.7%, BaseAcc(Other)=51.2%, Sens=100%, Spec=0%, Sens^2+Spec^2=-2"
## [1] "Thresh=0.1, Accuracy=59.4%, BaseAcc(Other)=51.2%, Sens=98.3%, Spec=22.3%, Sens^2+Spec^2=1.016"
## [1] "Thresh=0.2, Accuracy=64.6%, BaseAcc(Other)=51.2%, Sens=96%, Spec=34.8%, Sens^2+Spec^2=1.043"
## [1] "Thresh=0.3, Accuracy=69.7%, BaseAcc(Other)=51.2%, Sens=91.9%, Spec=48.5%, Sens^2+Spec^2=1.081"
## [1] "Thresh=0.4, Accuracy=73.6%, BaseAcc(Other)=51.2%, Sens=85.7%, Spec=62.2%, Sens^2+Spec^2=1.121"
## [1] "Thresh=0.5, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=76.7%, Spec=74.4%, Sens^2+Spec^2=1.143"
## [1] "Thresh=0.6, Accuracy=74%, BaseAcc(Other)=51.2%, Sens=63.8%, Spec=83.8%, Sens^2+Spec^2=1.109"
## [1] "Thresh=0.7, Accuracy=69.4%, BaseAcc(Other)=51.2%, Sens=46.9%, Spec=90.7%, Sens^2+Spec^2=1.044"
## [1] "Thresh=0.8, Accuracy=63%, BaseAcc(Other)=51.2%, Sens=28.7%, Spec=95.7%, Sens^2+Spec^2=0.999"
## [1] "Thresh=0.9, Accuracy=55.9%, BaseAcc(Other)=51.2%, Sens=10.5%, Spec=99%, Sens^2+Spec^2=0.992"
## [1] "Thresh=1, Accuracy=51.2%, BaseAcc(Other)=51.2%, Sens=0%, Spec=100%, Sens^2+Spec^2=-2"
## [1] "Best Sensitivity_Specificity threshold= 0.5 inc= 0.1"
## [1] "=====
## [1] "start= 0.4 end= 0.6 inc= 0.01"
## [1] "Thresh=0.4, Accuracy=73.6%, BaseAcc(Other)=51.2%, Sens=85.7%, Spec=62.2%, Sens^2+Spec^2=1.121"
## [1] "Thresh=0.41, Accuracy=73.9%, BaseAcc(Other)=51.2%, Sens=84.9%, Spec=63.5%, Sens^2+Spec^2=1.125"
## [1] "Thresh=0.42, Accuracy=74.2%, BaseAcc(Other)=51.2%, Sens=84.1%, Spec=64.8%, Sens^2+Spec^2=1.129"
## [1] "Thresh=0.43, Accuracy=74.5%, BaseAcc(Other)=51.2%, Sens=83.3%, Spec=66.1%, Sens^2+Spec^2=1.133"
## [1] "Thresh=0.44, Accuracy=74.8%, BaseAcc(Other)=51.2%, Sens=82.5%, Spec=67.4%, Sens^2+Spec^2=1.136"
## [1] "Thresh=0.45, Accuracy=75%, BaseAcc(Other)=51.2%, Sens=81.7%, Spec=68.6%, Sens^2+Spec^2=1.139"
## [1] "Thresh=0.46, Accuracy=75.2%, BaseAcc(Other)=51.2%, Sens=80.8%, Spec=69.8%, Sens^2+Spec^2=1.141"
## [1] "Thresh=0.47, Accuracy=75.3%, BaseAcc(Other)=51.2%, Sens=79.9%, Spec=71.1%, Sens^2+Spec^2=1.144"
## [1] "Thresh=0.48, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=78.9%, Spec=72.2%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.49, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=77.8%, Spec=73.3%, Sens^2+Spec^2=1.144"
## [1] "Thresh=0.5, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=76.7%, Spec=74.4%, Sens^2+Spec^2=1.143"
## [1] "Thresh=0.51, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=75.6%, Spec=75.5%, Sens^2+Spec^2=1.141"
## [1] "Thresh=0.52, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=74.4%, Spec=76.5%, Sens^2+Spec^2=1.139"
## [1] "Thresh=0.53, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=73.2%, Spec=77.5%, Sens^2+Spec^2=1.138"
## [1] "Thresh=0.54, Accuracy=75.3%, BaseAcc(Other)=51.2%, Sens=72%, Spec=78.5%, Sens^2+Spec^2=1.135"
## [1] "Thresh=0.55, Accuracy=75.2%, BaseAcc(Other)=51.2%, Sens=70.7%, Spec=79.5%, Sens^2+Spec^2=1.133"
## [1] "Thresh=0.56, Accuracy=75%, BaseAcc(Other)=51.2%, Sens=69.4%, Spec=80.3%, Sens^2+Spec^2=1.129"
## [1] "Thresh=0.57, Accuracy=74.8%, BaseAcc(Other)=51.2%, Sens=68.1%, Spec=81.2%, Sens^2+Spec^2=1.124"
## [1] "Thresh=0.58, Accuracy=74.6%, BaseAcc(Other)=51.2%, Sens=66.7%, Spec=82.1%, Sens^2+Spec^2=1.12"
## [1] "Thresh=0.59, Accuracy=74.3%, BaseAcc(Other)=51.2%, Sens=65.2%, Spec=82.9%, Sens^2+Spec^2=1.114"
## [1] "Best Sensitivity_Specificity threshold= 0.48 inc= 0.01"
## [1] "=====
## [1] "start= 0.47 end= 0.49 inc= 0.001"
## [1] "Thresh=0.47, Accuracy=75.3%, BaseAcc(Other)=51.2%, Sens=79.9%, Spec=71.1%, Sens^2+Spec^2=1.144"
```

```
## [1] "Thresh=0.471, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=79.8%, Spec=71.2%, Sens^2+Spec^2=1.144"
## [1] "Thresh=0.472, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=79.7%, Spec=71.3%, Sens^2+Spec^2=1.144"
## [1] "Thresh=0.473, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=79.6%, Spec=71.4%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.474, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=79.5%, Spec=71.6%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.475, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=79.4%, Spec=71.7%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.476, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=79.3%, Spec=71.8%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.477, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=79.2%, Spec=71.9%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.478, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=79.1%, Spec=72%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.479, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=79%, Spec=72.1%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.48, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=78.9%, Spec=72.2%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.481, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=78.8%, Spec=72.3%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.482, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=78.6%, Spec=72.5%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.483, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=78.5%, Spec=72.6%, Sens^2+Spec^2=1.144"
## [1] "Thresh=0.484, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=78.4%, Spec=72.7%, Sens^2+Spec^2=1.144"
## [1] "Thresh=0.485, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=78.3%, Spec=72.8%, Sens^2+Spec^2=1.144"
## [1] "Thresh=0.486, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=78.2%, Spec=72.9%, Sens^2+Spec^2=1.144"
## [1] "Thresh=0.487, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=78.1%, Spec=73%, Sens^2+Spec^2=1.144"
## [1] "Thresh=0.488, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=78%, Spec=73.1%, Sens^2+Spec^2=1.144"
## [1] "Thresh=0.489, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=77.9%, Spec=73.2%, Sens^2+Spec^2=1.144"
## [1] "Thresh=0.49, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=77.8%, Spec=73.3%, Sens^2+Spec^2=1.144"
## [1] "=====
## [1] "Best Threshold=0.476"
## [1] "Best Sensitivity_Specificity=1.14567294963844"

curThresh = as.numeric(result[bestThreshIndex])
Lodge_Agg_All_threshold = curThresh
```

The accuracy for the best threshold on the training set for Lodgepole Pine using all aggregated data is shown below.

```
result = calcLogisticModelAccuracy (forestTrain$LodgepolePine, Lodge_Agg_Train_predict,
                                     curThresh, curThresh, 1, "Lodgepole", "Other", 3)

## [1] "Model Performance for threshold= 0.476"
## [1] "predicted performance="
##                                     Predicted
## Actual      FALSE=Predict:Other TRUE=Predict:Lodgepole
## 0=Actual:Other      149739 (TN)      58659 (FP)
## 1=Actual:Lodgepole  40982 (FN)      157329 (TP)
## [1] "Sensitivity= 0.793344796809052 (True positive rate of Lodgepole = TP/(TP+FN) = 157329 /( 157329 + 40982) = 0.793344796809052)"
## [1] "Specificity= 0.718524170097602 (True negative rate of Other = TN/(TN+FP) = 149739 /( 149739 + 58659) = 0.718524170097602)"
## [1] "Sens^2+Spec^2=1.145"
## [1] "Baseline (Other) Accuracy=0.5124"
## [1] "Logistic Accuracy=0.755006"
```

The accuracy for the best threshold on the testing set for Lodgepole Pine using all aggregated data is shown below.

```
result = calcLogisticModelAccuracy (forestTest$LodgepolePine, Lodge_Agg_Test_predict,
                                     curThresh, curThresh, 1, "Lodgepole", "Other", 3,
                                     saveFile=saveFileName, desc="Lodgepole All Aggregate Vars",
                                     AIC=Lodge_Agg_All_aic, AUC=Lodge_Agg_All_ROC_AUC)

## [1] "Model Performance for threshold= 0.476"
## [1] "predicted performance="
##                                     Predicted
## Actual      FALSE=Predict:Other TRUE=Predict:Lodgepole
```



```
## 0=Actual:Other          64287 (TN)          25026 (FP)
## 1=Actual:Lodgepole     17512 (FN)          67478 (TP)
## [1] "Sensitivity= 0.793952229674079 (True positive rate of Lodgepole = TP/(TP+FN) = 67478 /( 67478 +
## [1] "Specificity= 0.719794430821941 (True negative rate of Other = TN/(TN+FP) = 64287 /( 64287 + 250
## [1] "Sens^2+Spec^2=1.148"
## [1] "Baseline (Other) Accuracy=0.5124"
## [1] "Logistic Accuracy=0.755953"

# retVal = c(modelPerformance, sensitivity, specificity) # TN, FN, FP, TP, sens, spec
# c(funcStat, accuracy, baseline, retVal)
list[RC, Lodge_Agg_All_model_acc, Lodge_Agg_All_baseline_acc,
      TN, FN, FP, TP, Lodge_Agg_All_sens, Lodge_Agg_All_spec] <- result
if (RC != "OK") {
  print(paste("Error - terminating:", RC))
  knitr::knit_exit()
}
Lodge_Agg_All_model_acc = as.integer(as.numeric(Lodge_Agg_All_model_acc)*1000)/10
Lodge_Agg_All_baseline_acc = as.integer(as.numeric(Lodge_Agg_All_baseline_acc)*1000)/10
Lodge_Agg_All_sens = as.integer(as.numeric(Lodge_Agg_All_sens)*1000)/10
Lodge_Agg_All_spec = as.integer(as.numeric(Lodge_Agg_All_spec)*1000)/10
```

## Calculate Lodgepole Pine Individuated Data Logistic Model Accuracy - All Vars

Find best threshold for Lodgepole Pine using all individuated data.

```
result = calcLogisticModelAccuracy (forestTrain$LodgepolePine, Lodge_Ind_Train_predict,
                                     0.0, 1, 10, "Lodgepole", "Other", 1,1)
```

```
## [1] "Searching for threshold producing best Sensitivity_Specificity"
## [1] "start= 0 end= 1 inc= 0.1"
## [1] "Thresh=0, Accuracy=48.7%, BaseAcc(Other)=51.2%, Sens=100%, Spec=0%, Sens^2+Spec^2=-2"
## [1] "Thresh=0.1, Accuracy=59.4%, BaseAcc(Other)=51.2%, Sens=98.3%, Spec=22.3%, Sens^2+Spec^2=1.016"
## [1] "Thresh=0.2, Accuracy=64.7%, BaseAcc(Other)=51.2%, Sens=95.9%, Spec=35%, Sens^2+Spec^2=1.043"
## [1] "Thresh=0.3, Accuracy=69.7%, BaseAcc(Other)=51.2%, Sens=91.9%, Spec=48.6%, Sens^2+Spec^2=1.081"
## [1] "Thresh=0.4, Accuracy=73.7%, BaseAcc(Other)=51.2%, Sens=85.7%, Spec=62.3%, Sens^2+Spec^2=1.122"
## [1] "Thresh=0.5, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=76.7%, Spec=74.4%, Sens^2+Spec^2=1.143"
## [1] "Thresh=0.6, Accuracy=74%, BaseAcc(Other)=51.2%, Sens=63.8%, Spec=83.8%, Sens^2+Spec^2=1.109"
## [1] "Thresh=0.7, Accuracy=69.4%, BaseAcc(Other)=51.2%, Sens=47%, Spec=90.7%, Sens^2+Spec^2=1.044"
## [1] "Thresh=0.8, Accuracy=63.1%, BaseAcc(Other)=51.2%, Sens=28.9%, Spec=95.6%, Sens^2+Spec^2=0.998"
## [1] "Thresh=0.9, Accuracy=56%, BaseAcc(Other)=51.2%, Sens=10.9%, Spec=98.9%, Sens^2+Spec^2=0.991"
## [1] "Thresh=1, Accuracy=51.2%, BaseAcc(Other)=51.2%, Sens=0%, Spec=100%, Sens^2+Spec^2=-2"
## [1] "Best Sensitivity_Specificity threshold= 0.5 inc= 0.1"
## [1] "=====
## [1] "start= 0.4 end= 0.6 inc= 0.01"
## [1] "Thresh=0.4, Accuracy=73.7%, BaseAcc(Other)=51.2%, Sens=85.7%, Spec=62.3%, Sens^2+Spec^2=1.122"
## [1] "Thresh=0.41, Accuracy=74%, BaseAcc(Other)=51.2%, Sens=84.9%, Spec=63.6%, Sens^2+Spec^2=1.126"
## [1] "Thresh=0.42, Accuracy=74.3%, BaseAcc(Other)=51.2%, Sens=84.1%, Spec=64.9%, Sens^2+Spec^2=1.13"
## [1] "Thresh=0.43, Accuracy=74.6%, BaseAcc(Other)=51.2%, Sens=83.3%, Spec=66.2%, Sens^2+Spec^2=1.134"
## [1] "Thresh=0.44, Accuracy=74.8%, BaseAcc(Other)=51.2%, Sens=82.5%, Spec=67.5%, Sens^2+Spec^2=1.137"
## [1] "Thresh=0.45, Accuracy=75%, BaseAcc(Other)=51.2%, Sens=81.7%, Spec=68.7%, Sens^2+Spec^2=1.14"
## [1] "Thresh=0.46, Accuracy=75.2%, BaseAcc(Other)=51.2%, Sens=80.7%, Spec=69.9%, Sens^2+Spec^2=1.142"
## [1] "Thresh=0.47, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=79.8%, Spec=71.1%, Sens^2+Spec^2=1.144"
## [1] "Thresh=0.48, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=78.8%, Spec=72.3%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.49, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=77.8%, Spec=73.4%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.5, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=76.7%, Spec=74.4%, Sens^2+Spec^2=1.143"
```

```
## [1] "Thresh=0.51, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=75.5%, Spec=75.5%, Sens^2+Spec^2=1.141"
## [1] "Thresh=0.52, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=74.3%, Spec=76.5%, Sens^2+Spec^2=1.139"
## [1] "Thresh=0.53, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=73.2%, Spec=77.5%, Sens^2+Spec^2=1.137"
## [1] "Thresh=0.54, Accuracy=75.3%, BaseAcc(Other)=51.2%, Sens=72%, Spec=78.5%, Sens^2+Spec^2=1.135"
## [1] "Thresh=0.55, Accuracy=75.2%, BaseAcc(Other)=51.2%, Sens=70.7%, Spec=79.5%, Sens^2+Spec^2=1.132"
## [1] "Thresh=0.56, Accuracy=75%, BaseAcc(Other)=51.2%, Sens=69.4%, Spec=80.3%, Sens^2+Spec^2=1.128"
## [1] "Thresh=0.57, Accuracy=74.8%, BaseAcc(Other)=51.2%, Sens=68.1%, Spec=81.2%, Sens^2+Spec^2=1.125"
## [1] "Thresh=0.58, Accuracy=74.6%, BaseAcc(Other)=51.2%, Sens=66.7%, Spec=82.1%, Sens^2+Spec^2=1.119"
## [1] "Thresh=0.59, Accuracy=74.3%, BaseAcc(Other)=51.2%, Sens=65.2%, Spec=82.9%, Sens^2+Spec^2=1.114"
## [1] "Best Sensitivity_Specificity threshold= 0.48 inc= 0.01"
## [1] "=====
## [1] "start= 0.47 end= 0.49 inc= 0.001"
## [1] "Thresh=0.47, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=79.8%, Spec=71.1%, Sens^2+Spec^2=1.144"
## [1] "Thresh=0.471, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=79.7%, Spec=71.3%, Sens^2+Spec^2=1.144"
## [1] "Thresh=0.472, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=79.6%, Spec=71.4%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.473, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=79.5%, Spec=71.5%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.474, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=79.4%, Spec=71.6%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.475, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=79.3%, Spec=71.7%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.476, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=79.2%, Spec=71.8%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.477, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=79.1%, Spec=72%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.478, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=79%, Spec=72.1%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.479, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=78.9%, Spec=72.2%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.48, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=78.8%, Spec=72.3%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.481, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=78.7%, Spec=72.4%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.482, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=78.6%, Spec=72.5%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.483, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=78.5%, Spec=72.6%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.484, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=78.4%, Spec=72.7%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.485, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=78.3%, Spec=72.9%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.486, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=78.2%, Spec=73%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.487, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=78.1%, Spec=73.1%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.488, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=78%, Spec=73.2%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.489, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=77.9%, Spec=73.3%, Sens^2+Spec^2=1.145"
## [1] "Thresh=0.49, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=77.8%, Spec=73.4%, Sens^2+Spec^2=1.145"
## [1] "=====
## [1] "Best Threshold=0.481"
## [1] "Best Sensitivity_Specificity=1.14556823166058"

curThresh = as.numeric(result[bestThreshIndex])
Lodge_Ind_All_threshold = curThresh
```

The accuracy for the best threshold on the training set for Lodgepole Pine using all individuated data is shown below.

```
result = calcLogisticModelAccuracy (forestTrain$LodgepolePine, Lodge_Ind_Train_predict,
                                     curThresh, curThresh, 1, "Lodgepole", "Other", 3)
```

```
## [1] "Model Performance for threshold= 0.481"
## [1] "predicted performance="
##                                     Predicted
## Actual      FALSE=Predict:Other TRUE=Predict:Lodgepole
## 0=Actual:Other      151027 (TN)          57371 (FP)
## 1=Actual:Lodgepole  42114 (FN)          156197 (TP)
## [1] "Sensitivity= 0.787636591011089 (True positive rate of Lodgepole = TP/(TP+FN) = 156197 /( 156197 + 42114) = 0.787636591011089"
## [1] "Specificity= 0.72470465167612 (True negative rate of Other = TN/(TN+FP) = 151027 /( 151027 + 57371) = 0.72470465167612"
## [1] "Sens^2+Spec^2=1.145"
```

```
## [1] "Baseline (Other) Accuracy=0.5124"
## [1] "Logistic Accuracy=0.75539"
```

The accuracy for the best threshold on the testing set for Lodgepole Pine using all individuated data is shown below.

```
result = calcLogisticModelAccuracy (forestTest$LodgepolePine, Lodge_Ind_Test_predict,
                                     curThresh, curThresh, 1, "Lodgepole", "Other", 3,
                                     saveFile=saveFileName, desc="Lodgepole All Individualized Vars",
                                     AIC=Lodge_Ind_All_aic, AUC=Lodge_Ind_All_ROC_AUC)
```

```
## [1] "Model Performance for threshold= 0.481"
## [1] "predicted performance="
##                                     Predicted
## Actual                               FALSE=Predict:Other TRUE=Predict:Lodgepole
## 0=Actual:Other                      64882 (TN)                24431 (FP)
## 1=Actual:Lodgepole                  17944 (FN)                67046 (TP)
## [1] "Sensitivity= 0.788869278738675 (True positive rate of Lodgepole = TP/(TP+FN) = 67046 /( 67046 +
## [1] "Specificity= 0.726456394925711 (True negative rate of Other = TN/(TN+FP) = 64882 /( 64882 + 244
## [1] "Sens^2+Spec^2=1.15"
## [1] "Baseline (Other) Accuracy=0.5124"
## [1] "Logistic Accuracy=0.756888"
```

```
list[RC, Lodge_Ind_All_model_acc, Lodge_Ind_All_baseline_acc,
      TN, FN, FP, TP, Lodge_Ind_All_sens, Lodge_Ind_All_spec] <- result
if (RC != "OK") {
  print(paste("Error - terminating:",RC))
  knitr::knit_exit()
}
Lodge_Ind_All_model_acc = as.integer(as.numeric(Lodge_Ind_All_model_acc)*1000)/10
Lodge_Ind_All_baseline_acc = as.integer(as.numeric(Lodge_Ind_All_baseline_acc)*1000)/10
Lodge_Ind_All_sens = as.integer(as.numeric(Lodge_Ind_All_sens)*1000)/10
Lodge_Ind_All_spec = as.integer(as.numeric(Lodge_Ind_All_spec)*1000)/10
```

The Lodgepole Pine aggregated model accuracy on the test data is 77.15% compared to 77.12% for the individuated data model, essentially identical. Both are ~ 14% better than the baseline model.

## Lodgepole Pine Logistic Regression - Significant Variables

### Create Lodgepole Pine Logistic Model - Sig Vars

Now create the logistic model for the Aggregated Soil data using just the significant variables and compare to the previous models.

### Lodgepole Pine Logistic Model using Significant Aggregated Data

Variables that have been removed are commented out in the code below.

```
Lodge_Agg_LogMod =
  glm(LodgepolePine ~
      Elev +      # Elevation in meters of cell
      Aspect +    # Direction in degrees slope faces
      Slope +     # Slope / steepness of hill in degrees (0 to 90)
      H20HD +     # Horizontal distance in meters to nearest water
      H20VD +     # Vertical distance in meters to nearest water
```

```

RoadHD + # Horizontal distance in meters to nearest road
FirePtHD + # Horizontal distance in meters to nearest fire point
# Shade9AM +
Shade12PM + Shade3PM + # Amount of shade at 9am, 12pm and 3pm
# Wilderness areas:
  RWwild + NEwild + CMwild +
  # CPwild +
# Aggregated Soil type:
  # ST01 +
  ST02 + ST03 + ST04 +
  # ST05 +
  ST06 +
  # ST07 +
  ST08 + ST09 + ST10 + ST11 + ST12 + ST13 +
  # ST14 + ST15 +
  ST16 +
  # ST17 + # removed 2nd pass
  ST18 + ST19 + ST20 +
  ST21 + ST22 + ST23 + ST24 + ST25 + ST26 + ST27 + ST28 + ST29 + ST30 +
  ST31 + ST32 + ST33 +
  ST34 + ST35 +
  ST36
  # ST37 + ST38 +
  # ST39 # removed 2nd pass
  # + ST40
,
data=forestTrain, family=binomial)

# save model for later use
Lodge_Agg_Sig_LogMod = Lodge_Agg_LogMod
save("Lodge_Agg_Sig_LogMod", file="Lodge_Agg_Sig_LogMod.Rdata")

Lodge_Agg_Sig_aic<-as.integer(Lodge_Agg_LogMod$aic)
Lodge_Agg_Sig_aic

```

```
## [1] 419472
```

Check the coefficients of the Lodgepole Pine model using significant aggregated data.

```
summary(Lodge_Agg_LogMod)
```

```

##
## Call:
## glm(formula = LodgepolePine ~ Elev + Aspect + Slope + H2OHD +
##      H2OVD + RoadHD + FirePtHD + Shade12PM + Shade3PM + RWwild +
##      NEwild + CMwild + ST02 + ST03 + ST04 + ST06 + ST08 + ST09 +
##      ST10 + ST11 + ST12 + ST13 + ST16 + ST18 + ST19 + ST20 + ST21 +
##      ST22 + ST23 + ST24 + ST25 + ST26 + ST27 + ST28 + ST29 + ST30 +
##      ST31 + ST32 + ST33 + ST34 + ST35 + ST36, family = binomial,
##      data = forestTrain)
##
## Deviance Residuals:
##      Min       1Q   Median       3Q      Max
## -2.9057  -0.8850  -0.1397   0.8644   3.6729
##

```

```

## Coefficients:
##           Estimate Std. Error z value Pr(>|z|)
## (Intercept)  3.097e+00  9.637e-02  32.136 < 2e-16 ***
## Elev        -5.309e-03  2.877e-05 -184.562 < 2e-16 ***
## Aspect      -2.867e-04  4.624e-05  -6.201 5.61e-10 ***
## Slope        1.410e-02  7.705e-04  18.294 < 2e-16 ***
## H20HD        1.518e-03  2.455e-05  61.826 < 2e-16 ***
## H20VD        4.717e-04  8.983e-05   5.252 1.51e-07 ***
## RoadHD       7.861e-05  3.098e-06  25.370 < 2e-16 ***
## FirePtHD     1.652e-05  3.418e-06   4.833 1.34e-06 ***
## Shade12PM    2.461e-02  3.249e-04  75.743 < 2e-16 ***
## Shade3PM    -2.869e-03  1.636e-04 -17.540 < 2e-16 ***
## RWwild       4.924e+00  3.940e-02 124.987 < 2e-16 ***
## NEwild       5.376e+00  4.192e-02 128.255 < 2e-16 ***
## CMwild       4.723e+00  3.528e-02 133.879 < 2e-16 ***
## ST02        -1.950e+00  5.470e-02 -35.656 < 2e-16 ***
## ST03        -4.212e-01  5.708e-02  -7.378 1.60e-13 ***
## ST04        -8.647e-01  4.002e-02 -21.604 < 2e-16 ***
## ST06         1.942e+00  5.880e-02  33.036 < 2e-16 ***
## ST08         2.181e+00  1.977e-01  11.030 < 2e-16 ***
## ST09         1.873e+00  1.058e-01  17.708 < 2e-16 ***
## ST10         1.441e+00  3.377e-02  42.669 < 2e-16 ***
## ST11         2.092e+00  3.862e-02  54.174 < 2e-16 ***
## ST12         3.302e+00  3.897e-02  84.745 < 2e-16 ***
## ST13         2.704e+00  3.626e-02  74.569 < 2e-16 ***
## ST16         1.779e+00  6.004e-02  29.630 < 2e-16 ***
## ST18         1.820e+00  9.554e-02  19.052 < 2e-16 ***
## ST19         1.810e+00  4.931e-02  36.712 < 2e-16 ***
## ST20         1.766e+00  3.931e-02  44.936 < 2e-16 ***
## ST21        -1.005e+00  2.732e-01  -3.680 0.000233 ***
## ST22         1.439e+00  3.264e-02  44.077 < 2e-16 ***
## ST23         1.782e+00  3.011e-02  59.176 < 2e-16 ***
## ST24         2.410e+00  3.313e-02  72.741 < 2e-16 ***
## ST25         3.633e+00  1.346e-01  26.982 < 2e-16 ***
## ST26         3.123e+00  7.219e-02  43.266 < 2e-16 ***
## ST27         2.069e+00  8.084e-02  25.596 < 2e-16 ***
## ST28         3.965e+00  1.814e-01  21.856 < 2e-16 ***
## ST29         2.522e+00  3.084e-02  81.779 < 2e-16 ***
## ST30         2.468e+00  3.401e-02  72.555 < 2e-16 ***
## ST31         2.505e+00  3.230e-02  77.549 < 2e-16 ***
## ST32         2.822e+00  3.022e-02  93.365 < 2e-16 ***
## ST33         2.573e+00  3.070e-02  83.820 < 2e-16 ***
## ST34         3.931e+00  1.030e-01  38.159 < 2e-16 ***
## ST35        -1.389e+00  3.800e-01  -3.655 0.000257 ***
## ST36         2.270e+00  2.249e-01  10.095 < 2e-16 ***
## ---
## Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## (Dispersion parameter for binomial family taken to be 1)
##
## Null deviance: 563568 on 406708 degrees of freedom
## Residual deviance: 419386 on 406666 degrees of freedom
## AIC: 419472
##

```

```
## Number of Fisher Scoring iterations: 7
```

The intercept looks much more reasonable. Some soil types that were significant previously are no longer significant.

## Lodgepole Pine Logistic Model using Significant Individuated Data

Create a logistic model for the significant individuated variables.

Again, the non-significant variables have been commented out.

```
Lodge_Ind_LogMod =  
  glm(LodgepolePine ~  
    Elev +      # Elevation in meters of cell  
    Aspect +    # Direction in degrees slope faces  
    Slope +     # Slope / steepness of hill in degrees (0 to 90)  
    H20HD +     # Horizontal distance in meters to nearest water  
    H20VD +     # Vertical distance in meters to nearest water  
    RoadHD +    # Horizontal distance in meters to nearest road  
    FirePtHD +  # Horizontal distance in meters to nearest fire point  
    # Shade9AM +  
    Shade12PM + Shade3PM + # Amount of shade at 9am, 12pm and 3pm  
    # Wilderness areas:  
    RWwild + NEwild + CMwild +  
    # CPwild +  
    # Climate Zone:  
    # Montane_low + Montane + # removed 2nd pass  
    SubAlpine + Alpine +  
    # Dry + Non_Dry + # removed 2nd pass  
    # Geology Zone:  
    Alluvium + Glacial +  
    # Sed_mix + Ign_Meta +  
    # Soil Family:  
    # Aquolis_cmplx + # removed 2nd pass  
    # Argiborolis_Pachic +  
    Borohemists_cmplx + Bross +  
    Bullwark +  
    # Bullwark_cmplx + Catamount +  
    Catamount_cmplx +  
    # Cathedral + Como +  
    # Cryaquepts_cmplx +  
    Cryaquepts_Typic + Cryaquolls +  
    Cryaquolls_cmplx +  
    # Cryaquolls_Typic +  
    Cryaquolls_Typic_cmplx +  
    # Cryoborolis_cmplx +  
    Cryorthents +  
    # Cryorthents_cmplx + Cryumbrepts + Cryumbrepts_cmplx + Gateview +  
    # Gothic +  
    Granile +  
    # Haploborolis +  
    # Legault +  
    # Legault_cmplx +  
    # Leighcan + Leighcan_cmplx + Leighcan_warm +  
    # Moran + Ratake + Ratake_cmplx + Rogert + Supervisor_Limber_cmplx +
```

```

# Troutville +
# Unspecified + # removed 2nd pass
# Vanet + Wetmore +
# Soil Rock composition:
# Bouldery_ext +
Rock_Land +
Rock_Land_cmplx
# Rock_Outcrop +
# Rock_Outcrop_cmplx +
# Rubbly + Stony + Stony_extreme + Stony_very + Till_Substratum ,
,
data=forestTrain, family=binomial)

# save model for later use
Lodge_Ind_Sig_LogMod = Lodge_Ind_LogMod
save("Lodge_Ind_Sig_LogMod", file="Lodge_Ind_Sig_LogMod.Rdata")

Lodge_Ind_Sig_aic<-as.integer(Lodge_Ind_LogMod$aic)
Lodge_Ind_Sig_aic

```

```
## [1] 438293
```

```
summary(Lodge_Ind_LogMod)
```

```

##
## Call:
## glm(formula = LodgepolePine ~ Elev + Aspect + Slope + H2OHD +
##      H2OVD + RoadHD + FirePtHD + Shade12PM + Shade3PM + RWild +
##      NEwild + CMwild + SubAlpine + Alpine + Alluvium + Glacial +
##      Borohemists_cmplx + Bross + Bullwark + Catamount_cmplx +
##      Cryaquepts_Typic + Cryaquolls + Cryaquolls_cmplx + Cryaquolls_Typic_cmplx +
##      Cryorthents + Granile + Rock_Land + Rock_Land_cmplx, family = binomial,
##      data = forestTrain)
##
## Deviance Residuals:
##      Min       1Q   Median       3Q      Max
## -2.8705  -0.9464  -0.1260   0.9295   3.2157
##
## Coefficients:
##              Estimate Std. Error z value Pr(>|z|)
## (Intercept)    3.102e+00  8.628e-02  35.954 < 2e-16 ***
## Elev          -4.362e-03  2.755e-05 -158.365 < 2e-16 ***
## Aspect        -3.301e-04  4.489e-05  -7.353 1.94e-13 ***
## Slope          6.554e-03  7.043e-04   9.305 < 2e-16 ***
## H2OHD          1.395e-03  2.376e-05  58.685 < 2e-16 ***
## H2OVD          3.602e-04  8.604e-05   4.186 2.84e-05 ***
## RoadHD         6.468e-05  3.037e-06  21.297 < 2e-16 ***
## FirePtHD       3.638e-05  3.295e-06  11.042 < 2e-16 ***
## Shade12PM      1.784e-02  3.005e-04  59.356 < 2e-16 ***
## Shade3PM      -4.397e-04  1.545e-04  -2.845 0.004441 **
## RWild          4.207e+00  3.045e-02 138.141 < 2e-16 ***
## NEwild         4.576e+00  3.565e-02 128.329 < 2e-16 ***
## CMwild         4.077e+00  2.861e-02 142.531 < 2e-16 ***
## SubAlpine      1.611e+00  1.759e-02  91.593 < 2e-16 ***

```



```
## Alpine -1.834e+00 9.785e-02 -18.746 < 2e-16 ***
## Alluvium -3.456e+00 1.047e-01 -33.018 < 2e-16 ***
## Glacial -1.002e+00 1.662e-02 -60.268 < 2e-16 ***
## Borohemists_cmplx 2.762e+00 1.121e-01 24.645 < 2e-16 ***
## Bross 2.234e+00 2.430e-01 9.191 < 2e-16 ***
## Bullwark 3.751e-01 2.012e-02 18.638 < 2e-16 ***
## Catamount_cmplx -6.020e-02 1.717e-02 -3.505 0.000456 ***
## Cryaquepts_Typic 2.559e+00 1.094e-01 23.387 < 2e-16 ***
## Cryaquolls 2.900e+00 1.162e-01 24.962 < 2e-16 ***
## Cryaquolls_cmplx 1.229e+00 9.962e-02 12.342 < 2e-16 ***
## Cryaquolls_Typic_cmplx 2.794e-01 1.897e-02 14.732 < 2e-16 ***
## Cryorthents -3.036e-01 9.258e-02 -3.280 0.001039 **
## Granile 8.062e-01 6.796e-02 11.864 < 2e-16 ***
## Rock_Land 8.842e-01 1.554e-02 56.897 < 2e-16 ***
## Rock_Land_cmplx 2.002e+00 2.229e-02 89.795 < 2e-16 ***
## ---
## Signif. codes: 0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1
##
## (Dispersion parameter for binomial family taken to be 1)
##
## Null deviance: 563568 on 406708 degrees of freedom
## Residual deviance: 438235 on 406680 degrees of freedom
## AIC: 438293
##
## Number of Fisher Scoring iterations: 6
```

Again the intercept looks much better. Also a few variables have become non-significant.

## Predict Lodgepole Pine Logistic Model Probabilities - Sig Vars

### Lodgepole Pine Probabilities using Significant Aggregated Data

Predict the probability of Lodgepole Pine for aggregated Data - significant variables.

```
# Predict Lodgepole Pine Agg Data - significant variables
```

```
Lodge_Agg_Train_predict= predict(Lodge_Agg_LogMod, type="response")
summary(Lodge_Agg_Train_predict)
```

```
##      Min.   1st Qu.   Median     Mean  3rd Qu.     Max.
## 0.001177 0.262623 0.507043 0.487599 0.720227 0.989996
```

```
Lodge_Agg_Test_predict= predict(Lodge_Agg_LogMod, type="response",newdata=forestTest)
summary(Lodge_Agg_Test_predict)
```

```
##      Min.   1st Qu.   Median     Mean  3rd Qu.     Max.
## 0.001063 0.263705 0.506269 0.487505 0.720219 0.989542
```

### Lodgepole Pine Probabilities using Significant Individuated Data

Predict the probability of Lodgepole Pine using significant Individuated Data.

```
Lodge_Ind_Train_predict= predict(Lodge_Ind_LogMod, type="response")
summary(Lodge_Ind_Train_predict)
```

```
##      Min.   1st Qu.   Median     Mean  3rd Qu.     Max.
```



```
## 0.0006416 0.3008665 0.5067524 0.4875992 0.6901729 0.9837541

Lodge_Ind_Test_predict= predict(Lodge_Ind_LogMod, type="response",newdata=forestTest)
summary(Lodge_Ind_Test_predict)

##      Min.    1st Qu.      Median        Mean     3rd Qu.        Max.
## 0.0006601 0.3014278 0.5062873 0.4876456 0.6904649 0.9832762

print(paste("ROCR graph 2 completed at",curTime))

## [1] "ROCR graph 2 completed at 2018-08-12 19:15:35"
```

## Lodgepole Pine Receiver Operating Characteristic (ROC) - Sig Vars

Look at the True Positive and False Positive rates based on threshold value.

```
if (calcROC) {
  ROCpred_Lodge_Agg = prediction(Lodge_Agg_Train_predict, forestTrain$LodgepolePine)
  summary(ROCpred_Lodge_Agg)

  ROCperf_Lodge_Agg = performance(ROCpred_Lodge_Agg, "tpr", "fpr")
  summary(ROCperf_Lodge_Agg)

  Lodge_Agg_Sig_ROC_AUC = as.numeric(performance(ROCpred_Lodge_Agg, "auc")@y.values)
  Lodge_Agg_Sig_ROC_AUC=as.integer(as.numeric(Lodge_Agg_Sig_ROC_AUC)*1000)/10
  Lodge_Agg_Sig_ROC_AUC

  jpeg(filename="Fig-ROCR_perf_Lodge_Agg_Sig.jpg")
  plot(ROCperf_Lodge_Agg, colorize=TRUE, print.cutoffs.at=seq(0,1,0.1), text.adj=c(-0.2,1.7))
  dev.off()
} else {
  Lodge_Agg_Sig_ROC_AUC = 83.7
}

## pdf
## 2

if (calcROC) {
  curTime=Sys.time()
  print(paste("ROCR graph 2 started at",curTime))

  ROCpred_Lodge_Ind = prediction(Lodge_Ind_Train_predict, forestTrain$LodgepolePine)
  summary(ROCpred_Lodge_Ind)

  ROCperf_Lodge_Ind = performance(ROCpred_Lodge_Ind, "tpr", "fpr")
  summary(ROCperf_Lodge_Ind)

  Lodge_Ind_Sig_ROC_AUC = as.numeric(performance(ROCpred_Lodge_Ind, "auc")@y.values)
  Lodge_Ind_Sig_ROC_AUC=as.integer(as.numeric(Lodge_Ind_Sig_ROC_AUC)*1000)/10
  Lodge_Ind_Sig_ROC_AUC

  jpeg(filename="Fig-ROC_perf_Lodge_Ind_Sig.jpg")
  plot(ROCperf_Lodge_Ind, colorize=TRUE, print.cutoffs.at=seq(0,1,0.1), text.adj=c(-0.2,1.7))
  dev.off()
} else {
```




Figure 3: Lodgepole Pine ROC for Aggregated Significant Data

```
Lodge_Ind_Sig_ROC_AUC = 83.8
}
```

```
## [1] "ROCR graph 2 started at 2018-08-12 19:20:56"
```

```
## pdf
## 2
```

The threshold graphs are essentially identical. This is making me think that there is not much difference between the two models. The AIC score for the Soil Type model is AIC: 351676 and for the individuated variables is: AIC: 351839. The Soil type model AIC score is 0.046% better than the individuated model.

## Calculate Accuracy of Lodgepole Pine Logistic Model - Sig Vars

### Calculate Lodgepole Pine Aggregated Data Logistic Model Accuracy - Significant Vars

Find best Lodgepole Pine threshold for Aggregated Data using significant variables.

```
result = calcLogisticModelAccuracy (forestTrain$LodgepolePine, Lodge_Agg_Train_predict,
                                     0.0, 1, 10, "Lodgepole", "Other", 1,1)
```

```
## [1] "Searching for threshold producing best Sensitivity_Specificity"
## [1] "start= 0 end= 1 inc= 0.1"
## [1] "Thresh=0, Accuracy=48.7%, BaseAcc(Other)=51.2%, Sens=100%, Spec=0%, Sens^2+Spec^2=-2"
## [1] "Thresh=0.1, Accuracy=59.5%, BaseAcc(Other)=51.2%, Sens=98.2%, Spec=22.7%, Sens^2+Spec^2=1.017"
## [1] "Thresh=0.2, Accuracy=64.5%, BaseAcc(Other)=51.2%, Sens=96.1%, Spec=34.4%, Sens^2+Spec^2=1.043"
## [1] "Thresh=0.3, Accuracy=69.5%, BaseAcc(Other)=51.2%, Sens=92.1%, Spec=47.9%, Sens^2+Spec^2=1.078"
## [1] "Thresh=0.4, Accuracy=73.4%, BaseAcc(Other)=51.2%, Sens=85.9%, Spec=61.6%, Sens^2+Spec^2=1.118"
## [1] "Thresh=0.5, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=77%, Spec=74.1%, Sens^2+Spec^2=1.142"
## [1] "Thresh=0.6, Accuracy=74%, BaseAcc(Other)=51.2%, Sens=63.8%, Spec=83.7%, Sens^2+Spec^2=1.109"
## [1] "Thresh=0.7, Accuracy=69.2%, BaseAcc(Other)=51.2%, Sens=46.5%, Spec=90.8%, Sens^2+Spec^2=1.041"
## [1] "Thresh=0.8, Accuracy=62.7%, BaseAcc(Other)=51.2%, Sens=27.9%, Spec=95.8%, Sens^2+Spec^2=0.997"
## [1] "Thresh=0.9, Accuracy=55.6%, BaseAcc(Other)=51.2%, Sens=10.1%, Spec=99%, Sens^2+Spec^2=0.991"
## [1] "Thresh=1, Accuracy=51.2%, BaseAcc(Other)=51.2%, Sens=0%, Spec=100%, Sens^2+Spec^2=-2"
## [1] "Best Sensitivity_Specificity threshold= 0.5 inc= 0.1"
## [1] "=====
## [1] "start= 0.4 end= 0.6 inc= 0.01"
## [1] "Thresh=0.4, Accuracy=73.4%, BaseAcc(Other)=51.2%, Sens=85.9%, Spec=61.6%, Sens^2+Spec^2=1.118"
## [1] "Thresh=0.41, Accuracy=73.8%, BaseAcc(Other)=51.2%, Sens=85.2%, Spec=62.9%, Sens^2+Spec^2=1.122"
## [1] "Thresh=0.42, Accuracy=74.1%, BaseAcc(Other)=51.2%, Sens=84.4%, Spec=64.3%, Sens^2+Spec^2=1.126"
## [1] "Thresh=0.43, Accuracy=74.4%, BaseAcc(Other)=51.2%, Sens=83.6%, Spec=65.6%, Sens^2+Spec^2=1.131"
## [1] "Thresh=0.44, Accuracy=74.7%, BaseAcc(Other)=51.2%, Sens=82.8%, Spec=66.9%, Sens^2+Spec^2=1.135"
## [1] "Thresh=0.45, Accuracy=74.9%, BaseAcc(Other)=51.2%, Sens=82%, Spec=68.1%, Sens^2+Spec^2=1.137"
## [1] "Thresh=0.46, Accuracy=75.1%, BaseAcc(Other)=51.2%, Sens=81.1%, Spec=69.4%, Sens^2+Spec^2=1.139"
## [1] "Thresh=0.47, Accuracy=75.2%, BaseAcc(Other)=51.2%, Sens=80.1%, Spec=70.6%, Sens^2+Spec^2=1.141"
## [1] "Thresh=0.48, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=79.1%, Spec=71.8%, Sens^2+Spec^2=1.143"
## [1] "Thresh=0.49, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=78%, Spec=73%, Sens^2+Spec^2=1.143"
## [1] "Thresh=0.5, Accuracy=75.5%, BaseAcc(Other)=51.2%, Sens=77%, Spec=74.1%, Sens^2+Spec^2=1.142"
## [1] "Thresh=0.51, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=75.7%, Spec=75.2%, Sens^2+Spec^2=1.14"
## [1] "Thresh=0.52, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=74.5%, Spec=76.3%, Sens^2+Spec^2=1.138"
## [1] "Thresh=0.53, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=73.3%, Spec=77.3%, Sens^2+Spec^2=1.136"
## [1] "Thresh=0.54, Accuracy=75.3%, BaseAcc(Other)=51.2%, Sens=72.1%, Spec=78.3%, Sens^2+Spec^2=1.134"
## [1] "Thresh=0.55, Accuracy=75.2%, BaseAcc(Other)=51.2%, Sens=70.8%, Spec=79.3%, Sens^2+Spec^2=1.131"
## [1] "Thresh=0.56, Accuracy=75%, BaseAcc(Other)=51.2%, Sens=69.5%, Spec=80.2%, Sens^2+Spec^2=1.128"
## [1] "Thresh=0.57, Accuracy=74.8%, BaseAcc(Other)=51.2%, Sens=68.2%, Spec=81.1%, Sens^2+Spec^2=1.124"
```




Figure 4: Lodgepole Pine ROC for Individuated Significant Data

```
## [1] "Thresh=0.58, Accuracy=74.5%, BaseAcc(Other)=51.2%, Sens=66.7%, Spec=82%, Sens^2+Spec^2=1.118"
## [1] "Thresh=0.59, Accuracy=74.3%, BaseAcc(Other)=51.2%, Sens=65.2%, Spec=82.8%, Sens^2+Spec^2=1.113"
## [1] "Best Sensitivity_Specificity threshold= 0.48 inc= 0.01"
## [1] "=====
## [1] "start= 0.47 end= 0.49 inc= 0.001"
## [1] "Thresh=0.47, Accuracy=75.2%, BaseAcc(Other)=51.2%, Sens=80.1%, Spec=70.6%, Sens^2+Spec^2=1.141"
## [1] "Thresh=0.471, Accuracy=75.3%, BaseAcc(Other)=51.2%, Sens=80%, Spec=70.7%, Sens^2+Spec^2=1.141"
## [1] "Thresh=0.472, Accuracy=75.3%, BaseAcc(Other)=51.2%, Sens=79.9%, Spec=70.9%, Sens^2+Spec^2=1.142"
## [1] "Thresh=0.473, Accuracy=75.3%, BaseAcc(Other)=51.2%, Sens=79.8%, Spec=71%, Sens^2+Spec^2=1.142"
## [1] "Thresh=0.474, Accuracy=75.3%, BaseAcc(Other)=51.2%, Sens=79.7%, Spec=71.1%, Sens^2+Spec^2=1.142"
## [1] "Thresh=0.475, Accuracy=75.3%, BaseAcc(Other)=51.2%, Sens=79.6%, Spec=71.2%, Sens^2+Spec^2=1.142"
## [1] "Thresh=0.476, Accuracy=75.3%, BaseAcc(Other)=51.2%, Sens=79.5%, Spec=71.3%, Sens^2+Spec^2=1.143"
## [1] "Thresh=0.477, Accuracy=75.3%, BaseAcc(Other)=51.2%, Sens=79.4%, Spec=71.5%, Sens^2+Spec^2=1.143"
## [1] "Thresh=0.478, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=79.3%, Spec=71.6%, Sens^2+Spec^2=1.143"
## [1] "Thresh=0.479, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=79.2%, Spec=71.7%, Sens^2+Spec^2=1.143"
## [1] "Thresh=0.48, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=79.1%, Spec=71.8%, Sens^2+Spec^2=1.143"
## [1] "Thresh=0.481, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=79%, Spec=72%, Sens^2+Spec^2=1.143"
## [1] "Thresh=0.482, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=78.9%, Spec=72.1%, Sens^2+Spec^2=1.143"
## [1] "Thresh=0.483, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=78.8%, Spec=72.2%, Sens^2+Spec^2=1.143"
## [1] "Thresh=0.484, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=78.7%, Spec=72.3%, Sens^2+Spec^2=1.143"
## [1] "Thresh=0.485, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=78.6%, Spec=72.4%, Sens^2+Spec^2=1.143"
## [1] "Thresh=0.486, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=78.5%, Spec=72.5%, Sens^2+Spec^2=1.143"
## [1] "Thresh=0.487, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=78.4%, Spec=72.6%, Sens^2+Spec^2=1.143"
## [1] "Thresh=0.488, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=78.3%, Spec=72.8%, Sens^2+Spec^2=1.143"
## [1] "Thresh=0.489, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=78.1%, Spec=72.9%, Sens^2+Spec^2=1.143"
## [1] "Thresh=0.49, Accuracy=75.4%, BaseAcc(Other)=51.2%, Sens=78%, Spec=73%, Sens^2+Spec^2=1.143"
## [1] "=====
## [1] "Best Threshold=0.482"
## [1] "Best Sensitivity_Specificity=1.14365324448173"

curThresh = as.numeric(result[bestThreshIndex])
Lodge_Agg_Sig_threshold = curThresh
```

The accuracy for the best threshold on the training set for Lodgepole Pine using significant aggregated data is shown below.

```
result = calcLogisticModelAccuracy (forestTrain$LodgepolePine, Lodge_Agg_Train_predict,
                                     curThresh, curThresh, 1, "Lodgepole", "Other", 3)
```

```
## [1] "Model Performance for threshold= 0.482"
## [1] "predicted performance="
##                                     Predicted
## Actual      FALSE=Predict:Other TRUE=Predict:Lodgepole
## 0=Actual:Other      150312 (TN)      58086 (FP)
## 1=Actual:Lodgepole  41731 (FN)      156580 (TP)
## [1] "Sensitivity= 0.789567900923297 (True positive rate of Lodgepole = TP/(TP+FN) = 156580 / ( 156580 + 41731) = 0.789567900923297)"
## [1] "Specificity= 0.721273716638355 (True negative rate of Other = TN/(TN+FP) = 150312 / ( 150312 + 58086) = 0.721273716638355)"
## [1] "Sens^2+Spec^2=1.143"
## [1] "Baseline (Other) Accuracy=0.5124"
## [1] "Logistic Accuracy=0.754573"
```

The accuracy for the best threshold on the testing set for Lodgepole Pine using significant aggregated data is shown below.

```
result = calcLogisticModelAccuracy (forestTest$LodgepolePine, Lodge_Agg_Test_predict,
                                     curThresh, curThresh, 1, "Lodgepole", "Other", 3,
```

```

saveFile=saveFileName, desc="Lodgepole Sig Aggregate Vars",
AIC=Lodge_Agg_Sig_aic, AUC=Lodge_Agg_Sig_ROC_AUC)

## [1] "Model Performance for threshold= 0.482"
## [1] "predicted performance="
##
## Predicted
## Actual FALSE=Predict:Other TRUE=Predict:Lodgepole
## 0=Actual:Other 64522 (TN) 24791 (FP)
## 1=Actual:Lodgepole 17844 (FN) 67146 (TP)
## [1] "Sensitivity= 0.7900458877515 (True positive rate of Lodgepole = TP/(TP+FN) = 67146 / ( 67146 + 17844 )"
## [1] "Specificity= 0.722425626728472 (True negative rate of Other = TN/(TN+FP) = 64522 / ( 64522 + 24791 )"
## [1] "Sens^2+Spec^2=1.146"
## [1] "Baseline (Other) Accuracy=0.5124"
## [1] "Logistic Accuracy=0.755397"

list(RC, Lodge_Agg_Sig_model_acc, Lodge_Agg_Sig_baseline_acc,
TN, FN, FP, TP, Lodge_Agg_Sig_sens, Lodge_Agg_Sig_spec) <- result
if (RC != "OK") {
  print(paste("Error - terminating:",RC))
  knitr::knit_exit()
}
Lodge_Agg_Sig_model_acc = as.integer(as.numeric(Lodge_Agg_Sig_model_acc)*1000)/10
Lodge_Agg_Sig_baseline_acc = as.integer(as.numeric(Lodge_Agg_Sig_baseline_acc)*1000)/10
Lodge_Agg_Sig_sens = as.integer(as.numeric(Lodge_Agg_Sig_sens)*1000)/10
Lodge_Agg_Sig_spec = as.integer(as.numeric(Lodge_Agg_Sig_spec)*1000)/10

```

## Calculate Lodgepole Pine Individuated Data Logistic Model Accuracy - Significant Vars

Find best Lodgepole Pine threshold for Individuated Data using significant variables.

```

result = calcLogisticModelAccuracy (forestTrain$LodgepolePine, Lodge_Ind_Train_predict,
0.0, 1, 10, "Lodgepole", "Other", 1,1)

```

```

## [1] "Searching for threshold producing best Sensitivity_Specificity"
## [1] "start= 0 end= 1 inc= 0.1"
## [1] "Thresh=0, Accuracy=48.7%, BaseAcc(Other)=51.2%, Sens=100%, Spec=0%, Sens^2+Spec^2=-2"
## [1] "Thresh=0.1, Accuracy=59%, BaseAcc(Other)=51.2%, Sens=98.5%, Spec=21.4%, Sens^2+Spec^2=1.016"
## [1] "Thresh=0.2, Accuracy=63.1%, BaseAcc(Other)=51.2%, Sens=97.6%, Spec=30.3%, Sens^2+Spec^2=1.045"
## [1] "Thresh=0.3, Accuracy=67.7%, BaseAcc(Other)=51.2%, Sens=93.9%, Spec=42.8%, Sens^2+Spec^2=1.066"
## [1] "Thresh=0.4, Accuracy=71%, BaseAcc(Other)=51.2%, Sens=86.1%, Spec=56.7%, Sens^2+Spec^2=1.064"
## [1] "Thresh=0.5, Accuracy=72.5%, BaseAcc(Other)=51.2%, Sens=74.1%, Spec=70.9%, Sens^2+Spec^2=1.053"
## [1] "Thresh=0.6, Accuracy=70.6%, BaseAcc(Other)=51.2%, Sens=57.2%, Spec=83.3%, Sens^2+Spec^2=1.022"
## [1] "Thresh=0.7, Accuracy=66.3%, BaseAcc(Other)=51.2%, Sens=39.9%, Spec=91.5%, Sens^2+Spec^2=0.996"
## [1] "Thresh=0.8, Accuracy=61.1%, BaseAcc(Other)=51.2%, Sens=24%, Spec=96.3%, Sens^2+Spec^2=0.986"
## [1] "Thresh=0.9, Accuracy=53.7%, BaseAcc(Other)=51.2%, Sens=6.1%, Spec=98.9%, Sens^2+Spec^2=0.983"
## [1] "Thresh=1, Accuracy=51.2%, BaseAcc(Other)=51.2%, Sens=0%, Spec=100%, Sens^2+Spec^2=-2"
## [1] "Best Sensitivity_Specificity threshold= 0.3 inc= 0.1"
## [1] "=====
## [1] "start= 0.2 end= 0.4 inc= 0.01"
## [1] "Thresh=0.2, Accuracy=63.1%, BaseAcc(Other)=51.2%, Sens=97.6%, Spec=30.3%, Sens^2+Spec^2=1.045"
## [1] "Thresh=0.21, Accuracy=63.6%, BaseAcc(Other)=51.2%, Sens=97.4%, Spec=31.4%, Sens^2+Spec^2=1.048"
## [1] "Thresh=0.22, Accuracy=64.1%, BaseAcc(Other)=51.2%, Sens=97.1%, Spec=32.6%, Sens^2+Spec^2=1.051"
## [1] "Thresh=0.23, Accuracy=64.6%, BaseAcc(Other)=51.2%, Sens=96.9%, Spec=33.8%, Sens^2+Spec^2=1.054"
## [1] "Thresh=0.24, Accuracy=65.1%, BaseAcc(Other)=51.2%, Sens=96.6%, Spec=35.1%, Sens^2+Spec^2=1.058"
## [1] "Thresh=0.25, Accuracy=65.6%, BaseAcc(Other)=51.2%, Sens=96.3%, Spec=36.4%, Sens^2+Spec^2=1.061"

```



```
## [1] "Thresh=0.26, Accuracy=66.1%, BaseAcc(Other)=51.2%, Sens=95.9%, Spec=37.8%, Sens^2+Spec^2=1.064"
## [1] "Thresh=0.27, Accuracy=66.5%, BaseAcc(Other)=51.2%, Sens=95.5%, Spec=39%, Sens^2+Spec^2=1.065"
## [1] "Thresh=0.28, Accuracy=66.9%, BaseAcc(Other)=51.2%, Sens=95%, Spec=40.2%, Sens^2+Spec^2=1.066"
## [1] "Thresh=0.29, Accuracy=67.3%, BaseAcc(Other)=51.2%, Sens=94.5%, Spec=41.5%, Sens^2+Spec^2=1.066"
## [1] "Thresh=0.3, Accuracy=67.7%, BaseAcc(Other)=51.2%, Sens=93.9%, Spec=42.8%, Sens^2+Spec^2=1.066"
## [1] "Thresh=0.31, Accuracy=68.1%, BaseAcc(Other)=51.2%, Sens=93.3%, Spec=44.1%, Sens^2+Spec^2=1.066"
## [1] "Thresh=0.32, Accuracy=68.5%, BaseAcc(Other)=51.2%, Sens=92.7%, Spec=45.5%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.33, Accuracy=68.9%, BaseAcc(Other)=51.2%, Sens=92.1%, Spec=46.9%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.34, Accuracy=69.3%, BaseAcc(Other)=51.2%, Sens=91.3%, Spec=48.3%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.35, Accuracy=69.6%, BaseAcc(Other)=51.2%, Sens=90.6%, Spec=49.7%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.36, Accuracy=69.9%, BaseAcc(Other)=51.2%, Sens=89.7%, Spec=51%, Sens^2+Spec^2=1.067"
## [1] "Thresh=0.37, Accuracy=70.2%, BaseAcc(Other)=51.2%, Sens=88.9%, Spec=52.4%, Sens^2+Spec^2=1.066"
## [1] "Thresh=0.38, Accuracy=70.5%, BaseAcc(Other)=51.2%, Sens=88%, Spec=53.7%, Sens^2+Spec^2=1.065"
## [1] "Thresh=0.39, Accuracy=70.7%, BaseAcc(Other)=51.2%, Sens=87.1%, Spec=55.1%, Sens^2+Spec^2=1.063"
## [1] "Best Sensitivity_Specificity threshold= 0.34 inc= 0.01"
## [1] "=====
## [1] "start= 0.33 end= 0.35 inc= 0.001"
## [1] "Thresh=0.33, Accuracy=68.9%, BaseAcc(Other)=51.2%, Sens=92.1%, Spec=46.9%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.331, Accuracy=68.9%, BaseAcc(Other)=51.2%, Sens=92%, Spec=47%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.332, Accuracy=69%, BaseAcc(Other)=51.2%, Sens=91.9%, Spec=47.2%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.333, Accuracy=69%, BaseAcc(Other)=51.2%, Sens=91.8%, Spec=47.3%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.334, Accuracy=69.1%, BaseAcc(Other)=51.2%, Sens=91.8%, Spec=47.5%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.335, Accuracy=69.1%, BaseAcc(Other)=51.2%, Sens=91.7%, Spec=47.6%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.336, Accuracy=69.1%, BaseAcc(Other)=51.2%, Sens=91.6%, Spec=47.7%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.337, Accuracy=69.2%, BaseAcc(Other)=51.2%, Sens=91.6%, Spec=47.9%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.338, Accuracy=69.2%, BaseAcc(Other)=51.2%, Sens=91.5%, Spec=48%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.339, Accuracy=69.2%, BaseAcc(Other)=51.2%, Sens=91.4%, Spec=48.2%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.34, Accuracy=69.3%, BaseAcc(Other)=51.2%, Sens=91.3%, Spec=48.3%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.341, Accuracy=69.3%, BaseAcc(Other)=51.2%, Sens=91.3%, Spec=48.4%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.342, Accuracy=69.4%, BaseAcc(Other)=51.2%, Sens=91.2%, Spec=48.6%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.343, Accuracy=69.4%, BaseAcc(Other)=51.2%, Sens=91.1%, Spec=48.7%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.344, Accuracy=69.4%, BaseAcc(Other)=51.2%, Sens=91%, Spec=48.9%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.345, Accuracy=69.5%, BaseAcc(Other)=51.2%, Sens=91%, Spec=49%, Sens^2+Spec^2=1.069"
## [1] "Thresh=0.346, Accuracy=69.5%, BaseAcc(Other)=51.2%, Sens=90.9%, Spec=49.1%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.347, Accuracy=69.5%, BaseAcc(Other)=51.2%, Sens=90.8%, Spec=49.3%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.348, Accuracy=69.5%, BaseAcc(Other)=51.2%, Sens=90.7%, Spec=49.4%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.349, Accuracy=69.6%, BaseAcc(Other)=51.2%, Sens=90.6%, Spec=49.5%, Sens^2+Spec^2=1.068"
## [1] "Thresh=0.35, Accuracy=69.6%, BaseAcc(Other)=51.2%, Sens=90.6%, Spec=49.7%, Sens^2+Spec^2=1.068"
## [1] "=====
## [1] "Best Threshold=0.345"
## [1] "Best Sensitivity_Specificity=1.06905744668083"

curThresh = as.numeric(result[bestThreshIndex])
Lodge_Ind_Sig_threshold = curThresh
```

The accuracy for the best threshold on the training set for Lodgepole Pine using significant individuated data is shown below.

```
result = calcLogisticModelAccuracy (forestTrain$LodgepolePine, Lodge_Ind_Train_predict,
                                     curThresh, curThresh, 1, "Lodgepole", "Other", 3)
```

```
## [1] "Model Performance for threshold= 0.345"
## [1] "predicted performance="
##                                     Predicted
## Actual      FALSE=Predict:Other TRUE=Predict:Lodgepole
```

```
## 0=Actual:Other      102229 (TN)      106169 (FP)
## 1=Actual:Lodgepole   17813 (FN)      180498 (TP)
## [1] "Sensitivity= 0.910176440036105 (True positive rate of Lodgepole = TP/(TP+FN) = 180498 /( 180498 + 17813)"
## [1] "Specificity= 0.490546934231614 (True negative rate of Other = TN/(TN+FP) = 102229 /( 102229 + 106169)"
## [1] "Sens^2+Spec^2=1.069"
## [1] "Baseline (Other) Accuracy=0.5124"
## [1] "Logistic Accuracy=0.695157"
```

The accuracy for the best threshold on the testing set for Lodgepole Pine using significant individuated data is shown below.

```
result = calcLogisticModelAccuracy (forestTest$LodgepolePine, Lodge_Ind_Test_predict,
                                     curThresh, curThresh, 1, "Lodgepole", "Other", 3,
                                     saveFile=saveFileName, desc="Lodgepole Sig Individualized Vars",
                                     AIC=Lodge_Ind_Sig_aic, AUC=Lodge_Ind_Sig_ROC_AUC)

## [1] "Model Performance for threshold= 0.345"
## [1] "predicted performance="
##                                     Predicted
## Actual      FALSE=Predict:Other TRUE=Predict:Lodgepole
## 0=Actual:Other      43983 (TN)      45330 (FP)
## 1=Actual:Lodgepole   7544 (FN)      77446 (TP)
## [1] "Sensitivity= 0.911236616072479 (True positive rate of Lodgepole = TP/(TP+FN) = 77446 /( 77446 + 7544)"
## [1] "Specificity= 0.492459104497666 (True negative rate of Other = TN/(TN+FP) = 43983 /( 43983 + 45330)"
## [1] "Sens^2+Spec^2=1.072"
## [1] "Baseline (Other) Accuracy=0.5124"
## [1] "Logistic Accuracy=0.696654"

list[RC, Lodge_Ind_Sig_model_acc, Lodge_Ind_Sig_baseline_acc,
      TN, FN, FP, TP, Lodge_Ind_Sig_sens, Lodge_Ind_Sig_spec] <- result
if (RC != "OK") {
  print(paste("Error - terminating:",RC))
  knitr::knit_exit()
}
Lodge_Ind_Sig_model_acc = as.integer(as.numeric(Lodge_Ind_Sig_model_acc)*1000)/10
Lodge_Ind_Sig_baseline_acc = as.integer(as.numeric(Lodge_Ind_Sig_baseline_acc)*1000)/10
Lodge_Ind_Sig_sens = as.integer(as.numeric(Lodge_Ind_Sig_sens)*1000)/10
Lodge_Ind_Sig_spec = as.integer(as.numeric(Lodge_Ind_Sig_spec)*1000)/10

##### End End End End End End End End End End End End End End #####
```

The accuracy of the models is shown below:

Logistic Model	Accuracy	Sens	Spec	AIC	AUC	Threshold
Lodgepole Pine Aggregate All Vars	75.5%	79.3%	71.9%	418219	82.6%	0.476
Lodgepole Pine Individual All Vars	75.6%	78.8%	72.6%	418474	82.6%	0.481
Lodgepole Pine Aggregate Sig Vars	75.5%	79%	72.2%	419472	82.6%	0.482
Lodgepole Pine Individual Sig Vars	69.6%	91.1%	49.2%	438293	80.3%	0.345

There is a slight degradation in the accuracy with insignificant variables eliminated, but not by much.



## Conclusion

It is beginning to look like there is no advantage to dis-aggregating the Soil Type variables into their component parts. I was hoping there would be some improvement by allowing the individual variables to be “more finely” tuned. There is probably a mathematical explanation that proves there is no advantage of breaking out aggregated variables. I have to think about that more.

The logistic regression results for Spruce and Fir are 7% better than the original paper this project was modeled after. These tests need to be done for the remaining 6 forest cover types to see how regression does overall.

```
curTime=Sys.time()
print(paste("Forest Cover Logistic script ended at",curTime))
```

```
## [1] "Forest Cover Logistic script ended at 2018-08-12 19:24:44"
```