

Middleware Architectures 2

Lecture 3: Security

doc. Ing. Tomáš Vitvar, Ph.D.

tomas@vitvar.com • @TomasVitvar • <https://vitvar.com>



Czech Technical University in Prague

Faculty of Information Technologies • Software and Web Engineering • <https://vitvar.com/lectures>




Modified: Mon Mar 10 2025, 06:59:34
Humla v1.0

Overview


- **Security Concepts**
- Transport Level Security
- JSON Web Token
- OAuth 2.0
- OpenID

Web Service Security Concepts

- Securing the client-server communication
 - *Message-level security*
 - *Transport-level security*
- Ensure
 - *Authentication* – *verify a client's identity*
 - *Authorization* – *rights to access resources*
 - *Message Confidentiality* – *keep message content secret*
 - *Message Integrity* – *message content does not change during transmission*
 - *Non-repudiation* – *proof of integrity and origin of data*



Data on the Web



Authentication and Authorization


- Authentication
 - *verification of user's identity*
- Authorization
 - *verification that a user has rights to access a resource*
- Standard: HTTP authentication
 - *HTTP defines several main options*
 - *Basic Access Authentication*
 - *Digest Access Authentication*
 - *Bearer tokens to access OAuth 2.0-protected resources*
 - *Mutual authentication using password-based when server knows the user's encrypted password*
 - *Basic and Digest are defined in*
 - *RFC 2616: Hypertext Transfer Protocol – HTTP/1.1*
 - *RFC 2617: HTTP Authentication: Basic and Digest Access Authentication*
- Custom/proprietary: use of cookies

Overview


- Security Concepts
- **Transport Level Security**
- JSON Web Token
- OAuth 2.0
- OpenID

Overview

- SSL and TLS
 - *SSL and TLS is used interchangeably*
 - *SSL 3.0 developed by Netscape*
 - *IETF standardization of SSL 3.0 is TLS 1.0*
 - *TLS 1.0 is upgrade of SSL 3.0*
 - *Due to security flaws in TLS 1.0, TLS 1.1 and TLS 1.2 were created*
- TLS layer



TLS Handshake Protocol



- TLS Handshake
 - 56 ms: ClientHello, TLS protocol version, list of ciphersuites, TLS options*
 - 84 ms: ServerHello, TLS protocol version, ciphersuite, certificate*
 - 112 ms: RSA or Diffie-Hellman key exchange*
 - 140 ms: Message integrity checks, sends encrypted "Finished" message*
 - 168 ms: Decrypts the message, app data can be sent*

TLS and Proxy Servers

- TLS Offloading
 - Inbound TLS connection, plain outbound connection
 - Proxy can inspect messages
- TLS Bridging
 - Inbound TLS connection, new outbound TLS connection
 - Proxy can inspect messages
- End-to-End TLS (TLS pass-through)
 - TLS connection is passed-through the proxy
 - Proxy cannot inspect messages
- Load balancer
 - Can use TLS offloading or TLS bridging
 - Can use TLS pass-through with help of Server Name Indication (SNI)

Overview

- Security Concepts
- Transport Level Security
- JSON Web Token
- OAuth 2.0
- OpenID

Overview

- JSON Web Token (JWT)
 - *Open standard (RFC 7519)*
 - *Mechanism to securely transmit information between parties as a JSON object.*
 - *Can be **verified** and **trusted** as it is **digitally signed**.*
- Basic concepts
 - *Compact*
 - *has a small size*
 - *can be transmitted via a URL, POST, HTTP header.*
 - *Self-contained*
 - *payload contains all required user information.*

Use of JWT

- Authentication
 - *After user logs in, following requests contain JWT token.*
 - *Single Sign On widely uses JWT nowadays*
- Information Exchange
 - *Signature ensures senders are who they say they are.*
 - *Message integrity – signature calculated using the header and the payload.*

JWT Structure

`<header>.<payload>.<signature>`

- Header

- Contains two parts, the type of the token (JWT) and the hashing algorithm being used (e.g. HMAC, SHA256, RSA).

```
{  
  "alg": "HS256",  
  "typ": "JWT"  
}
```

- Payload

- Contains the claims, i.e. statements about an entity (e.g. user).
- Can be registered, public and private
- Registered and public should be defined in [IANA JSON Web Token Registry](#)

```
{  
  "sub": "1234567890",  
  "name": "John Doe",  
  "admin": true  
}
```

JWT Structure (Cont.)

- Signature

- Signed encoded header, encoded payload and a secret.
- For example, signature using HMAC SHA256 algorithm


```
HMACSHA256(  
  base64UrlEncode(header) + "." +  
  base64UrlEncode(payload),  
  secret)
```

- Example

- JWT is a three Base64-URL strings separated by dots

```
eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9.  
eyJzdWIiOiIxMjM0NTY3ODkwIiwibmFtZSI6IkpvaG4  
gRG9lIiwiaXNtb2NpYWwiOnRydWV9.  
4pcPyMD09o1PSyXnrXCjTwXyr4BsezdI1AVTmud2fU4
```

How to use JWT



1. User sends username and password
2. Server verifies user, creates JWT token with a secret and a expiration time
3. Server sends JWT token back to the Browser
4. Browser sends JWT token on subsequent interactions

Notes

- Authorization header does not behave the same as cookies!
- JWT should not contain secrets (passwords) as it can be read (on the client or if non-https connection is used)

Expiration and revocation

- Expiration
 - Tokens should be valid for a limited time
 - Use **exp** claim
 - Timestamp of the token expiration
 - Token should be checked on every request
- Revocation
 - Tokens (access tokens) usually stored in memory
 - Tokens should be refreshed using refresh tokens
 - Refresh tokens are stored in the DB
 - When you need to revoke access tokens stored them in the DB
 - You can expire all tokens by changing the secret on the server


Overview

- Security Concepts
- Transport Level Security
- JSON Web Token
- **OAuth 2.0**
 - *Client-side Web Apps*
 - *Server-side Web Apps*
- OpenID

Motivation

- Cloud Computing – Software as a Service
 - *Users utilize apps in clouds*
 - *they access **resources** via Web browsers*
 - *they store their data in the cloud*
 - *Google Docs, Contacts, etc.*
 - *The trend is that SaaS are open*
 - *can be extended by 3rd-party developers through APIs*
 - *attract more users ⇒ increases value of apps*
 - *Apps extensions need to have an access to users' data*
- Need for a new mechanism to access resources
 - *Users can grant access to third-party apps without exposing their users' credentials*

When there is no OAuth



- Users must share their credentials with the 3rd-party app
- Users cannot control what and how long the app can access resources
- Users must trust the app
 - In case of misuse, users can only change their passwords

OAuth 2.0 Protocol

- OAuth Objectives
 - users can grant access to third-party applications
 - users can revoke access any time
 - supports:
 - client-side web apps (implicit grant),
 - server-side apps (authorization code), and
 - native (desktop) apps (authorization code)
- History
 - Initiated by Google, Twitter, Yahoo!
 - Different, non-standard protocols first: ClientLogin, AuthSub
 - OAuth 1.0 – first standard, security problems, quite complex
 - OAuth 2.0 – new version, not backward compatible with 1.0
- Specifications and adoption
 - OAuth 2.0 Protocol [🔗](#)
 - OAuth 2.0 Google Support [🔗](#)

Terminology

- **Client**
 - a *third-party app* accessing resources owned by **resource owner**
- **Resource Owner** (also user)
 - a person that owns a resource stored in the **resource server**
- **Authorization and Token Endpoints**
 - endpoints provided by an **authorization server** through which a **resource owner** authorizes requests.
- **Resource Server**
 - an app that stores resources owned by a **resource owner**
 - For example, contacts in Google Contacts
- **Authorization Code**
 - a code that a **client** uses to request **access tokens** to access resources
- **Access Token**
 - a code that a **client** uses to access resources

Overview

- Security Concepts
- Transport Level Security
- JSON Web Token
- OAuth 2.0
 - *Client-side Web Apps*
 - *Server-side Web Apps*
- OpenID


Client-side Web Apps

- Simplified version of OAuth 2.0 protocol
 - JavaScript/AJAX apps running in a browser
 - Apps that cannot easily "remember" app state
 - limited number of interactions
- Architecture
 - User-agent processes a javascript/HTML code from the client
 - No need of authorization code
- Basic Steps
 - A client redirects a user agent to the authorization endpoint
 - A resource owner grants an access to the client
 - or he/she rejects the request
 - Authorization server provides an **access_token** to the client
 - Client access the resource with the **access_token**
 - When the token expires, client requests a new token

Demo – List of Contacts

- Display your Google contacts
 - this demo requests authorization from you to access your Google contacts using client-side OAuth 2.0 protocol and then displays the contacts below. In order to transfer **access_token** from authorization window, it stores the **access_token** in a cookie.
 - **access_token**
 - *Show contacts* or *revoke access*

Client-side Web Apps Protocol



Redirection – Step 1

- **Methods and Parameters**
 - *Methods:* **GET** or **POST**
 - *example authorization endpoint url (Google):*
`https://accounts.google.com/o/oauth2/auth`
 - *query string parameters or **application/x-www-form-urlencoded***
 - **client_id** – id of the client that was previously registered
 - **redirect_uri** – an URI that auth. server will redirect to when user grants/rejects
 - **scope** – string identifying resources/services to be accessed
 - **response_type** – type of the response (**token** or **code**)
 - **state** (optional) – state between request and redirect
 - *Example*

```

1 | https://accounts.google.com/o/oauth2/auth?
2 | client_id=621535099260.apps.googleusercontent.com&
3 | redirect_uri=http://w20.vitvar.com/examples/oauth/callback.html&
4 | scope=https://www.google.com/m8/feeds&
5 | response_type=token
                
```

Callback – steps 4 and 5

- Resource owner grants the access
 - *authorization server calls back **redirect_uri***
 - *client parses URL in JavaScript (Step 5)*
 - *extracts **access_token** and **expires_in** (by using **window.location.hash**)*
 - *Example:*

```
1 | https://w20.vitvar.com/examples/oauth/callback.html#
2 | access_token=1/QbZfgDNsnd&
3 | expires_in=4301
```
- Resource owner rejects the access
 - *authorization server calls back **redirect_uri** with query string parameter **error=access_denied***
 - *Example:*

```
1 | http://w20.vitvar.com/examples/oauth/callback.html?
2 | error=access_denied
```


Accessing Resources – Step 6

- Request
 - *client can access resources defined by **scope***
 - *resources' URIs defined in a particular documentation*
 - *Example Google Contacts*
 - *to access all users' contacts stored in Google*
 - ***scope** is **https://www.google.com/m8/feeds***
 - *Query string parameter **oauth_token***

```
1 | curl https://www.google.com/m8/feeds/contacts/default/full?
2 |   oauth_token=1/dERFd34Sf
```
 - *HTTP Header **Authorization***

```
1 | curl -H "Authorization: OAuth 1/dERFd34Sf"
2 |   https://www.google.com/m8/feeds/contacts/default/full
```
 - *The client can do any allowed operations on the resource*
- Response
 - *Success – **200 OK***
 - *Error – **401 Unauthorized** when token expires or the client hasn't performed the authorization request.*

Cross-Origin Resource Sharing



— see *Same Origin and Cross-Origin* for details

Example Application Registration

The screenshot shows the Google APIs console interface for a project named "vitvar.com". The left sidebar contains navigation links: Overview, Services, Team, API Access (selected), Billing, Reports, and Quotas. The main content area displays the following information:

- API Access**: To prevent abuse, Google places limits on API requests. Using a valid OAuth token or API key allows you to exceed anonymous limits by connecting requests back to your project.
- Authorized API Access**: OAuth allows users to share specific data with you (for example, contact lists) while keeping their usernames, passwords, and other information private. [Learn more](#)
- Branding information**: The following information is shown to users whenever you request access to their private data.
 - Product name: w20-test
 - Google account: t.vitvar@gmail.com
 - [Edit branding information...](#)
- Client ID for web applications**:
 - Client ID: 621535099260.apps.googleusercontent.com
 - Client secret: RxWM917Sv-7cyfWMW7KhNV9R
 - Redirect URIs: `http://vitvar.com/examples/oauth/callback.html`
 - JavaScript origins: `http://example.org`
 - [Edit settings...](#)
 - [Reset client secret...](#)
- [Create another client ID...](#)


Overview

- Security Concepts
- Transport Level Security
- JSON Web Token
- OAuth 2.0
 - *Client-side Web Apps*
 - *Server-side Web Apps*
- OpenID

Server-side Web Apps

- Additional interactions
 - *server-side code (any language), the app can maintain the state*
 - *additional interactions, authorization code*
- Architecture
 - *Client at a server requests, remembers and refresh access tokens*
- Basic steps
 - *Client redirects user agent to the authorization endpoint*
 - *Resource owner grants access to the client or rejects the request*
 - *Authorization server provides **authorization code** to the client*
 - *Client requests **access and refresh tokens** from the auth. server*
 - *Client access the resource with the access token*
 - *When the token expires, client refreshes a token with refresh token*
- Advantages
 - *Access tokens not visible to clients, they are stored at the server*
 - *more secure, clients need to authenticate before they can get tokens*

Server-side Web Apps Protocol



Redirection – Step 1

- Methods and Parameters
 - same as for client-side app, except **response_type** must be **code**
- Example
 - 1 | `https://accounts.google.com/o/oauth2/auth?`
 - 2 | `client_id=621535099260.apps.googleusercontent.com&`
 - 3 | `redirect_uri=http://w20.vitvar.com/examples/oauth/callback.html&`
 - 4 | `scope=https://www.google.com/m8/feeds&`
 - 5 | `response_type=code`

Callback + Access Token Request – steps 4, 5

- Callback
 - authorization server calls back **redirect_uri**
 - client gets the **code** and requests **access_token**
 - example (resource owner grants access):
`http://w20.vitvar.com/examples/oauth/callback.html?code=4/P7...`
 - when user rejects → same as client-side access
- Access token request
 - **POST** request to token endpoint
→ example Google token endpoint:
`https://accounts.google.com/o/oauth2/token`
 - ```
1 POST /o/oauth2/token HTTP/1.1
2 Host: accounts.google.com
3 Content-Type: application/x-www-form-urlencoded
4
5 code=4/P7q7W91a-oMsCeLvIaQm6bTrgtp6&
6 client_id=621535099260.apps.googleusercontent.com&
7 client_secret=XTHhXh1S2UggvyWgWdK1EjXB&
8 redirect_uri=http://w20.vitvar.com/examples/oauth/callback.html&
9 grant_type=authorization_code
```

## Access Token (cont.)

- Access token response
  - Token endpoint responds with **access\_token** and **refresh\_token**
  - ```
1 { "access_token" : "1/fFAGRnJru1FTz70BzhT3Zg",
2   "expires_in"   : 3920,
3   "refresh_token" : "1/6BMfW9j53gdGimsixUH6kU5RsR4zwI9lUVX-tqf8JXQ" }
```
- Refreshing a token
 - **POST** request to the token endpoint with **grant_type=refresh_token** and the previously obtained value of **refresh_token**
 - ```
1 POST /o/oauth2/token HTTP/1.1
2 Host: accounts.google.com
3 Content-Type: application/x-www-form-urlencoded
4
5 client_id=21302922996.apps.googleusercontent.com&
6 client_secret=XTHhXh1S1UNGvyWgWdK1EjXB&
7 refresh_token=1/6BMfW9j53gdGimsixUH6kU5RsR4zwI9lUVX-tqf8JXQ&
8 grant_type=refresh_token
```
- Accessing a resource is the same as in the client-side app


## Overview

- Security Concepts
- Transport Level Security
- JSON Web Token
- OAuth 2.0
- **OpenID**
  - *OpenID Connect*

## OpenID Protocol

- Motivation – many user accounts
  - *users need to maintain many accounts to access various services*
  - *multiple passwords problem*
- Objectives
  - *allows apps to utilize an OpenID provider*
    - *a third-party authentication service*
    - *federated login*
  - *users have one account with the OpenID provider and use it for apps that support the provider*
- OpenID providers
  - *it is a protocol, anybody can build a provider*
  - *Google, Yahoo!, Seznam.cz, etc.*
- Specification
  - *OpenID Protocol* [🔗](#)

## Interaction Sequence



- Discovery – discovery of a service associated with a resource
- XRDS – eXtensible Resource Descriptor Sequence
  - *format for discovery result*
  - *developed to serve resource discovery for OpenID*
  - *Web app retrieves endpoint to send login authentication requests*

## Login Authentication Request – Step 5

- Example Google OpenID provider

```
1 https://www.google.com/accounts/o8/id
2 ?openid.ns=http://specs.openid.net/auth/2.0
3 &openid.return_to=https://www.example.com/checkauth
4 &openid.realm=http://www.example.com/
5 &openid.assoc_handle=ABSmpf6DNMw
6 &openid.mode=checkid_setup
```

- Parameters

- **ns** – *protocol version (obtained from the XRDS)*
- **mode** – *type of message or additional semantics (**checkid\_setup** indicates that interaction between the provider and the user is allowed during authentication)*
- **return\_to** – *callback page the provider sends the result*
- **realm** – *domain the user will trust, consistent with **return\_to***
- **assoc\_handle** – *"log in" for web app with openid provider*

*\* Not all fields shown, check the OpenID spec for the full list of fields and their values*

## Login Authentication Response – Step 8

- User logs in successfully

```
1 http://www.example.com/checkauth
2 ?openid.ns=http://specs.openid.net/auth/2.0
3 &openid.mode=id_res
4 &openid.return_to=http://www.example.com:8080/checkauth
5 &openid.assoc_handle=ABSmpf6DNMw
6 &openid.identity=https://www.google.com/accounts/o8/id?id=ACyQatiscWwqs4UQV_L
```

- Web app will use **identity** to identify user in the application
- response is also signed using a list of fields in the response (not shown in the listing)

- User cancels

```
1 http://www.example.com/checkauth
2 ?openid.mode=cancel
3 &openid.ns=http://specs.openid.net/auth/2.0
```

*\* Not all fields shown, check the OpenID spec for the full list of fields and their values*

## Overview

- Security Concepts
- Transport Level Security
- JSON Web Token
- OAuth 2.0
- OpenID
  - *OpenID Connect*

# OpenID Connect (OIDC)

- Simple identity layer on top of the OAuth 2.0 protocol
  - *Authorization Server to verify identity of users*
  - *Clients can obtain basic profile information about users*
- OIDC vs OpenID
  - *OIDC does many of the same tasks as OpenID 2.0*
  - *API-friendly*
    - *can be used by native and mobile applications*
  - *Robust signing and encryption mechanisms*
  - *Native integration with OAuth 2.0.*
- Defined by OpenID open standard
  - *OpenID Connect*

## Interaction sequence

