



Joachim Faulhaber

# An Introduction to the Interval Template Library

**Lecture**  
held at the Boost Library Conference 2009

**2009-05-08**

- Background and Motivation
- Characteristics of interval containers
- Examples
- Semantics
- Implementation
- Future Works
- Availability



# Background and Motivation

- Interval containers simplified the implementation of date and time related tasks
  - Decomposing a stream of attributed events into segments with constant attributes.
  - Working with time grids, e.g. a grid of months.
  - Aggregations of values associated to date or time intervals.
- ... that occurred frequently in programs like
  - Billing modules
  - Therapy scheduling programs
  - Hospital and controlling statistics

# Characteristics of Interval Containers

- Background is the date time problem domain ...
- ... but the scope of the **Itl** as a generic library is more general:

*an **interval\_set** implements a **set**  
via a set of intervals*

*an **interval\_map** implements a **map**  
via a map of interval value pairs*



- There are two aspects in the design of interval containers

- Conceptual aspect

```
interval_set<int> mySet;  
mySet.insert(42);  
bool has_answer = mySet.contains(42);
```

- On the conceptual aspect an interval\_set can be used just as a set of elements
- except for . . .
- . . . *iteration*
- consider interval\_set<double> or interval\_set<string>

## ■ Iterative aspect

```
// Switch on my favorite telecasts using an interval_set.
interval<seconds> news(make_seconds("20:00:00"),
                      make_seconds("20:15:00"));
interval<seconds> talk_show(make_seconds("22:45:30"),
                           make_seconds("23:30:50"));

interval_set<seconds> myTvProgram;
myTVProgram.add(news).add(talk_show);

// Iterating over elements (seconds) would be silly ...
for(interval_set<seconds>::iterator telecast =
    myTvProgram.begin();
    telecast != myTvProgram.end(); ++telecast)
    //...so this iterates over intervals
    TV.switch_on(*telecast);
```



# Characteristics of Interval Containers

## • Addability and Subtractability

- All of itl's (interval) containers are *Addable* and *Subtractable*
- They implement **operators**  $+=$ ,  $+$ ,  $-=$  and  $-$


	$+=$	$-=$
sets	set union	set difference
maps	?	?

## • A possible implementation for maps

- Propagate addition/subtraction to the associated values
- . . . or aggregate on overlap
- . . . or aggregate on collision

# Characteristics of Interval Containers

## Aggregate on overlap



- Decompositional effect on Intervals
- Accumulative effect on associated values



# Characteristics of Interval Containers

## Aggregate on overlap, a minimal example

```
typedef itl::set<string> guests;
interval_map<time, guests> party;

party += make_pair(
    interval<time>::rightopen(20:00, 22:00), guests("Mary"));

party += make_pair(
    interval<time>::rightopen(21:00, 23:00), guests("Harry"));

// party now contains
[20:00, 21:00) -> {"Mary"}
[21:00, 22:00) -> {"Harry", "Mary"} //guest sets aggregated
[22:00, 23:00) -> {"Harry"}
```

# Characteristics of Interval Containers

## • The Itl's class templates

Granularity	Style	Sets	Maps
interval		<code>interval</code>	
	joining	<code>interval_set</code>	<code>interval_map</code>
	separating	<code>separate_interval_set</code>	
	splitting	<code>split_interval_set</code>	<code>split_interval_map</code>
element		<code>set</code>	<code>map</code>



# Characteristics of Interval Containers

- Interval Combining Styles: *Joining*
  - Intervals are joined on overlap or on touch
  - ... *for maps*, if associated values are equal
  - Keeps interval\_maps and sets in a minimal form

## interval\_set

```
{ [1      3)
+   [2      4)
+   [4  5)

= { [1      4)
   }

= { [1      5) }
```

## interval\_map

```
{ [1      3) ->1
+   [2      4) ->1
+   [4  5) ->1

= { [1  2) [2  3) [3  4)
    ->1   ->2   ->1
   }

= { [1  2) [2  3) [3      5)
    ->1   ->2           ->1
   }
```

# Characteristics of Interval Containers

- Interval Combining Styles: *Splitting*
  - Intervals are split on overlap and kept separate on touch
  - All interval borders are preserved (insertion memory)

## `split_interval_set`

```
{ [1      3)      }  
+      [2      4)  
+      [4  5)  
  
= { [1  2) [2  3) [3  4)      }  
= { [1  2) [2  3) [3  4) [4  5) }
```

## `split_interval_map`

```
{ [1      3) ->1      }  
+      [2      4) ->1  
+      [4  5) ->1  
  
= { [1  2) [2  3) [3  4)      }  
   ->1   ->2   ->1  
= { [1  2) [2  3) [3  4) [4  5) }  
   ->1   ->2   ->1   ->1
```



# Characteristics of Interval Containers

- Interval Combining Styles: *Separating*
  - Intervals are joined on overlap but kept separate on touch
  - Preserves borders that are never crossed (preserves a hidden grid).

*separate\_interval\_set*

```
{ [1      3)      }  
+      [2      4)  
+      [4  5)  
  
= { [1      4)      }  
  
= { [1      4) [4  5) }
```

## ● A few instances of intervals (interval.cpp)

```
interval<int> int_interval = interval<int>::closed(3,7);

interval<double> sqrt_interval
    = interval<double>::rightopen(1/sqrt(2.0), sqrt(2.0));

interval<std::string> city_interval
    = interval<std::string>::leftopen("Barcelona", "Boston");

interval<boost::ptime> time_interval
    = interval<boost::ptime>::open(
        time_from_string("2008-05-20 19:30"),
        time_from_string("2008-05-20 23:00")
    );
```



## • A way to iterate over months and weeks (month\_and\_week\_grid.cpp)

```
#include <boost/itl/gregorian.hpp> //boost::gregorian plus adapter code
#include <boost/itl/split_interval_set.hpp>

// A split_interval_set of gregorian dates as date_grid.
typedef split_interval_set<boost::gregorian::date> date_grid;

// Compute a date_grid of months using boost::gregorian.
date_grid month_grid(const interval<date>& scope)
{
    date_grid month_grid;
    // Compute a date_grid of months using boost::gregorian.
    . . .
    return month_grid;
}

// Compute a date_grid of weeks using boost::gregorian.
date_grid week_grid(const interval<date>& scope)
{
    date_grid week_grid;
    // Compute a date_grid of weeks using boost::gregorian.
    . . .
    return week_grid;
}
```

## ● A way to iterate over months and weeks

```
void month_and_time_grid()
{
    date someday = day_clock::local_day();
    date thenday = someday + months(2);
    interval<date> scope = interval<date>::rightopen(someday, thenday);

    // An intersection of the month and week grids ...
    date_grid month_and_week_grid
        = month_grid(scope) & week_grid(scope);

    // ... allows to iterate months and weeks. Whenever a month
    // or a week changes there is a new interval.
    for(date_grid::iterator it = month_and_week_grid.begin();
        it != month_and_week_grid.end(); it++)
    {
        . . .
    }

    // We can also intersect the grid into an interval_map to make
    // shure that all intervals are within months and week bounds.
    interval_map<boost::gregorian::date, some_type> accrual;
    compute_some_result(accrual, scope);
    accrual &= month_and_week_grid;
}
```



## • Aggregating with interval\_maps (1) (boost\_party.cpp)

```
typedef itl::set<string> guests;  
interval_map<time, guests> party;  
  
party += make_pair(  
    interval<time>::rightopen(20:00, 22:00), guests("Mary"));  
  
party += make_pair(  
    interval<time>::rightopen(21:00, 23:00), guests("Harry"));  
  
// party now contains  
[20:00, 21:00) -> {"Mary"}  
[21:00, 22:00) -> {"Harry", "Mary"} //guest sets aggregated  
[22:00, 23:00) -> {"Harry"}
```

## • Aggregating with interval\_maps (2)

- Computing averages via implementing **operator +=**  
(partys\_guest\_average.cpp)

```
class counted_sum
{
public:
    counted_sum() : _sum(0), _count(0) {}
    counted_sum(int sum) : _sum(sum), _count(1) {}

    int sum() const {return _sum;}
    int count() const {return _count;}
    double average() const
    { return _count==0 ? 0.0 : _sum/static_cast<double>(_count); }

    counted_sum& operator += (const counted_sum& right)
    { _sum += right.sum(); _count += right.count(); return *this; }

private:
    int _sum;
    int _count;
};

bool operator == (const counted_sum& left, const counted_sum& right)
{ return left.sum()==right.sum() && left.count()==right.count(); }
```



## ■ Aggregating with interval\_maps (2)

### ■ Computing averages via implementing **operator +=**

```
void partys_height_average()
{
    interval_map<ptime, counted_sum> height_sums;

    height_sums += (
        make_pair(
            interval<ptime>::rightopen(
                time_from_string("2008-05-20 19:30"),
                time_from_string("2008-05-20 23:00")),
            counted_sum(165)) // Mary is 1,65 m tall.
    );

    // Add height of more party guests . . .

    interval_map<ptime, counted_sum>::iterator height_sum_ =
        height_sums.begin();
    while(height_sum_ != height_sums.end())
    {
        interval<ptime> when = height_sum_->first;
        double height_average = (*height_sum_++).second.average();

        cout << "[" << when.first() << " - " << when.upper() << "]"
            << ": " << height_average << " cm" << endl;
    }
}
```

## ■ Aggregating with interval\_maps (3)

- Computing maxima via instantiation of a template parameter (partys\_tallest\_guests.cpp)

```
typedef interval_map<ptime, int, partial_absorber, less, inplace_max>
    PartyHeightHistoryT;

void partys_height()
{
    PartyHeightHistoryT tallest_guest;

    tallest_guest += (
        make_pair(
            interval<ptime>::rightopen(
                time_from_string("2008-05-20 19:30"),
                time_from_string("2008-05-20 23:00")),
            180) // Max of Mary & Harry: Harry is 1,80 m tall.
    );

    . . .
}
```



- Interval containers allow to express a variety of date and time operations in an easy way.
  - Example `man_power.cpp` ...
  - Subtract weekends and holidays from an `interval_set`  
`worktime -= weekends(scope)`  
`worktime -= german_reunification_day`
  - Intersect an `interval_map` with an `interval_set`  
`claudias_working_hours &= worktime`
  - Subtract an `interval_set` from an `interval_map`  
`claudias_working_hours -= claudias_absense_times`
  - Adding `interval_maps`  
`interval_map<date, int> manpower;`  
`manpower += claudias_working_hours;`  
`manpower += bodos_working_hours;`

## Interval\_maps can also be intersected Example `user_groups.cpp`

```
typedef boost::itl::set<string> MemberSetT;
typedef interval_map<date, MemberSetT> MembershipT;

void user_groups()
{
    . . .

    MembershipT med_users;
    // Compute membership of medical staff
    med_users += make_pair(member_interval_1, MemberSetT("Dr.Jekyll"));
    med_users += . . .

    MembershipT admin_users;
    // Compute membership of administration staff
    med_users += make_pair(member_interval_2, MemberSetT("Mr.Hyde"));
    . . .

    MembershipT all_users    = med_users + admin_users;

    MembershipT super_users = med_users & admin_users;
    . . .

}
```



- The semantics of *itl sets* is based on a concept `itl::Set`
  - `itl::set`, `interval_set`, `split_interval_set` and `separate_interval_set` are models of concept `itl::Set`

```
// Abstract or conceptual part
empty set:      Set::Set()
subset relation: bool Set::contained_in(const Set& s2) const
equality:       bool is_element_equal(const Set& s1, const Set& s2)
set union:      Set& operator += (Set& s1, const Set& s2)
                Set operator + (const Set& s1, const Set& s2)
set difference: Set& operator -= (Set& s1, const Set& s2)
                Set operator - (const Set& s1, const Set& s2)
set intersection: Set& operator &= (Set& s1, const Set& s2)
                Set operator & (const Set& s1, const Set& s2)

// Part related to sequence and iteration
sorting order:  bool operator < (const Set& s1, const Set& s2)
lexicographical equality:
                bool operator == (const Set& s1, const Set& s2)
```


- The semantics of *itl maps* is based on a concept `itl::Map`
  - `itl::map`, `interval_map` and `split_interval_map` are models of concept `itl::Map`

```
// Abstract or conceptual part
empty map:      Map::Map()
submap relation: bool Map::contained_in(const Map& m2) const
equality:       bool is_element_equal(const Map& m1, const Map& m2)
map union:      Map& operator += (Map& m1, const Map& m2)
                Map& operator +  (const Map& m1, const Map& m2)
map difference: Map& operator -= (Map& m1, const Map& m2)
                Map& operator -  (const Map& m1, const Map& m2)
map intersection: Map& operator &= (Map& m1, const Map& m2)
                Map& operator &  (const Map& m1, const Map& m2)

// Part related to sequence and iteration
sorting order:  bool operator <  (const Map& m1, const Map& m2)
lexicographical equality:
                bool operator == (const Map& m1, const Map& m2)
```



- Defining semantics of itl concepts via sets of laws
  - aka c++0x axioms
- Checking law sets via automatic testing:
  - A **Law Based Test Automaton** **LaBatea**



## • Lexicographical Ordering and Equality

- For all itl containers `operator <` implements a ***strict weak ordering***.
- The ***induced equivalence*** of this ordering is ***lexicographical equality*** which is implemented as `operator ==`
- This is in line with the semantics of `SortedAssociativeContainers`



## • Subset Ordering and Element Equality

- For all itl containers function `contained_in` implements a *partial ordering*.
- The *induced equivalence* of this ordering is *equality of elements* which is implemented as function `is_element_equal`.

- itl::Sets
- **All** itl sets implement a **Set Algebra**, which is to say satisfy a “*classical*” set of laws . . .
  - . . . using `is_element_equal` as equality
  - Associativity, Neutrality, Commutativity
  - Distributivity, DeMorgan, Symmetric Difference
- **Most of** the itl sets satisfy the classical set of laws even if . . .
  - . . . lexicographical equality: `operator ==` is used
  - The differences reflect proper inequalities in sequence that occur for `separate_interval_set` and `split_interval_set`.



- itl::Maps
- Two major use cases
  - Maps of Sets: Collectors
  - Maps of Numbers: Quantifiers

## Map Traits:

### Definedness

- partial
- total

### Neutron semantics: Given a value pair $(k, 0)$ , the associated neutron value *codes*

- non existence*.  $(k, 0)$  will be deleted: neutron absorber
- 0-quantification*.  $(k, 0)$  will **not** be deleted:  
neutron enricher

	neutron absorber	neutron enricher
partial	partial_absorber	partial_enricher
total	total_absorber	total_enricher



## Collectors: Maps of Sets . . .

- Condition: `Trait == partial_absorber`.  
`interval_map<int, itl::set<int>, partial_absorber>`
- *partial*: only value pairs exist that have been added
- *neutron absorber*: If a value pair carries a neutron  $(k, 0)$ , it is deleted ( $0$  codes *non existence*).
- . . . then an itl Map of Sets is model of `itl::Set`
- . . . it satisfies the same set of laws that **itl sets** do.

- Concepts induction / concept transition
  - Semantics of itl Maps appears to be dominated by the codomain type of the map
  - Itl Maps are mapping the semantics of the codomain type on themselves.

	<i>is model of</i>	<i>if Trait</i>	<i>example</i>
Map<D, <b>Monoid</b> >	<b>Monoid</b>		interval_map<int, <b>string</b> >
Map<D, <b>Set</b> >	<b>Set</b>	<i>is_partial</i> <i>_aborber</i>	interval_map<int, <b>set&lt;int&gt;</b> >
Map<D, <b>CommutMonoid</b> >	<b>CommutMonoid</b>		interval_map<int, <b>unsigned</b> >
Map<D, <b>AbelianGroup</b> >	<b>AbelianGroup</b>	<i>is_total</i>	interval_map<int, <b>int</b> >



- Interval containers are implemented simply based on `std::set` and `std::map`
  - Basic operations like adding and subtracting intervals have a best case complexity of  $O(\lg n)$ , if the added or subtracted intervals are small.
  - Worst case complexity of adding or subtracting intervals for `interval_set` is  $O(n)$ .
  - For all other interval containers adding or subtracting intervals has a worst case performance of  $O(n \lg(n))$ .
  - There is a potential for optimization . . .

- A segment\_tree implementation: A balanced tree, where . . .
  - an interval represents a perfectly balanced subtree
  - large intervals are rotated towards the root
- First results
  - much better worst case performance  $O(n)$  instead of  $O(n \lg(n))$
  - but slower for best case due to heavier bookkeeping and recursive algorithms.



- Completing and optimizing the segment\_tree implementation of interval containers
- Implementing interval\_maps of sets more efficiently
- Revision of elements of the extended itl (itl\_xt)
  - **Decomposition of histories**:  $k$  histories  $h_k$  with attribute types  $A_1, \dots, A_k$  are “*decomposed*” to a product history of attribute set tuples:  
$$(h_1\langle T, A_1 \rangle, \dots, h\langle T, A_k \rangle) \rightarrow h\langle T, (\text{set}\langle A_1 \rangle, \dots, \text{set}\langle A_k \rangle) \rangle$$
  - **Cubes** (generalized crosstables): Applying *aggregate on collision* to **maps of tuples** in order to organize hierarchical data and their aggregates.

- Itl project on **sourceforge** (version 2.0.1)  
<http://sourceforge.net/projects/itl>
- Latest version on **boost vault/Containers** (3.0.0)  
<http://www.boostpro.com/vault/> → containers
  - itl.zip : Core itl in preparation for boost
  - itl\_plus.zip : Extended itl including product histories, cubes and automatic validation (LaBatea).
- **Online documentation** at  
<http://www.herold-faulhaber.de/>
  - Doxygen generated docs for (version 2.0.1)  
<http://www.herold-faulhaber.de/itl/>
  - Latest boost style documentation (version 3.0.0)  
[http://www.herold-faulhaber.de/boost\\_itl/doc/libs/itl/doc/html/](http://www.herold-faulhaber.de/boost_itl/doc/libs/itl/doc/html/)