
Boost.Octonions

Hubert Holin

Copyright © 2001 -2003 Hubert Holin

Distributed under the Boost Software License, Version 1.0. (See accompanying file LICENSE_1_0.txt or copy at http://www.boost.org/LICENSE_1_0.txt)

Table of Contents

Octonions	1
Overview	1
Header File	2
Synopsis	3
Template Class octonion	6
Octonion Specializations	9
Octonion Member Typedefs	14
Octonion Member Functions	14
Octonion Non-Member Operators	17
Octonion Value Operations	19
Octonion Creation Functions	20
Octonions Transcendentals	20
Test Program	22
Acknowledgements	22
History	22
To Do	23

Octonions

Overview

Octonions, like [quaternions](#), are a relative of complex numbers.

Octonions see some use in theoretical physics.

In practical terms, an octonion is simply an octuple of real numbers $(\alpha, \beta, \gamma, \delta, \epsilon, \zeta, \eta, \theta)$, which we can write in the form $o = \alpha + i + j + k + e' + i' + j' + k'$, where i, j and k are the same objects as for quaternions, and e', i', j' and k' are distinct objects which play essentially the same kind of role as i (or j or k).

Addition and a multiplication is defined on the set of octonions, which generalize their quaternionic counterparts. The main novelty this time is that **the multiplication is not only not commutative, is now not even associative** (i.e. there are octonions x, y and z such that $x(yz) \neq (xy)z$). A way of remembering things is by using the following multiplication table:

	1	i	j	k	e'	i'	j'	k'
1	1	i	j	k	e'	i'	j'	k'
i	i	-1	k	$-j$	i'	$-e'$	$-k'$	j'
j	j	$-k$	-1	i	j'	k'	$-e'$	$-i'$
k	k	j	$-i$	-1	k'	$-j'$	i'	$-e'$
e'	e'	$-i'$	$-j'$	$-k'$	-1	i	j	k
i'	i'	e'	$-k'$	j'	$-i$	-1	$-k$	j
j'	j'	k'	e'	$-i'$	$-j$	k	-1	$-i$
k'	k'	$-j'$	i'	e'	$-k$	$-j$	i	-1

Octonions (and their kin) are described in far more details in this other [document](#) (with [errata and addenda](#)).

Some traditional constructs, such as the exponential, carry over without too much change into the realms of octonions, but other, such as taking a square root, do not (the fact that the exponential has a closed form is a result of the author, but the fact that the exponential exists at all for octonions is known since quite a long time ago).

Header File

The interface and implementation are both supplied by the header file [octonion.hpp](#).

Synopsis



```
template<typename T, typename charT, class traits>
::std::basic_ostream<charT,traits> & operator << (::std::basic_ostream<charT,traits> & os, octonion<T> o) {
    os << o;
    return os;
}

// values

template<typename T> T      real(octonion<T> const & o);
template<typename T> octonion<T> unreal(octonion<T> const & o);

template<typename T> T      sup(octonion<T> const & o);
template<typename T> T      ll(octonion<T> const & o);
template<typename T> T      abs(octonion<T> const & o);
template<typename T> T      norm(octonion<T> const & o);
template<typename T> octonion<T> conj(octonion<T> const & o);

template<typename T> octonion<T> spherical(T const & rho, T const & theta, T const & phi, T const & phi2);
template<typename T> octonion<T> multipolar(T const & rho1, T const & theta1, T const & rho2, T const & theta2, T const & phi, T const & phi2);
template<typename T> octonion<T> cylindrical(T const & r, T const & angle, T const & h1, T const & h2, T const & phi);

// transcendentals

template<typename T> octonion<T> exp(octonion<T> const & o);
template<typename T> octonion<T> cos(octonion<T> const & o);
template<typename T> octonion<T> sin(octonion<T> const & o);
template<typename T> octonion<T> tan(octonion<T> const & o);
template<typename T> octonion<T> cosh(octonion<T> const & o);
template<typename T> octonion<T> sinh(octonion<T> const & o);
template<typename T> octonion<T> tanh(octonion<T> const & o);

template<typename T> octonion<T> pow(octonion<T> const & o, int n);

} } // namespaces
```

Template Class octonion

```

namespace boost{ namespace math {

template<typename T>
class octonion
{
public:
    typedef T value_type;

    explicit octonion(T const & requested_a = T(), T const & requested_b = T(), T const & requested_c =
    explicit octonion(::std::complex<T> const & z0, ::std::complex<T> const & z1 = ::std::complex<T>(),
    explicit octonion(::boost::math::quaternion<T> const & q0, ::boost::math::quaternion<T> const & q1 =
    template<typename X>
    explicit octonion(octonion<X> const & a_recopier);

    T real() const;
    octonion<T> unreal() const;

    T R_component_1() const;
    T R_component_2() const;
    T R_component_3() const;
    T R_component_4() const;
    T R_component_5() const;
    T R_component_6() const;
    T R_component_7() const;
    T R_component_8() const;

    ::std::complex<T> C_component_1() const;
    ::std::complex<T> C_component_2() const;
    ::std::complex<T> C_component_3() const;
    ::std::complex<T> C_component_4() const;

    ::boost::math::quaternion<T> H_component_1() const;
    ::boost::math::quaternion<T> H_component_2() const;

    octonion<T> & operator = (octonion<T> const & a_affecter);
    template<typename X>
    octonion<T> & operator = (octonion<X> const & a_affecter);
    octonion<T> & operator = (T const & a_affecter);
    octonion<T> & operator = (::std::complex<T> const & a_affecter);
    octonion<T> & operator = (::boost::math::quaternion<T> const & a_affecter);

    octonion<T> & operator += (T const & rhs);
    octonion<T> & operator += (::std::complex<T> const & rhs);
    octonion<T> & operator += (::boost::math::quaternion<T> const & rhs);
    template<typename X>
    octonion<T> & operator += (octonion<X> const & rhs);

    octonion<T> & operator -= (T const & rhs);
    octonion<T> & operator -= (::std::complex<T> const & rhs);
    octonion<T> & operator -= (::boost::math::quaternion<T> const & rhs);
    template<typename X>
    octonion<T> & operator -= (octonion<X> const & rhs);

    octonion<T> & operator *= (T const & rhs);
    octonion<T> & operator *= (::std::complex<T> const & rhs);
    octonion<T> & operator *= (::boost::math::quaternion<T> const & rhs);
    template<typename X>
    octonion<T> & operator *= (octonion<X> const & rhs);

    octonion<T> & operator /= (T const & rhs);
    octonion<T> & operator /= (::std::complex<T> const & rhs);
    octonion<T> & operator /= (::boost::math::quaternion<T> const & rhs);
    template<typename X>

```

```
    octonion<T> & operator /= (octonion<X> const & rhs);  
};  
  
} } // namespaces
```


Octonion Specializations

```

namespace boost{ namespace math{

template<>
class octonion<float>
{
public:
    typedef float value_type;

    explicit octonion(float const & requested_a = 0.0f, float const & requested_b = 0.0f, float const & requested_c = 0.0f, float const & requested_d = 0.0f, float const & requested_e = 0.0f, float const & requested_f = 0.0f, float const & requested_g = 0.0f, float const & requested_h = 0.0f) {}
    explicit octonion(::std::complex<float> const & z0, ::std::complex<float> const & z1 = ::std::complex<float>(), float const & requested_c = 0.0f, float const & requested_d = 0.0f, float const & requested_e = 0.0f, float const & requested_f = 0.0f, float const & requested_g = 0.0f, float const & requested_h = 0.0f) {}
    explicit octonion(::boost::math::quaternion<float> const & q0, ::boost::math::quaternion<float> const & q1 = ::boost::math::quaternion<float>(), float const & requested_c = 0.0f, float const & requested_d = 0.0f, float const & requested_e = 0.0f, float const & requested_f = 0.0f, float const & requested_g = 0.0f, float const & requested_h = 0.0f) {}
    explicit octonion(octonion<double> const & a_recopier);
    explicit octonion(octonion<long double> const & a_recopier);

    float real() const;
    octonion<float> unreal() const;

    float R_component_1() const;
    float R_component_2() const;
    float R_component_3() const;
    float R_component_4() const;
    float R_component_5() const;
    float R_component_6() const;
    float R_component_7() const;
    float R_component_8() const;

    ::std::complex<float> C_component_1() const;
    ::std::complex<float> C_component_2() const;
    ::std::complex<float> C_component_3() const;
    ::std::complex<float> C_component_4() const;

    ::boost::math::quaternion<float> H_component_1() const;
    ::boost::math::quaternion<float> H_component_2() const;

    octonion<float> & operator = (octonion<float> const & a_affecter);
    template<typename X>
    octonion<float> & operator = (octonion<X> const & a_affecter);
    octonion<float> & operator = (float const & a_affecter);
    octonion<float> & operator = (::std::complex<float> const & a_affecter);
    octonion<float> & operator = (::boost::math::quaternion<float> const & a_affecter);

    octonion<float> & operator += (float const & rhs);
    octonion<float> & operator += (::std::complex<float> const & rhs);
    octonion<float> & operator += (::boost::math::quaternion<float> const & rhs);
    template<typename X>
    octonion<float> & operator += (octonion<X> const & rhs);

    octonion<float> & operator -= (float const & rhs);
    octonion<float> & operator -= (::std::complex<float> const & rhs);
    octonion<float> & operator -= (::boost::math::quaternion<float> const & rhs);
    template<typename X>
    octonion<float> & operator -= (octonion<X> const & rhs);

    octonion<float> & operator *= (float const & rhs);
    octonion<float> & operator *= (::std::complex<float> const & rhs);
    octonion<float> & operator *= (::boost::math::quaternion<float> const & rhs);
    template<typename X>
    octonion<float> & operator *= (octonion<X> const & rhs);

    octonion<float> & operator /= (float const & rhs);
    octonion<float> & operator /= (::std::complex<float> const & rhs);
    octonion<float> & operator /= (::boost::math::quaternion<float> const & rhs);
    template<typename X>

```

```
octonion<float> & operator /= (octonion<X> const & rhs) ;  
};
```

```

template<>
class octonion<double>
{
public:
    typedef double value_type;

    explicit octonion(double const & requested_a = 0.0, double const & requested_b = 0.0, double const & requested_c = 0.0, double const & requested_d = 0.0, double const & requested_e = 0.0, double const & requested_f = 0.0, double const & requested_g = 0.0, double const & requested_h = 0.0);
    explicit octonion(::std::complex<double> const & z0, ::std::complex<double> const & z1 = ::std::complex<double>(), double const & requested_c = 0.0, double const & requested_d = 0.0, double const & requested_e = 0.0, double const & requested_f = 0.0, double const & requested_g = 0.0, double const & requested_h = 0.0);
    explicit octonion(::boost::math::quaternion<double> const & q0, ::boost::math::quaternion<double> const & q1 = ::boost::math::quaternion<double>(), double const & requested_c = 0.0, double const & requested_d = 0.0, double const & requested_e = 0.0, double const & requested_f = 0.0, double const & requested_g = 0.0, double const & requested_h = 0.0);
    explicit octonion(octonion<float> const & a_recopier);
    explicit octonion(octonion<long double> const & a_recopier);

    double real() const;
    octonion<double> unreal() const;

    double R_component_1() const;
    double R_component_2() const;
    double R_component_3() const;
    double R_component_4() const;
    double R_component_5() const;
    double R_component_6() const;
    double R_component_7() const;
    double R_component_8() const;

    ::std::complex<double> C_component_1() const;
    ::std::complex<double> C_component_2() const;
    ::std::complex<double> C_component_3() const;
    ::std::complex<double> C_component_4() const;

    ::boost::math::quaternion<double> H_component_1() const;
    ::boost::math::quaternion<double> H_component_2() const;

    octonion<double> & operator = (octonion<double> const & a_affecter);
    template<typename X>
    octonion<double> & operator = (octonion<X> const & a_affecter);
    octonion<double> & operator = (double const & a_affecter);
    octonion<double> & operator = (::std::complex<double> const & a_affecter);
    octonion<double> & operator = (::boost::math::quaternion<double> const & a_affecter);

    octonion<double> & operator += (double const & rhs);
    octonion<double> & operator += (::std::complex<double> const & rhs);
    octonion<double> & operator += (::boost::math::quaternion<double> const & rhs);
    template<typename X>
    octonion<double> & operator += (octonion<X> const & rhs);

    octonion<double> & operator -= (double const & rhs);
    octonion<double> & operator -= (::std::complex<double> const & rhs);
    octonion<double> & operator -= (::boost::math::quaternion<double> const & rhs);
    template<typename X>
    octonion<double> & operator -= (octonion<X> const & rhs);

    octonion<double> & operator *= (double const & rhs);
    octonion<double> & operator *= (::std::complex<double> const & rhs);
    octonion<double> & operator *= (::boost::math::quaternion<double> const & rhs);
    template<typename X>
    octonion<double> & operator *= (octonion<X> const & rhs);

    octonion<double> & operator /= (double const & rhs);
    octonion<double> & operator /= (::std::complex<double> const & rhs);
    octonion<double> & operator /= (::boost::math::quaternion<double> const & rhs);
    template<typename X>
    octonion<double> & operator /= (octonion<X> const & rhs);
};

```

```

template<>
class octonion<long double>
{
public:
    typedef long double value_type;

    explicit octonion(long double const & requested_a = 0.0L, long double const & requested_b = 0.0L, long double const & requested_c = 0.0L, long double const & requested_d = 0.0L, long double const & requested_e = 0.0L, long double const & requested_f = 0.0L, long double const & requested_g = 0.0L, long double const & requested_h = 0.0L) {}
    explicit octonion( ::std::complex<long double> const & z0, ::std::complex<long double> const & z1, long double const & z2, long double const & z3, long double const & z4, long double const & z5, long double const & z6, long double const & z7, long double const & z8) {}
    explicit octonion( ::boost::math::quaternion<long double> const & q0, ::boost::math::quaternion<long double> const & q1, long double const & q2, long double const & q3, long double const & q4, long double const & q5, long double const & q6, long double const & q7, long double const & q8) {}
    explicit octonion(octonion<float> const & a_recopier);
    explicit octonion(octonion<double> const & a_recopier);

    long double real() const;
    octonion<long double> unreal() const;

    long double R_component_1() const;
    long double R_component_2() const;
    long double R_component_3() const;
    long double R_component_4() const;
    long double R_component_5() const;
    long double R_component_6() const;
    long double R_component_7() const;
    long double R_component_8() const;

    ::std::complex<long double> C_component_1() const;
    ::std::complex<long double> C_component_2() const;
    ::std::complex<long double> C_component_3() const;
    ::std::complex<long double> C_component_4() const;

    ::boost::math::quaternion<long double> H_component_1() const;
    ::boost::math::quaternion<long double> H_component_2() const;

    octonion<long double> & operator = (octonion<long double> const & a_affecter);
    template<typename X>
    octonion<long double> & operator = (octonion<X> const & a_affecter);
    octonion<long double> & operator = (long double const & a_affecter);
    octonion<long double> & operator = (::std::complex<long double> const & a_affecter);
    octonion<long double> & operator = (::boost::math::quaternion<long double> const & a_affecter);

    octonion<long double> & operator += (long double const & rhs);
    octonion<long double> & operator += (::std::complex<long double> const & rhs);
    octonion<long double> & operator += (::boost::math::quaternion<long double> const & rhs);
    template<typename X>
    octonion<long double> & operator += (octonion<X> const & rhs);

    octonion<long double> & operator -= (long double const & rhs);
    octonion<long double> & operator -= (::std::complex<long double> const & rhs);
    octonion<long double> & operator -= (::boost::math::quaternion<long double> const & rhs);
    template<typename X>
    octonion<long double> & operator -= (octonion<X> const & rhs);

    octonion<long double> & operator *= (long double const & rhs);
    octonion<long double> & operator *= (::std::complex<long double> const & rhs);
    octonion<long double> & operator *= (::boost::math::quaternion<long double> const & rhs);
    template<typename X>
    octonion<long double> & operator *= (octonion<X> const & rhs);

    octonion<long double> & operator /= (long double const & rhs);
    octonion<long double> & operator /= (::std::complex<long double> const & rhs);
    octonion<long double> & operator /= (::boost::math::quaternion<long double> const & rhs);
    template<typename X>
    octonion<long double> & operator /= (octonion<X> const & rhs);
};

```

```
} } // namespaces
```

Octonion Member Typedefs

value_type

Template version:

```
typedef T value_type;
```

Float specialization version:

```
typedef float value_type;
```

Double specialization version:

```
typedef double value_type;
```

Long double specialization version:

```
typedef long double value_type;
```

These provide easy access to the type the template is built upon.

Octonion Member Functions

Constructors

Template version:

```
explicit octonion(T const & requested_a = T(), T const & requested_b = T(), T const & requested_c = T(),  
explicit octonion(::std::complex<T> const & z0, ::std::complex<T> const & z1 = ::std::complex<T>(), ::s  
explicit octonion(::boost::math::quaternion<T> const & q0, ::boost::math::quaternion<T> const & q1 = ::  
template<typename X>  
explicit octonion(octonion<X> const & a_recopier);
```

Float specialization version:

```
explicit octonion(float const & requested_a = 0.0f, float const & requested_b = 0.0f, float const & requested_c = 0.0f,  
explicit octonion(::std::complex<float> const & z0, ::std::complex<float> const & z1 = ::std::complex<float>(), ::s  
explicit octonion(::boost::math::quaternion<float> const & q0, ::boost::math::quaternion<float> const & q1 = ::  
explicit octonion(octonion<double> const & a_recopier);  
explicit octonion(octonion<long double> const & a_recopier);
```

Double specialization version:

```
explicit octonion(double const & requested_a = 0.0, double const & requested_b = 0.0, double const & requested_c = 0.0,  
explicit octonion(::std::complex<double> const & z0, ::std::complex<double> const & z1 = ::std::complex<double>(), ::s  
explicit octonion(::boost::math::quaternion<double> const & q0, ::boost::math::quaternion<double> const & q1 = ::  
explicit octonion(octonion<float> const & a_recopier);  
explicit octonion(octonion<long double> const & a_recopier);
```

Long double specialization version:

```
explicit octonion(long double const & requested_a = 0.0L, long double const & requested_b = 0.0L, long double const & requested_c = 0.0L, long double const & requested_d = 0.0L, long double const & requested_e = 0.0L, long double const & requested_f = 0.0L, long double const & requested_g = 0.0L);
explicit octonion(std::complex<long double> const & z0, std::complex<long double> const & z1, std::complex<long double> const & z2, std::complex<long double> const & z3, std::complex<long double> const & z4, std::complex<long double> const & z5, std::complex<long double> const & z6, std::complex<long double> const & z7);
explicit octonion(boost::math::quaternion<long double> const & q0, boost::math::quaternion<long double> const & q1);
explicit octonion(octonion<float> const & a_recopier);
explicit octonion(octonion<double> const & a_recopier);
```

A default constructor is provided for each form, which initializes each component to the default values for their type (i.e. zero for floating numbers). This constructor can also accept one to eight base type arguments. A constructor is also provided to build octonions from one to four complex numbers sharing the same base type, and another taking one or two quaternions sharing the same base type. The unspecialized template also sports a templarized copy constructor, while the specialized forms have copy constructors from the other two specializations, which are explicit when a risk of precision loss exists. For the unspecialized form, the base type's constructors must not throw.

Destructors and untemplated copy constructors (from the same type) are provided by the compiler. Converting copy constructors make use of a templated helper function in a "detail" subnamespace.

Other member functions

Real and Unreal Parts

```
T          real() const;
octonion<T> unreal() const;
```

Like complex number, octonions do have a meaningful notion of "real part", but unlike them there is no meaningful notion of "imaginary part". Instead there is an "unreal part" which itself is a octonion, and usually nothing simpler (as opposed to the complex number case). These are returned by the first two functions.

Individual Real Components

```
T R_component_1() const;
T R_component_2() const;
T R_component_3() const;
T R_component_4() const;
T R_component_5() const;
T R_component_6() const;
T R_component_7() const;
T R_component_8() const;
```

A octonion having eight real components, these are returned by these eight functions. Hence real and R_component_1 return the same value.

Individual Complex Components

```
::std::complex<T> C_component_1() const;
::std::complex<T> C_component_2() const;
::std::complex<T> C_component_3() const;
::std::complex<T> C_component_4() const;
```

A octonion likewise has four complex components. Actually, octonions are indeed a (left) vector field over the complexes, but beware, as for any octonion $o = 1 + i + j + k + e' + i' + j' + k'$ we also have $o = (1 + i) + (j + i)j + (k + i)e' + (-i)j'$ (note the **minus** sign in the last factor). What the C_component_n functions return, however, are the complexes which could be used to build the octonion using the constructor, and **not** the components of the octonion on the basis $(1, j, e', j')$.

Individual Quaternion Components

```
::boost::math::quaternion<T> H_component_1() const;
::boost::math::quaternion<T> H_component_2() const;
```

Likewise, for any octonion $o = \text{real} + i + j + k + e' + i' + j' + k'$ we also have $o = (\text{real} + i + j + k) + (\text{real}' + i' + j' - k')e'$, though there is no meaningful vector-space-like structure based on the quaternions. What the `H_component_n` functions return are the quaternions which could be used to build the octonion using the constructor.

Octonion Member Operators

Assignment Operators

```
octonion<T> & operator = (octonion<T> const & a_affecter);
template<typename X>
octonion<T> & operator = (octonion<X> const & a_affecter);
octonion<T> & operator = (T const & a_affecter);
octonion<T> & operator = (::std::complex<T> const & a_affecter);
octonion<T> & operator = (::boost::math::quaternion<T> const & a_affecter);
```

These perform the expected assignment, with type modification if necessary (for instance, assigning from a base type will set the real part to that value, and all other components to zero). For the unspecialized form, the base type's assignment operators must not throw.

Other Member Operators

```
octonion<T> & operator += (T const & rhs)
octonion<T> & operator += (::std::complex<T> const & rhs);
octonion<T> & operator += (::boost::math::quaternion<T> const & rhs);
template<typename X>
octonion<T> & operator += (octonion<X> const & rhs);
```

These perform the mathematical operation $(*this) + rhs$ and store the result in $*this$. The unspecialized form has exception guards, which the specialized forms do not, so as to insure exception safety. For the unspecialized form, the base type's assignment operators must not throw.

```
octonion<T> & operator -= (T const & rhs)
octonion<T> & operator -= (::std::complex<T> const & rhs);
octonion<T> & operator -= (::boost::math::quaternion<T> const & rhs);
template<typename X>
octonion<T> & operator -= (octonion<X> const & rhs);
```

These perform the mathematical operation $(*this) - rhs$ and store the result in $*this$. The unspecialized form has exception guards, which the specialized forms do not, so as to insure exception safety. For the unspecialized form, the base type's assignment operators must not throw.

```
octonion<T> & operator *= (T const & rhs)
octonion<T> & operator *= (::std::complex<T> const & rhs);
octonion<T> & operator *= (::boost::math::quaternion<T> const & rhs);
template<typename X>
octonion<T> & operator *= (octonion<X> const & rhs);
```

These perform the mathematical operation $(*this) * rhs$ in this order (order is important as multiplication is not commutative for octonions) and store the result in $*this$. The unspecialized form has exception guards, which the specialized forms do not, so as to insure exception safety. For the unspecialized form, the base type's assignment operators must not throw. Also, for clarity's

sake, you should always group the factors in a multiplication by groups of two, as the multiplication is not even associative on the octonions (though there are of course cases where this does not matter, it usually does).

```
octonion<T> & operator /= (T const & rhs)
octonion<T> & operator /= (::std::complex<T> const & rhs);
octonion<T> & operator /= (::boost::math::quaternion<T> const & rhs);
template<typename X>
octonion<T> & operator /= (octonion<X> const & rhs);
```

These perform the mathematical operation `(*this)*inverse_of(rhs)` in this order (order is important as multiplication is not commutative for octonions) and store the result in `*this`. The unspecialized form has exception guards, which the specialized forms do not, so as to insure exception safety. For the unspecialized form, the base type's assignment operators must not throw. As for the multiplication, remember to group any two factors using parenthesis.

Octonion Non-Member Operators

Unary Plus and Minus Operators

```
template<typename T> octonion<T> operator + (octonion<T> const & o);
```

This unary operator simply returns `o`.

```
template<typename T> octonion<T> operator - (octonion<T> const & o);
```

This unary operator returns the opposite of `o`.

Binary Addition Operators

```
template<typename T> octonion<T> operator + (T const & lhs, octonion<T> const & rhs);
template<typename T> octonion<T> operator + (octonion<T> const & lhs, T const & rhs);
template<typename T> octonion<T> operator + (::std::complex<T> const & lhs, octonion<T> const & rhs);
template<typename T> octonion<T> operator + (octonion<T> const & lhs, ::std::complex<T> const & rhs);
template<typename T> octonion<T> operator + (::boost::math::quaternion<T> const & lhs, octonion<T> const & rhs);
template<typename T> octonion<T> operator + (octonion<T> const & lhs, ::boost::math::quaternion<T> const & rhs);
template<typename T> octonion<T> operator + (octonion<T> const & lhs, octonion<T> const & rhs);
```

These operators return `octonion<T>(lhs) += rhs`.

Binary Subtraction Operators

```
template<typename T> octonion<T> operator - (T const & lhs, octonion<T> const & rhs);
template<typename T> octonion<T> operator - (octonion<T> const & lhs, T const & rhs);
template<typename T> octonion<T> operator - (::std::complex<T> const & lhs, octonion<T> const & rhs);
template<typename T> octonion<T> operator - (octonion<T> const & lhs, ::std::complex<T> const & rhs);
template<typename T> octonion<T> operator - (::boost::math::quaternion<T> const & lhs, octonion<T> const & rhs);
template<typename T> octonion<T> operator - (octonion<T> const & lhs, ::boost::math::quaternion<T> const & rhs);
template<typename T> octonion<T> operator - (octonion<T> const & lhs, octonion<T> const & rhs);
```

These operators return `octonion<T>(lhs) -= rhs`.

Binary Multiplication Operators

```
template<typename T> octonion<T> operator * (T const & lhs, octonion<T> const & rhs);
template<typename T> octonion<T> operator * (octonion<T> const & lhs, T const & rhs);
template<typename T> octonion<T> operator * (::std::complex<T> const & lhs, octonion<T> const & rhs);
template<typename T> octonion<T> operator * (octonion<T> const & lhs, ::std::complex<T> const & rhs);
template<typename T> octonion<T> operator * (::boost::math::quaternion<T> const & lhs, octonion<T> const & rhs);
template<typename T> octonion<T> operator * (octonion<T> const & lhs, ::boost::math::quaternion<T> const & rhs);
template<typename T> octonion<T> operator * (octonion<T> const & lhs, octonion<T> const & rhs);
```

These operators return `octonion<T>(lhs) *= rhs`.

Binary Division Operators

```
template<typename T> octonion<T> operator / (T const & lhs, octonion<T> const & rhs);
template<typename T> octonion<T> operator / (octonion<T> const & lhs, T const & rhs);
template<typename T> octonion<T> operator / (::std::complex<T> const & lhs, octonion<T> const & rhs);
template<typename T> octonion<T> operator / (octonion<T> const & lhs, ::std::complex<T> const & rhs);
template<typename T> octonion<T> operator / (::boost::math::quaternion<T> const & lhs, octonion<T> const & rhs);
template<typename T> octonion<T> operator / (octonion<T> const & lhs, ::boost::math::quaternion<T> const & rhs);
template<typename T> octonion<T> operator / (octonion<T> const & lhs, octonion<T> const & rhs);
```

These operators return `octonion<T>(lhs) /= rhs`. It is of course still an error to divide by zero...

Binary Equality Operators

```
template<typename T> bool operator == (T const & lhs, octonion<T> const & rhs);
template<typename T> bool operator == (octonion<T> const & lhs, T const & rhs);
template<typename T> bool operator == (::std::complex<T> const & lhs, octonion<T> const & rhs);
template<typename T> bool operator == (octonion<T> const & lhs, ::std::complex<T> const & rhs);
template<typename T> bool operator == (::boost::math::quaternion<T> const & lhs, octonion<T> const & rhs);
template<typename T> bool operator == (octonion<T> const & lhs, ::boost::math::quaternion<T> const & rhs);
template<typename T> bool operator == (octonion<T> const & lhs, octonion<T> const & rhs);
```

These return true if and only if the four components of `octonion<T>(lhs)` are equal to their counterparts in `octonion<T>(rhs)`. As with any floating-type entity, this is essentially meaningless.

Binary Inequality Operators

```
template<typename T> bool operator != (T const & lhs, octonion<T> const & rhs);
template<typename T> bool operator != (octonion<T> const & lhs, T const & rhs);
template<typename T> bool operator != (::std::complex<T> const & lhs, octonion<T> const & rhs);
template<typename T> bool operator != (octonion<T> const & lhs, ::std::complex<T> const & rhs);
template<typename T> bool operator != (::boost::math::quaternion<T> const & lhs, octonion<T> const & rhs);
template<typename T> bool operator != (octonion<T> const & lhs, ::boost::math::quaternion<T> const & rhs);
template<typename T> bool operator != (octonion<T> const & lhs, octonion<T> const & rhs);
```

These return true if and only if `octonion<T>(lhs) == octonion<T>(rhs)` is false. As with any floating-type entity, this is essentially meaningless.

Stream Extractor

```
template<typename T, typename charT, class traits>
::std::basic_istream<charT,traits> & operator >> (::std::basic_istream<charT,traits> & is, octonion<T> & o);
```

Extracts an octonion `o`. We accept any format which seems reasonable. However, since this leads to a great many ambiguities, decisions were made to lift these. In case of doubt, stick to lists of reals.

The input values must be convertible to T. If bad input is encountered, calls `is.setstate(ios::failbit)` (which may throw `ios::failure` (27.4.5.3)).

Returns `is`.

Stream Inserter

```
template<typename T, typename charT, class traits>
::std::basic_ostream<charT,traits> & operator << ( ::std::basic_ostream<charT,traits> & os, octonion<T> o )
```

Inserts the octonion `o` onto the stream `os` as if it were implemented as follows:

```
template<typename T, typename charT, class traits>
::std::basic_ostream<charT,traits> & operator << ( ::std::basic_ostream<charT,traits> & os,
octonion<T> const & o )
{
    ::std::basic_ostringstream<charT,traits> s;

    s.flags(os.flags());
    s.imbue(os.getloc());
    s.precision(os.precision());

    s << '(' << o.R_component_1() << ',' <<
        << o.R_component_2() << ',' <<
        << o.R_component_3() << ',' <<
        << o.R_component_4() << ',' <<
        << o.R_component_5() << ',' <<
        << o.R_component_6() << ',' <<
        << o.R_component_7() << ',' <<
        << o.R_component_8() << ')';

    return os << s.str();
}
```

Octonion Value Operations

Real and Unreal

```
template<typename T> T real(octonion<T> const & o);
template<typename T> octonion<T> unreal(octonion<T> const & o);
```

These return `o.real()` and `o.unreal()` respectively.

conj

```
template<typename T> octonion<T> conj(octonion<T> const & o);
```

This returns the conjugate of the octonion.

sup

```
template<typename T> T sup(octonion<T> const & o);
```

This return the sup norm (the greatest among `abs(o.R_component_1())` . . . `abs(o.R_component_8())`) of the octonion.

abs

norm

Octonion Creation Functions

Octonions Transcendentals

We do, however provide several transcendentals, chief among which is the exponential. That it allows for a "closed formula" is a result of the author (the existence and definition of the exponential, on the octonions among others, on the other hand, is a few cen-

turies old). Basically, any converging power series with real coefficients which allows for a closed formula in \mathbb{C} can be transposed to \mathbb{O} . More transcendentals of this type could be added in a further revision upon request. It should be noted that it is these functions which force the dependency upon the [boost/math/special_functions/sinc.hpp](#) and the [boost/math/special_functions/sinhc.hpp](#) headers.

exp

```
template<typename T>
octonion<T> exp(octonion<T> const & o);
```

Computes the exponential of the octonion.

cos

```
template<typename T>
octonion<T> cos(octonion<T> const & o);
```

Computes the cosine of the octonion

sin

```
template<typename T>
octonion<T> sin(octonion<T> const & o);
```

Computes the sine of the octonion.

tan

```
template<typename T>
octonion<T> tan(octonion<T> const & o);
```

Computes the tangent of the octonion.

cosh

```
template<typename T>
octonion<T> cosh(octonion<T> const & o);
```

Computes the hyperbolic cosine of the octonion.

sinh

```
template<typename T>
octonion<T> sinh(octonion<T> const & o);
```

Computes the hyperbolic sine of the octonion.

tanh

```
template<typename T>
octonion<T> tanh(octonion<T> const & o);
```

Computes the hyperbolic tangent of the octonion.

pow

```
template<typename T>
octonion<T> pow(octonion<T> const & o, int n);
```

Computes the n-th power of the octonion q.

Test Program

The `octonion_test.cpp` test program tests octonions specialisations for float, double and long double ([sample output](#)).

If you define the symbol `BOOST_OCTONION_TEST_VERBOSE`, you will get additional output ([verbose output](#)); this will only be helpful if you enable message output at the same time, of course (by uncommenting the relevant line in the test or by adding `--log_level=messages` to your command line,...). In that case, and if you are running interactively, you may in addition define the symbol `BOOST_INTERACTIVE_TEST_INPUT_ITERATOR` to interactively test the input operator with input of your choice from the standard input (instead of hard-coding it in the test).

Acknowledgements

The mathematical text has been typeset with [Nisus Writer](#). Jens Maurer has helped with portability and standard adherence, and was the Review Manager for this library. More acknowledgements in the History section. Thank you to all who contributed to the discussion about this library.

History

- 1.5.8 - 17/12/2005: Converted documentation to Quickbook Format.
- 1.5.7 - 25/02/2003: transitionned to the unit test framework; `<boost/config.hpp>` now included by the library header (rather than the test files), via `<boost/math/quaternion.hpp>`.
- 1.5.6 - 15/10/2002: Gcc2.95.x and stlport on linux compatibility by Alkis Evlogimenos (alkis@routescience.com).
- 1.5.5 - 27/09/2002: Microsoft VCPP 7 compatibility, by Michael Stevens (michael@acfr.usyd.edu.au); requires the /Za compiler option.
- 1.5.4 - 19/09/2002: fixed problem with multiple inclusion (in different translation units); attempt at an improved compatibility with Microsoft compilers, by Michael Stevens (michael@acfr.usyd.edu.au) and Fredrik Blomqvist; other compatibility fixes.
- 1.5.3 - 01/02/2002: bugfix and Gcc 2.95.3 compatibility by Douglas Gregor (gregod@cs.rpi.edu).
- 1.5.2 - 07/07/2001: introduced namespace math.
- 1.5.1 - 07/06/2001: (end of Boost review) now includes `<boost/math/special_functions/sinc.hpp>` and `<boost/math/special_functions/sinhc.hpp>` instead of `<boost/special_functions.hpp>`; corrected bug in `sin` (Daryle Walker); removed check for self-assignment (Gary Powel); made converting functions explicit (Gary Powel); added overflow guards for division operators and `abs` (Peter Schmitteckert); added `sup` and `ll`; used Vesa Karvonen's CPP metaprograming technique to simplify code.
- 1.5.0 - 23/03/2001: boostification, inlining of all operators except input, output and `pow`, fixed exception safety of some members (template version).
- 1.4.0 - 09/01/2001: added `tan` and `tanh`.
- 1.3.1 - 08/01/2001: cosmetic fixes.
- 1.3.0 - 12/07/2000: `pow` now uses Maarten Hilferink's (mhilferink@tip.nl) algorithm.
- 1.2.0 - 25/05/2000: fixed the division operators and output; changed many signatures.

- 1.1.0 - 23/05/2000: changed sinc into sinc_pi; added sin, cos, sinh, cosh.
- 1.0.0 - 10/08/1999: first public version.

To Do

- Improve testing.
- Rewrite input operators using Spirit (creates a dependency).
- Put in place an Expression Template mechanism (perhaps borrowing from uBlas).