

# Study Guide Project Improvement

Tong Yi

In this project, we display questions and answer them. If the answer is correct, we display true, otherwise, we display false. This project can serve as a study guide for our courses or Civics (History and Government) Questions for the Naturalization Test, as in <https://www.uscis.gov/sites/default/files/document/questions-and-answers/100q.pdf>.

## Warning:

1. These are copyrighted materials and cannot be uploaded to the Internet.
2. Only ask help from teaching staff of this course.
3. Use solutions from ChatGPT or online tutoring websites like, but not limited to, chegg.com, violates academic integrity and is not allowed.

## 1 Task A: organize the program into functions

Motivation: In previous tasks, we put every code in main function. Also, we enter a file name and read its contents. We may need to read several files, for example,

`cs135_midterm_f24_v1.txt` and `cs135_midterm_f24_v2.txt`.

Then add the questions to an array of Questions.

In Task A, we do the following.

1. Name your source code `checkAnswer_function.cpp`.
2. Define function

```
void read_file(string fileName, Question ques[], int capacity, int& size);
```

Note that the return type is void, but the size of the array may be increased after reading a file, so size needs to be passed by reference. See the `&` near type `int` for parameter size?

(a) Given struct Question as follows.

```
1 struct Question {
2     string text; //question text
3     string answer;
4     string explanation;
5     string version;
6     string type;
7     string label;
8 };
```

- (b) Read a file whose name is saved in `fileName`.
  - (c) Read each question in the file, if the current size `Question` array `ques` does not equal to the capacity of the array, add to the end of the array. Increase the current size by 1.
3. Download [link to cs135 midterm f24 v1](#).
  4. Download [link to cs135 midterm f24 v2](#).
  5. Download [link to cs135 midterm s24 v1](#).
  6. Define `void display(Question ques[], int size)` function, which displays the fields of each question in array `ques`. You need to fill in the ... parts.

```

1 void display(Question ques[], int size) {
2     for (int i = ...; i < ...; ...) {
3         cout << i + 1 << endl; //start labeling from 1
4
5         //display question text of the ith question
6         cout << "question: " << ... << endl;
7
8         //display answer of the ith question
9         cout << "answer: " << ... << endl;
10
11        //display explanation of the ith question
12        cout << "explanation: " << ... << endl;
13        cout << "type: " << ... << endl;
14        cout << "version: " << ... << endl;
15        cout << "label: " << ... << endl;
16        cout << endl;
17    }
18 }

```

7. In main function, test `read_file` function as follows.

```

1 int main() {
2     const int CAPACITY = 1000;
3     Question ques[CAPACITY]; //question array
4
5     int size = 0;
6
7     //TODO: call read_file for "cs135_midterm_f24_v1.txt",
8     //save the questions in array ques if the capacity is not yet
9     reached.
10
11    //TODO: call read_file for "cs135_midterm_f24_v2.txt",
12    //save the questions in array ques if the capacity is not yet
13    reached.

```

```

13 //TODO: call read_file to read "cs135_midterm_s24_v1.txt"
14
15 //TODO: call display function on array ques.
16 //Do not forget to pass the size of array ques,
17 //that is, the number of elements in ques,
18 //as the second parameter.
19
20 return 0;
21 }

```

Here is a sample output (the number of empty lines between fields might be a little different).

```

1 1
2 question: Given char arr[] = {'A', 'B', 'C'}, what is arr[1]?
3 answer: 'B'
4 explanation: arr[1] is the second element of array arr, which is 'B'
   in this example.
5
6 type: array
7 version: f24 v1
8 label: 1.1
9
10 2
11 question: Declare function increase, given an integer array arr with
   size many elements, increase each element of the array by 1.
   Return type is void. Define the function header (no implementation
   is needed).
12 answer: void increase(int arr[], int size);
13 explanation: (1) the first parameter is int arr[], the name of array
   arr, which also implies the address of the first element of array.
14 (2) the second parameter represents the number of elements of the
   array.
15
16 type: function; array
17 version: f24 v1
18 label: 1.2
19
20 3
21 question: Assume that n is properly declared and initialized. Write a
   statement to declare lastDigit as an integer and initialize it to
   be the least significant digit of integer n. Suppose n is 123,
   after the statement, lastDigit is 3.
22 answer: int lastDigit = n % 10;
23 explanation: (1) operator % is called remainder or modular operator.
24 (2) For example, 12 % 10 means the remainder when dividing 12 pens
   among 10 students, each student gets 1 pen, and there are 2 pens
   left.

```

```

25 (3) In general, n % 10 returns the last digit, or the rightmost digit
    (least significant digit), of n.
26 (4) int lastDigit = n % 10; is a statement to declare lastDigit as an
    int and initialize it by the last digit of n.
27
28 type: arithmetic; modular; remainder
29 version: f24 v1
30 label: 1.3
31
32 ... //omit the contents
33
34 29
35 question: What is the output for the following code?
36 #include <iostream>
37 using namespace std;
38
39 void foo(int& a, int b);
40
41 int main() {
42     int i = 1;
43     int j = 3;
44     foo(i, j);
45     cout << "i = " << i
46         << ", j = " << j << endl;
47
48     return 0;
49 }
50
51 void foo(int& a, int b) {
52     a++;
53     b--;
54 }
55
56
57 answer: i = 2, j = 3
58 explanation:
59 type: function; pass by value; pass by reference
60 version: s24 v1
61 label: 1.9
62
63 30
64 question: Write a condition to represent that char variable ch is
    none of the following: 'a', 'b', or 'c'.
65 answer: (ch != 'a' && ch != 'b' && ch != 'c')
66 explanation: another solution is (! (ch == 'a' || ch == 'b' || ch ==
    'c'))

```

```
67  
68 type: condition  
69 version: s24 v1  
70 label: 1.10
```

## 2 Task B: more functions

The goal is to organize the tasks into functions, each concentrate on a task. In this way, we can unit test a function before moving to the next.

Here is an outline.

1. Name your source code `checkAnswer_function_rand.cpp`.
2. Extract types from `type` field of `Question`, which is separated by semicolons (symbol `;`).
3. The `type` field of a question may involve more than one type. As a result, we need to use an array to hold each type.
  - (a) If a type is  
`integer division; arithmetic`  
Then the returned array has two elements: `integer division` and `arithmetic`.
  - (b) If a type is  
`integer division; arithmetic; remainder`  
Then the returned array has three elements: `integer division`, `arithmetic` and `remainder`.
4. Then add the types to an array of strings. Make sure that the array is sorted.
5. Define a function to answer questions based on types.
6. Define a function to give feedback.

In this task, we define functions, let each function concentrate on a task, then main function calls the key functions.

### 2.1 Define function `trim`

Define a function to trim (remove) all the spaces before the leftmost non-space character and all the spaces after the rightmost non-space character from a string.

```
1 string trim(string str);
```

For example, `trim(" hello, world ")` should return `"hello, world"`.

1. Why do we need the function? When we extract possible types from `type` field of a question, the extracted result might contain spaces before the first non-space character and the after the last non-space character, to avoid adding " `array` " and `"array"` to the array at the same time, we only add a type without those extra spaces.

2. Here are some hints for this function.

- (a) Find out the index of first non-space character of a string using `find_first_not_of` method. Or, search the string from the first character to the last character until there is no more character in the string or the first non-space character is encountered. Save that index.
- (b) Find the index of the last non-space character of a string using `find_last_not_of` method. Or, search the string **backwards** from the last character to the first one until there is no more character or a non-space character is found. Save the index.
- (c) Use `substr` method to find out the substring between those two indices (inclusive). Note that the first parameter of `substr` method in C++ is the index of the first character of the resulting substring in the original string, and the second parameter is the number of characters in the substring.

## 2.2 Define function `count_occurrence`

Define a function to count number of occurrences of a char `ch` in string `str`.

```
1 int count_occurrence(string str, char ch);
```

- 1. Refer to Lab 7A for help. This function belongs a category called counting. Given an array, find out the number of elements of a feature (equal to something, longer than or larger than something, and so on).
- 2. A string can be thought as an array of characters (type `char`) with methods to find out number of elements using its `length` or `size` method.

Warning: an array of C++ is not a class, so dot operator does not apply. Specifically, the size of an array needs to be given explicitly in a function.

In general, codes for array can be modified to work on similar problems for strings.

- 3. Call the above function to find out the number of semicolons of the type field of a question to find out the number of elements in a dynamically allocated array in function `extract_type`.

If the number of semicolons is `n`, then the number of types in this type field is `n+1`. For example, if there are two semicolons like the type field `integer division; arithmetic; remainder`, then the number of individual types is 3.

We need this number as the size to apply for a dynamically allocated array of strings to hold the types in that type field.

## 2.3 Define function `extract_type`

Extract types separated by semicolon symbol (`;`) and put the types in an array of dynamically allocated string array.

```
1 string* extract_type(string type, int& num_types_curr_item);
```

The return type is `string*`, which saves the initial address of the dynamically allocated memory.

1. Need a parameter to hold the number of elements in this array. Since a function in C++ can return at most one value, we need to work around this limit by pass a parameter by reference as shown in `int& num_types_curr_item`, where `&` after `int` means the following parameter pass by reference.

Pass by reference means the formal parameter is the **original** actual parameter (aka argument). Whatever change made on the formal parameter in the function is carried back to its caller.

By contrast, pass by value – no `&` after the type in formal parameters in function header – means to a formal parameter is the **duplicated** copy of the actual parameter. Whatever changes made on the duplicated copy, it will not affect the actual parameter in the caller function, unless the value is returned.

Note that if a formal parameter is an array, which implies the address of the first element of the array, then the contents of the array can be modified. Reason: each element has a unique address. Once the address is know, we can access and may change the elements.

2. Here are some hints.

- (a) Call `count_occurrences` to find out number of semicolon symbol (`;`) in `type`, add 1 to this value (why?) and save it to `num_types_curr_item`.
- (b) Apply a dynamically allocated array of strings with size `num_types_curr_item`.
- (c) Extract the corresponding types in `type` separated by semicolon (`;`).
- (d) Trim those obtained types and save them to the dynamically allocated array.
- (e) Return the dynamically allocated array. No need to sort the array.
  - i. For example, if the argument for `type` is `integer division; array; remainder`, apply a dynamically allocated array of size 3. Initialize with elements "integer division", "array", and "remainder". Return the dynamically allocated array.

3. Students may wonder what the difference of statically allocated memory and dynamically allocated memory are.

- (a) Statically allocated array memory, whose size is a const int, is allocated in the stack or a separate data segment (also known as the static memory region).
- (b) Dynamically allocated array memory, whose size can be an int variable, is allocated from heap.
- (c) Statically allocated memory is released once a function finishes and returns to its caller. So a statically allocated array declared and initialized in a callee function cannot return to its caller.
- (d) Dynamically allocated array applied in a callee function can be carried back to its caller. That is, dynamically allocated memory allocated in a callee function can be kept even after the callee function finishes.
- (e) Related example: you may rent a textbook for 120 days. After the expiration date, the book is returned to the publisher, whether you like it or not. The publisher removes the book from your bookshelf.

This is like statically allocated memory is released back to the operating system automatically when the function ends.

On the other hand, my textbook came from a different branch (memory) of the publisher (system). My book is like dynamically allocated memory. I can keep it until I no longer need the book and then return it to the publisher. The return is initialized from me.

It is like I use **new** (fill an application) to apply for an instructor book from the publisher. When I no longer need the book (memory), I use **delete** (remove the book from my bookshelf) to return it.

## 2.4 Define function `insert_order_unique`

```
1 void insert_order_unique(string types[], int type_capacity, int&  
    type_count, string  
    toAdd);
```

These are parameters.

1. `types`: an already-sorted array of strings
2. `type_capacity`: capacity of array `types`, that is, the maximum number of elements array `types` can hold.
3. `type_count`: number of current elements in `types`
4. `toAdd`: a string to be added to `types`
5. Goal: insert `toAdd` to `types` if there the string does not appear in the array and the array is not full. The array is sorted before insertion and need to be sorted after insertion. Here are some hints.
  - (a) If the array is full, that is, `type_count` is larger than or equal to `type_capacity`, do nothing and return.
  - (b) Traverse through the array until the end is reached or the elements are smaller than `toAdd`. String `a` is smaller than string `b` means `a` appears in a dictionary before `b`. For example, "`success`" is smaller than "`work`" since "`success`" appears before "`work`" in dictionary.
  - (c) If the end is reached, that means all current elements are smaller than `toAdd`, add `toAdd` to the end.
  - (d) Otherwise, there is an element in the array is larger than or equal to `toAdd`.
    - i. If they are equal, no need to add a type already saved in the array, do nothing and return to the caller.
    - ii. Otherwise, move the element in the array and all its right side neighbor one spot to the right to make room for `toAdd`.
    - iii. Put `toAdd` to the correct position.
    - iv. After `toAdd` is inserted, increase `type_count` by 1.
6. Here is a summary on the sorting algorithms we have learned so far.
  - (a) Learn bubble sort on 3/6/25. Key idea: swap out-of-order adjacent pairs from beginning to the end, doing so would put the largest element to the rightmost position.
    - i. Repeat the above process to put the second largest element to the second-to-rightmost position. Keep the process until  $n - 1$  out of  $n$  elements are in their correct position after sorting, where  $n$  is the number of element of the array.



- ii. In Problem 1.9 of midterm of Spring 25, we test bubble sort in descending order.
- (b) On 3/10/25, we share ideas of homework E5.14 and E5.15, to put four elements **a**, **b**, **c**, and **d** in order.
  - i. First, if **a** is larger than **b**, we swap **a** and **b**. Now **a** is the smaller of **a** and **b**.
  - ii. Second, if **a** is larger than **c**, swap **a** and **c**. Now **a** is the smallest of **a**, **b**, and **c**.
  - iii. Third, if **a** is larger than **d**, swap **a** and **d**. Now **a** is the smallest of **a**, **b**, **c**, and **d**.
  - iv. Repeat the above process to work with **b**, **c**, and **d**.
  - v. In general, select the smallest element of an array and put it in the first position of the array. Select the second smallest element of the array and put it in the second position of the array, and so on. This is the key idea of selection sort.
- (c) In this project, we learn insertion sort, insert an element to a sorted array and keep it sorted after insertion.
- (d) Bubble sort, selection sort, and insert sort are not efficient. The most efficient sorting algorithm is quick sort.

## 2.5 Define function `insert_order_unique` for types of each question

```
1 void insert_order_unique(string types[], int type_capacity, int&
   type_count, Question ques[], int ques_size);
```

1. You may notice the function has exact the same name as the above function but the parameter list is different. This is called **function overload**. That is, two or more functions have
  - (a) exactly the same name
  - (b) similar functionality
  - (c) different parameter lists. The difference can be shown in
    - i. number of parameters  
For example, `substr(int)` and `substr(int, int)`. The first function takes only one parameter, while the second one takes two parameters.
    - ii. type of parameters  
For example, `int foo(int a)` and `string foo(string str)`, where `foo` is a function name when we do not want to delve in details. It like we use John Doe to represent a person.
    - iii. order of parameters  
For example, `int foo(int, string)` is different from `int foo(string, int)`.
  - (d) It does not matter whether the return types are the same or not.
  - (e) An example in daily life involves two washing machines.
    - i. One is used in home, which has only an input slot for laundries. It is similar to a function with only one input parameter.
    - ii. The other is for commercial usage, which has one more input slot to take in money. It is similar to a function with two input parameters.

- iii. Both machines provide similar functionalities called wash, no need to use two different names `home_wash` and `commerical_wash`.

2. In this function, for each question,

- (a) Call the following function to extract each type from `type` field of a question.

```
1 string* extract_type(string type, int& num_types_curr_item);
```

- (b) Call the following version to insert each type to array `types`.

```
1 void insert_order_unique(string types[], int type_capacity, int&
   type_count, string
   toAdd);
```

- (c) Do not forget to release dynamically allocated memory returned from `extract_type` function. Afterwards, `types` save all types, once and exactly once, from the `type` field of all questions in sorted order.

## 2.6 Define function choose\_type

The function header shows as follows.

```
1 string choose_type(string* types, int type_count);
```

The goal of this function is to list available types from sorted array `types`, where the label of the first type starts from 1. If 0 is chosen, then all types are chosen, which is represented by an empty string.

Do the following.

1. Print string "0. ALL TYPES" with a new line.
2. Print items from sorted array `types`, where the label of the first type starts from label 1. The label of the last type is `type_count`.
3. Ensure to choose an integer in `[0, type_count]`, where both ends are included. If the number is out of range, prompt the user to select again.
4. If a user chooses 0, then return an empty string representing all types, otherwise, return the corresponding item in array `types`. Note that the label starts from 1, but the index starts from 0, so there is an offset by 1.

## 2.7 Define function randomize

Sometimes we work on the problems in a fixed order and memorize the answer. To avoid this situation, we randomize array of questions.

```
1 void randomize(Question ques[], int size);
```

You **must** follow the ideas listed below, or your code will not pass gradescope.

1. Declare an integer variable to save number of elements to be randomized. Call it `numToRandomize`. Initialize it to be `size`.
2. Choose a random integer in `[0, numToRandomize)`. That is, a random integer that is at least 0 but is smaller than `numToRandomize`. That is a valid index of the sub-array of the first `numToRandomize` elements.
3. The above step is like to choose the element indexed at that generated random number. To avoid that element to be chosen again, swap the element with the element indexed at `numToRandomize - 1`, the last element in the sub-array with the first `numToRandomize` elements.
4. Reduce `numToRandomize` by 1.
5. Repeat the above process by going back to Step 2 until `numToRandomize` is reduced to 1.

## 2.8 Define function feedback

Based on the number of problems correctly answered and the total number of problems worked, print feedback to users.

```
1 void feedback(int numCorrect, int numQuestions);
```

Do the following in the function.

1. Print out the number of correctly answered questions, saved in parameter `numCorrect` in a line.
2. Calculate and print the percentage based on `numCorrect` and `numQuestions`. The latter is the total number of questions worked.
3. If percentage is at least 90%, print "excellent", otherwise, if percentage is at least 80%, print "good", otherwise, if percentage is at least 70%, print "pass", otherwise, print "please ask help ASAP".

## 2.9 Define function answer\_by\_type

```
1 void answer_by_type(Question ques[], int size, string chosenType);
```

Given array `ques` of questions and its `size`, select all questions whose type contains `chosenType`. That is, search `chosenType` from the type field of each element of `ques`. Each user has at most 3 tries to answer a question. After providing three wrong answers, or, correctly answer the question in at most three tries, move to the next question in array of Questions. Record the number of correctly answered questions.

Call `feedback` function and provide feedback to users.

## 2.10 When to call `cin.ignore(INT_MAX, 'n')` statement?

The above statement ignores the remaining characters, including new line character, left in the keyboard buffer.

The above line is useful in the following pseudocode.

```

1 //File name: use_cin_ignore.cpp
2 //sample input:
3 //Enter your age: 18
4 //Enter your major: Your age is 18
5 //Your major is
6
7 #include <iostream>
8 #include <string>
9 using namespace std;
10
11 int main() {
12     cout << "Enter your age: ";
13     int age;
14     cin >> age;
15
16     cout << "Enter your major: ";
17     string major;
18     getline(cin, major);
19     //major might contain spaces,
20     //so we use getline function to read the whole line.
21
22     cout << "Your age is " << age << endl;
23     cout << "Your major is " << major << endl;
24     return 0;
25 }

```

When `getline(cin, stringVariable);` follows `cin >> variable;`.

1. To finish input, need to enter return key, which is `\n` new line character.
2. However, Operator `>>` only takes input before `\n`.
3. If statement `getline(cin, stringVariable);` follows, then `getline` statement takes everything before and at `\n`. So it is like to `stringVariable` is set to be an empty string. This might not be what we want.
4. Fix: add `cin.ignore(INT_MAX, '\n');` to clear the keyboard buffer.

```

1 //sample input / output:
2 //Enter your age: 18
3 //Enter your major: computer science
4 //Your age is 18
5 //Your major is computer science
6
7 #include <iostream>
8 #include <string>
9 using namespace std;
10

```

```

11 int main() {
12     cout << "Enter your age: ";
13     int age;
14     cin >> age;
15
16     cin.ignore(INT_MAX, '\n'); //ADD
17     //ignore the remaining contents of keyboard buffer.
18
19     cout << "Enter your major: ";
20     string major;
21     getline(cin, major); //major might contain spaces
22     cout << "Your age is " << age << endl;
23     cout << "Your major is " << major << endl;
24     return 0;
25 }

```

## 2.11 Unit test each function

Here is `unit_test.cpp`, downloaded from [link to unit\\_test.cpp](#), which tests each function. Note that the following `main` function takes parameters, parameter `argv` is the number of parameters, parameter `argc` is an array of `char*` – an array of chars, string variable in C – to hold those parameters.

To test functions of `checkAnswer_function_rand.cpp`, do the following.

1. We have two files, `checkAnswer_function_rand.cpp` and `unit_test.cpp`.
2. File `checkAnswer_function_rand.cpp` is source code of our project.
3. Both files have `main` functions. However, each C++ project can have only one `main` function.
4. To use the `main` function from `unit_test.cpp`, change the name of function `main` of `checkAnswer_function_rand.cpp` to be `main2` when we run unit test for functions in the above source code.

In terminal, run the following command with return key.

(a) `g++ -std=c++20 unit_test.cpp -o test`

If there is no error, a runnable file called `test` is generated. Run the following commands to test functions of our source code.

```

./test 3
./test 4
...
./test c

```

5. Remember to change function `main2` back to `main` when running `checkAnswer_function_rand.cpp`.

```

1 #include <iostream>
2 #include <string>
3 #include <climits> //INT_MAX
4 #include "checkAnswer_function_rand.cpp"
5
6 //How to run this file:
7 //1. We have two files, checkAnswer_function_rand.cpp and unit_test.cpp.
8 //2. File checkAnswer_function_rand.cpp is the source code of our project
9 //3. unit_test.cpp is to test functions defined in
   checkAnswer_function_rand.cpp.
10 //4. Both files have main functions. However, each C++ project can have
   only one main function.
11 //5. To run the main function in unit_test.cpp, change the name of
   function main of checkAnswer_function_rand.cpp to be main2.
12 //6. g++ -std=c++20 unit_test.cpp -o test
13 //7. If there is no error in unit_test.cpp, a runnable file called test
   is generated, run the following commands with return key to test each
   function.
14
15 //./test 1
16 //or
17 //./test 2
18 //./test 3
19 //...
20 //./test c
21
22 //8. Change main2 function in checkAnswer_function_rand.cpp back to main.
23
24 void read_file_into_array(Question ques[], int capacity);
25
26 int main(int argc, char** argv) {
27     if (argc < 2) {
28         std::cout << "missing argument in main function" << std::endl;
29         exit(0);
30     }
31
32     //test answer_by_type
33     Question q1;
34     q1.text = "Given char arr[] = {'A', 'B', 'C'}, what is arr[1]?";
35     q1.answer = "'B'";
36     q1.explanation = "arr[1] is the second element of array arr,
   which is 'B' in this example.";
37     q1.version = "f24 v1";
38     q1.label = "1.1";
39     q1.type = "array";

```

```

40
41 Question q2;
42 q2.text = "Declare function increase, given an integer array
      arr with size many elements, increase each element of the
      array by 1. Return type is void. Define the function
      header (no implementation is needed).";
43 q2.answer = "void increase(int arr[], int size);";
44 q2.explanation = "(1) the first parameter is int arr[], the
      name of array arr, which also implies the address of the
      first element of array.\n(2) the second parameter
      represents the number of elements of the array.";
45 q2.version = "f24 v1";
46 q2.label = "1.2";
47 q2.type = "function; array";
48
49 Question q3;
50 q3.text = "Assume that n is properly declared and initialized
      . Write a statement to declare lastDigit as an integer and
      initialize it to be the least significant digit of
      integer n. Suppose n is 123, after the statement,
      lastDigit is 3.";
51 q3.answer = "int lastDigit = n % 10;";
52 q3.explanation = "(1) operator % is called remainder or
      modular operator.\n(2) For example, 12 % 10 means the
      remainder when dividing 12 pens among 10 students, each
      student gets 1 pen, and there are 2 pens left.\n(3) In
      general, n % 10 returns the last digit, or the rightmost
      digit (least significant digit), of n.\n(4) int lastDigit
      = n % 10; is a statement to declare lastDigit as an int
      and initialize it by the last digit of n.";
53 q3.version = "f24 v1";
54 q3.label = "1.3";
55 q3.type = "arithmetic; modular; remainder";
56
57 Question q4;
58 q4.text = "What is the output?\n\nstring tens_name(int n);\n
      nint main() {\n      cout << tens_name(82) << endl;\n
      return 0;\n}\nstring tens_name(int n) {\n      if (n < 20 ||
      n > 99)\n      return \"\";\n      string names[] =
      {\"\", \"\", \"twenty\", \"thirty\", \"forty\", \"fifty\",
      \"sixty\", \"seventy\", \"eighty\", \"ninety\"};\n
      return names[n / 10];\n}";
59 q4.answer = "eighty";
60 q4.explanation = "(1) When calling tens_name(82), n in
      tens_name is initialized to be 82.\n(2) Since 82 is not
      less than 20 or 82 is not larger than 99, no return \"\";\n

```

```
n(3) 82 / 10 is integer division. It is like to divide 82
pens among 10 students, each student get 8 pens. So 82 /
10 returns 8.\n(4) names[n / 10] is names[82 / 10], which
is names[8].\n\nindex      0      1      2      3      4
      5      6      7      8\n\nelement
```

```
n\|\\"|\\"|\\"|\\"twenty\\"|\\"thirty\\"|\\"forty\\"|\\"fifty\\"|\\"
sixty\\"|\\"seventy\\"|\\"eighty\\"|\\"...\n
```

```
n\n(5) The return of tens_name(82) is \"eighty\".\n(6) In
main function, print tens_name(82), so the print out is \"
eighty\" (without quotes).";
```

```
q4.version = "f24 v1";
q4.label = "1.4";
q4.type = "integer division; array";
```

```
Question ques[] = {q1, q2, q3, q4};
```

```
int size = sizeof(ques) / sizeof(ques[0]);
```

```
switch (*argv[1]) {
    case '1': {
        const int CAPACITY = 1000;
        Question ques[CAPACITY]; //question array

        read_file_into_array(ques, CAPACITY);
        break;
    }

    case '2': {
        //test when capacity is reached
        const int CAPACITY = 25;
        Question ques[CAPACITY]; //question array

        read_file_into_array(ques, CAPACITY);
        break;
    }

    case '3': {
        //test trim
        //the string is given randomly in gradescript
        cout << "Enter a string: ";
        string inputStr;
        getline(cin, inputStr);
        //cout << "input String: " << inputStr << endl;
    }
}
```



```

95         string trimmedStr = trim(inputStr);
96         cout << "\""
97             << trimmedStr << "\"";
98         break;
99
100 //Run ./test 3
101 //sample input / output
102 //Enter a string:     Hello, World
103 // "Hello, World"
104     }
105     case '4': {
106         //test string* extract_type(string type, int&
107             num_types_curr_item)
108         string types[] = {"function; array",
109             "arithmetic; modular; remainder",          "integer
110             division; array" };
111         for (string type : types) {
112             int num_types_curr_item = 0;
113             string* pStr = extract_type(type, num_types_curr_item);
114             for (int i = 0; i < num_types_curr_item; i++)
115                 cout << pStr[i] << endl;
116
117             //release dynamically allocated memory
118             delete[] pStr;
119             pStr = nullptr;
120         }
121
122         break;
123
124 //run
125 //./test 4
126 //Sample input/output:
127 //function
128 //array
129 //arithmetic
130 //modular
131 //remainder
132 //integer division
133 //array
134     }
135     case '5': {
136         //test int count_occurrences(string str, char ch)
137         string strs[] = {"integer division; array", "arithmetic;
138             modular; remainder"};
139         int size = sizeof(strs) / sizeof(strs[0]);

```

```

138         for (int i = 0; i < size; i++) {
139             cout << count_occurrences(strs[i], ';') << endl;
140             cout << count_occurrences(strs[i], 'a') << endl;
141         }
142
143         break;
144 //Run ./test 5 in terminal
145 //Here is the sample input / output:
146         //1
147         //2
148         //2
149         //3
150     }
151
152     case '6': {
153         //insert_order_unique(string types[], int type_capacity, int&
154         type_count, string toAdd)
155         const int TYPE_CAPACITY = 30;
156         string types[TYPE_CAPACITY];
157         int type_count = 0;
158
159         string elmsToAdd[] = {"function",
160             "array",
161             "integer division",
162             "array"
163         };
164
165         for (string str: elmsToAdd) {
166             insert_order_unique(types,
167                 , type_count, str);
168
169             cout << type_count << endl;
170             for (int i = 0; i < type_count;
171                 i++) {
172                 cout << types[i] << endl;
173             }
174         }
175         break;
176
177 //Run ./test 6 with return key in terminal.
178 //Sample output:
179         //1
180         //function
181         //2
182         //array
183         //function

```

```

182         //3
183         //array
184         //function
185         //integer division
186         //3
187         //array
188         //function
189         //integer division
190     }
191
192 //void insert_order_unique(string types[], int type_capacity, int&
193     type_count, Question ques[], int ques_size);
194     case '7': {
195         const int QUES_CAPACITY = 1000;
196         Question ques[QUES_CAPACITY];
197         int ques_size = 10;
198         ques[0].type = "array";
199         ques[1].type = "function; array";
200         ques[2].type = "arithmetic; modular; remainder";
201         ques[3].type = "integer division; array";
202         ques[4].type = "string; substring";
203         ques[5].type = "arithmetic; integer division";
204         ques[6].type = "arithmetic; integer division";
205         ques[7].type = "repetition";
206         ques[8].type = "function";
207         ques[9].type = "condition";
208
209         const int TYPE_CAPACITY = 30;
210         string types[TYPE_CAPACITY];
211         int type_count = 0;
212         insert_order_unique(types, TYPE_CAPACITY, type_count, ques,
213             ques_size);
214
215         for (int i = 0; i < type_count; i++)
216             cout << i + 1 << ". " << types[i] << endl;
217
218         break;
219
220 //Run ./test 7 with return key in terminal,
221 //here is a sample output.
222 //1. arithmetic
223 //2. array
224 //3. condition
225 //4. function
226 //5. integer division
227 //6. modular

```

```

226 //7. remainder
227 //8. repetition
228 //9. string
229 //10. substring
230     }
231
232     case '8': {
233         const int SIZE = 10;
234         Question ques[SIZE];
235         for (int i = 0; i < SIZE; i++) {
236             string str = "1.";
237             ques[i].label = str + to_string(i+1);
238         }
239
240         randomize(ques, SIZE);
241
242         //Run in linux environment like onlinegdb to get same
243         //running out in gradescope.
244         for (int i = 0; i < SIZE; i++)
245             cout << ques[i].label << endl;
246
247         break;
248
249         //output in Mac when no srand setting up
250         //Run ./test 8 with return key in terminal
251         //1.4
252         //1.9
253         //1.6
254         //1.1
255         //1.3
256         //1.5
257         //1.7
258         //1.2
259         //1.10
260         //1.8
261     }
262
263     case '9': {
264         answer_by_type(ques, size, "array");
265         break;
266
267         //Run the following command with return key in terminal
268         //./test 9
269         //sample input/output:
270         //question f24 v1 1.1: Given char arr[] = {'A', 'B', 'C'}, what is arr
271         //1]?
272         //Enter you answer: 'B'
273         //number of tries: 1

```

```

270 //true
271 //
272 //question f24 v1 1.2: Declare function increase, given an integer array
    arr with size many elements, increase each element of the array by 1.
    Return type is void. Define the function header (no implementation is
    needed).
273 //Enter you answer: void increase(int arr[], int size);
274 //number of tries: 1
275 //true
276 //
277 //question f24 v1 1.4: What is the output?
278 //
279 //string tens_name(int n);
280 //
281 //int main() {
282 //    cout << tens_name(82) << endl;
283 //    return 0;
284 //}
285 //string tens_name(int n) {
286 //    if (n < 20 || n > 99)
287 //        return "";
288 //
289 //    string names[] = {"", "", "twenty", "thirty", "forty", "fifty", "
    sixty", "seventy", "eighty", "ninety"};
290 //    return names[n / 10];
291 //}
292 //Enter you answer: eighty
293 //number of tries: 1
294 //true
295 //
296 //number of correct problems: 3
297 //percentage of correct: 100%
298 //excellent
299     }
300
301     case 'a': {
302         answer_by_type(ques, size, "");
303         break;
304
305 //Run the following command with return key in terminal
306 //./test a
307 //sample input/output:
308 //question f24 v1 1.1: Given char arr[] = {'A', 'B', 'C'}, what is arr
    [1]?
309 //Enter you answer: 'a'
310 //number of tries: 1

```

```

311 //false
312 //Enter you answer: 'A'
313 //number of tries: 2
314 //false
315 //Enter you answer: 'B'
316 //number of tries: 3
317 //true
318 //
319 //question f24 v1 1.3: Assume that n is properly declared and initialized
    . Write a statement to declare lastDigit as an integer and initialize
    it to be the least significant digit of integer n. Suppose n is 123,
    after the statement, lastDigit is 3.
320 //Enter you answer: int lastDigit = n % 10;
321 //number of tries: 1
322 //true
323 //
324 //question f24 v1 1.2: Declare function increase, given an integer array
    arr with size many elements, increase each element of the array by 1.
    Return type is void. Define the function header (no implementation is
    needed).
325 //Enter you answer: void increase(int arr[], int size);
326 //number of tries: 1
327 //true
328 //
329 //question f24 v1 1.4: What is the output?
330 //
331 //string tens_name(int n);
332 //
333 //int main() {
334 //    cout << tens_name(82) << endl;
335 //    return 0;
336 //}
337 //string tens_name(int n) {
338 //    if (n < 20 || n > 99)
339 //        return "";
340 //
341 //    string names[] = {"", "", "twenty", "thirty", "forty", "fifty", "
    sixty", "seventy", "eighty", "ninety"};
342 //    return names[n / 10];
343 //}
344 //Enter you answer: eighty
345 //number of tries: 1
346 //true
347 //
348 //number of correct problems: 4
349 //percentage of correct: 100%

```

```

350 //excellent
351     }
352
353     case 'b': {
354         string types[] = {
355             "arithmetic",
356             "array",
357             "condition",
358             "function",
359             "integer division",
360             "modular",
361         };
362         int size = sizeof(types) / sizeof(types[0]);
363
364         string chosenType = choose_type(types, size);
365         cout << "chosen type: \"" << chosenType << "\"" << endl;
366
367         cout << "\n\nTest when users choose 0. ALL TYPES\n\n";
368         //run choose_type the second time
369         chosenType = choose_type(types, size);
370         cout << "chosen type: \"" << chosenType << "\"" << endl;
371         break;
372
373         //Run the following command with return key in terminal
374         //./test b
375         //sample input/output:
376         //0. ALL TYPES
377         //1. arithmetic
378         //2. array
379         //3. condition
380         //4. function
381         //5. integer division
382         //6. modular
383         //Enter a type: 1
384         //chosen type: "arithmetic"
385         //
386         //
387         //Test when users choose 0. ALL TYPES
388         //
389         //0. ALL TYPES
390         //1. arithmetic
391         //2. array
392         //3. condition
393         //4. function
394         //5. integer division
395         //6. modular

```

```

396 //Enter a type: 0
397 //chosen type: ""
398     }
399
400     case 'c': {
401         //void feedback(int numCorrect, int numQuestions)
402         int numQuestions = 7;
403         for (int numCorrect = 4;
404             numCorrect <= numQuestions;
405             numCorrect++)
406             feedback(numCorrect, numQuestions);
407
408         break;
409
410 //Run the following command with return key in terminal
411 //./test c
412
413 //sample input/output
414 //number of correct problems: 4
415 //percentage of correct: 57.1429%
416 //please ask help ASAP
417 //number of correct problems: 5
418 //percentage of correct: 71.4286%
419 //pass
420 //number of correct problems: 6
421 //percentage of correct: 85.7143%
422 //good
423 //number of correct problems: 7
424 //percentage of correct: 100%
425 //excellent
426     }
427 }
428
429 return 0;
430 }
431
432 void read_file_into_array(Question ques[], int capacity) {
433     int size = 0;
434
435     //The following code does not work, why?
436     //     string fileNames[] = {"cs135_midterm_f24_v1.txt",
437     //                             "cs135_midterm_f24_v2.txt",
438     //                             "cs135_midterm_s24_v1.txt"
439     //};
440     //
441     //     int numFiles = sizeof(fileNames, fileNames[0]);

```



```

442 //      for (int i = 0; i < numFiles; i++) {
443 //          //cout << "file name: " << fileNames[i] << endl;
444 //          read_file(fileNames[i], ques, capacity, size);
445 //      }
446
447 read_file("cs135_midterm_f24_v1.txt", ques, capacity, size);
448 read_file("cs135_midterm_f24_v2.txt", ques, capacity, size);
449 read_file("cs135_midterm_s24_v1.txt", ques, capacity, size);
450
451 string expected = "";
452 for (int i = 0; i < size; i++) {
453     expected += std::to_string(i + 1) + '\n';
454     expected += "question: " + ques[i].text + '\n';
455     expected += "answer: " + ques[i].answer + '\n';
456     expected += "explanation: " + ques[i].explanation + '\n';
457     expected += "type: " + ques[i].type + '\n';
458     expected += "version: " + ques[i].version + '\n';
459     expected += "label: " + ques[i].label + '\n';
460 }
461
462 cout << expected << endl;
463 }

```

## 2.12 Define main function

Now the functions are defined and tested, tidy everything up by defining `main` function. The file can be downloaded from [link to incomplete checkAnswer\\_function\\_rand.cpp](#).

```

1 #include <iostream>
2 #include <fstream> //ifstream
3 #include <string> //starts_with, c++20
4 #include <climits> //INT_MAX
5 #include <string.h> //c-string, strlen(...)
6 #include <cctype> //isspace
7
8 using namespace std;
9
10 struct Question {
11     string text; //question text
12     string answer;
13     string explanation;
14     string version;
15     string type;
16     string label;
17 };
18

```

```

19 void read_file(string fileName, Question ques[], int capacity, int& size)
20 ;
21 void display(Question ques[], int size);
22
23 string trim(string str);
24
25 //count number of occurrences of ch in str
26 int count_occurrence(string str, char ch);
27
28 //extract type separated by ;
29 //then put the trimmed type in
30 //dynamically allocated array of strings
31 string* extract_type(string type, int& num_types_curr_item);
32
33 void insert_order_unique(string types[], int type_capacity, int&
34     type_count, string toAdd);
35
36 void insert_order_unique(string types[], int type_capacity, int&
37     type_count, Question ques[], int ques_size);
38
39 void randomize(Question ques[], int size);
40
41 string choose_type(string* types, int type_count);
42
43 //answer questions, let users try at most 3 times,
44 //and return the number of correct answers in three or fewer tries
45 void answer_by_type(Question ques[], int size, string chosenType);
46
47 void feedback(int numCorrect, int numQuestionsInType);
48
49 int main() {
50     //Declare CAPACITY as a const int with value 1000.
51     const int CAPACITY = 1000;
52     //Declare ques as an array of Questions
53     //that hold CAPACITY many Questions.
54     Question ques[CAPACITY]; //question array
55
56     //Declare size to be 0.
57     int size = 0;
58     read_file("cs135_midterm_f24_v1.txt", ques, CAPACITY, size);
59     read_file("cs135_midterm_f24_v2.txt", ques, CAPACITY, size);
60     read_file("cs135_midterm_s24_v1.txt", ques, CAPACITY, size);
61
62     //optional

```

```

62 //display(ques, size);
63
64 //suppose that there are at most 30 types.
65 const int TYPE_CAPACITY = 30;
66 string types[TYPE_CAPACITY];
67
68 //declare typeCount to be an int with value 0
69 int typeCount = 0;
70
71 //TODO: call insert_order_unique function on questions.
72
73 //TODO: call choose_type function, save the return in a variable.
74
75 //TODO: call answer_by_type with the return from the above statement.
76
77 return 0;
78 }
79
80 //TODO: implement code
81 void read_file(string fileName, Question ques[], int capacity, int& size)
82 {
83     ifstream fin(fileName);
84
85     if (fin.fail()) {
86         cerr << fileName << " cannot be opened" << endl;
87         exit(1);
88     }
89
90     string text;
91     string answer;
92     string explanation;
93     string version;
94     string type; //type of the code
95     string label;
96
97     string line;
98
99 //skip lines until get the first question
100 while ( getline(fin, line) && !( line.starts_with("question: ") ||
101     line.starts_with("Question: ") ) )
102     ;
103
104 while (line.starts_with("question: ")) {
105     text = line.substr(strlen("question: "));
106
107     line = "";

```

```

106 while (getline(fin, line) && !line.starts_with("answer: ") )
107     text += '\n' + line;
108
109 if ( line.starts_with("answer: ") ) {
110     answer = line.substr(strlen("answer: "));
111
112     line = "";
113     while (getline(fin, line) && !(line.starts_with("question: ")
114         || line.starts_with("version: ") || line.starts_with("label
115         : ") || line.starts_with("type: ") || line.starts_with("
116         explanation: ") ) )
117         answer += line + '\n';
118
119     //explanation is the next entry following answer.
120     //Need to starts with "explanation: ",
121     //cannot handle the case like "explanation:\n"
122     if ( line.starts_with("explanation: ") ) {
123         explanation = line.substr(strlen("explanation: ")) + '\n';
124         line = "";
125         while (getline(fin, line) && !(line.starts_with("question:
126             ") || line.starts_with("version: ") || line.starts_with(
127             "label: ") || line.starts_with("type: ") ) )
128             explanation += line + '\n';
129     }
130
131     //use do-while statement, otherwise, the entry following
132     answer: is not read
133     do {
134         if (line.starts_with("version: "))
135             version = line.substr(strlen("version: "));
136         else if (line.starts_with("type: "))
137             type = line.substr(strlen("type: "));
138         else if (line.starts_with("label: "))
139             label = line.substr(strlen("label: "));
140         line = "";
141     } while (getline(fin, line) && !(line.starts_with("question: "
142         ))));

```

*//TODO: if size is larger or equal to capacity, close the file and return.*

*//TODO: save text, answer, ..., explantion, to the corresponding field of ques[size].*

```

143         //TODO: increase size by 1
144
145
146         text = "";
147         answer = "";
148         version = "";
149         type = "";
150         label = "";
151         explanation = "";
152     }
153 }
154 fin.close();
155 }
156
157 void display(Question ques[], int size) {
158     for (int i = 0; i < size; i++) {
159         cout << i + 1 << endl;
160         cout << "question: " << ques[i].text << endl;
161         cout << "answer: " << ques[i].answer << endl;
162         cout << "explanation: " << ques[i].explanation << endl;
163         cout << "type: " << ques[i].type << endl;
164         cout << "version: " << ques[i].version << endl;
165         cout << "label: " << ques[i].label << endl;
166         cout << endl;
167     }
168 }
169
170 //TODO: implement code
171 string trim(string str) {
172
173 }
174
175 //TODO: implement code
176 //count number of occurrences of ch in str
177 int count_occurrences(string str, char ch) {
178
179 }
180
181 //TODO: implement code
182 string* extract_type(string type, int& num_types_curr_item) {
183
184 }
185
186 //TODO: implement code
187 void insert_order_unique(string types[], int type_capacity, int& size,
    string toAdd) {

```

```

188 }
189
190
191 //TODO: implement code
192 void insert_order_unique(string types[], int type_capacity, int& numTypes
    , Question ques[], int ques_size) {
193
194 }
195
196 //TODO: implement code
197 string choose_type(string* types, int type_count) {
198
199 }
200
201 //TODO: implement code
202 void answer_by_type(Question ques[], int size, string chosenType) {
203     //TODO: call randomize function
204
205     //TODO: display questions and answer them
206     //If fail to answer a question correctly in 3 tries,
207     //if explanation field is not empty,
208     //display explantion field of that question.
209
210     //TODO: call feedback function
211
212 }
213
214 //TODO: implement code
215 void feedback(int numCorrect, int numQuestions) {
216
217 }
218
219 //TODO: implement code
220 void randomize(Question ques[], int size) {
221
222 }

```

## 3 Task C

### 3.1 Motivation

When we listen to an artist in youtube for a couple of times, all other songs by the artist will be moved forward in the play list. Similarly, when we cannot correctly answer a question after three tries, those questions become our weak points. We are prone to make errors in questions of similar types.

1. When a user fails to answer the (idx)th question after three tries, re-order the remaining questions

by moving forward the questions related with (idx)th question. That is, move forward the questions whose types contain at least one item of the type of (idx)th question.

2. Since the re-order request is decided by type only, we list type for each question, while ignoring other fields like text, answer, and so on.

In the following example, the type of the first question – indexed at 0 – is condition. The type of the second question is on function and array, and so on.

index of question	type of question
0	condition
1	function; array
2	arithmetic; modular; remainder
3	string; substring
4	arithmetic; integer division
5	function
6	array; integer division
7	arithmetic

3. Suppose we fail the second question (indexed at 1) after three tries.

- (a) Find out whether two types are related or not. Two types are related if they share at least one common item. For example, “function; array” and “array” are related, but not “function; array” and “integer division; remainder”.

index of question	type of question	related with “function; array” or not
0	condition	false
1	function; array	true
2	arithmetic; modular; remainder	false
3	string; substring	false
4	arithmetic; integer division	false
5	function	true
6	array; integer division	true
7	arithmetic	false

- (b) Suppose the type of the wrongly answered question is "function; array", which is the type to focus. Move forward questions whose type are related with the type to focus, that is, the type of the failed-to-answer question.

- i. Find out the **first** question **AFTER** the current question whose type is not related to the current question. In this example, it is the question indexed at 2. Save this in a variable. We do not need to check questions already answered.

index of question	type of question	related with “function; array” or not
0	condition	false
1	function; array	true
2	arithmetic; modular; remainder	false
3	string; substring	false
4	arithmetic; integer division	false
5	function	true
6	array; integer division	true
7	arithmetic	false

- ii. Starting from the last unchecked (what does that mean?) question, moving backwards, find out the first question that is related with the question to focus. In this example, the question to focus is indexed at 2 and the question last related with it is indexed at 6. Save the latter index in a variable.

index of question	type of question	related with “function; array” or not
0	condition	false
1	function; array	true
2	arithmetic; modular; remainder	false
3	string; substring	false
4	arithmetic; integer division	false
5	function	true
6	array; integer division	true
7	arithmetic	false

- iii. Swap the questions found in Steps (i) and (ii).

index of question	type of question	related with “function; array” or not
0	condition	false
1	function; array	true
2	array; integer division	true
3	string; substring	false
4	arithmetic; integer division	false
5	function	true
6	arithmetic; modular; remainder	false
7	arithmetic	false

- iv. Keep on working the **unchecked** (what does that mean?) questions that is after the question to focus but is not related with it. In this example, it is the question indexed at 3.

index of question	type of question	related with “function; array” or not
0	condition	false
1	function; array	true
2	array; integer division	true
3	string; substring	false
4	arithmetic; integer division	false
5	function	true
6	arithmetic; modular; remainder	false
7	arithmetic	false

- v. Keep on working the **unchecked** questions that is after the question to focus but is related with it. In this example, it is the question indexed at 5.

index of question	type of question	related with “function; array” or not
0	condition	false
1	function; array	true
2	array; integer division	true
3	string; substring	false
4	arithmetic; integer division	false
5	function	true
6	arithmetic; modular; remainder	false
7	arithmetic	false



- vi. Swap the above two questions, so one more related question is moved forward to be closer to the question to focus, which is indexed at 2.

index of question	type of question	related with “function; array” or not
0	condition	false
1	function; array	true
2	array; integer division	true
3	function	true
4	arithmetic; integer division	false
5	string; substring	false
6	arithmetic; modular; remainder	false
7	arithmetic	false

- vii. All questions have been checked (why?), and the re-order process is finished.

### 3.2 Define function `type_related(string type_to_focus, string curr_type)`

Hint: you may call `extract_type` to get an array of items of `type_to_focus`, then use `find` method of `string` class to see whether any item is contained in `curr_type`. If the answer is yes, return `true`, otherwise, return `false`.

```

1 void reorder(Question ques[], int size, int idx);
2
3 bool type_related(string type_to_focus, string curr_type);

```

### 3.3 Define function `reorder`

### 3.4 When to call `reorder` function

In the following function, when `chosenType` is an empty string, which means all types, when a question is tried three times but fails, call `reorder` to move the related questions forward.

```

1 void answer_by_type(Question ques[], int size, string chosenType) {
2     ...
3 }

```

### 3.5 Test code in local computers

1. Download [link to unit\\_test\\_focus\\_errors.cpp](#).
2. Copy the code from Project 2B, rename the copy as `checkAnswer_focus_errors.cpp`. Declare and add the following functions.

```

1 void reorder(Question ques[], int size, int idx);
2
3 bool type_related(string type_to_focus, string curr_type);

```

3. In `checkAnswer_focus_errors.cpp`, you should enclose its main function with `#ifndef UNIT_TEST` and `#endif`

```

1 #ifndef UNIT_TEST
2 int main() {
3     ...
4 }
5 #endif

```

4. Run the following command to choose the main function of `unit_test_focus_errors.cpp`, where `-DUNIT_TEST` means to define `+UNIT_TEST+`. Note that in main function of `unit_test_focus_errors.cpp`, its main function is enclosed with `##ifdef UNIT_TEST` and `#endif`

```

1 g++ -std=c++20 -DUNIT_TEST unit_test_focus_errors.cpp -o test

```

5. Run

```

1 ./test d

```

You should see the following output.

```

1 false
2 true
3 false
4 false
5 false
6 true
7 true

```

6. Run the following command.

```

1 ./test e

```

You should see the following result.

```

1 original order of questions
2 condition
3 function; array
4 arithmetic; modular; remainder
5 string; substring
6 arithmetic; integer division
7 function
8 array; integer division
9
10 If fail the second problems for three times, reorder the rest array
11 condition
12 function; array
13 array; integer division
14 function
15 arithmetic; integer division

```

```
16 string; substring
17 arithmetic; modular; remainder
```

7. Without `-DUNIT_TEST`, then `UNIT_TEST` is not defined, so main function from `checkAnswer_focus_errors.c` is chosen.

If you want to call main function in `checkAnswer_focus_errors.cpp`, you can run

```
1 g++ -std=c++20 checkAnswer_focus_errors.cpp -o check
```

Then run

```
1 ./check
```