

FINAL EXAM F24 FINAL V3
CSCI 13500: Software Analysis and Design 1
Hunter College, City University of New York

Dec 19, 2024, 1:45 PM - 3:45 PM, N118

Exam Rules

- Show all your work. Your grade will be based on the work shown.
- The exam is closed book and closed notes with the exception of a provided cheat sheet.
- When taking the exam, you may bring pens and pencils.
- Scratch paper is provided. For your convenience, you may take the scratch paper and cheat sheet off. But make sure **not** to put solutions to the scratch paper.
- You may not use a computer, calculator, tablet, phone, earbuds, or other electronic device.
- **Do not open this exam until instructed to do so.**

Hunter College regards acts of academic dishonesty (e.g., plagiarism, cheating on examinations, obtaining unfair advantage, and falsification of records and official documents) as serious offenses against the values of intellectual honesty. The College is committed to enforcing the CUNY Policy on Academic Integrity and will pursue cases of academic dishonesty according to the Hunter College Academic Integrity Procedures.

I understand that all cases of academic dishonesty will be reported to the Dean of Students and will result in sanctions.

Name:

EmpID:									
--------	--	--	--	--	--	--	--	--	--

Email:

Signature:

1 (30 points) Answer the following questions.

- (1) Given `string groceries[] = {"milk", "oat", "pecan pie"}`, what is `groceries[2].substr(3, 4)`?

- (2) Given a declaration `std::vector<int> v(10, 1);`, what is the value of `v.size()`?

- (3) What possible numbers does code `rand() % 6 - 2` generate?

- (4) Given `string numStr = std::to_string(10) + "25";`, where `to_string` converts an integer to a string. What is the value for `numStr`?

- (5) What is the value of `5 - 7 % 3 / 2` in C++?

- (6) Write **header** of a function called sum, given an array of characters (type `char`) with *size* many elements, return the sum of ASCII code of all the elements in the array.

- (7) Declare class `Coord` as follows.

```
1 class Coord {  
2 public:  
3     double x;  
4     double y;  
5 };
```

Declare a `Coord` object `point` and initialize its `x` as 9 and `y` as 7.

(8) Given `int grades[] = {73, 100, 99, 62};` What is the value of `*grades + 3`?

(9) Given the following code segment.

```
1 void foo(double *pf, double *pg);
2
3 int main() {
4     double f = 1.7;
5     double g = 2.0;
6
7     //TODO: write a statement to call foo using appropriate attributes of f and g.
8
9     return 0;
10 }
```

(10) Suppose we have main function defined as follows. And calling `foo(a, b, 3)`, the values of `a` is increased by 3 and `b` is decreased by 3. That is, `a` becomes ~~2~~ 4 and `b` becomes ~~5~~ -1.

```
1 int main() {
2     int a = 1;
3     int b = 2;
4     foo(a, b, 3);
5     return 0;
6 }
```

What is the **header** of function `foo`? Suppose its return type is `void`.

(11) What is output for the following code?

```
1  int a = 1;
2  int* p = &a;
3  a *= 2;
4  cout << *p << endl;
```

(12) What is the output for the following code?

```
1  vector<int> nums = {2, 0, 2, 5};
2
3  int count = 0;
4  for (int i = 0; i < nums.size(); i++)
5      if (nums[i] % 2 == 0)
6          count++;
7
8  cout << count << endl;
```

(13) What the output of the following code?

```
1  #include <iostream>
2  #include <string>
3  using namespace std;
4
5  int main() {
6      for (int row = 0; row < 4; row++) {
7          for (int col = 0; col < 3; col++) {
8              if (col < 2)
9                  cout << "*";
10                 else cout << "#";
11             }
12             cout << endl;
13         }
14         return 0;
15     }
```

(14) What is panel after slide down operation?

1	6	2
5		8
3	4	7

(15) Suppose in Project 3, data member **bins** have the following values,

$\{\{1, 1, 2\}, \{3, 2, 3\}, \{1, 2\}, \{3\}\}$,

After moving eligible element(s), according to rules listed in Project 3, from the second bin to the left to the rightmost bin, what are the elements in the **second bin to the left**?

2 (15 points) Answer the following questions.

- (1) Define function `countSuccessiveEndElms`, for a given array of chars with its size, return the number of successive (aka consecutive) elements in the end of this array.

For example, call the function with array with values `'r', 'b', 'r', 'r'`, the size of array is 4. There are two `'r'`'s residing successively (aka consecutively) in the end of array, the return is 2. Note that the leftmost `'r'` is not adjacent with those `'r'`'s in the end, so it is not counted as part of the results.

In main function, write the following statements. No need to write the full definition of main function.

Define a char array with elements `'r', 'b', 'r', 'r'`.

Call the above function and print the number of successive end elements of the above array.

- (2) Define function `searchFirst`, given an array of strings, its size, and a target (a string), return a pointer to the **first** occurrence of the target in an array, or `nullptr` if there is no match.

For example, suppose an array has elements `"how"`, `"hi"`, `"hello"`, `"hi"`, if the target is `"hi"`, then the return of the function is a pointer to the second element. if the target is `"wonderful"`, then the return is `nullptr`.

3 (10 points) Programming exercise on class

1. Define class for representing weight in pounds (also called lbs) and ounces. It is reasonable to define it to have two integer fields:

lb for the number of pounds, and oz for the number of ounces. Note that a pound has 16 ounces, so we need to make sure that oz is in $[0, 15]$.

```
1 class Weight {  
2 public:  
3     int lb;  
4     int oz; //value in [0, 15]  
5 };
```

Define `Weight addOzs(Weight curr, int ozVal)`;

The function should create and return a weight object that is ozVal ounces more than curr. Note that $1 \text{ lb} = 16 \text{ oz}$. Example:

`addOzs({2, 8}, 23) // should return {3, 15}`

Reason: 2 lbs 8 ounces is $2 * 16 + 8 = 40$ ounces. Then $40 + 23 = 63$ ounces, which equals 3 lbs and 15 ounces.

2. In main function, write the following statements. No need to define the whole main function.
 - Declare and instantiate `curr` as a `Weight` object with lb equals 2 and oz equals 8.
 - Declare and instantiate a `Weight` object called `heavier` that are 23 ounces more than `curr`. You may call `addOzs` with appropriate parameters.

4 (10 points) Write codes of vector

Define a function called **choose**, for a vector **v** of characters (type `char`), return a vector with all the elements from **v** that are uppercase letters, in the same order. In English, uppercase letters are 'A' - 'Z'


For example, given a vector of characters with elements 'a', 'B', '#', 'D', 'c', the return is a vector with elements 'B', 'D'.

Hint: `int isupper (int c);` checks if parameter `c` is an uppercase alphabetic letter. Return a value different from zero (i.e., true) if indeed `c` is an uppercase alphabetic letter. Zero (i.e., false) otherwise.

`isupper` is from `cctype` library. However, you do not need to include library in your code.

5 (15 points) Define class for triangular ring shape.

1. Define a triangular ring as the region between two concentric equilateral triangles (aka the sides of a triangle are of same length). Call it a TriRing. It has two parameters:



- (a) edge of the inner or the smaller triangle **eSmall**
 - (b) edge of the outer or the bigger triangle **eBig**
2. Assume that **TriRing.hpp** is provided where data members **eSmall** and **eBig** are declared as double types. Your job is to define **TriRing.cpp** with the following requirement.
 3. Define a default constructor, set data members **eSmall** to be 1 and **eBig** to be 2.

4. Define a non-default constructor, which takes formal parameters eSmall and eBig, both are double types.
 - (a) If both eSmall and eBig are positive and eBig is larger than eSmall, set data member **eSmall** by given parameter eSmall and set data member **eBig** by given parameter eBig.
 - (b) otherwise, set data members **eSmall** to be 1 and **eBig** to be 2.

5. Define method **getArea**, return the value of $\frac{\sqrt{3}}{4}(eBig)^2 - \frac{\sqrt{3}}{4}(eSmall)^2$, where **sqrt** is defined as square root in **cmath** library. Note that *eBig* and *eSmall* are data members, not *e* * *Big* or *e* * *Small*.

6. Define method **getPerimeter**, which returns $3(eSmall) + 3(eBig)$. Note that *eBig* and *eSmall* are data members, not `e * Big` or `e * Small`.

Define **TriRingTest.cpp**, do the following:

7. Create a TriRing object named **tri** from its default constructor.

8. Find out and print the area of **tri**.

9. Find out and print the perimeter of **tri**.

6 (10 points) function on vectors

Define a function called `compare`, given two vectors of strings, if they have the same number of elements, find out whether the length of **every** element in the first vector is larger than that of the same-index element in the second vector, if yes, return true, otherwise, return false. If these vectors do not have the same number of elements, return false.

For example, if the first vector is {"hello", "hi"} and the second vector is {"abcdef", "abc", "123"}, the return is false. Reason: the two vectors have different number of elements.

If the first vector is {"hellooo", "hey", "abcd"} and the second vector is {"hello", "hi", "how"}, return true. Reason: both vectors have the same number of elements. Furthermore, the length of the first element "hellooo" in the first vector is larger than the length of the first element "hello" in the second vector. The length of the second element "hey" in the first vector is larger than the length of the second element "hi" in the second vector. The length of the third element "abcd" in the first vector is larger than the length of the third element "how" in the second vector.

If the first vector is {"abcdef", "ab"} and the second vector is {"hello", "hi"}, the return is false. Reason: even though both vectors have the same number of elements, the length of the second element "ab" of the first vector is not larger than the length of the second element "hi" of the second vector.

7 (10 points) Define recursive function

Define a recursive function `printArray`, given an array of int with size many elements, print all elements from the first one to the last one, separated by a space, in the same line.

For example, if an array with elements 1, 2, and 3, the print is

1 2 3

Warning: If you do not use recursion, you will not get any point.

No repetition statement, global or static variables are allowed in this function.

Use array, not vector.