

Kevin Tong - Bird Image Classification

Packages

```
In [11]: import datetime
import time
from packaging import version
from collections import Counter
import numpy as np
import pandas as pd

import matplotlib as mpl # EA
import matplotlib.pyplot as plt
import seaborn as sns

from sklearn.metrics import confusion_matrix, classification_report
from sklearn.decomposition import PCA
from sklearn.manifold import TSNE
from sklearn.ensemble import RandomForestClassifier
from sklearn.metrics import mean_squared_error as MSE
from sklearn.metrics import accuracy_score
from sklearn.model_selection import train_test_split

import tensorflow as tf
from tensorflow.keras.utils import to_categorical
from tensorflow import keras
from tensorflow.keras import layers, models
from tensorflow.keras.models import Sequential
import tensorflow.keras.backend as z
from tensorflow.keras.utils import plot_model
from tensorflow.keras.layers import Conv2D, MaxPool2D, BatchNormalization, Dropout, Flatten, Dense
from tensorflow.keras.callbacks import ModelCheckpoint, EarlyStopping
from tensorflow.keras.preprocessing import image
from tensorflow.keras.utils import to_categorical
from tensorflow.keras.layers import Dropout
import os
import cv2
from PIL import Image
```

```
In [2]: # from google.colab import drive
# drive.mount('/content/drive')
data_dir = '/content/drive/MyDrive/Northwestern MSDS/MSDS 458/458_Final_Notebooks/spectrogram_output'
```

Preprocessing

```
In [3]: # Initialize a set to store unique classes (bird species)
unique_classes = set()

# Define a function to load and preprocess images
def load_and_preprocess_images(image_paths):
    images = []
    for path in image_paths:
        img = Image.open(path)
        img = img.resize((224, 224)) # Resize to your desired dimensions
        img = img.convert("RGB") # Convert to RGB (remove alpha channel if present)
        img = np.array(img) / 255.0 # Normalize pixel values
        images.append(img)
    return np.array(images)

# Loop through directories and load images
all_images = []
for bird_folder in os.listdir(data_dir):
    bird_folder_path = os.path.join(data_dir, bird_folder)
    if os.path.isdir(bird_folder_path) and len(os.listdir(bird_folder_path)) > 1:
        # Add the current folder name to the set of unique classes
        unique_classes.add(bird_folder)

        image_paths = [os.path.join(bird_folder_path, img) for img in os.listdir(bird_folder_path)]
        images = load_and_preprocess_images(image_paths)
        all_images.extend(images)

all_images = np.array(all_images)

# Calculate the total number of classes
num_classes = len(unique_classes)
print("Number of classes:", num_classes)
```

Number of classes: 110

```
In [4]: # Load and preprocess labels
all_labels = []
for bird_folder in os.listdir(data_dir):
    bird_folder_path = os.path.join(data_dir, bird_folder)
    if os.path.isdir(bird_folder_path) and len(os.listdir(bird_folder_path)) > 1:
        label = bird_folder # Assuming folder name is the label
        labels = [label] * len(os.listdir(bird_folder_path))
        all_labels.extend(labels)

# Convert labels to numerical format (e.g., one-hot encoding)
from sklearn.preprocessing import LabelEncoder, OneHotEncoder

label_encoder = LabelEncoder()
integer_encoded = label_encoder.fit_transform(all_labels)
onehot_encoder = OneHotEncoder(sparse=False)
encoded_labels = onehot_encoder.fit_transform(integer_encoded.reshape(-1, 1))

/usr/local/lib/python3.10/dist-packages/sklearn/preprocessing/_encoders.py:868: FutureWarning: `sparse` was renamed to `sparse_output` in version 1.2 and will be removed in 1.4. `sparse_output` is ignored unless you leave `sparse` to its default value.
warnings.warn()
```

```
In [5]: from sklearn.model_selection import train_test_split

# Split data into training and temporary set (which includes validation and test data)
train_images, temp_images, train_labels, temp_labels = train_test_split(all_images, encoded_labels, test_size=0.2, random_state=42)

# Split temporary set into validation and test sets
val_images, test_images, val_labels, test_labels = train_test_split(temp_images, temp_labels, test_size=0.5, random_state=42)
```

```
In [6]: print("Train images shape:", train_images.shape)
print("Validation images shape:", val_images.shape)
print("Test images shape:", test_images.shape)
```

Train images shape: (1725, 224, 224, 3)  
Validation images shape: (216, 224, 224, 3)  
Test images shape: (216, 224, 224, 3)

Neural Network

```
In [61]: start_time = time.time()

model = models.Sequential([
    layers.Conv2D(32, (3, 3), activation='relu', input_shape=(224, 224, 3)),
    layers.MaxPooling2D((2, 2)),

    layers.Conv2D(64, (3, 3), activation='relu'),
    layers.MaxPooling2D((2, 2)),

    layers.Flatten(),

    layers.Dense(128, activation='relu'),
    layers.Dropout(0.5),

    layers.Dense(num_classes, activation='softmax')
])

# Compile the model
model.compile(optimizer='adam',
              loss='categorical_crossentropy',
              metrics=['accuracy'])
```

```
In [62]: # Print the model summary
model.summary()

Model: "sequential_10"

Layer (type) Output Shape Param #
=====
conv2d_15 (Conv2D) (None, 222, 222, 32) 896
max_pooling2d_15 (MaxPoolin (None, 111, 111, 32) 0
g2D)
conv2d_16 (Conv2D) (None, 109, 109, 64) 18496
max_pooling2d_16 (MaxPoolin (None, 54, 54, 64) 0
g2D)
flatten_10 (Flatten) (None, 186624) 0
dense_26 (Dense) (None, 128) 23888000
dropout_15 (Dropout) (None, 128) 0
dense_27 (Dense) (None, 110) 14190
=====
Total params: 23,921,582
Trainable params: 23,921,582
Non-trainable params: 0
```

```
In [63]: # Train the model
history = model.fit(train_images, train_labels, epochs=200, batch_size=64,
                    validation_data=(val_images, val_labels), callbacks=[
                        tf.keras.callbacks.ModelCheckpoint("CNN_model.h5", save_best_only=True, save_weights_only=False)
                        ,tf.keras.callbacks.EarlyStopping(monitor='val_accuracy', patience=3),
                    ])


# Evaluate the model
test_loss, test_acc = model.evaluate(test_images, test_labels)
print('Test accuracy:', test_acc)

Epoch 1/200
27/27 [=====] - 3s 57ms/step - loss: 5.1636 - accuracy: 0.0133 - val_loss: 4.6338 - val_acc
uracy: 0.0556
Epoch 2/200
27/27 [=====] - 1s 44ms/step - loss: 4.4957 - accuracy: 0.0690 - val_loss: 4.1619 - val_acc
uracy: 0.1528
Epoch 3/200
27/27 [=====] - 1s 43ms/step - loss: 3.8302 - accuracy: 0.1768 - val_loss: 3.4086 - val_acc
uracy: 0.3241
Epoch 4/200
27/27 [=====] - 1s 45ms/step - loss: 3.0184 - accuracy: 0.3258 - val_loss: 2.7543 - val_acc
uracy: 0.4491
Epoch 5/200
27/27 [=====] - 4s 168ms/step - loss: 2.3852 - accuracy: 0.4441 - val_loss: 2.3954 - val_ac
curacy: 0.5417
Epoch 6/200
27/27 [=====] - 1s 46ms/step - loss: 1.9409 - accuracy: 0.5368 - val_loss: 2.1881 - val_acc
uracy: 0.5741
Epoch 7/200
27/27 [=====] - 2s 66ms/step - loss: 1.5067 - accuracy: 0.6325 - val_loss: 1.9698 - val_acc
uracy: 0.5972
Epoch 8/200
27/27 [=====] - 1s 25ms/step - loss: 1.2747 - accuracy: 0.6870 - val_loss: 1.9700 - val_acc
uracy: 0.6111
Epoch 9/200
27/27 [=====] - 1s 44ms/step - loss: 1.0773 - accuracy: 0.7223 - val_loss: 1.8309 - val_acc
uracy: 0.6528
Epoch 10/200
27/27 [=====] - 1s 24ms/step - loss: 0.8935 - accuracy: 0.7745 - val_loss: 1.9582 - val_acc
uracy: 0.6343
Epoch 11/200
27/27 [=====] - 1s 25ms/step - loss: 0.8184 - accuracy: 0.7901 - val_loss: 1.9541 - val_acc
uracy: 0.6296
Epoch 12/200
27/27 [=====] - 1s 25ms/step - loss: 0.7865 - accuracy: 0.7901 - val_loss: 2.0050 - val_acc
uracy: 0.6111
7/7 [=====] - 0s 10ms/step - loss: 2.0534 - accuracy: 0.6528
Test accuracy: 0.6527777910232544
```

```
In [64]: end_time = time.time()
runtime = end_time - start_time
print('Total runtime:', runtime, 'seconds')
```

Total runtime: 23.06349515914917 seconds

```
In [65]: # Plot training and validation accuracy
plt.plot(history.history['accuracy'], label='Train Accuracy')
plt.plot(len(history.history['val_accuracy']), test_acc, 'ro', label='Test Accuracy')
plt.xlabel('Epochs')
plt.ylabel('Accuracy')
plt.title('Training and Validation Accuracy')
plt.legend()
plt.show()
```



```
In [66]: # Plot test accuracy
plt.plot(history.history['accuracy'], label='Train Accuracy')
plt.plot(len(history.history['val_accuracy']), test_acc, 'ro', label='Test Accuracy')
plt.xlabel('Epochs')
plt.ylabel('Accuracy')
plt.title('Test Accuracy')
plt.legend()
plt.show()
```

