

Spring Boot Testing Lab

Purpose

In this lab you will gain experience with Spring Boot testing, which provides a set of annotations and utilities to help you test your Spring Boot application.

Learning Outcomes

You will learn how to:

- Enable Spring Boot testing
- Perform integration testing without having to manually run your application
- Perform Web slice testing using mocking

You will be using the 40-boot-test project.

Estimated time to complete: 45 minutes.

Prerequisites

The prerequisites are included as part of the Introduction to the Spring Professional Learning Path course Lab Setup lesson.

If you already completed it, you should be ready to do this lab. If not, assuming you already have JDK 11 or 17 installed and Java IDE, you will need to do following:

- 1. Download the lab codebase zip file.
- 2. Once you have downloaded the file, unzip it under a directory of your choice. The unzipped directory core-spring-labfiles/lab contains the lab projects.
- 3. Run ./mvnw clean install (if you plan on using Maven as your build tool).

Use Case

Testing is a critical part of the software development. For Spring Boot applications, writing and running test code gets easier and faster through the use of various testing utilities and annotations provided by Spring Boot Testing.

Instructions

Add Spring Boot Testing Starter

1. Note that the pom.xml and build.gradle of the parent project already has spring-boot-starter-test

Note that the starter adds several libraries including Mockito framework.

Perform Integration Testing

Run Integration Testing Without Using Spring Boot Testing

Without the use of Spring Boot Testing, you will have to start your application manually before running integration tests. The existing tests in the AccountClientTests are examples of this.

- 1. Stop any application that is running on port 8080.
- 2. Run existing tests in the AccountClientTests and observe that they fail. (If you are using Gradle, remove test exclude statement from build.grad befor running the test.)
- 3. Start the application. And run the tests again and observe that they now pass.
- 4. Stop the application since we will not need a manually started application.

Run Integration Testing Using Spring Boot Testing

You are going to refactor AccountClientTests to use Spring Boot Testing.

TODO-01 Make this test Spring Boot test class

1. Use @SpringBootTest annotation with WebEnvironment.RANDOM_PORT.

```
@SpringBootTest(webEnvironment = WebEnvironment.RANDOM_PORT)
public class AccountClientTests {
    ...
}
```

Note that <u>@SpringBootTest</u> registers a TestRestTemplate bean.

TODO-02 Use TestRestTemplate bean

1. Autowire TestRestTemplate bean.

```
@Autowired
private TestRestTemplate restTemplate;
```

TODO-03 Update the code to use TestRestTemplate bean

- 1. Remove RestTemplate from the code since it is no longer needed.
- 2. Remove BASE_URL and its use in the code since TestRestTemplate will use relative path.
- 3. Run the tests and observe that the tests pass except addAndDeleteBeneficiary test.

TODO-04 Handle an error status from the server

1. Modify addAndDeleteBeneficiary() method and run the tests again.

```
@Test
public void addAndDeleteBeneficiary() {
    // perform both add and delete to avoid issues with side effects
    String addUrl = "/accounts/{accountId}/beneficiaries";
    URI newBeneficiaryLocation = restTemplate.postForLocation(addUrl, "David", 1);
    Beneficiary newBeneficiary = restTemplate.getForObject(newBeneficiaryLocation, Beneficiary.class);
    assertThat(newBeneficiary.getName()).isEqualTo("David");

restTemplate.delete(newBeneficiaryLocation);

ResponseEntity<Beneficiary> response =
    restTemplate.getForEntity(newBeneficiaryLocation, Beneficiary.class);
    assertThat(response.getStatusCode()).isEqualTo(HttpStatus.NOT_FOUND);
}
```

TestRestTemplate is, by design, fault tolerant. This means that it does not throw exceptions when an error response (400 or greater) is received.

This makes it easier to test error scenarios as, rather than having to catch an exception, you can simply assert that the response's status code is as expected for the scenario in question.

2. In your IDE, run all the tests in AccountClientTests - they should all pass.

Note: The tests are disabled in the maven POM, since they cannot run without a server to talk to, so you should run them from the IDE. If you are interested - look for the maven-surefire-plugin to see how to disable tests.

1. Observe, in the console log, that Spring Boot Testing framework started an embedded Tomcat server on a random port.

```
INFO : o.s.b.w... - Tomcat started on port(s): 54209 (http) ...
```

Perform Web Slice Testing

TODO-06 Get yourself familiarized with various testing utility classes

To test Spring MVC Controllers, you can use @WebMvcTest. It auto-configures the Spring MVC infrastructure (and nothing else) for the web slice tests.

Note that the Web slice testing runs faster than an integration testing since it does not need to start a server.

In order to do this part of the lab, you need to know how to use the following API's:

```
• BDDMockito: given(..), willReturn(..), willThrow(..)
```

- MockMvc: perform(..)
- ResultActions: andExpect(..)
- MockMvcRequestBuilders: get(..), post(..), put(..), delete(..)
- MockMvcResultMatchers: status(), content(), jsonPath(..), header()

Create Controller Test Class With @webMvcTest

TODO-07 Write slice test code for the controller

- 1. Go to AccountControllerBootTests testing class under accounts.web package in src/test/java.
- 2. Use @WebMvcTest annotation

```
@WebMvcTest(AccountController.class)
public class AccountControllerBootTests {
   // Test code
}
```

Note that <u>@WebMvcTest</u> auto-configures MockMvc bean.

TODO-08 Autowire MockMvc bean

 $\textbf{TODO-09} \ \textbf{Create AccountManager mock bean using @MockBean annotation}$

Write Test for GET Request for an Account

TODO-10 Write positive test for GET request for an account

1. Write test for getting account detail for a valid account with arrange/act and assert/verify structure as shown below.

```
@Test
public void testAccountDetails() throws Exception {

    // arrange
    given(..).willReturn(..);

    // act and assert
    mockMvc.perform(get("/URL-TO-FETCH"))
        .andExpect(..);

    // verify
    verify(..).getAccount(0L);
}
```

The testing should verify the following:

- The returned Http status is 200
- The returned content type is JSON (MediaType.APPLICATION_JSON)
- The returned data contains correct name and number of an account

Make sure you are using the correct imports for @Test and jsonPath

```
import org.junit.jupiter.api.Test;
import static org.springframework.test.web.servlet.result.MockMvcResultMatchers.*;
```

TODO-11 Write negative test for GET request for an account

- 1. Write test for getting account detail for a non-existent account. The testing should verify the following:
 - The returned Http status is 404

Write Test for POST Request for Account

TODO-12 Write test for POST request for an account

- 1. Write test for creating a new account. The testing should verify the following:
 - The returned Http status is 201
 - The Location header should contain the URI of the newly created Account

For converting an Account to JSON string, add and use the following method:

```
public static String asJsonString(final Object obj) {
    try {
        final ObjectMapper mapper = new ObjectMapper();
        final String jsonContent = mapper.writeValueAsString(obj);
        return jsonContent;
    } catch (Exception e) {
        throw new RuntimeException(e);
    }
}
```

Experiment With @MockBean vs @Mock (Optional)

TODO-13 (Optional) Experiment with @MockBean vs @Mock

- 1. Change @MockBean to @Mock for the AccountManager dependency.
- 2. Run the test. Observe that the test fails.

3. Reverse the change so that the test passes again.

Summary

In this lab, you have used Spring Boot Testing framework for integration testing and Web slice testing.

Extra Part 1

If you are finished with this lab before the rest of the class, try doing some or all of the following:

Test Get All Accounts

- 1. Add another MockMvc test for getting all accounts. The test should verify the following:
 - The returned Http status is 200
 - The returned content type is JSON (MediaType.APPLICATION_JSON)
 - The returned data contains the correct name, number, and contains the correct number of accounts (at least 21 maybe more of the POST test creating new accounts)

Test GET/POST/DELETE for Beneficiary

- 1. Write test for getting a valid beneficiary for an account. The testing should verify the following:
 - The returned Http status is 200
 - The returned content type is JSON (MediaType.APPLICATION_JSON)
 - The returned data contains correct name and allocationPercentage of a beneficiary
- 2. Write test for getting an non-existent beneficiary for an account. The testing should verify the following:
 - The returned Http status is 404
- 3. write test for adding a new beneficiary to an account. the testing should verify the following:
 - the returned http status is 201
 - the location header should contain the uri of the newly added beneficiary
- 4. Write test for removing a beneficiary from an account. The testing should verify the following:
 - The returned Http status is 204
- 5. Write test for removing a non-existent beneficiary from an account. The testing should verify the following:
 - The returned Http Status is 404

Summary Instructors

In this lab you took the concepts you learned in this module and apply them to your Spring Application.

Give Feedback

Help us improve by sharing your thoughts.

Give Feedback



Guides | Courses | Learning Path | Community | Instructors | About | Give Feedback

Contact | FAQs | Terms | Privacy | Your California Privacy Rights

Unlock your full potential with Spring courses designed by experts.

 $Copyright © 2005-2024 \ Broadcom. \ All \ Rights \ Reserved. \ The \ term \ "Broadcom" \ refers \ to \ Broadcom \ Inc. \ and/or \ its \ subsidiaries.$