

## Index

<b>Threat Intelligence - MISP</b>	<b>1</b>
<b>Define your organization</b>	<b>3</b>
<b>Create a user with <i>Org admin</i> permissions on your new organization.</b>	<b>4</b>
<b>Key concepts</b>	<b>5</b>
<b>Event</b>	<b>6</b>
<b>Attributes</b>	<b>7</b>
<b>Feeds</b>	<b>8</b>
<b>Automatic enrichment</b>	<b>9</b>
<b>Tags</b>	<b>11</b>
Activity 1 . . . . .	11
Activity 2 . . . . .	12
<b>Galaxies</b>	<b>12</b>
<b>Cluster</b>	<b>14</b>
Activity 3 . . . . .	15
Activity 4 . . . . .	16

## Threat Intelligence - MISP


MISP Threat Sharing (Malware Information Sharing Platform) <https://www.misp-project.org/>

The MISP is an open source software solution for collecting, storing, distributing and sharing cyber security indicators and threats about cyber security. The project is funded by the European Union and the Computer Incident Response Center Luxembourg (CIRCL).

You can download a virtual machine from: <https://vm.misp-project.org/latest/> It comes with the following credentials:

```
1 For the MISP web interface -> admin@admin.test:admin
2 For the system -> misp:Password1234
```

**This virtual machine is not made for production, it's not secure.**



Initial Install, please configure

**MISP**  
**Threat Sharing**  
Welcome to MISP on ubuntu, change this message in MISP Settings

Login

Email

Password


Login

**Figure 1:** “MISP Login”

### Set an administrator password for the whole system.

Password Policy:

- 1 [12]: Ensure that the password is at least 12 characters **long**
- 2
- 3 [A-Z]: contains at least one upper-**case**
- 4
- 5 [0-9| ]: includes a digit or a special character
- 6
- 7 [a-z]: at least one lower-**case** character




**Figure 2:** “Change password”

## Define your organization

From the menu bar, select Add Organizations and fill the fields of your own organization.

For this example I created one for our school:



Organisations - MISP

Not secure | https://192.168.1.191/admin/organisations/add

Home Event Actions Dashboard Galaxies Input Filters Global Actions Sync Actions Administration Logs API

Add User  
List Users  
Pending registrations  
User settings  
Set Setting  
Contact Users

Add Organisation  
List Organisations

Add Role  
List Roles

Server Settings & Maintenance  
Update Progress

Jobs

Scheduled Tasks  
Event Block Rules  
Blacklist Event

## Add Organisation

### Mandatory Fields

☒ Local organisation

If the organisation should have access to this instance, make sure that the Local organisation setting is checked. If you would only like to add a known external organisation for inclusion in sharing groups, uncheck the Local organisation setting.

Organisation Identifier

Institut Montilivi

UUID

f1a77f47-be42-4d0c-b40e-73a9cab94662 Generate UUID

### Optional Fields

A brief description of the organisation


Una de les característiques de Montilivi és ser un centre acollidor, on tothom és valorat, i no únicament per les seves capacitats acadèmiques sinó també, i molt especialment, per les seves qualitats humanes.

En el nostre Projecte Educatiu de Centre assenalem que la voluntat de l'Institut Montilivi és esdevenir un centre prestigiós per la seriositat de la seva feina, pel

Figure 3: ”””

## Create a user with *Org admin* permissions on your new organization.

Select *Add User* from the *Administration* menu bar.



**Admin Add User**

Email: a2102226@institutmontilivi.cat

☒ Set password


Password: ..... Confirm Password: .....

Organisation: Institut Montilivi

Role: Org Admin NIDS SID: .....

PGP key: Paste the user's PGP key here or try to retrieve it from the CIRCL key server by clicking on "Fetch PGP key" below.

Figure 4: "Add User"



The user has been saved. User notification of new credentials could not be send.

**Users index**

Click [here](#) to reset the API keys of all sync and org admin users in one shot. This will also automatically inform them of their new API keys.

« previous next »

Search: [Enter value to search] Filter

	ID	Org	Role	Email	Event alert	Contact alert	PGP Key	NIDS SID	Terms Accepted	Last Login	Created	Disabled	Actions
<input type="checkbox"/>	2	Institut Montilivi	Org Admin	a2102226@institutmontilivi.cat	✓	✓	✗	7178087	✗	Never	2022-05-16 18:52:09	✗	
<input type="checkbox"/>	1	ORGNAME	admin	admin@admin.test	✗	✗	✗	4000000	✗	2022-05-16 18:44:21		✗	

Figure 5: "List Users"

## Key concepts

Event: This is a study case.

Attributes: These are the information elements that shape the event.

Feeds: These are data sources that enrich our events.

Tags: Categories that we put on an event in order to classify it.

Galaxies: These are templates for describing attributes.


Cluster: Is an instance of a galaxy.

## Event

Let's understand what an event is while creating one. Suppose that a user in our organization receives an email with a suspicious link, for example: `linksys.secureshellz.net`. Obviously, we don't want to open the link without knowing if this domain is malware free.

From the menu bar, select *Event Actions* and *Add Event*.

Fill it with the information requested:



The screenshot shows the MISP web interface for adding a new event. The browser address bar indicates the URL `https://192.168.1.191/events/add`. The navigation menu includes 'Home', 'Event Actions', 'Dashboard', 'Galaxies', 'Input Filters', 'Global Actions', 'Sync Actions', and 'Administration'. A sidebar on the left lists various actions: 'List Events', 'Add Event' (highlighted), 'Import from...', 'REST client', 'List Attributes', 'Search Attributes', 'View Proposals', 'Events with proposals', 'View delegation requests', 'Export', and 'Automation'. The main form, titled 'Add Event', contains the following fields: 'Date' (text input with value '2022-05-16'), 'Distribution' (dropdown menu with value 'Your organisation only'), 'Threat Level' (dropdown menu with value 'Undefined'), 'Analysis' (dropdown menu with value 'Initial'), 'Event Info' (text input with value 'Suspicious domain'), and 'Extends Event' (text input with placeholder 'Event UUID or ID. Leave blank if not applicable.'). A blue 'Submit' button is located at the bottom of the form.

**Figure 6:** "Add Event"

Now, if you list the events you should see something like this:




Figure 7: “List Events”

Let’s add attributes to this event.

## Attributes

Attributes give shape and meaning to the event.

In our example, a very clear attribute is the domain that we consider suspicious.

Click on the event ID to see its contents:





Figure 8: “Event info”

Then add a new attribute from the menu. Fill the data.



Attributes - MISP

Not secure | https://192.168.1.191/attributes/add/1

Home Event Actions Dashboard Galaxies Input Filters Global Actions Sync Actions Administration

View Event  
View Correlation Graph  
View Event History

Edit Event  
Delete Event  
Add Attribute  
Add Object  
Add Attachment  
Add Event Report  
Populate from...  
Enrich Event  
Merge attributes from...

Publish Event  
Publish (no email)  
Delegate Publishing  
Contact Reporter  
Download as...

List Events  
Add Event

### Add Attribute

Category ⓘ Network activity Type ⓘ domain

Distribution ⓘ Your organisation only

Value

linksys.secureshellz.net

Contextual Comment

☐ For Intrusion Detection System  
☐ Batch Import  
☐ Disable Correlation

First seen date 📅 2022-05-16 Last seen date 📅 2022-05-16

First seen time 🕒 HH:MM:SS.ssssss+TT:TT Last seen time 🕒 HH:MM:SS.ssssss+TT:TT

Expected format: HH:MM:SS.ssssss+TT:TT

**Figure 9:** “Add Attribute”

## Feeds

In order to find out if someone else has found this link and has already studied it, we will add the feeds, which are serie of OSINT events that we can import.

Select the *List Feeds* option.

By default, the application has two but the are disabled.

Select and enable them.






Figure 10: “List Feeds”

In a short time we will start receiving events created by the two enabled feeds. We can see events listed:




Figure 11: “Events created”

## Automatic enrichment

Now, the part that interests us is in our event. Click the event to display its content and go to its attribute.

We can see in the *Related Events* column our related event. Click it.

<div><div><div><div>+</div><div>☰</div><div>☒</div><div>☒</div></div><div>Scope toggle</div><div>Deleted</div><div>Decay score</div><div>SightingDB</div><div>Context</div><div>Related Tags</div><div>Filtering tool</div></div><div>Enter value to search</div></div>														
<input type="checkbox"/>	Date ↑	Org	Category	Type	Value	Tags	Galaxies	Comment	Correlate	Related Events	Feed hits	IDS	Distribution	Sighting
<input type="checkbox"/>	2022-05-16		Network activity	domain	linksys.secureshellz.net	<div><div><div><div></div></div><div><div></div></div></div><div><div><div></div></div><div><div></div></div></div></div>	<div><div><div></div></div><div><div></div></div></div> <div><div><div></div></div><div><div></div></div></div>		<input checked="" type="checkbox"/>	2	<input type="checkbox"/>		Organisation	<div><div><div></div></div><div><div></div></div><div><div></div></div></div>

**Figure 12:** “Related Events”

This event is created by the CthulhuSPRL.be organization with data from 2014 and contains 1067 attributes.

[Home](#)
[Event Actions](#)
[Dashboard](#)
[Galaxies](#)
[Input Filters](#)
[Global Actions](#)
[Sync Actions](#)
[Administration](#)
[Logs](#)
[API](#)

Not secure

https://192.168.1.191/events/view/2/1/1

MISP

Admin

Log out

You are currently logged in as a site administrator and about to edit an event not belonging to your organisation. This goes against the sharing model of MISP. Use a normal user account for day to day work.

View Event

View Correlation Graph

View Event History

Edit Event

Delete Event

Add Attribute

Add Object

Add Attachment

Add Event Report

Populate from...

Enrich Event

Merge attributes from...

Unpublish

Publish Sightings

Download as...

List Events

Add Event

OSINT ShellShock scanning IPs from OpenDNS

Event ID

2

UUID

542e49c-cadc-4f8f-bb11-6d13950d210e

Creator org

CthulhuSPRL.be

Owner org

ORGNAME

Creator user

admin@admin.test

Protected Event (experimental)

Event is in unprotected mode.

Tags

type:OSINT

tip:green

tip:white

Taxonomy 'tip' is an exclusive Taxonomy

tip:green

tip:white

Date

2014-10-02

Threat Level

Low

Analysis

Completed

Distribution

All communities

Info

OSINT ShellShock scanning IPs from OpenDNS

Published

Yes (2022-05-16 19:01:29)

#Attributes

1067 (0 Objects)

First recorded change

2014-10-03 09:14:05

Warning: Taxonomy inconsistencies

tip

tip is an exclusive taxonomy. Only one Tag of this taxonomy is allowed on an element.

Related Events

Suspicious domain

2022-05-16

1

OSINT Democracy in Hong Kong Under Attack blog post from Volexity (Site)

2014-10-09

**Figure 13:** “View Event”

Below the description we can see the list of all its attributes, one of which we are interested in:

Scope toggle  Deleted  Decay score  SightingDB  Context  Related Tags  Filtering tool												Enter value to search				
<input type="checkbox"/>	Date ↑	Org	Category	Type	Value	Tags	Galaxies	Comment	Correlate	Related Events	Feed hits	IDS	Distribution	Sightings	Activity	Actions
<input type="checkbox"/>	2018-02-05		Network activity	ip-src	217.13.197.5				<input checked="" type="checkbox"/>			<input type="checkbox"/>	Inherit	(0/0/0)		
<input type="checkbox"/>	2014-10-03		Network activity	hostname	linksys.secureshellz.net				<input checked="" type="checkbox"/>	1		<input checked="" type="checkbox"/>	Inherit	(0/0/0)		
<input type="checkbox"/>	2014-10-03		Network activity	domain	stablehost.us				<input checked="" type="checkbox"/>			<input checked="" type="checkbox"/>	Inherit	(0/0/0)		
<input type="checkbox"/>	2014-10-03		Network activity	hostname	fb1.bot.nu				<input checked="" type="checkbox"/>			<input checked="" type="checkbox"/>	Inherit	(0/0/0)		
<input type="checkbox"/>	2014-10-03		Network activity	hostname	us.bot.nu				<input checked="" type="checkbox"/>			<input checked="" type="checkbox"/>	Inherit	(0/0/0)		
<input type="checkbox"/>	2014-10-03		Network activity	ip-src	222.158.252.39				<input checked="" type="checkbox"/>			<input checked="" type="checkbox"/>	Inherit	(0/0/0)		
<input type="checkbox"/>	2014-10-03		Network activity	ip-src	221.221.219.63				<input checked="" type="checkbox"/>			<input checked="" type="checkbox"/>	Inherit	(0/0/0)		
<input type="checkbox"/>	2014-10-03		Network activity	ip-src	221.250.87.66				<input checked="" type="checkbox"/>			<input checked="" type="checkbox"/>	Inherit	(0/0/0)		

**Figure 14:** “List Attributes”

So, yes, this link is already classified as **OSINT ShellShock scanning IPs from OpenDNS**.

## Tags

Tags are used to classify and add information to an event. This is the link where MISP has collected all tags and taxonomies:

<https://www.misp-project.org/taxonomies.html>

From this list we will work with one type: the TLP taxonomy.

TLP (Tragic Light Protocol) is designed to classify event information depending on the data protection and reputation of the company.

They have defined the following tags:

- Red
- Amber
- Green
- White

### Activity 1

**According to the information given the taxonomies by MISP, explain briefly what involves each color in an event.**

- **Red**

For information that is limited to selected persons and its disclosure could have a negative impact on operations.

It can be distributed only to designated persons.

- **Amber**

For internal information that with its misuse or distribution would cause privacy risks affecting reputation and operations.

It can be distributed only with the members of the organization who are authorized to have knowledge of the information.

- **Green**

For all the information that can be shared in the organization and with third parties.

It can be distributed to partner organizations, but not by public means.

- **White**


For information that can be used without causing any risk in case it's misused.

Information can be shared publicly in accordance with the law.

## Activity 2

When the event is captured in the previous page, there is a warning in the *Tags* section.


What is the warning telling us?



**Figure 15:** “Warning”

It’s saying that this taxonomy is exclusive, therefore it only makes sense to have one tlp color.


If we remove one of the colors we will no longer see the warning.



**Figure 16:** “Warning corrected”

## Galaxies

Galaxies are templates for describing more information about an event or attribute. To list them we go to *List Galaxies* from the *Galaxies* menu bar.




The screenshot shows the MISP Galaxy index page. The left sidebar contains navigation links: List Galaxies, List Cluster Blocklists, List Relationships, Update Galaxies, Force Update Galaxies, Wipe Default Galaxy Clusters, and Import Galaxy Clusters. The main content area is titled 'Galaxy index' and features a search bar and a table of galaxies. The table has columns for Galaxy ID, Icon, Name, version, Namespace, Description, Enabled, and Local Only. The table lists 10 galaxies, including Tool, Threat Actor, Tea Matrix, TDS, Target Information, Surveillance Vendor, Stealer, SoD Matrix, Dark Patterns, Sector, rsit, Regions UN M49, and RAT.

Galaxy ID	Icon	Name	version	Namespace	Description	Enabled	Local Only
58		Tool	3	misp	Threat actors tools is an enumeration of tools used by adversaries. The list includes malware but also common software regularly used by the adversaries.	✓	✗
57		Threat Actor	3	misp	Threat actors are characteristics of malicious actors (or adversaries) representing a cyber attack threat including presumed intent and historically observed behaviour.	✓	✗
56		Tea Matrix	1	tea-matrix	Tea Matrix	✓	✗
55		TDS	4	misp	TDS is a list of Traffic Direction System used by adversaries	✓	✗
54		Target Information	1	misp	Description of targets of threat actors.	✓	✗
53		Surveillance Vendor	1	misp	List of vendors selling surveillance technologies including malware, interception devices or computer exploitation services	✓	✗
52		Stealer	1	misp	Malware stealer galaxy.	✓	✗
51		SoD Matrix	1	sod-matrix	SoD Matrix	✓	✗
50		Dark Patterns	1	misp	Social Engineering - Dark Patterns	✓	✗
49		Sector	2	misp	Activity sectors	✓	✗
48		rsit	1	RSIT	Reference Security Incident Classification Taxonomy	✓	✗
47		Regions UN M49	2	misp	Regions based on UN M49.	✓	✗
46		RAT	3	misp	remote administration tool or remote access tool (RAT), also called sometimes remote access trojan, is a piece of software or programming that allows a remote "operator" to control a system as if they have physical access to that system.	✓	✗

Figure 17: “List Galaxies”

Let's look at one: *Threat Actor*



The screenshot shows the MISP Threat Actor galaxy view page. The left sidebar contains navigation links: List Galaxies, List Cluster Blocklists, List Relationships, Update Galaxies, Force Update Galaxies, Wipe Default Galaxy Clusters, Import Galaxy Clusters, Export Galaxy Clusters, View Galaxy, and Add Cluster. The main content area is titled 'Threat Actor galaxy' and displays a detailed view of the galaxy. The details include Galaxy ID, Name, Namespace, UUID, Description, Version, and Local Only. The description states: 'Threat actors are characteristics of malicious actors (or adversaries) representing a cyber attack threat including presumed intent and historically observed behaviour.' The version is 3 and it is not local only. At the bottom, there is a pagination bar showing 7 items.

Galaxy ID	Name	Namespace	UUID	Description	Version	Local Only
57	Threat Actor	misp	698774c7-8022-42c4-917f-8d6e4f06ada3	Threat actors are characteristics of malicious actors (or adversaries) representing a cyber attack threat including presumed intent and historically observed behaviour.	3	No

Figure 18: ””

This is a fairly simple case, we got only a name and a description. We can see all the published instances of this galaxy:

Home Event Actions Dashboard Galaxies Input Filters Global Actions Sync Actions Administration Logs API											
Add Cluster											
« previous 1 2 3 4 5 6 7 next » last »											
All Default Custom 0 My Clusters Deleted View Fork Tree View Galaxy Relationships											
Enter value to se											
ID	Published	Value	Synonyms	Owner Org	Creator Org	Default	Activity	#Events	#Relations	Description	
9760	N/A	Stealth Mango and Tangelo		MISP	MISP	✓		0	0 0 0	This threat actor targets organizations in the satellite communications, telecommunications, geospatial-imaging, and defense sectors in the United States and Southeast Asia for espionage purposes.	
9741	N/A	ALLANITE	Palmetto Fusion, Allanite	MISP	MISP	✓		0	0 0 0	Adversaries abusing ICS (based on Dragos Inc adversary list). ALLANITE accesses business and industrial control (ICS) networks, conducts reconnaissance, and gathers intelligence in United States and United Kingdom electric utility sectors. Dragos assesses with moderate confidence that ALLANITE operators continue to maintain ICS network access to: (1) understand the operational environment necessary to develop disruptive capabilities, (2) have ready access from which to disrupt electric utilities. ALLANITE uses email phishing campaigns and compromised websites called watering holes to steal credentials and gain access to target networks, including collecting and distributing screenshots of industrial control systems. ALLANITE operations limit themselves to information gathering and have not demonstrated any disruptive or damaging capabilities. ALLANITE conducts malware-less operations primarily leveraging legitimate and available tools in the Windows operating system.	
9718	N/A	ANDROMEDA SPIDER		MISP	MISP	✓		0	0 0 0		
9865	N/A	ANTHROPOID SPIDER	Empire Monkey, CobaltGoblin	MISP	MISP	✓		0	0 0 0	Publicly known as 'EmpireMonkey', ANTHROPOID SPIDER conducted phishing campaigns in February and March 2019, spoofing French, Norwegian and Belizean financial regulators and institutions. These campaigns used macro-enabled Microsoft documents to deliver the PowerShell Empire post-exploitation	

Figure 19: “Threat Actor galaxy”

We select one to see its history:

Feeds - MISP x GalaxyClusters - MISP x +																															
← → ↺ ⚠ Not secure   https://192.168.1.191/galaxy_clusters/view/9760																															
Home Event Actions Dashboard Galaxies Input Filters Global Actions Sync Actions Administration Logs API																															
<a href="#">List Galaxies</a> <a href="#">List Cluster Blocklists</a> <a href="#">List Relationships</a>  <a href="#">Update Galaxies</a> <a href="#">Force Update Galaxies</a> <a href="#">Wipe Default Galaxy Clusters</a>  <a href="#">Import Galaxy Clusters</a> <a href="#">Export Galaxy Clusters</a>  <a href="#">View Galaxy</a> <a href="#">View Cluster</a> <a href="#">Add Cluster</a> <a href="#">Fork Cluster</a>  <a href="#">View Correlation Graph</a>																															
<h2>Threat Actor :: Stealth Mango and Tangelo</h2> <table> <tr> <td>Cluster ID</td><td>9760</td></tr> <tr> <td>Name</td><td>Stealth Mango and Tangelo</td></tr> <tr> <td>Parent Galaxy</td><td>Threat Actor</td></tr> <tr> <td>Description</td><td>This threat actor targets organizations in the satellite communications, telecommunications, geospatial-imaging, and defense sectors in the United States and Southeast Asia for espionage purposes.</td></tr> <tr> <td>Default</td><td>Yes</td></tr> <tr> <td>Version</td><td>226</td></tr> <tr> <td>UUID</td><td>f82b352e-a9f8-11e8-8be8-fb6cf6eddd58c</td></tr> <tr> <td>Collection UUID</td><td>7cdf317-a673-4474-84ec-4f1754947823</td></tr> <tr> <td>Source</td><td>MISP Project</td></tr> <tr> <td>Authors</td><td>Alexandre Dulaunoy, Florian Roth, Thomas Schreck, Timo Steffens, Various</td></tr> <tr> <td>Distribution</td><td>All communities</td></tr> <tr> <td>Owner Organisation</td><td>MISP</td></tr> <tr> <td>Creator Organisation</td><td>MISP</td></tr> <tr> <td>Connector tag</td><td>misp-galaxy:threat-actor=" Stealth Mango and Tangelo "</td></tr> <tr> <td>Events</td><td>0</td></tr> </table>		Cluster ID	9760	Name	Stealth Mango and Tangelo	Parent Galaxy	Threat Actor	Description	This threat actor targets organizations in the satellite communications, telecommunications, geospatial-imaging, and defense sectors in the United States and Southeast Asia for espionage purposes.	Default	Yes	Version	226	UUID	f82b352e-a9f8-11e8-8be8-fb6cf6eddd58c	Collection UUID	7cdf317-a673-4474-84ec-4f1754947823	Source	MISP Project	Authors	Alexandre Dulaunoy, Florian Roth, Thomas Schreck, Timo Steffens, Various	Distribution	All communities	Owner Organisation	MISP	Creator Organisation	MISP	Connector tag	misp-galaxy:threat-actor=" Stealth Mango and Tangelo "	Events	0
Cluster ID	9760																														
Name	Stealth Mango and Tangelo																														
Parent Galaxy	Threat Actor																														
Description	This threat actor targets organizations in the satellite communications, telecommunications, geospatial-imaging, and defense sectors in the United States and Southeast Asia for espionage purposes.																														
Default	Yes																														
Version	226																														
UUID	f82b352e-a9f8-11e8-8be8-fb6cf6eddd58c																														
Collection UUID	7cdf317-a673-4474-84ec-4f1754947823																														
Source	MISP Project																														
Authors	Alexandre Dulaunoy, Florian Roth, Thomas Schreck, Timo Steffens, Various																														
Distribution	All communities																														
Owner Organisation	MISP																														
Creator Organisation	MISP																														
Connector tag	misp-galaxy:threat-actor=" Stealth Mango and Tangelo "																														
Events	0																														

Figure 20: “Instances of the galaxy”


## Cluster

Clusters are simply an instance of a galaxy.

### Activity 3


Create a cluster as an instance of the *Threat Actor* galaxy, defining the attacker “Estudiant del curs de ciberseguretat Montilivi”.

Attach a screenshot of your new cluster.



The screenshot shows the MISP interface. On the left, a sidebar contains a list of actions: List Galaxies, List Cluster Blocklists, List Relationships, Update Galaxies, Force Update Galaxies, Wipe Default Galaxy Clusters, Import Galaxy Clusters, Export Galaxy Clusters, View Galaxy, and Add Cluster. The 'Add Cluster' button is highlighted with a red rectangle. The main content area displays the details for the 'Threat Actor' galaxy, including its ID (57), Name, Namespace (misp), UUID, Description, Version (3), and Local Only status (No). A pagination bar at the bottom shows page 1 of 7.

Figure 21: “Add Cluster”



The screenshot shows the MISP interface with the newly created cluster details. The browser address bar shows the URL: https://192.168.1.191/galaxy\_clusters/view/10489. The main content area displays the details for the 'Threat Actor :: Estudiant del curs de ciberseguretat Montilivi' cluster, including its ID (10489), Name, Parent Galaxy (Threat Actor), Description, Published status (Yes), Default status (No), Version (1652721539), UUID, Collection UUID, Source, Authors (N/A), Distribution (Your organisation only), Owner Organisation (ORGNAME), Creator Organisation (ORGNAME), Connector tag, and Events (0).

Figure 22: “Our new Cluster”


In order to use this new cluster, we must publish it.

Publish is not an immediate action, it may take a few minutes.

Now, we add this cluster to the created event. List events, select yours and edit it. Add a cluster MISP, *Threat Actor*, and then start typing the name of your cluster until you see it.

## Activity 4

**Attach a screenshot of your event from Montilivi's cluster that you just created.**



**Figure 23:** "Add new cluster"

Publish the event.



**View Event**

[View Correlation Graph](#)

[View Event History](#)

---

[Edit Event](#)

[Delete Event](#)

[Add Attribute](#)

[Add Object](#)

[Add Attachment](#)

[Add Event Report](#)

[Populate from...](#)

[Enrich Event](#)

[Merge attributes from...](#)

---

[Unpublish](#)

[Publish Sightings](#)

[Delegate Publishing](#)

[Contact Reporter](#)

[Download as...](#)

---

[List Events](#)

[Add Event](#)

## Suspicious domain

Event ID	1
UUID	f487f16e-c930-43d3-b780-642b9382d46a
Creator org	ORGNAME
Owner org	ORGNAME
Creator user	admin@admin.test
Protected Event (experimental)	Event is in unprotected mode. <a href="#">Switch to protected mode</a>
Tags	
Date	2022-05-16
Threat Level	? Undefined
Analysis	Initial
Distribution	Your organisation only
Info	Suspicious domain
Published	Yes (2022-05-16 19:22:46)
#Attributes	1 (0 Objects)
First recorded change	2022-05-16 18:57:00
Last change	2022-05-16 19:21:57
Modification map	
Sightings	0 (0) - restricted to own organisation only.

Figure 24: “Published event 1”

— Pivots — Galaxy + Event graph + Event timeline + Correlation graph + ATT&CK matrix + Event reports — Attributes — Discussion

x 1: Suspicious domain

Galaxies

**Threat Actor**

Estudiant del curs de ciberseguretat Montilivi

« previous
next »
view all

+     Scope toggle  Deleted  Decay score  SightingDB  Context  Related Tags  Filtering tool

<input type="checkbox"/>	Date ↑	Org	Category	Type	Value	Tags	Galaxies	Comment	Correlate	Relate
<input type="checkbox"/>	2022-05-16		Network activity	domain	linksys.secureshellz.net				<input checked="" type="checkbox"/>	2

Figure 25: “Published event 2”