TEST REPORT

Project No.: TM-2602000050P

Applicant: Aplex Technology Inc.
Address: 15F-1,No.186,Jian Yi Road,Zhonghe Dist., New Taipei City,235 Taiwan
Manufacturer: Aplex Technology Inc.
Address: 15F,No.150,Jian Yi Road,Zhonghe Dist., New Taipei City,235 Taiwan
Equipment Under Test (EUT):
Name: Panel PC
Model No.: ARCHMI-821B
Added Model(s): ARCHMI-8XXXXXXXXXXXXX (X=0-9,a-z,A-Z,Blank or Dash);
ARCHMI-PXXXXXXXXXXXX (X=0-9,a-z,A-Z,Blank or Dash)

Standards:

EN 55032: 2015 + A11: 2020, Class B CISPR 32: 2015 (Ed 2.0) + C1: 2016	BS EN 55032: 2015 + A11: 2020
EN IEC 61000-3-2: 2019 + A1: 2021	BS EN IEC 61000-3-2: 2019 + A1: 2021
EN 61000-3-3: 2013 + A1: 2019 + A2: 2021	BS EN 61000-3-3: 2013 + A1: 2019 + A2: 2021
EN 55035: 2017 + A11: 2020	BS EN 55035: 2017 + A11: 2020
IEC 61000-4-2: 2008	IEC 61000-4-6: 2013 + COR1: 2015
IEC 61000-4-3: 2020 (Ed. 4.0)	IEC 61000-4-8: 2009
IEC 61000-4-4: 2012	IEC 61000-4-11: 2020 + COR1: 2020 + COR2: 2022 (Ed. 3.0)
IEC 61000-4-5: 2014 + A1: 2017	

Date of Sample Receipt : October 6, 2023
Date of Test : October 4, 2023 ~ October 14, 2023
Date of Issue : March 4, 2026

Remarks:

This test report can be used for CE and UKCA marking application which is based on equivalent requirements between UK and EU. It is appropriate using designated standards to provide presumption of conformity with GB law.

This report shall not be reproduced except in full, without approval of the Compliance Certification Services Inc. in writing.
This document may be altered or revised by Compliance Certification Services Inc. personnel only. The applicant should not use it to claim product endorsement by TAF or any other Government agencies.

Disclaimer

Variants information between/among model numbers / trademarks is provided by the applicant, test results of this test report are applicable to the sample EUT received of main test model name.

Approved By Stanley Cheng ***Date*** ***March 4, 2026***
Stanley Cheng (Supervisor of engineering dept.)

Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only.
除非另有說明，此報告結果僅對測試之樣品負責，同時此樣品僅保留 90 天。本報告未經本公司書面許可，不可部份複製。
This document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at http://www.sgs.com.tw/Terms-and-Conditions and, for electronic format documents, subject to Terms and Conditions for Electronic Documents at http://www.sgs.com.tw/Terms-and-Conditions. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instruction, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced, except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law.

Revision History

Revision	Report Number	Description	Issue Date
00	TMXD2310004092DE	Original.	October 25, 2023
01	TMXD2602000415DE	Add model	March 4, 2026

Note:

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Contents

1. GENERAL DESCRIPTION 4

1.1 GENERAL DESCRIPTION OF EUT 4
1.2 DETAILS OF EUT 4
1.3 DESCRIPTION OF SUPPORT UNITS 5
1.4 I/O PORT DESCRIPTION 5
1.5 DECISION OF TEST MODE 6
1.6 THE FINAL TEST MODE OF THE EUT 6
1.7 CONFIGURATION OF TESTED SYSTEM 7
1.8 OPERATION PROCEDURE 7
1.9 SUMMARY OF RESULTS 8
1.10 REPORTING STATEMENTS OF CONFORMITY 8
1.11 DEVIATION 8

2. EMISSION 9

2.1 LIMIT 9
2.2 CONDUCTED EMISSION 11
2.3 RADIATED EMISSION 15

3. HARMONICS 19

3.1 TEST INSTRUMENTS 19
3.2 MEASUREMENT DATA 20

4. FLICKER 23

4.1 TEST INSTRUMENTS 23
4.2 MEASUREMENT DATA 24

5. IMMUNITY 25

5.1 STANDARD PERFORMANCE CRITERIA DESCRIPTION 25
5.2 SPECIAL PERFORMANCE CRITERIA DESCRIPTION 26
5.3 TEST OF IEC 61000-4-2 32
5.4 TEST OF IEC 61000-4-3 37
5.5 TEST OF IEC 61000-4-4 41
5.6 TEST OF IEC 61000-4-5 42
5.7 TEST OF IEC 61000-4-6 43
5.8 TEST OF IEC 61000-4-8 46
5.9 TEST OF IEC 61000-4-11 47

APPENDIX 48

PHOTOGRAPH OF TESTING GENERAL SET-UP 48
PHOTOGRAPHS OF EUT UNIT 64

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

1. General Description

1.1 General Description of EUT

Name of EUT	Panel PC
Model No.(s)	ARCHMI-821B
Added Model(s)	ARCHMI-8XXXXXXXXXXXXX (X=0-9,a-z,A-Z,Blank or Dash); ARCHMI-PXXXXXXXXXXXX (X=0-9,a-z,A-Z,Blank or Dash)

Variant Description

Model Name	Difference	Tested (Check)
ARCHMI-821B	Original	☒
ARCHMI-8XXXXXXXXXXXXX	1. X=0-9,a-z,A-Z,Blank or Dash 2. The manufacturer declares that the serial products are identical to main test sample. For marketing reason, there are different serial numbers.	☐
ARCHMI-PXXXXXXXXXXXX	1. X=0-9,a-z,A-Z,Blank or Dash 2. For marketing	☐

1.2 Details of EUT

EUT Power Rating	12VDC from AC Adaptor
AC Adaptor Manufacturer	EDAC
AC Adaptor Model	EA11011B-1200
AC Adaptor Power Rating	I/P: 100-240V~, 2.0A, 50-60Hz; O/P: 12VDC, 7.5A
Highest internal frequency	2000MHz

Accessories Cable List

Cable Type	Core	Length	Category	Shielding/Non-shielding
DC Power Cord	1	1.15m	N/A	Non-shielding
AC Power Cord	N/A	1.8m	N/A	Non-shielding

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

1.3 Description of Support Units

EUT Devices:

No.	Equipment	Model No.	Brand Name
1	MB	SBC-7130	APLEX
2	CPU (2.0GHz)	Intel Atom® x6211E Processor	Intel
3	Memory (64GB)	DDR4-2400 SDRAM	Transcend
4	Storage (128GB)	SATA3 M.2 2242	Transcend
5	Power Adapter	EA11011B-1200	EDAC
6	LCD Panel (21.5”)	G215HAN01.3	AUO

Peripherals Devices:

No.	PRODUCT	MANUFACTURER	MODEL NO.	SERIAL NO.
1	Earphone	Atayal	SEP912	N/A
2-3	USB HDD	Transcend	TS1TSJ25MC	N/A
4	USB Mouse	LOGITECH	M-U0026	N/A
5	USB Keyboard	LOGITECH	Y-U0011	N/A
6	Monitor	ASUS	VP28U	KCLMTF168414
7	HUB	TP-LINK	TL-SX105	221A3A1000134
8	Server PC	DELL	T3610	57TT032
9	COM Loopback	N/A	N/A	N/A

Support Equipment Used in Tested Cable

No.	Cable Type	Core	Length	Shielding/Non-shielding
1	Audio	N/A	1.8m	Shielding
2-3	USB	N/A	1.8m	Shielding
4	USB	N/A	1.8m	Shielding
5	USB	N/A	1.8m	Shielding
6	DP	N/A	1.8m	Shielding
7	RJ45	N/A	20m X2	Non-shielding
8	RJ45	N/A	2.0m	Non-shielding
9	COM	N/A	1.5m	Shielding

1.4 I/O Port Description

I/O Port Types	Q’TY
1. DP Port	1
2. USB Port	4
3. LAN Port	2
4. COM Port	1
5. Audio Port	1
6. SW Port	1

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

1.5 Decision of Test Mode

The test configuration/ modes are as the following:

Conduction Modes (Power port):

1	**DP 3840*2160@60Hz**	**120VAC / 60Hz**
2		**230VAC / 60Hz**

Conduction Modes (Wired network ports):

1	**LAN 1**	**2.5Gbps**
2	**LAN 2**	**10Mbps**
3		**100Mbps**
4		**1Gbps**
5		**2.5Gbps**

Radiation Modes:

1	**DP 3840*2160@60Hz**	**100VAC / 50Hz**
2	**DP 3840*2160@60Hz**	**230VAC / 50Hz**
	DP 3840*2160@60Hz / 1-6GHz	

1.6 The Final Test Mode of the EUT

After the preliminary scan, the following test mode was found to produce the highest emission level.

Final Test Mode	
Conducted Emission	**Mode 2**
ISN	**Mode 2**
Radiated Emission Below 1GHz	**Mode 2**
Radiated Emission Above 1GHz	**Mode 2**
Harmonics & Flicker	**Mode 2**
Immunity	**Mode 2**

Then, the above highest emission mode of the configuration of the EUT and cable was chosen for all final test items.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

1.7 Configuration of Tested System



1.8 Operation Procedure

1. Windows 11 boots system.
2. Run colorbarmove.mp4 to activate all peripherals for test EUT.
3. Press the start menu, select executive and type ping 192.168.1.1&2 –t (EUT), ping 192.168.1.99 –t (Server PC).

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

1.9 Summary of Results

Emission		
Standard	**Test Type**	**Result**
EN 55032: 2015 + A11: 2020 CISPR 32: 2015 (Ed 2.0) + C1: 2016 BS EN 55032: 2015 + A11: 2020	Conducted Emission	PASS
	ISN	PASS
	Radiated Emission	PASS
EN IEC 61000-3-2: 2019 + A1: 2021 BS EN IEC 61000-3-2: 2019 + A1: 2021	Harmonic current emissions	PASS
EN 61000-3-3: 2013 + A1: 2019 + A2: 2021 BS EN 61000-3-3: 2013 + A1: 2019 + A2: 2021	Voltage changes, voltage fluctuations & flicker	PASS

Immunity			
Standard	**Test Type**	**Result**	**Performance Criteria**
IEC 61000-4-2: 2008	ESD	PASS	B
IEC 61000-4-3: 2020 (Ed. 4.0)	RS	PASS	A
IEC 61000-4-4: 2012	EFT	PASS	B
IEC 61000-4-5: 2014 + A1: 2017	Surge	PASS	B
IEC 61000-4-6: 2013 + COR1: 2015	CS	PASS	A
IEC 61000-4-8: 2009	PFMF	PASS	A
IEC 61000-4-11: 2020 + COR1: 2020 + COR2: 2022 (Ed. 3.0)	DIP	PASS	C/C/B

1.10 Reporting Statements of Conformity

The conformity statement in this report is based solely on the test results, measurement uncertainty is excluded.

1.11 Deviation

No deviation from the mentioned test methods and applicable standards.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

2. EMISSION

2.1 Limit

Maximum permissible level of Line Conducted Emission

FREQUENCY (MHz)	Class A(dBuV)		Class B(dBuV)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	79	66	66 - 56	56 - 46
0.50 - 5.0	73	60	56	46
5.0 - 30.0	73	60	60	50

Note: The lower limit shall apply at the transition frequency.

Maximum permissible level of Common Mode Conducted Emission (Asymmetric Mode)

Class A

FREQUENCY (MHz)	Voltage Limit(dBuV)		Current Limit(dBuA)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	97 - 87	84 - 74	53 - 43	40 - 30
0.5 - 30.0	87	74	43	30

Class B

FREQUENCY (MHz)	Voltage Limit(dBuV)		Current Limit(dBuA)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 - 0.5	84 - 74	74 - 64	40 - 30	30 - 20
0.5 - 30.0	74	64	30	20

Note: The lower limit shall apply at the transition frequency.

Maximum permissible level of Radiated Emission measured at 10 meter

FREQUENCY (MHz)	Class A(dBuV/m)	Class B(dBuV/m)
	Quasi - peak	Quasi - peak
30 - 230	40	30
230 - 1000	47	37

Note: The lower limit shall apply at the transition frequency.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Maximum permissible level of Radiated Emission measured at 3 meter

Frequency range (MHz)	Class A(dBuV/m)	Class B(dBuV/m)
	Quasi - peak	Quasi - peak
30 - 230	50	40
230 - 1000	57	47

Note: The lower limit shall apply at the transition frequency.

Limits above 1 GHz
Limits for radiated disturbance of Class A ITE at a measurement distance of 3m

Frequency range (GHz)	Average Limit dB(µV/m)	Peak Limit dB(µV/m)
1 - 3	56	76
3 - 6	60	80

Note: The lower limit applies at the transition frequency.

Limits for radiated disturbance of Class B ITE at a measurement distance of 3m

Frequency range (GHz)	Average Limit dB(µV/m)	Peak Limit dB(µV/m)
1 - 3	50	70
3 - 6	54	74

Note: The lower limit applies at the transition frequency.

Requirements for radiated emissions from FM receivers

Frequency range (MHz)	Measurement				Class B Limit dB(µV/m)
	Facility	Distance (m)	Detector type / Bandwidth	Fundamental	Harmonics
30 - 230	OATS/SAC	10	Quasi Peak / 120 kHz	50	42
230 - 300					42
300 - 1000					46
30 - 230	OATS/SAC	3	Quasi Peak / 120 kHz	60	52
230 - 300					52
300 - 1000					56
These relaxed limits apply only to emissions at the fundamental and harmonic frequencies of the LO. Signals at all other frequencies shall be compliant with the limits					

Note: SAC: Semi Anechoic Chamber
OATS: Open Area Test Site

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

2.2 Conducted Emission

2.2.1 Test Instruments

Conducted Emission Room # B					
EQUIPMENT TYPE	Manufacturer	Model Number	Serial Number	Calibration Date	Calibration Due
Attenuator	MCL	HAT-10	SD-C012	03/20/2023	03/19/2024
BNC Cable	EMEC	CFD300-NL	SD-C020	12/30/2022	12/29/2023
EMI Test Receiver	R&S	ESR3	102166	03/14/2023	03/13/2024
ISN	Teseq	ISN T800	30847	03/27/2023	03/26/2024
LISN	Schwarzbeck	NSLK 8127	01082	03/22/2023	03/21/2024
LISN(EUT)	Schwarzbeck	NSLK 8127	01084	03/22/2023	03/21/2024
Thermo-Hygro Meter	Wisewind	N/A	SD-S017	08/16/2023	08/15/2024
ISN	Teseq	ISN T8-Cat6	62685	07/20/2023	07/19/2024
Test S/W	EZ-EMC Ver.CCS-03A1				

Testing Site : No.163-1, Jhongsheng Rd., Xindian Dist., New Taipei City, Taiwan
Measurement Uncertainty of Conducted Emission
Expanded uncertainty Ulab (k=2) of Conducted Emission is 2.8 dB.
Expanded uncertainty Ulab (k=2) of ISN Conducted Emission is 3.1 dB
Expanded uncertainty CISPR 16-4-2:2011+A1:2014+A2:2018 (k=2) of Conducted Emission measurement is 3.8 dB.
Expanded uncertainty CISPR 16-4-2:2011+A1:2014+A2:2018 (k=2) of ISN Conducted Emission measurement is 5.0dB.

2.2.2 Measurement Level Calculation

Factor = LISN insertion loss + Cable loss + Pulse Limiter insertion loss
Measurement Level = Reading Level + Factor
Over (Margin) = Measurement Level – Limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

2.2.3 Measurement Data (CE)

Model No.	ARCHMI-821B	**6dB Bandwidth**	9 kHz
Environmental Conditions	24.8ºC, 52% RH	**Test Mode**	Mode 2
Tested by	Richard Liang	**Phase**	L1
Standard	EN 55032 CLASS B		



Conducted Emission Readings							
Frequency Range Investigated				**150 kHz to 30 MHz**			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
0.1770	**44.00**	**10.08**	**54.08**	**64.62**	**-10.54**	**P**	**L1**
0.4695	**33.89**	**10.11**	**44.00**	**56.52**	**-12.52**	**P**	**L1**
0.6000	**31.20**	**10.12**	**41.32**	**56.00**	**-14.68**	**P**	**L1**
4.5240	**32.98**	**10.30**	**43.28**	**56.00**	**-12.72**	**P**	**L1**
17.0925	**30.87**	**10.56**	**41.43**	**60.00**	**-18.57**	**P**	**L1**
26.5560	**29.85**	**10.67**	**40.52**	**60.00**	**-19.48**	**P**	**L1**

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Model No.	ARCHMI-821B	**6dB Bandwidth**	9 kHz
Environmental Conditions	24.8ºC, 52% RH	**Test Mode**	Mode 2
Tested by	Richard Liang	**Phase**	L2
Standard	EN 55032 CLASS B		



Conducted Emission Readings							
Frequency Range Investigated				**150 kHz to 30 MHz**			
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)	Line (L1/L2)
0.1770	**43.42**	**10.08**	**53.50**	**64.62**	**-11.12**	**P**	**L2**
0.3570	**32.74**	**10.08**	**42.82**	**58.80**	**-15.98**	**P**	**L2**
0.4650	**35.31**	**10.10**	**45.41**	**56.60**	**-11.19**	**P**	**L2**
0.6090	**34.26**	**10.11**	**44.37**	**56.00**	**-11.63**	**P**	**L2**
4.5465	**32.76**	**10.30**	**43.06**	**56.00**	**-12.94**	**P**	**L2**
28.3875	**25.94**	**10.72**	**36.66**	**60.00**	**-23.34**	**P**	**L2**

Note: 1. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line).

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

2.2.4 Measurement Data (ISN)

Model No.	ARCHMI-821B	**6dB Bandwidth**	9 kHz
Environmental Conditions	24.8°C, 52% RH	**Test Mode**	Mode 2
Tested by	Richard Liang	**Standard**	EN 55032 CLASS B



Conducted Emission Readings						
Frequency Range Investigated				150 kHz to 30 MHz		
Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Detector (P/Q/A)
0.6090	48.15	19.72	67.87	74.00	-6.13	P
0.6090	38.77	19.72	58.49	64.00	-5.51	A
1.6215	46.10	19.68	65.78	74.00	-8.22	P
1.6215	23.69	19.68	43.37	64.00	-20.63	A
1.8330	46.59	19.68	66.27	74.00	-7.73	P
1.8330	24.22	19.68	43.90	64.00	-20.10	A
2.0400	47.83	19.68	67.51	74.00	-6.49	P
2.0400	25.97	19.68	45.65	64.00	-18.35	A
2.2380	48.48	19.68	68.16	74.00	-5.84	P
2.2380	28.79	19.68	48.47	64.00	-15.53	A
2.8770	49.87	19.67	69.54	74.00	-4.46	P
2.8770	28.17	19.67	47.84	64.00	-16.16	A
3.0840	51.23	19.67	70.90	74.00	-3.10	P
3.0840	31.46	19.67	51.13	64.00	-12.87	A
3.3000	46.48	19.66	66.14	74.00	-7.86	Q
3.3000	34.05	19.66	53.71	64.00	-10.29	A

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

2.3 Radiated Emission

2.3.1 Test Instruments

Below 1GHz

Open Area Test Site # H					
EQUIPMENT TYPE	Manufacturer	Model Number	Serial Number	Calibration Date	Calibration Due
Bilog Antenna	Teseq	CBL 6112D	35411	05/04/2023	05/03/2024
Cable	EMEC	CFD400E-LW	SD-R074	08/10/2023	08/09/2024
EMI Test Receiver	R&S	ESCI	101340	02/04/2023	02/03/2024
Pre-Amplifier	HP	8447D	1937A01554	09/21/2023	09/20/2024
Thermo-Hygro Meter	Wisewind	201A	No. 03	05/23/2023	05/22/2024
Test S/W	EZ-EMC Ver.CCS-03A1				

Testing Site : No.163-1, Jhongsheng Rd., Xindian Dist., New Taipei City, Taiwan

Measurement Uncertainty of Radiated Emission

Expanded uncertainty Ulab (k=2) of Radiated Emission is 5.1 dB.(30MHz-1000MHz)

Expanded uncertainty CISPR 16-4-2:2011+A1:2014+A2:2018 (k=2) of Radiated Emission measurement is 5.2 dB.(30MHz-1000MHz)

Above 1GHz

Chamber # E					
EQUIPMENT TYPE	Manufacturer	Model Number	Serial Number	Calibration Date	Calibration Due
Horn Antenna	ETS-Lindgren	3117	00139062	06/08/2023	06/07/2024
Microflex Cable x 7m	JMT	LF01	SD-R089	06/07/2023	06/06/2024
K-Type Cable x 1m	JMT	LK01	SD-R087	06/07/2023	06/06/2024
Pre-Amplifier	EMCI	EMC012645SE	980917	06/21/2023	06/20/2024
Signal Analyzer	R&S	FSV40	101269	06/07/2023	06/06/2024
Thermo-Hygro Meter	Wisewind	201A	SD-R046	07/24/2023	07/23/2024
Test S/W	EZ-EMC Ver.CCS-03A1				

Testing Site : No.163-1, Jhongsheng Rd., Xindian Dist., New Taipei City, Taiwan

Measurement Uncertainty of Radiated Emission

Expanded uncertainty (k=2) of Radiated Emission measurement is 4.6 dB.(1-6GHz)

Expanded uncertainty CISPR 16-4-2:2011+A1:2014+A2:2018 (k=2) of Radiated Emission measurement is 5.5 dB.(1-6GHz)

2.3.2 Measurement Level Calculation

Correction Factor = Antenna Factor + Cable loss- Amplifier Gain
Measurement Level = Reading Level + Correction Factor
Over (Margin) = Measurement Level – Limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

2.3.3 Measurement Data

Below 1GHz

Model No.	ARCHMI-821B	**Test Mode**	Mode 2
Environmental Conditions	25.2°C, 52% RH	**6dB Bandwidth**	120 kHz
Antenna Pole	Vertical	**Antenna Distance**	10m
Detector Function	Quasi-peak.	**Tested by**	Richard Liang
Standard	EN 55032 CLASS B		



Radiated Emission Readings									
Frequency Range Investigated				**30 MHz to 1000 MHz at 10m**					
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Detector (P/Q)	Pol. (H/V)
152.4000	**34.20**	**-9.42**	**24.78**	**30.00**	**-5.22**	**100**	**330**	**Q**	**V**
185.1700	**34.30**	**-10.58**	**23.72**	**30.00**	**-6.28**	**100**	**248**	**Q**	**V**
599.9600	**31.10**	**1.51**	**32.61**	**37.00**	**-4.39**	**400**	**290**	**Q**	**V**
647.9500	**29.20**	**2.46**	**31.66**	**37.00**	**-5.34**	**400**	**76**	**Q**	**V**
695.9699	**31.50**	**2.07**	**33.57**	**37.00**	**-3.43**	**400**	**161**	**Q**	**V**
840.0100	**27.50**	**4.30**	**31.80**	**37.00**	**-5.20**	**400**	**110**	**Q**	**V**

Note: 1. P= Peak Reading; Q= Quasi-peak Reading.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Model No.	ARCHMI-821B	**Test Mode**	Mode 2
Environmental Conditions	25.2°C, 52% RH	**6dB Bandwidth**	120 kHz
Antenna Pole	Horizontal	**Antenna Distance**	10m
Detector Function	Quasi-peak.	**Tested by**	Richard Liang
Standard	EN 55032 CLASS B		



Radiated Emission Readings									
Frequency Range Investigated				**30 MHz to 1000 MHz at 10m**					
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Detector (P/Q)	Pol. (H/V)
36.2500	**27.50**	**-5.44**	**22.06**	**30.00**	**-7.94**	**400**	**158**	**Q**	**H**
151.7800	**34.80**	**-9.32**	**25.48**	**30.00**	**-4.52**	**400**	**48**	**Q**	**H**
600.0100	**31.80**	**1.51**	**33.31**	**37.00**	**-3.69**	**100**	**331**	**Q**	**H**
648.0100	**28.60**	**2.46**	**31.06**	**37.00**	**-5.94**	**100**	**29**	**Q**	**H**
695.9900	**31.50**	**2.07**	**33.57**	**37.00**	**-3.43**	**100**	**75**	**Q**	**H**
744.0000	**28.50**	**3.68**	**32.18**	**37.00**	**-4.82**	**100**	**139**	**Q**	**H**

Note: 1. P= Peak Reading; Q= Quasi-peak Reading.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Above 1GHz

Model No.	ARCHMI-821B	**Test Mode**	Mode 2
Environmental Conditions	25.3ºC, 52% RH	**6dB Bandwidth**	1 MHz
Antenna Pole	Vertical / Horizontal	**Antenna Distance**	3m
Highest frequency generated or used	2000MHz	**Upper frequency**	6000MHz
Detector Function	Peak and average.	**Tested by**	Richard Liang
Standard	EN 55032 CLASS B		

Radiated Emission Readings							
Frequency Range Investigated				Above 1GHz at 3m			
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
1525.000	**57.15**	**-8.85**	**48.30**	**70.00**	**-21.70**	**P**	**V**
1995.000	**53.77**	**-5.29**	**48.48**	**70.00**	**-21.52**	**P**	**V**
2250.000	**52.27**	**-4.95**	**47.32**	**70.00**	**-22.68**	**P**	**V**
2380.000	**52.16**	**-4.88**	**47.28**	**70.00**	**-22.72**	**P**	**V**
3200.000	**52.96**	**-4.09**	**48.87**	**74.00**	**-25.13**	**P**	**V**
5400.000	**54.48**	**-1.10**	**53.38**	**74.00**	**-20.62**	**P**	**V**

Radiated Emission Readings							
Frequency Range Investigated				Above 1GHz at 3m			
Freq. (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector (P/A)	Pol. (H/V)
1595.000	**53.90**	**-8.40**	**45.50**	**70.00**	**-24.50**	**P**	**H**
2220.000	**52.81**	**-5.04**	**47.77**	**70.00**	**-22.23**	**P**	**H**
2385.000	**53.18**	**-4.87**	**48.31**	**70.00**	**-21.69**	**P**	**H**
3195.000	**50.52**	**-4.08**	**46.44**	**74.00**	**-27.56**	**P**	**H**
4250.000	**48.85**	**-3.22**	**45.63**	**74.00**	**-28.37**	**P**	**H**
5400.000	**47.07**	**-1.10**	**45.97**	**74.00**	**-28.03**	**P**	**H**

Note: 1. P= Peak Reading; A= Average Reading.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

3. Harmonics

3.1 Test Instruments

Immunity A					
EQUIPMENT TYPE	Manufacturer	Model Number	Serial Number	Calibration Date	Calibration Due
5kVA Power Source	Teseq	NSG 1007-5	1537A01296	03/03/2023	03/02/2024
Signal Conditioning Unit	Teseq	CCN 1000-1	1846A01831	03/03/2023	03/02/2024
Test Software	WIN2100V4 Ver. 4.22				
Testing Site : No.163-1, Jhongsheng Rd., Xindian Dist., New Taipei City, Taiwan					

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

3.2 Measurement Data

Test Result: Pass **Source qualification: Normal**

Current & voltage waveforms



Harmonics and Class A limit line **European Limits**



Test result: Pass Worst harmonics H15-5.3% of 150% limit, H15-7% of 100% limit

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Result: Pass Source qualification: Normal
THC(A): 0.086 I-THD(%): 39.9 POHC(A): 0.013 POHC Limit(A): 0.251

Highest parameter values during test:

V_RMS (Volts):	229.86	Frequency(Hz):	50.00
I_Peak (Amps):	0.577	I_RMS (Amps):	0.252
I_Fund (Amps):	0.215	Crest Factor:	2.376
Power (Watts):	46.2	Power Factor:	0.817

Harm#	Harms(avg)	100%Limit	%of Limit	Harms(max)	150%Limit	%of Limit	Status
2	0.004	1.080	N/A	0.004	1.620	N/A	Pass
3	0.077	2.300	3.3	0.079	3.450	2.3	Pass
4	0.003	0.430	N/A	0.003	0.645	N/A	Pass
5	0.019	1.140	1.7	0.020	1.710	1.2	Pass
6	0.002	0.300	N/A	0.003	0.450	N/A	Pass
7	0.018	0.770	2.3	0.019	1.155	1.6	Pass
8	0.002	0.230	N/A	0.002	0.345	N/A	Pass
9	0.011	0.400	2.8	0.012	0.600	2.0	Pass
10	0.002	0.184	N/A	0.003	0.276	N/A	Pass
11	0.008	0.330	2.4	0.009	0.495	1.7	Pass
12	0.002	0.153	N/A	0.002	0.230	N/A	Pass
13	0.008	0.210	3.6	0.009	0.315	3.0	Pass
14	0.002	0.131	N/A	0.003	0.197	N/A	Pass
15	0.011	0.150	7.0	0.012	0.225	5.3	Pass
16	0.002	0.115	N/A	0.003	0.173	N/A	Pass
17	0.006	0.132	4.7	0.007	0.198	3.4	Pass
18	0.002	0.102	N/A	0.003	0.153	N/A	Pass
19	0.005	0.118	4.6	0.006	0.178	3.2	Pass
20	0.002	0.092	N/A	0.003	0.138	N/A	Pass
21	0.004	0.107	N/A	0.006	0.161	N/A	Pass
22	0.002	0.084	N/A	0.003	0.125	N/A	Pass
23	0.007	0.098	6.7	0.007	0.147	4.9	Pass
24	0.002	0.077	N/A	0.003	0.115	N/A	Pass
25	0.004	0.090	N/A	0.004	0.135	N/A	Pass
26	0.002	0.071	N/A	0.002	0.107	N/A	Pass
27	0.003	0.083	N/A	0.004	0.125	N/A	Pass
28	0.003	0.066	N/A	0.003	0.099	N/A	Pass
29	0.005	0.078	6.6	0.005	0.116	4.7	Pass
30	0.002	0.061	N/A	0.003	0.092	N/A	Pass
31	0.003	0.073	N/A	0.003	0.109	N/A	Pass
32	0.003	0.058	N/A	0.003	0.086	N/A	Pass
33	0.004	0.068	N/A	0.004	0.102	N/A	Pass
34	0.003	0.054	N/A	0.003	0.081	N/A	Pass
35	0.003	0.064	N/A	0.004	0.096	N/A	Pass
36	0.002	0.051	N/A	0.003	0.077	N/A	Pass
37	0.005	0.061	N/A	0.005	0.091	N/A	Pass
38	0.003	0.048	N/A	0.003	0.073	N/A	Pass
39	0.003	0.058	N/A	0.003	0.087	N/A	Pass
40	0.002	0.046	N/A	0.002	0.069	N/A	Pass

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Test Result: Pass **Source qualification: Normal**

Highest parameter values during test:

Voltage (Vrms):	229.86	Frequency(Hz):	50.00
I_Peak (Amps):	0.577	I_RMS (Amps):	0.252
I_Fund (Amps):	0.215	Crest Factor:	2.376
Power (Watts):	46.2	Power Factor:	0.817

Harm#	Harmonics V-rms	Limit V-rms	% of Limit	Status
2	0.040	0.460	8.80	OK
3	0.321	2.068	15.53	OK
4	0.021	0.460	4.51	OK
5	0.095	0.919	10.29	OK
6	0.029	0.460	6.35	OK
7	0.013	0.689	1.82	OK
8	0.008	0.460	1.72	OK
9	0.022	0.460	4.71	OK
10	0.009	0.460	2.02	OK
11	0.012	0.230	5.39	OK
12	0.015	0.230	6.34	OK
13	0.012	0.230	5.13	OK
14	0.005	0.230	2.13	OK
15	0.014	0.230	6.05	OK
16	0.007	0.230	2.89	OK
17	0.006	0.230	2.75	OK
18	0.011	0.230	4.97	OK
19	0.009	0.230	3.89	OK
20	0.024	0.230	10.23	OK
21	0.006	0.230	2.45	OK
22	0.003	0.230	1.51	OK
23	0.007	0.230	3.24	OK
24	0.003	0.230	1.23	OK
25	0.006	0.230	2.51	OK
26	0.003	0.230	1.38	OK
27	0.009	0.230	3.79	OK
28	0.003	0.230	1.15	OK
29	0.008	0.230	3.42	OK
30	0.005	0.230	2.15	OK
31	0.004	0.230	1.66	OK
32	0.003	0.230	1.28	OK
33	0.004	0.230	1.56	OK
34	0.003	0.230	1.30	OK
35	0.006	0.230	2.59	OK
36	0.003	0.230	1.37	OK
37	0.008	0.230	3.49	OK
38	0.003	0.230	1.16	OK
39	0.005	0.230	2.09	OK
40	0.016	0.230	6.77	OK

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4. Flicker

4.1 Test Instruments

Immunity A					
EQUIPMENT TYPE	Manufacturer	Model Number	Serial Number	Calibration Date	Calibration Due
5kVA Power Source	Teseq	NSG 1007-5	1537A01296	03/03/2023	03/02/2024
Signal Conditioning Unit	Teseq	CCN 1000-1	1846A01831	03/03/2023	03/02/2024
Test Software	WIN2100V4 Ver. 4.22				
Testing Site : No.163-1, Jhongsheng Rd., Xindian Dist., New Taipei City, Taiwan					

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

4.2 Measurement Data

Test Result: Pass **Status: Test Completed**

Pst$_i$ and limit line **European Limits**



Plt and limit line

Parameter values recorded during the test:

Vrms at the end of test (Volt):	229.70			
Highest dt (%):		Test limit (%):		
T-max (mS):	0	Test limit (mS):	500.0	Pass
Highest dc (%):	0.00	Test limit (%):	3.30	Pass
Highest dmax (%):	0.00	Test limit (%):	4.00	Pass
Highest Pst (10 min. period):	0.064	Test limit:	1.000	Pass
Highest Plt (2 hr. period):	0.028	Test limit:	0.650	Pass

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

5. IMMUNITY

5.1 STANDARD PERFORMANCE CRITERIA DESCRIPTION

Criterion A - The apparatus shall continue to operate as intended. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended.

Criterion B - The apparatus shall continue to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended.

Criterion C - Temporary loss of function is allowed, provided the function is self recoverable or can be restored by the operation of the controls.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

5.2 SPECIAL PERFORMANCE CRITERIA DESCRIPTION

5.2.1 Performance Criteria Description for Print function

Criterion A - Apply criterion A as defined in 8.2. Additionally, the following shall not occur as a consequence of the application of the disturbance:

- change of operating state;
- unintended pausing of the print operation;
- a change of print quality or legibility, as appropriate to the test pattern;
- change of character font;
- unintended line feed;
- unintended page feed;
- paper feed failure.

Criterion B - Apply criterion B as defined in 8.3 with the following specifics and additional limitations. Paper feed failures are allowed only if, after removal of the jammed sheets, the job is automatically recovered and there is no loss of printed information. Any low-quality print output caused by the application of the disturbance shall not continue beyond the sheet of media being printed, or beyond the typical length of a finished page or sheet printed from continuous roll media. False indicators are permitted during the test provided that a normal operator response to that false indicator is simple (such as pressing a button). False indicators are not acceptable if they would cause the user to discard printing supplies such as ink, toner or paper, when those supplies are actually not empty or faulty. Any false indicator shall either clear automatically or after the operator's response. After the disturbance, the print function may print the remainder of the print job at a quality level within the manufacturer's specifications. Alternately, the print function may halt processing of a print job as a result of the disturbance, but only if the operator is capable of reprinting the job (for example, a fax printing job where the image to be printed still resides in local memory). Automatically restarting the print job from the beginning is also acceptable. In any scenario, the pairing of front and back images during double-sided printing shall be correct.

Criterion C - Temporary loss of function is allowed, provided the function is self recoverable or can be restored by the operation of the controls.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

5.2.2 Performance Criteria Description for Scan function

Criterion A - Apply criterion A as defined in 8.2. Additionally, the following shall not occur as a consequence of the application of the test:

- change of settings, such as which side(s) of the page to be scanned, colour or monochrome, and resolution;
- corruption of the image, for example stretching, compressing or change in colour;
- paper feed failures;
- errors in the reading of bar codes.

Criterion B - Apply criterion B as defined in 8.3 with the following specifics and additional limitations.

- Document feed failures are allowed only if the original documents are undamaged and, after removal of the jammed sheets, the job is automatically recovered and there is no loss of scanned information.
- During the test, the representation of the image shall not be degraded such that reading mistakes occur.

Criterion C - Temporary loss of function is allowed, provided the function is self recoverable or can be restored by the operation of the controls.

5.2.3 Performance Criteria Description for Display and display output function

Criterion A - Apply criterion A as defined in 8.2. Additionally, an increase in any degradation greater than just perceptible by observation of the image shall not occur as a consequence of the application of the test. Examples of such degradations are:

- superimposed patterning;
- positional disturbances due to synchronisation errors;
- geometric distortion;
- change of contrast or brightness;
- picture artefacts;
- freezing or disturbance of motion;
- image loss;
- video data or decoding errors.

Criterion B - The apparatus shall continue to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended.

Criterion C - Temporary loss of function is allowed, provided the function is self recoverable or can be restored by the operation of the controls.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

5.2.4 Performance Criteria Description for Musical tone generating function

Criterion A - Performance criterion A is subdivided according to the type of equipment and its use. Three subgroups corresponding to different equipment types are defined in Table E.1 and have corresponding performance criteria A1, A2 and A3. The relevant subgroup shall be selected by the manufacturer in accordance with the product specification. The description of criteria A1, A2 and A3 are presented in Table E.2.

Criterion B - During the test, degradation of performance beyond that defined in criterion A1 of Table E.2 is allowed. However, sudden amplification of tone to a level that exceeds the expected level by more than 6 dB is not allowed. After the test, normal operation of the EUT shall be self-recovered. In the case of unintended tone holding caused by a MIDI protocol communication error, the EUT can be re-initialised by the operation of the controls by the user controls in accordance with the manufacturer's instructions. Due to the nature of the MIDI protocol, it is necessary to modify the performance criterion B to allow user intervention when the unintended tone holding is caused by a missing MIDI communication error (for example missing a 'NOTE OFF' message).

Criterion C - Degradation of the performance beyond that defined in criterion A1 of Table E.2 is permitted provided that the normal operation of the EUT can be restored after the test by operator intervention. However, sudden amplification of tone to a level that exceeds the expected level by more than 6 dB is not allowed.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

5.2.5 Performance Criteria Description for Networking function

Criterion A - Where relevant, during the application of the test the network function shall, as a minimum, operate ensuring that:

- established connections shall be maintained throughout the application of the test;
- no change of operational state or corruption of stored data occurs;
- no increase in error rate above the figure defined by the manufacturer occurs. The manufacturer should select the most appropriate performance measurement criteria for the product or system, for example bit error rate, block error rate;
- no request for retry above the figure defined by the manufacturer;.
- the data transmission rate does not reduce below the figure defined by the manufacturer;
- no protocol failure occurs;
- the audio noise level at a two-wire analogue interface (supporting telephony) shall satisfy the requirements of Table G.3. The audio level measurements shall be performed at the demodulated frequency of the disturbance using a narrowband filter with a 3 dB bandwidth of 100 Hz using the method defined in table clause G.1.4. See G.6.1. As described in the example given in J.3.5 the networking function is monitored during testing using direct functions specified elsewhere in this document. If needed to verify the operation of the protocol, the following functions shall be verified as described in Table H.1 when performing the additional spot frequency tests contained in Clause 5:
- ability to establish a connection,
- ability to clear a connection.

Where an EUT has supervisory functions they shall not be affected. Elements that should be monitored include, but are not limited to:

- alarms,
- signalling lamps,
- printer output errors,
- network traffic rates,
- network monitor errors,
- measured network parameters.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Criterion B - Established connections shall be maintained throughout the test, or shall self-recover in a way and timescale that is imperceptible to the user.

The error rate, request for retry and data transmission rates may be degraded during the application of the test. Degradation of the performance as described in criterion A is permitted, provided that the normal operation of the EUT is self-recoverable to the condition established prior to the application of the test. Where required, as defined in Clause 5, the acceptable operation of the function shall be verified at the completion of the test as described in Table H.1, by confirming the following:

• the EUT's ability to establish a connection,
• the EUT's ability to clear a connection.

During surge testing disconnection is allowed on the analogue/digital data port being tested. If the EUT is a supervisory equipment, it shall not impact the normal operation of the network being monitored. In addition, any supervisory functions impacted during the period of the test shall return to the state prior to the test. Elements to consider include:

• alarms,
• signalling lamps,
• printer output,
• network traffic rates,
• network monitoring. is used as intended.

Criterion C - Degradation of performance as described in criteria A and B is permitted provided that the normal operation of the EUT is self-recoverable to the condition immediately before the application of the test, or can be restored after the test by the operator.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

5.2.6 Performance Criteria Description for Audio output function

Criterion A - The interference ratio (electrical or acoustic) shall meet the limits in column 3; or,
the acoustic level of the demodulated audio shall be less than the limits in column 4; or,
the digitally coded level of demodulated audio shall be less than limits in column 5; or,
the analogue level of the demodulated audio shall be less than the limits in column 6.

Criterion B - The apparatus shall continue to operate as intended after the test. No degradation of performance or loss of function is allowed below a performance level specified by the manufacturer, when the apparatus is used as intended.

Criterion C - Temporary loss of function is allowed, provided the function is self recoverable or can be restored by the operation of the controls.

5.2.7 Performance Criteria Description for Telephony function

Function to be exercised	Performance criteria		
	A	B	C
Establish new communication	At the additional spot frequency tests a, c	Performed before and after the application of the test or disturbance	Performed before and after the application of the test or disturbance
Maintain established communication	Yes In addition, the requirements of Annex G for the audio output function shall be satisfied c	Yes b	No
Terminate established communication	At the additional spot frequency tests a, c	Performed before and after the application of the test or disturbance	Performed before and after the application of the test or disturbance

Communication refers to a telephone call or other form of voice connection.
a Applicable to TTE with a dial function that provides dedicated emergency service/safety of life call capability. Where the EUT does not provide this functionality, this limitation shall be stated in the equipment user manual.
b Communication shall be established prior to the application of the disturbance, the communication shall be maintained and the quality of that communication (for example, volume setting, the level of background noise) shall be maintained after completion of the test or disturbance.
c Where defined in Clause 5 (for the tests in Table 1 to Table 4), these functional tests shall be performed during the additional spot frequency tests.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

5.3 Test of IEC 61000-4-2

5.3.1 Test Instruments

Immunity Shielded Room					
EQUIPMENT TYPE	Manufacturer	Model Number	Serial Number	Calibration Date	Calibration Due
Aneroid Barometer	SATO	7610-20	89090	07/24/2023	07/23/2024
ESD Simulator	Teseq	NSG 437	1812	12/19/2022	12/18/2023
Thermo-Hygro Meter	Wisewind	201A	SD-S041	12/23/2022	12/22/2023
Testing Site : No.163-1, Jhongsheng Rd., Xindian Dist., New Taipei City, Taiwan					

5.3.2 EUT Operating Condition

Environment:

Temperature	Humidity	Air Pressure
22.8 °C	48 %RH	1009 hpa

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

5.3.3 Results of Electrostatic Discharge Test (ESD)

Model No. : ARCHMI-821B
Tested By : Richard Liang
Tested Date : October 12, 2023
Test Mode : Mode 2
Basic Standard : IEC 61000-4-2
Discharge Impedance : 330 ohm / 150 pF
Discharge Voltage : Air Discharge: ±2, 4, 8 kV
Contact Discharge: ±2, 4 kV
HCP/VCP: ±2, 4 kV
Polarity : Positive/Negative
Number of Discharge : 10 times at each test point
Discharge Mode : Single Discharge
Discharge Period : 1 second

A.Observations:

Test points: 1. Front side. 2. Back side. 3. Left side. 4. Right side.
5. Top side. 6. Bottom side

Direct Application			Test Results	
Discharge Level (kV)	Polarity (+/-)	Test Point	Contact Discharge	Air Discharge
2, 4, 8 (Air.)	+/-	1~2	N/A	A
2, 4 (Cont.)	+/-	1	No discharge point	N/A
2, 4 (Cont.)	+/-	2~5	A	N/A

Remark: A: No degradation of performance or loss of function.
N/A: Not Applicable.

B.Observations:

Test points: 1. Front side. 2. Back side. 3. Left side. 4. Right side.

Indirect Application			Test Results	
Discharge Level (kV)	Polarity (+/-)	Test Point	Horizontal Coupling	Vertical Coupling
2, 4	+/-	1-4	A	A

Remark: A: No degradation of performance or loss of function.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

ESD Test point

Front

Back

Air Discharge: ↑
Contact Discharge: ↑

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Left

Right

Air Discharge: ↑
Contact Discharge: ↑

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Top

Air Discharge:
Contact Discharge:

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

5.4 Test of IEC 61000-4-3

5.4.1 Test Instruments

844 RS Chamber					
EQUIPMENT TYPE	Manufacturer	Model Number	Serial Number	Calibration Date	Calibration Due
Electric Field Probe	AR	FL7006	0356656	03/19/2023	03/18/2024
Field of Calibration	CCS	Chamber#RS	80-1000MHz	02/20/2023	02/19/2024
RF Power Meter	Boonton	4242	17419	02/14/2023	02/13/2024
Power Sensor	Boonton	51011A-EMC	36833	02/14/2023	02/13/2024
Power Sensor	Boonton	51011A-EMC	36834	02/14/2023	02/13/2024
Thermo-Hygro Meter	Wisewind	N/A	SD-S019	09/21/2023	09/20/2024
Broadband Antenna	AR	AT1080	311819	N.C.R	N.C.R
Power Amplifier	Teseq	CBA1G-600D	1098099	N.C.R	N.C.R
Analog Signal Generator	Agilent	E8257D	MY48051214	06/05/2023	06/04/2024
Field of Calibration	CCS	Chamber#RS	1000-6000MHz	02/17/2023	02/16/2024
Microwave Antenna	Schwarzbeck	STLP 9149	767	N.C.R	N.C.R
Power Amplifier	Teseq	CBA6G-100D	1087370	N.C.R	N.C.R
Sound Level Calibrator	B&K	4231	3010869	07/29/2023	07/28/2024
Audio Bandpass Amp.	CCSRF	ABT-F	007	05/22/2023	05/21/2024
Test Software	EmcwareVer. 2.6.0.16				
Testing Site : No.163-1, Jhongsheng Rd., Xindian Dist., New Taipei City, Taiwan					

5.4.2 EUT Operating Condition

Environment:

Temperature	Humidity	Air Pressure
23.5 °C	48 %RH	1009 hpa

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

5.4.3 Results of Radiated Radio Frequency Electromagnetic (RS)

Model No. : ARCHMI-821B
Tested By : Richard Liang
Tested Date : October 12, 2023
Test Mode : Mode 2
Basic Standard : IEC 61000-4-3
Frequency range : 80 MHz - 1000 MHz
Frequency range : 1800 MHz, 2600 MHz, 3500 MHz, 5000 MHz (±1%)
Field strength : 3 V/m
Modulation : 80% AM (1kHz)
Frequency step : 1 % of fundamental
Polarity of Antenna : Horizontal and Vertical
Dwell Time : 3 seconds
Test distance : 3 m

No.	Frequency (MHz)	Antenna Orientation	Observation	EUT Orientation
1	80 - 1000	Vertical/Horizontal	A	0 degree
2	80 - 1000	Vertical/Horizontal	A	90 degree
3	80 - 1000	Vertical/Horizontal	A	180 degree
4	80 - 1000	Vertical/Horizontal	A	270 degree

Remark: A: No degradation of performance or loss of function.

No.	Frequency (MHz)	Antenna Orientation	Observation	EUT Orientation
1	1800, 2600, 3500, 5000 (±1%)	Vertical/Horizontal	A	0 degree
2	1800, 2600, 3500, 5000 (±1%)	Vertical/Horizontal	A	90 degree
3	1800, 2600, 3500, 5000 (±1%)	Vertical/Horizontal	A	180 degree
4	1800, 2600, 3500, 5000 (±1%)	Vertical/Horizontal	A	270 degree

Remark: A: No degradation of performance or loss of function.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Model No. : ARCHMI-821B
Tested By : Richard Liang
Tested Date : October 12, 2023
Test Mode : Mode 2 (Audio)
Basic Standard : IEC 61000-4-3
Frequency range : 80 MHz - 1000 MHz
Frequency range : 1800 MHz, 2600 MHz, 3500 MHz, 5000 MHz (±1%)
Field strength : 3 V/m
Modulation : 80% AM (1kHz)
Frequency step : 1 % of fundamental
Polarity of Antenna : Horizontal and Vertical
Dwell Time : 3 seconds
Test distance : 3 m

No.	Frequency (MHz)	Antenna Orientation	Observation	EUT Orientation
1	80 - 1000	Vertical/Horizontal	A	0 degree
2	80 - 1000	Vertical/Horizontal	A	90 degree
3	80 - 1000	Vertical/Horizontal	A	180 degree
4	80 - 1000	Vertical/Horizontal	A	270 degree

Remark: A: No degradation of performance or loss of function.

No.	Frequency (MHz)	Antenna Orientation	Observation	EUT Orientation
1	1800, 2600, 3500, 5000 (±1%)	Vertical/Horizontal	A	0 degree
2	1800, 2600, 3500, 5000 (±1%)	Vertical/Horizontal	A	90 degree
3	1800, 2600, 3500, 5000 (±1%)	Vertical/Horizontal	A	180 degree
4	1800, 2600, 3500, 5000 (±1%)	Vertical/Horizontal	A	270 degree

Remark: A: No degradation of performance or loss of function

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Model No. : ARCHMI-821B
Tested By : Richard Liang
Tested Date : October 12, 2023
Test Mode : Mode 2 (Speaker)
Basic Standard : IEC 61000-4-3
Frequency range : 80 MHz - 1000 MHz
Frequency range : 1800 MHz, 2600 MHz, 3500 MHz, 5000 MHz (±1%)
Field strength : 3 V/m
Modulation : 80% AM (1kHz)
Frequency step : 1 % of fundamental
Polarity of Antenna : Horizontal and Vertical
Dwell Time : 3 seconds
Test distance : 3 m

No.	Frequency (MHz)	Antenna Orientation	Observation	EUT Orientation
1	80 - 1000	Vertical/Horizontal	A	0 degree
2	80 - 1000	Vertical/Horizontal	A	90 degree
3	80 - 1000	Vertical/Horizontal	A	180 degree
4	80 - 1000	Vertical/Horizontal	A	270 degree

Remark: A: No degradation of performance or loss of function.

No.	Frequency (MHz)	Antenna Orientation	Observation	EUT Orientation
1	1800, 2600, 3500, 5000 (±1%)	Vertical/Horizontal	A	0 degree
2	1800, 2600, 3500, 5000 (±1%)	Vertical/Horizontal	A	90 degree
3	1800, 2600, 3500, 5000 (±1%)	Vertical/Horizontal	A	180 degree
4	1800, 2600, 3500, 5000 (±1%)	Vertical/Horizontal	A	270 degree

Remark: A: No degradation of performance or loss of function

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

5.5 Test of IEC 61000-4-4

5.5.1 Test Instruments

Immunity Shield Room					
EQUIPMENT TYPE	Manufacturer	Model Number	Serial Number	Calibration Date	Calibration Due
Capacitive Clamp	EMC-Partner	CN-EFT1000	589	02/21/2023	02/20/2024
EMC Test System	Teseq	NSG 3060	1718	11/24/2022	11/23/2023
Software	WIN 3000Ver. 1.3.2				
Testing Site : No.163-1, Jhongsheng Rd., Xindian Dist., New Taipei City, Taiwan					

5.5.2 EUT Operating Condition

Environment:

Temperature	Humidity	Air Pressure
22.8 °C	48 %RH	1009 hpa

5.5.3 Results of Electrical Fast Transient (EFT)

Model No. : ARCHMI-821B
Tested By : Richard Liang
Tested Date : October 12, 2023
Test Mode : Mode 2
Basic Standard : IEC 61000-4-4
Test Voltage : AC Input: ± 1 kV
Signal/Comm. : ± 0.5 kV
Polarity : Positive/Negative
Impulse Frequency : 5 kHz
Tr/Th : 5/50ns
Burst : 15ms/300ms

Observation:

Test Point	Polarity	Test Level (kV)	Results
L	+/-	1	A
N	+/-	1	A
L – N	+/-	1	A
PE	+/-	1	A
L – PE	+/-	1	A
N – E	+/-	1	A
L – N – PE	+/-	1	A
RJ45	+/-	0.5	A
RJ45 (2.5G)	+/-	0.5	A

Remark: A: No degradation of performance or loss of function

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

5.6 Test of IEC 61000-4-5

5.6.1 Test Instruments

Immunity Shield Room					
EQUIPMENT TYPE	Manufacturer	Model Number	Serial Number	Calibration Date	Calibration Due
CDN	EMC-Partner	CDN-UTP8	1505	11/24/2022	11/23/2023
EMC Test System	Teseq	NSG 3060	1718	11/24/2022	11/23/2023
Software	WIN 3000Ver. 1.3.2				
Testing Site : No.163-1, Jhongsheng Rd., Xindian Dist., New Taipei City, Taiwan					

5.6.2 EUT Operating Condition

Environment:

Temperature	Humidity	Air Pressure
22.8 °C	48 %RH	1009 hpa

5.6.3 Results of Surge Test

Model No. : ARCHMI-821B
Tested By : Richard Liang
Tested Date : October 4, 2023
Test Mode : Mode 2
Basic Standard : IEC 61000-4-5
Test Rate : 1 pulse every minute
No. of Tests : 5 positive and 5 negative pulses
Waveform : 1.2/50μs (8/20μs)

Observation Description

AC input line:

Test Point	Phase Angle (degree)	Polarity (+/-)	Test Level (kV)	Observation
L – N	0, 90, 180, 270	+/-	1	A
L – PE	0, 90, 180, 270	+/-	2	A
N – PE	0, 90, 180, 270	+/-	2	A

Remark: A: No degradation of performance or loss of function.

Signal line:
Test Rate : 1 pulse every minute
No. of Tests : 5 positive and 5 negative pulses
Waveform : 10/700μs (5/320μs); 1.2/50μs (8/20μs)

Observation Description

Signal line:

Test Point	Phase Angle (degree)	Polarity (+/-)	Test Level (kV)	Observation
RJ45	No phase angle (degree)	+/-	1	B
RJ45 (2.5G)	No phase angle (degree)	+/-	0.5	B

Remark: B: During the test, data accessing via LAN was paused. It could become normal after test stopped.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

5.7 Test of IEC 61000-4-6

5.7.1 Test Instruments

CS Room					
EQUIPMENT TYPE	Manufacturer	Model Number	Serial Number	Calibration Date	Calibration Due
CDN	Teseq	CDN M116	35362	12/13/2022	12/12/2023
CDN	Teseq	CDN M016	35820	12/13/2022	12/12/2023
CDN	Teseq	CDN T400A	25674	12/13/2022	12/12/2023
CDN	SCHAFFNER	CDN M325	17457	12/13/2022	12/12/2023
CDN	Teseq	CDN T8-10	40378	07/07/2023	07/06/2024
Continuous Wave Simulator	EM Test	CWS 500N1.4	P1446143188	12/11/2022	12/10/2023
EM Clamp	Schaffner	KEMZ 801	19227	12/14/2022	12/13/2023
Attenuator	EMCI	SA3NL	10006F	N.C.R	N.C.R
Sound Level Calibrator	B&K	4231	3010869	07/29/2023	07/28/2024
Power Module	G.R.A.S.	12AK	35913	N/A	N/A
Bandpass Filter	CCSRF	35-01	SD-S018	N/A	N/A
RF Counter	Agilent	53210A	MY50000797	05/10/2023	05/09/2024
Audio Bandpass Amp.	CCSRF	ABT-CB	007	05/22/2023	05/21/2024
Test Software	NSG 4070 Control Program V1.2.0				
Testing Site : No.163-1, Jhongsheng Rd., Xindian Dist., New Taipei City, Taiwan					

5.7.2 EUT Operating Condition

Environment:

Temperature	Humidity	Air Pressure
23.2 °C	48 %RH	1009 hpa

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

5.7.3 Results of Immunity to Conducted Disturbances (CS)

Model No. : ARCHMI-821B
Tested By : Richard Liang
Tested Date : October 12, 2023
Test Mode : Mode 2
Basic Standard : IEC 61000-4-6
Frequency range : 0.15 MHz -10 MHz
Field strength : 3 Vrms
Frequency range : 10 MHz - 30 MHz
Field strength : 3 V to 1Vrms
Frequency range : 30 MHz - 80 MHz
Field strength : 1 Vrms
Modulation : 80% AM, 1 kHz Sinewave
Frequency step : 1 % of fundamental
Dwell Time : 3 seconds
Coupling Method : CDN-M3; CDN-T8; EM Clamp

Cable Description	Frequency (MHz)	Observation
AC input	0.15 – 80	A

Signal Ports

Cable Description	Frequency (MHz)	Observation
RJ45	0.15 – 80	A
RJ45 (2.5G)	0.15 – 80	A

Remark: A: No degradation of performance or loss of function.

Model No. : ARCHMI-821B
Tested By : Richard Liang
Tested Date : October 12, 2023
Test Mode : Mode 2 (Audio)
Basic Standard : IEC 61000-4-6
Frequency range : 0.15 MHz -10 MHz
Field strength : 3 Vrms
Frequency range : 10 MHz - 30 MHz
Field strength : 3 V to 1Vrms
Frequency range : 30 MHz - 80 MHz
Field strength : 1 Vrms
Modulation : 80% AM, 1 kHz Sinewave
Frequency step : 1 % of fundamental
Dwell Time : 3 seconds
Coupling Method : CDN-M3; CDN-T8; EM Clamp

Cable Description	Frequency (MHz)	Observation
AC input	0.15 – 80	A

Signal Ports

Cable Description	Frequency (MHz)	Observation
RJ45	0.15 – 80	A
RJ45 (2.5G)	0.15 – 80	A

Remark: A: No degradation of performance or loss of function.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Model No. : ARCHMI-821B
Tested By : Richard Liang
Tested Date : October 12, 2023
Test Mode : Mode 2 (Speaker)
Basic Standard : IEC 61000-4-6
Frequency range : 0.15 MHz -10 MHz
Field strength : 3 Vrms
Frequency range : 10 MHz - 30 MHz
Field strength : 3 V to 1Vrms
Frequency range : 30 MHz - 80 MHz
Field strength : 1 Vrms
Modulation : 80% AM, 1 kHz Sinewave
Frequency step : 1 % of fundamental
Dwell Time : 3 seconds
Coupling Method : CDN-M3; CDN-T8; EM Clamp

Cable Description	Frequency (MHz)	Observation
AC input	0.15 – 80	A

Signal Ports

Cable Description	Frequency (MHz)	Observation
RJ45	0.15 – 80	A
RJ45 (2.5G)	0.15 – 80	A

Remark: A: No degradation of performance or loss of function.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

5.8 Test of IEC 61000-4-8

5.8.1 Test Instruments

Immunity Shield Room					
EQUIPMENT TYPE	Manufacturer	Model Number	Serial Number	Calibration Date	Calibration Due
5kVA Power Source	Teseq	5001IX-208-SCH	1207A03643	09/15/2022	09/14/2024
AC/DC Clamp Meter	Fluke	353	33360025	06/09/2023	06/08/2024
Magnetic Field Coil	Teseq	INA 703 W/ 2141	1976 / 1413	02/22/2023	02/21/2024
Magnetic Field Meter	Sypris	4080	0247	11/28/2022	11/27/2023
Test Software	Win2120Ver. 5.0				
Testing Site : No.163-1, Jhongsheng Rd., Xindian Dist., New Taipei City, Taiwan					

5.8.2 EUT Operating Condition

Environment:

Temperature	Humidity	Air Pressure
21 °C	49 %RH	1008 hpa

5.8.3 Result of Immunity to Power Frequency Magnetic Field

Model No. : ARCHMI-821B
Tested By : Richard Liang
Tested Date : October 12, 2023
Test Mode : Mode 2
Basic Standard : IEC 61000-4-8
Power Frequency : 50 Hz
Magnetic Field : 1 A/m(r.m.s)
Coil Orientation : X, Y, Z Axis
Observation : A

Remark: A: No degradation of performance or loss of function

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

5.9 Test of IEC 61000-4-11

5.9.1 Test Instruments

Immunity Shielded Room					
EQUIPMENT TYPE	Manufacturer	Model Number	Serial Number	Calibration Date	Calibration Due
AC/DC Clamp Meter	Lutron	CM-9930R	I.200121	03/27/2023	03/26/2024
EMC Test System	Teseq	NSG 3060	1718	11/24/2022	11/23/2023
Software	WIN 3000Ver. 1.3.2				
Testing Site : No.163-1, Jhongsheng Rd., Xindian Dist., New Taipei City, Taiwan					

5.9.2 EUT Operating Condition

Environment:

Temperature	Humidity	Air Pressure
22.8 °C	48 %RH	1009 hpa

5.9.3 Results of Voltage Dips Immunity Test

Model No. : ARCHMI-821B
Tested By : Richard Liang
Tested Date : October 12, 2023
Test Mode : Mode 2
Basic Standard : IEC 61000-4-11
EUT Rated Voltage : 230 Volts.
Reduction Voltage : 30, >95 % Ut
Phase Angle : 0,180 degree
Total events : 3 dropouts
Event interval : 10 seconds

Test Power: 230Vac, 50Hz			
Environmental phenomena	**Test specification (% reduction)**	**Duration (in periods of the rated frequency)**	**Observation**
Voltage Interruptions	>95	250	C
Voltage dips	30	25	A
	>95	0.5	A

Test Power: 230Vac, 60Hz			
Environmental phenomena	**Test specification (% reduction)**	**Duration (in periods of the rated frequency)**	**Observation**
Voltage Interruptions	>95	300	C
Voltage dips	30	30	A

Remark: A: No degradation of performance or loss of function.
C: EUT shut down, it could not become normal except reinstalled by operator.

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

APPENDIX

Photograph of Testing General Set-up

CE Testing Set-up

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

ISN Testing Set-up (10Mbps / 100Mbps / 1Gbps)

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

ISN Testing Set-up (2.5Gbps)

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

RE Testing Set-up

Below 1GHz

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Above 1GHz





This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

HARMONIC & FLICKER Testing Set-up

ESD Testing Set-up

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

RS Testing Set-up

RS Testing Set-up (Audio)

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

RS Testing Set-up (Speaker)



EFT Testing Set-up



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

EFT For RJ45 Testing Set-up

EFT For RJ45 Testing Set-up (2.5G)

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Surge Testing Set-up



Surge For RJ45 Testing Set-up

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Surge For RJ45 Testing Set-up (2.5G)

CS Testing Set-up

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

CS For RJ45 Testing Set-up

CS For RJ45 Testing Set-up (2.5G)



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

CS Testing Set-up (Audio)

CS For RJ45 Testing Set-up (Audio)

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

CS For RJ45 Testing Set-up (2.5G) (Audio)

CS Testing Set-up (Speaker)



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

CS For RJ45 Testing Set-up (Speaker)



CS For RJ45 Testing Set-up (2.5G) (Speaker)



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

PFMF Testing Set-up

DIP Testing Set-up



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

Photographs of EUT Unit

Exterior



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。



This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。

** End of Report **

This document cannot be reproduced except in full, without prior written approval of the Company. 本報告未經本公司書面許可，不可部份複製。