



PROJECT SPECIFICATION

FlightSurety**Separation of Concerns, Operational Control and "Fail Fast"**

CRITERIA	MEETS SPECIFICATIONS
Smart Contract Separation	<p>Smart Contract code is separated into multiple contracts:</p> <ol style="list-style-type: none">1) FlightSuretyData.sol for data persistence2) FlightSuretyApp.sol for app logic and oracles code
Dapp Created and Used for Contract Calls	<p>A Dapp client has been created and is used for triggering contract calls. Client can be launched with "npm run dapp" and is available at http://localhost:8000</p> <p>Specific contract calls:</p> <ol style="list-style-type: none">1) Passenger can purchase insurance for flight2) Trigger contract to request flight status update
Oracle Server Application	<p>A server app has been created for simulating oracle behavior. Server can be launched with "npm run server"</p>

CRITERIA	MEETS SPECIFICATIONS
Operational status control is implemented in contracts	Students has implemented operational status control.
Fail Fast Contract	Contract functions "fail fast" by having a majority of "require()" calls at the beginning of function body

Airlines

CRITERIA	MEETS SPECIFICATIONS
Airline Contract Initialization	First airline is registered when contract is deployed.
Multiparty Consensus	<p>Only existing airline may register a new airline until there are at least four airlines registered</p> <p>Demonstrated either with Truffle test or by making call from client Dapp</p>

CRITERIA	MEETS SPECIFICATIONS
Multiparty Consensus	<p>Registration of fifth and subsequent airlines requires multi-party consensus of 50% of registered airlines</p> <p>Demonstrated either with Truffle test or by making call from client Dapp</p>
Airline Ante	<p>Airline can be registered, but does not participate in contract until it submits funding of 10 ether</p> <p>Demonstrated either with Truffle test or by making call from client Dapp</p>

Passengers

CRITERIA	MEETS SPECIFICATIONS
Passenger Airline Choice	Passengers can choose from a fixed list of flight numbers and departure that are defined in the Dapp client
Passenger Payment	Passengers may pay up to 1 ether for purchasing flight insurance.
Passenger	If flight is delayed due to airline fault, passenger

Repayment	receives credit of 1.5X the amount they paid
CRITERIA	MEETS SPECIFICATIONS
Passenger Withdraw	Passenger can withdraw any funds owed to them as a result of receiving credit for insurance payout
Insurance Payouts	Insurance payouts are not sent directly to passenger's wallet

Oracles (Server App)

CRITERIA	MEETS SPECIFICATIONS
Functioning Oracle	Oracle functionality is implemented in the server app.
Oracle Initialization	Upon startup, 20+ oracles are registered and their assigned indexes are persisted in memory
Oracle Updates	Update flight status requests from client Dapp result in OracleRequest event emitted by Smart Contract that is captured by server (displays on console and handled in code)
Oracle Functionality	Server will loop through all registered oracles, identify those oracles for which the OracleRequest event applies, and respond by calling into FlightSuretyApp contract with random status code of Unknown (0), On

CRITERIA	Time (10) or Late Airline (20), Late Weather (30), Late METIS SPECIFICATIONS Other (50)